

194

JUN 06 1992

Courtaulds Coatings
 fka International Paint (USA), Inc.
 2270 Morris Avenue
 Union, NJ 07083

Attention: Raymond P. Gangi

Subject: NP Supertrop Antifouling Paint Red NB1609
 EPA Registration No. 2693-54
 Amendment Dated March 13, 1991

The amendment referred to above submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable provided that you make the labeling changes below and submit five copies of final printed labeling.

1. If applicable, indicate the minimum temperature at which the product should be applied.
2. Change "New Building" to read "New Ship Construction".
3. Ask discussed with the Agency, include the sentence "For use in fresh, salt, and brackish waters."
4. Revise your storage and disposal statement to read as follows:

STORAGE AND DISPOSAL

Do not contaminate water, food, feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL

Pesticide wastes are toxic. Paint that cannot be used according to label instructions must be disposed of according to Federal, State or local procedures under the Resources Conservation and Recovery Act.

CONTAINER DISPOSAL

Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved State and local procedures. If burned stay out of smoke.

CONCURRENCES

SYMBOL							
SURNAME							
DATE							

The heading "STORAGE AND DISPOSAL" must be of the same type size as the child hazard warning statement.

5. Revise the "If Swallowed" statement to read "If swallowed, drink promptly a large quantity of water. Avoid Alcohol. Get medical attention."

A stamped copy of the label is enclosed for your records.

If you have any questions concerning this letter, contact Marshall Swindell at (703) 305-6908.

Sincerely yours,



John H. Lee
Product Manager 31
Antimicrobial Programs Branch
Registration Division (H7505C)

ional.



DIRECTIONS FOR USE (CONTINUED)

This product is an antifouling protective coating resistant to algae, barnacles, and other marine growth.

SURFACE PREPARATION AND COMPATIBILITY. Surface preparation is required in order to ensure adhesion. Surface must always be clean and dry prior to application.

GENERAL APPLICATION PROCEDURES: Unless spray, a recommendation of 30:1 or greater. For small areas, brush or roller may be used but must meet the required dry film thickness. It is recommended to apply by airless product.

MIXING AND THINNING INSTRUCTIONS: Mix thoroughly with power. This product is designed to be applied without thinning. Should thinning be required, use a representative prior to altering this coating.

CLEAN UP: For tools, equipment, etc., use International GTA007.

MINIMUM DRY AND LAUNCHING TIMES: Minimum drying time before launching is 4 hours at a temperature of 73 °F.

THEORETICAL COVERAGE: 441 square feet per gallon per coat at 2 mil dry film thickness. Representative for practical application coverages. Practical square foot coverage is proportional to surface application techniques and climatic conditions.

APPLICATION SYSTEMS

EXISTING ANTIFOULING SYSTEMS - GOOD CONDITION: High pressure water (2500 p.s.i.) and/or scrape to remove all marine growth, slime, salts, etc. to a Near White Metal Standard of SSPC SP10-85. Blow down with clean, compressed air. Apply an approved underwater anticorrosive system.

POOR CONDITION: For "optimum" results, blast entire area to a Near White Metal Standard. Apply an approved underwater anticorrosive system.

NEW BUILDING: Blast entire area to a Near White Metal Standard. Apply an approved underwater anticorrosive system.

WOOD AND NON FERROUS SURFACES: Use surface preparation as recommended.

DISCLAIMER: The performance of any marine paint or coating depends on the condition of the surface to which it is applied. Courtaulds Coatings Inc. including surface preparation, proper application. Therefore, Courtaulds Coatings Inc. cannot guarantee this product's performance. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. COURTAULDS COATINGS INC. SHALL NOT BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. BY PURCHASING AND APPLYING THIS PRODUCT, BUYER AGREES THAT THE SOLE AND EXCLUSIVE REMEDY, IF ANY, FOR DEFECTIVE OR UNSATISFACTORY PERFORMANCE OF THIS PRODUCT IS THE PRICE OR REPLACEMENT OF THE PRODUCT AT COURTAULDS COATINGS' OPTION.

ANTIFOULING

PERCENT
21.8%
78.2%
100.0%

BEST AVAILABLE COPY

EPA REG. NO. 2693-54
EPA EST 2693-TX-1

FOR COMMERCIAL USE ONLY

Courtaulds Coatings

HOUSTON, TX 77091 • LOUISVILLE, KY 40203

International.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long sleeved cotton shirt, long pants and hat. Wash thoroughly with soap and water after handling and before eating and smoking. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. When product is used in confined areas or applied by spraying, wear a respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health. **Statement of Medical Treatment:** If in eyes, immediately flush with plenty of water for at least 15 minutes. Get medical attention. If on skin, immediately remove contaminated clothing, wash with plenty of soap and water. Get medical attention. Wash contaminated clothing before reuse. If inhaled, Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth. Get medical attention. If swallowed, Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Never give anything by mouth to an unconscious person. Avoid alcohol. Get immediate medical attention.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow sludge and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE: Keep away from heat, sparks or open flame.

DIRECTIONS FOR USE

This material is to be used in a manner consistent with its labeling.
NOTE: Protective clothing and respirators should be used as described under Precautionary Statements.

GENERAL DESCRIPTION

This product is an antifouling protective coating resistant to algae, barnacles and other marine fouling.

STORAGE & DISPOSAL

Do not allow paint, water, fumes or leachate from storage or disposal. Open dumping is prohibited.

When this material is used in a manner that cannot be used according to label instructions must be disposed of according to Federal, or approved State or local procedures under the Resource Conservation and Recovery Act.

When this material is prepared, repackaged and disposed of in an approved landfill, Federal, State or local disposal authorities for approved alternative procedures.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUN 06 1992

BEST AVAILABLE COPY

Under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, for the product registered under EPA Reg. No. 2693-54

**NB SUPERTROP ANTIFOULING
PAINT RED NB1609**

ACTIVE INGREDIENTS	PERCENT
CUPROUS OXIDE	21.6%
INERT INGREDIENTS	78.2%
	100.0%

ELEMENTAL COPPER 19.3 %
CONTAINS PETROLEUM DISTILLATES
KEEP OUT OF REACH OF CHILDREN

WARNING

See Side Panel for additional precautionary statements.

ONE U.S. GALLON (3.785 LITERS)

EPA REG. NO. 2693-54
EPA EST 2693-TX-1

FOR COMMERCIAL USE ONLY

 **COURTAULDS
COATINGS**