

# International Red Hand



## WARNING!

Harmful if swallowed. May be absorbed through the skin. May cause irritation. Do not get in eyes, on skin or on clothing. In case of skin contact, remove contaminated clothing and immediately wash with soap and water; for eyes, immediately flush with water. If irritation persists, get medical attention. Wash contaminated clothing before re-use. Do not contaminate or store near feed or foodstuffs.

### When Using Spray Application Methods

Workers must wear protective clothing. Use complete face shield with respirator, rubber gloves, long sleeves, hat or cap. Cover the skin completely. Spray men should be equipped with air line respirators in lieu of mouth type in addition to the other protective devices. Clothes should be thrown away or laundered before re-use. Do not eat, drink or smoke while working.

If it is necessary to burn or weld a newly applied (3 months or less) coating, furnish welder with a respirator.

**FOR USE BY  
COMMERCIAL OR PROFESSIONAL  
APPLICATORS ONLY**

## WIDE SPECTRUM ANTIFOULING

PIK MARK II 3211

Active Ingredients	Percent
Cuprous Oxide-----	26.4 %
Tributyltin Fluoride	7.1 %
Inert Ingredients	66.5 %
	<hr/> 100.0 %

Elemental Copper--23.4 %  
Elemental Tin --- 2.7 %

U.S.D.A. REG. NO. 2693-69

### NET ONE U.S. GALLON


## International Paint Company, Inc

NEW YORK, N.Y. 10006 SAN FRANCISCO, CALIF. 94103 NEW ORLEANS, LA 70126


ACCEPTED

APR 30 1971

UNDER THE FEDERAL INSECTICIDE ACT  
FUNGICIDE ACT AND RELATED ACTS  
FOR ECONOMIC PEACE AND REGISTER  
NO. 2693-69 SUBJECT  
TO ATTACHED COMMENTS



# International Red Hand



## WARNING!

Swallowed. May be absorbed through skin and cause irritation. Do not get in eyes, on clothing. In case of skin contact, remove contaminated clothing and immediately wash with soap and water: for eyes, immediately flush with water. If irritation persists, get medical attention. Do not use on contaminated clothing before re-contaminate or store near feed or food.

## Spray Application Methods

Must wear protective clothing. Use eye shield with respirator, rubber gloves, hat or cap. Cover the skin. Spray men should be equipped with respirators in lieu of mouth type in addition to other protective devices. Clothes washed away or laundered before re-use. Do not drink or smoke while working. Do not attempt to burn or weld a newly applied (one or less) coating, furnish welder with proper ventilation.

FOR USE BY  
COMMERCIAL OR PROFESSIONAL  
APPLICATORS ONLY

### WIDE SPECTRUM ANTIFOULING

PIK MARK II 3211

Active Ingredients	Percent
Cuprous Oxide-----	26.4 %
Tributyltin Fluoride	7.1 %
Inert Ingredients	66.5 %
	<hr/> 100.0 %

Elemental Copper--23.4 %  
Elemental Tin --- 2.7 %

U.S.D.A. REG. NO. 2693-69

## NET ONE U.S. GALLON

## DIRECTIONS

### MIXING

THOROUGHLY MIX BEFORE USING BY STIRRING AND BY POURING FROM ONE CONTAINER INTO ANOTHER SEVERAL TIMES. RESTIR FREQUENTLY DURING APPLICATION.

### APPLICATION

THE SURFACE TO BE PAINTED MUST BE CLEAN, FREE FROM RUST, GREASE, LOOSE PAINT AND MOISTURE.

THIS PAINT IS MADE IN READY-TO-USE CONSISTENCY AND SHOULD REQUIRE NO THINNERS. HOWEVER, IF THINNING IS NECESSARY, USE SPARINGLY.

WE SHALL UPON REQUEST SUPPLY SPECIFIC INSTRUCTIONS RELATING TO THE APPLICATION OF OUR PRODUCTS.

## International Paint Company, Inc.

NEW YORK, N.Y. 10006 SAN FRANCISCO, CALIF. 94108 NEW ORLEANS, LA 70126