

FEB 18 1993

Courtaulds Coatings
fka International Paint (USA), Inc.
2270 Morris Avenue
Union, NJ 07083

Attention: Raymond P. Gangi


Subject: Red Hand Antifouling 72 Blue
EPA Registration No. 2692-90
Amendment Dated October 22, 1992

The amendment referred to above submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable provided that you make the labeling changes below and submit five copies of final printed labeling.

1. If applicable, indicate the minimum temperature at which the product should be applied.
2. Change "New Building" to read "New Ship Construction".
3. Use your complete product name wherever it appears in the label text. We note that your correct product name is "Red Hand Antifouling 72 Blue" and not "Red Hand Antifouling Blue 72"

A stamped copy of the label is enclosed for your records. If you have any questions concerning this letter, contact Marshall Swindell at (703) 305-6908.

Sincerely yours,



John H. Lee
District Manager 31
Antimicrobial Programs Branch
Registration Division (H7505C)

| CONCURRENCES | | | | | | | |
|--------------|--|--|--|--|--|--|--|
| SYMBOL | | | | | | | |
| SURNAME | | | | | | | |
| DATE | | | | | | | |

ACCEPTED
with COMMENTS
in EPA Letter Dated:

FEB 18 1993

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.
2693-90



PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND
DOMESTIC ANIMALS

WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long sleeved cotton shirt, long pants and hat. Wash thoroughly with soap and water after handling and before eating and smoking. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. When product is used in confined areas or applied by spraying, wear a respirator (mask) approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health. **Statement of Practical Treatment:** If in eyes, immediately flush with plenty of water for at least 15 minutes. Get medical attention. If on skin, immediately remove contaminated clothing, wash with plenty of soap and water. Get medical attention. Wash contaminated clothing before reuse. If inhaled, Remove victim to fresh air. If not breathing, give orificial respiration, preferably mouth to mouth. Get medical attention. If swallowed, Drink promptly large quantities of water. Avoid alcohol. Get immediate medical attention.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE! Keep away from heat, sparks or open flame.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. **NOTE:** Protective clothing and respirators should be used as described under Precautionary Statements.

GENERAL DESCRIPTION

This product is an antifouling protective coating resistant to algae, barnacles and other marine fouling for use in fresh, salt and brackish waters.

STORAGE & DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Paint that cannot be used according to label instructions must be disposed of according to Federal, State or Local procedures under the Resources Conservation and Recovery Act.

CONTAINER DISPOSAL: Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved State and Local procedures. If buried, stay out of reach.

Red
ANTIFOULING

72 B

KEEP OUT OF REACH OF CHILDREN

See Side Panel for additional information
ONE U.S. GALLON

BEST AVAILABLE COPY

terlux®

d Hand® ING BOTTOM PAINT BLUE

OUT OF REACH OF CHILDREN
WARNING!

Panel for additional precautionary statements.
5.5 GALLON (3.785 LITERS)

DISCLAIMER The performance of any marine paint or coating depends on many factors outside the control of Courtauld's Coatings Inc including surface preparation, proper application, and environmental conditions. Therefore, Courtauld's Coatings Inc cannot guarantee the product's suitability for your particular purpose or application. **IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED.** COURTAULD'S COATINGS INC SHALL NOT BE LIABLE UNDER ANY CIRCUMSTANCES OR UNDER ANY THEORY OF TORT OR CONTRACTUAL DAMAGE. By purchase or use of this product, buyer agrees that the sale and exclusive remedy, if any is limited to the refund of the purchase price or replacement of the product at Courtauld's Coatings Inc's option.

| ACTIVE INGREDIENTS | PERCENT |
|------------------------|---------|
| Cuprous Oxide | 20.0% |
| INERT INGREDIENTS | 79.1% |
| | 100.00% |
| ELEMENTAL COPPER 18.5% | |

CONTAINS PETROLEUM DISTILLATES

EPA REG NO 2003-90
EPA EST 2003 NJ-1

PROVED DESCR
performance. Soft
minimal paint by
SURFACE PREPAR
lead to eventual b
716 to remove so
GENERAL APPLICA
and previously pai
ed for best perfor
MIXING & THINNING
not thin bottom p
THEORETICAL COV
square feet of sur
CLEAN-UP: Use INT
ESTIMATED DRY TH
allow a minimum c
thickly, longer per

PREVIOUSLY PAINT
entire surface with
Poor Condition: Co
wood and by sand
described below.
BARE FIBERGLASS-
changing rags keep
Repair imperfection
continuous coat of 1
wood 23 hours—no
Sanding System: W
quently before impo
tions with EPOXY SI
BO 120 grit product
BARE WOOD: Sand
Repair imperfection
of bottom paint red
seams with SEAM C
* **BARE STEEL:** Sand
apply one very thin
sand fill in all impe
Apply 3 coats of INT
second, and overing
* This is a simple s
Technical Departmen

BEST AVAILABLE COPY

**SUBSET A
DIRECTIONS FOR USE (CONTINUED)**

This product is an antifouling protective coating resistant to algae, barnacles, and other marine growth.

SURFACE PREPARATION AND COMPATIBILITY: Surface preparation order to ensure adhesion. Surface must always be clean and dry prior to application.

GENERAL APPLICATION PROCEDURES: Airless spray is recommended of 30:1 or greater. For small areas, brush or roller may be used but must meet the required dry film thickness. It is recommended to apply by airless spray product.

MIXING AND THINNING INSTRUCTIONS: Mix thoroughly with power mixer. Thinning is designed to be applied without thinning. Should thinning be required, representative prior to altering this coating.

CLEAN UP: For tools, equipment, etc., use International GTA007.

MINIMUM DRY AND LAUNCHING TIMES: Minimum drying time to launching is 12 hours at a temperature of 73°F.

THEORETICAL COVERAGE: 385 square feet per gallon, per coat at 2.0 mils. Representative for practical application coverages. Practical square foot coverage is proportional to surface, application techniques and climatic conditions.

APPLICATION SYSTEMS

EXISTING ANTIFOULING SYSTEMS - GOOD CONDITION: High pressure 2500 p.s.i. and/or scrape to remove all marine growth, slime, salts, etc. to a Near White Metal Standard of SSPC-SP10-85. Blow down with clean compressed air. Apply an approved underwater anticorrosive system.

POOR CONDITION: For "optimum" results, blast entire area to a Near White Metal Standard SSPC-SP10-85. Apply an approved underwater anticorrosive system.

NEW BUILDING: Blast entire area to a Near White Metal Standard SSPC-SP10-85. Apply an approved underwater anticorrosive system.

WOOD AND NON-FERROUS SURFACES: Use surface preparation and application instructions for these surfaces.

DISCLAIMER: The performance of any marine paint or coating depends on the surface preparation, including surface preparation, proper application. Therefore, Courtaulds Coatings Inc. cannot guarantee this product's performance in any application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. COURTAULDS COATINGS INC. SHALL NOT BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. BY PURCHASING AND APPLYING THIS PRODUCT, BUYER AGREES THAT THE SOLE AND EXCLUSIVE REMEDY, IF ANY, FOR DEFECTIVE OR UNSATISFACTORY PERFORMANCE OF THIS PRODUCT, IS THE PRICE OR REPLACEMENT OF THE PRODUCT AT COURTAULDS COATINGS' OPTION.

BEST AVAILABLE COPY

SUBSETA DIRECTIONS FOR USE (CONTINUED)

This product is an antifouling protective coating resistant to algae, barnacles

SURFACE PREPARATION AND COMPATIBILITY: Surface preparation direct order to ensure adhesion. Surface must always be clean and dry prior to painting.

GENERAL APPLICATION PROCEDURES: Airless spray is recommended: Tip of 30:1 or greater. For small areas, brush or roller may be used but multiple the required dry film thickness. It is recommended to apply by airless spray product.

MIXING AND THINNING INSTRUCTIONS: Mix thoroughly with power mixer is designed to be applied without thinning. Should thinning be necessary representative prior to altering this coating.

CLEAN UP: For tools, equipment, etc., use International GTA007.

MINIMUM DRY AND LAUNCHING TIMES: Minimum drying time between launching is 12 hours at a temperature of 73°F.

THEORETICAL COVERAGE: 385 square feet per gallon, per coat at 2.0 mils representative for practical application coverages. Practical square foot coverage proportional to surface, application techniques and climatic conditions.

APPLICATION SYSTEMS

EXISTING ANTIFOULING SYSTEMS - GOOD CONDITION: High pressure 2500 p.s.i. and/or scrape to remove all marine growth, slime, salts, etc. Spent Near White Metal Standard of SSPC-SP10-85. Blow down with clean and spent abrasives. Apply an approved underwater anticorrosive system.

POOR CONDITION: For "optimum" results, blast entire area to a Near White Metal Standard of SSPC-SP10-85. Apply an approved underwater anticorrosive system.

NEW BUILDING: Blast entire area to a Near White Metal Standard SSPC-SP10-85. Blow down with clean and spent abrasives. Apply an approved underwater anticorrosive system.

WOOD AND NON-FERROUS SURFACES: Use surface preparation and priming as directed.

DISCLAIMER: The performance of any marine paint or coating depends on the surface preparation and application of Courtaulds Coatings Inc. including surface preparation, proper application. Therefore, Courtaulds Coatings Inc. cannot guarantee this product's suitability for a particular application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. COURTAULDS COATINGS INC. SHALL NOT BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES OF THIS PRODUCT. BUYER AGREES THAT THE SOLE AND EXCLUSIVE REMEDY, IF ANY, IS THE PRICE OR REPLACEMENT OF THE PRODUCT AT COURTAULDS COATINGS' OPTION.