

ional Red Hand

WIDE SPECTRUM SPEEDCOAT II

PART B 3057

ONE U.S. GALLON

BEST DOCUMENT AVAILABLE

DIRECTIONS

MIXING


THOROUGHLY MIX BEFORE USING BY STIRRING AND BY POURING FROM ONE CONTAINER INTO ANOTHER SEVERAL TIMES. RESTIR FREQUENTLY DURING APPLICATION.

APPLICATION

THE SURFACE TO BE PAINTED MUST BE CLEAN, FREE FROM RUST, GREASE, LOOSE PAINT AND MOISTURE.

THIS PAINT IS MADE IN READY-TO USE CONSISTENCY AND SHOULD REQUIRE NO THINNERS. HOWEVER, IF THINNING IS NECESSARY, USE SPARINGLY.

Do not contaminate water by cleaning of equipment, or disposal of wastes.



International Red

BEST DOCUMENT AVAILABLE

DANGER

May cause eye damage. May be fatal if swallowed. May cause skin irritation. Wear goggles or face shield when handling. Do not get in eyes, on skin or on clothing. Use with adequate ventilation. Avoid breathing vapor or spray mist. Do not store near food or feed.

**DO NOT USE, POUR, SPILL
OR STORE NEAR HEAT OR
OPEN FLAME**

**DO NOT REUSE CONTAINER.
DESTROY WHEN EMPTY.**

FIRST AID—In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get prompt medical attention; wash skin with plenty of soap and water. Wash contaminated clothing before reusing.

**FOR USE BY COMMERCIAL
OR PROFESSIONAL APPLICATORS ONLY**

WIDE SPECTRUM SPEEDCOTE

ANTIPOULING RED F300
PART A

ACTIVE INGREDIENTS

CUPROUS OXIDE

TRI(PHENYL TIN FLUORIDE)

INERT INGREDIENTS

ELEMENTAL COPPER— 42.2%

ELEMENTAL TIN --- 3.7%

NET ONE U.S. GALLON

International Paint Company

RECOMMENDED FOR USE ON STEEL, ALUMINUM, AND OTHER METALS