

"TRI-LUX" ANTIFOULING PAINTS

"TRI-LUX" ANTIFOULING PAINTS utilize organo-tin as an antifoulant. "TRI-LUX" ANTIFOULING PAINTS will not cause pitting due to galvanic attack even if aluminum is scratched to bare metal during use.

DIRECTIONS

WOOD—Apply two to three coats of "TRI-LUX" ANTIFOULING PAINT to bare wood. Wood should be dry and clean before application of paint.

FIBERGLASS—Wipe fiberglass thoroughly with 202 "INTERLUX" FIBERGLASS SOLVENT WASH to remove mold release and apply one coat 200 "INTERLUX" FIBERGLASS PRIMER. After overnight drying time apply two coats "TRI-LUX" ANTIFOULING PAINT.

OR

Sand fiberglass thoroughly with 80 Grit Production Paper. Wipe surface clean with 355 VINYL-LUX SOLVENT. Apply two coats of "TRI-LUX" ANTIFOULING PAINT.

ALUMINUM—Roughen surface with medium grit Emery Cloth to a uniform bright finish. Wipe surface with a clean cloth wet with 216 "INTERLUX" SPECIAL THINNER until all residue is removed. Apply one coat of 353/354 VINYL-LUX PRIME-WASH. (This step is absolutely necessary in order to obtain proper adhesion of the "TRI-LUX" PAINTS.) Follow with two coats of "TRI-LUX" ANTIFOULING PAINT of the desired color.

ALUMINUM YACHTS—25 FEET AND OVER—Ask your "INTERLUX" representative for application directions.

Except when "TRI-LUX" PAINTS are applied over themselves, or to another known vinyl-type paint in good condition, they should always be applied to bare surfaces or recommended primed surfaces.

Under normal painting conditions, "TRI-LUX" FINISHES may be overcoated within four hours of application. "TRI-LUX" ANTIFOULING PAINTS need not be immediately immersed after painting. Several days, or even weeks, may transpire before launching. However, because the paint film will deteriorate to some extent when exposed to atmospheric exposure, it is wise to keep the boat in the water, or under cover, to protect the paint film.

To clean brushes and equipment, or to replace solvent that may be lost due to evaporation, use 355 VINYL-LUX SOLVENT. Use a good quality natural bristle brush for application of "TRI-LUX" ANTIFOULING PAINTS.



**ONE U.S. GALLON
DANGER**

KEEP OUT OF REACH OF CHILDREN
See other warnings on back panel

Tri-lux
VINYL-BASE PAINT
Antifouling Paint

CONTAINS
bioMET.

ACTIVE INGREDIENTS
Tributyltin Fluoride
INERT INGREDIENTS

PERCENT
13.8%
86.2%
100.0%

ELEMENTAL TIN — 5.25%

63 WIDE SPECTRUM LIGHT GREEN MARK I (TB)

E. P. A. REG. NO. 2693-101



International Paint Company

NEW YORK, N. Y. 10006 • SAN FRANCISCO, CAL. 94080 • NEW ORLEANS

ONE U.S. GALLON

DANGER

KEEP OUT OF REACH OF CHILDREN
See other warnings on back panel



Tri-lux[®]
VINYL-BASE PAINT
CONTAINS **bic**
Antifouling Paint

63 WIDE SPECTRUM LIGHT GREEN MARK I (TBTF)

E. P. A. REG. NO. 2693-101

ACCEPTED
FEB 14 1975
Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 2693-101

Do not contaminate water by cleaning
of equipment or disposal of wastes.

FACTORIES

U.S.A.	UNION, N. J.	HOLLAND	RIJSDWIJK
U.S.A.	SAN FRANCISCO	ITALY	GENOA
U.S.A.	NEW ORLEANS	ITALY	TRIESTE
AUSTRALIA	SYDNEY	MEXICO	MEXICO CITY
BRAZIL	RIO DE JANEIRO	NEW ZEALAND	AUCKLAND
CANADA	MONTREAL	NEW ZEALAND	WELLINGTON
CANADA	REGINA	NIGERIA	IKERJA
CANADA	VANCOUVER	NORWAY	BIRGEN
DENMARK	COPENHAGEN	PORTUGAL	SETUBAL
ENGLAND	FELLING-ON-TYNE	SCOTLAND	GLASGOW
FRANCE	ROUEN	SPAIN	BILBAO
GERMANY	HAMBURG	SWEDEN	GOTHEBURG
		VENEZUELA	MARACAIBO

EPA EST. 2693-NJ-1

DANGER

May be fatal if Swallowed. May be absorbed through skin.
Causes skin irritation. Do not spray; apply by brush only.

Use with adequate ventilation.

Do not get in eyes, on skin, or clothing. In case of skin
contact remove contaminated clothing and immediately
wash skin with soap and water. If irritation persist, get
medical attention. Wash contaminated clothing before
reuse. For eyes, flush with plenty of water and get medical
attention. Avoid storage near food and feed products.
Flammable. Keep away from heat and open flame. Close
container after each use.

Do not reuse empty container. Destroy it by perforating or
crushing. Bury or discard in a safe place.

International Paint Company, Inc.

NEW YORK, N. Y. 10006 • SAN FRANCISCO, CAL. 94080 • NEW ORLEANS, LA. 70126

