

**WARNING!**  
 KEEP OUT OF REACH OF CHILDREN  
 See Side Panel for additional precautionary statements.



**Interlux**®

2693-119

ACCEPTED

DEC 28 1982

Under the Federal Insecticide,  
 Fungicide, and Rodenticide Act,  
 as amended, for the pesticide  
 registered under  
 No. 2693-119

**PRECAUTIONARY STATEMENTS  
 HAZARDS TO HUMANS AND  
 DOMESTIC ANIMALS**

**WARNING**  
**KEEP OUT OF REACH OF CHILDREN**

Causes eye and skin irritation. **FIRST AID:** If in contact with eyes, immediately flush eyes with plenty of water for at least 15 minutes. If swallowed, call a physician. If inhaled, remove to fresh air. Remove and wash contaminated clothing before reuse. Wash thoroughly with soap and water after handling and before eating and smoking. If swallowed, drink plenty of water. If necessary, give egg whites, gelatin solution or if these are not available, large quantities of water. Never give anything by mouth to an unconscious person. Call a physician immediately.

**ENVIRONMENTAL HAZARD**  
 Do not contaminate water, food, or feed by storage or disposal of wastes.  
**PHYSICAL OR CHEMICAL HAZARD**  
**FLAMMABLE!** Keep away from heat.

**DIRECTIONS FOR USE**

It is a violation of federal law to use this product in a manner inconsistent with its labeling.  
**NOTE:** Wear protective clothing when product is used in confined areas or applied by spraying, wear a respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U. S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11.

**GENERAL DESCRIPTION**

Super Bottomkote is an anti-fouling protective coating resistant to algae, barnacles and other marine fouling.

**STORAGE & DISPOSAL**

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State, or local disposal authorities.

Container - Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved State and local procedures.

**SUPER**  
**Bottomkote**  
**A MODIFIED EPOXY ANTIFOULING PAINT**

**456 RED**

ACTIVE INGREDIENT	PER CENT
Cuprous Oxide	57.0%
INERT INGREDIENTS	43.0%
Elemental Copper	50.6%
	100.0%

This product contains 10.6 lbs of cuprous oxide per

**ONE GALLON (3.785 LITERS)**

CONT

12/28/1982

1/3

## SUPER BOTTOMKOTE® ANTIFOULING BOTTOM PAINT

**GENERAL DESCRIPTION:** Super Bottomkote Antifouling Paint is highly loaded with antifouling ingredients to resist fouling under the most severe conditions. It is especially recommended for southern waters where fouling conditions prevail on a "year around" basis. Because of its epoxy resin modification and high copper content, it is a tough, durable coating which can be applied several weeks before launching without fear of losing its effectiveness. Super Bottomkote is a superior product, well suited for application to large motor sailors and cruising powerboats.

**GENERAL PREPARATION:** Surface must ALWAYS be clean and dry prior to painting. After sanding ALWAYS wipe surface clean with INTERLUX SPECIAL THINNER 216 to remove sanding residue.

**GENERAL APPLICATION:** Can be brushed or rolled over all other antifouling bottom paints; on fiberglass, wood and steel surfaces (per application systems below)—EXCEPT aluminum. Apply TWO coats.

**MIXING INSTRUCTIONS:** Shake or mix well and stir continuously while using.

**THINNING INSTRUCTIONS:** When brushing or rolling, do not thin bottom paints—EXCEPT for the first coat on bare wood.

**DRY TIMES BEFORE: OVERCOATING - Overnight**

**LAUNCHING - Minimum overnight; Maximum 60 days.**

**THEORETICAL COVERAGE:** 425 square feet per gallon.

**CLEAN-UP:** Use INTERLUX SPECIAL THINNER 216 for cleaning brushes and tools.

### APPLICATION SYSTEMS

**PREVIOUSLY PAINTED FIBERGLASS & WOOD:** Remove all traces of loose paint and surface contamination. Sand thoroughly with 80-120 grit production paper; wipe surface clean. Apply two coats of bottom paint.

**NEW FIBERGLASS —No Sand Method:** Wash entire surface with INTERLUX FIBERGLASS SOLVENT WASH 202 to remove wax and dirt, changing rag frequently. Repair scratches and dents with INTERLUX INTERFILL PUTTY 217; sand and clean repaired areas. Apply with brush or roller one thin coat of INTERLUX FIBERGLASS PRIMER 200 to ensure paint adhesion. Do not spray. Allow to cure between 2-3 hours—no more, no less. Do not sand. Apply two coats of bottom paint.

**Sanding Method:** Clean entire surface with INTERLUX FIBERGLASS SOLVENT WASH 202 to remove wax and dirt, changing rag frequently. Sand entire surface with 80-120 grit production paper; wipe clean. Apply two coats of bottom paint.

**NEW & BARE WOOD:** Sand well with 80-120 grit production paper; wipe surface clean. Apply first coat of bottom paint reduced with INTERLUX SPECIAL THINNER 216 (10% maximum) to penetrate the grain of wood. Fair seams with SEAM COMPOUND 30. Apply second and third coats of bottom paint UNREDUCED.

**PREVIOUSLY PAINTED STEEL:** Remove all loose paint, rust and surface contamination by sanding or using a wire brush; wipe surface clean. Touch up bare spots by roughening with 80 grit production paper then spot priming with 3 coats of INTERLUX SILVER PRIMOCON 347; allow 3 hours for first coat to dry, 6 hours for the second, and overnight for the third. Apply two coats of bottom paint.

**NEW STEEL:** Sandblast to a near white finish; wipe surface clean. Immediately apply one thin coat of VINY-LUX PRIMEWASH 353/354 to condition the surface; allow to dry minimum of 1 hour, maximum of 24. Do not sand. Fill in all imperfections with RED HAND FILLER 4498/4499; sand filled areas smooth; wipe clean. Apply 3 coats of INTERLUX SILVER PRIMOCON 347; allow 3 hours for the first coat to dry, 6 hours for the second, and overnight for the third. Do not apply 347 above the waterline. Apply two coats of bottom paint.

EPA REG. No. 2693-119  
EPA EST. 2693-M-1



gallon

AINS PETROLEUM DISTILLATES

International Paint Company, Inc.

UNION, N.J. 07083 • SAN FRANCISCO, CAL. 94080 • NEW ORLEANS, LA. 70186

2/3

Causes eye and skin irritation. When handling wear full protective clothing, rubber gloves, goggles, face shield or other approved eye protection. May be fatal if swallowed or inhaled. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Remove and wash contaminated clothing before reuse. Avoid breathing vapor, spray mist, dust or chips from sanding or blasting. Wash thoroughly with soap and water after handling and before eating or smoking. Use with adequate ventilation.

FIRST AID: If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention immediately.

If on skin, wash with plenty of soap and water. Get medical attention. If in eyes, flush with water for at least 15 minutes. Get medical attention immediately. If inhaled, remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention immediately.

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS: FLAMMABLE! Keep away from heat or open flame.