



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

February 5, 2015

John P. Pazdera
Pesticide Registration Manager
International Paint LLC
2270 Morris Avenue
Union NJ 07083

Subject: Label Notification per PRN 98-10 – Revise Storage and Disposal Language
Product Name: Super Bottomkote 456 Red
EPA Registration Number: 2693-119
Application Date: January 20, 2015
Decision Number: 499303

Dear Pazdera:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

If you have any questions, you may contact Terria Northern at 703-347-0265 or via email at northern.terria@epa.gov.

Sincerely,

A handwritten signature in black ink, appearing to be "S. Murasaki", written over a horizontal line.

for
Seiichi Murasaki, Acting Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

Super Bottomkote 456 Red

- Serious Protection for Heavy Fouling Areas
- For Fiberglass, Wood or Steel Power Boats
- Excellent Protection for Severe Fouling Areas
- Hard Scrubbable Finish

KEEP OUT OF REACH OF CHILDREN

WARNING

See side panel for additional precautionary statements

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

NOTIFICATION

2693-119

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

02/05/2015

EPA Registration No. 2693-119
EPA Establishment No. 2693-NJ

Active Ingredient:

Cuprous Oxide = 57.00%
CAS #1317-39-1

Inert Ingredients: = $\frac{43.00\%}{100.00\%}$

Elemental Copper: = 50.6%

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of International Paint LLC, including the surface preparation, proper application and the environmental conditions. Therefore, International Paint LLC cannot guarantee the suitability of this product for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT LLC SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use of the product buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at the discretion of International Paint LLC.

**International Paint LLC
2270 Morris Avenue
Union, New Jersey 07083**

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
WARNING**

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Safety & Health Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

FIRST AID

IF SWALLOWED:

- Call a poison control center or doctor immediately for treatment advice.
- Have person sip a glass of water if able to swallow.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give anything by mouth to an unconscious person.

IF ON SKIN OR CLOTHING:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

IF INHALED:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for treatment advice.

IF IN EYES:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

OTHER:

- Have the product container or label with you when calling a poison control center or doctor or going for treatment.

ENVIRONMENTAL HAZARD: This material is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System [NPDES] permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS: **Flammable.** Keep away from heat and open flame.

[Subset A – Directions for Use for Pleasure Craft]

SUPER BOTTOMKOTE COPOLYMER EPOXY

DIRECTIONS FOR USE: It is a violation of federal law to use this product in a manner inconsistent with its labeling. SUPER BOTTOMKOTE Antifouling Paint is highly loaded with antifouling ingredients to resist fouling under the most severe conditions. It is especially recommended for southern waters where fouling conditions prevail on a “year around” basis. Because of its epoxy resin modification and high copper content, it is a tough, durable coating which can be applied several weeks before launching without fear of losing its effectiveness. SUPER BOTTOMKOTE is a superior product, well suited for application to large motor sailers and cruising power boats.

GENERAL DESCRIPTION: SUPER BOTTOMKOTE is an antifouling protective coating resistant to algae, barnacles and other marine fouling.

GENERAL PREPARATION: Surface must ALWAYS be clean and dry prior to painting. After sanding ALWAYS wipe surface clean with INTERLUX SPECIAL THINNER 216 to remove sanding residue.

GENERAL APPLICATION: Can be brushed or rolled over all other antifouling bottom paints, on fiberglass, wood and steel surfaces (per application systems below) – EXCEPT aluminum. Apply TWO coats.

MIXING INSTRUCTIONS: Shake or mix well and stir continuously while using.

THINNING INSTRUCTIONS: When brushing or rolling, do not thin bottom paints – EXCEPT for the first coat on bare wood.

DRY TIMES BEFORE: OVERCOATING – Overnight

LAUNCHING – Minimum overnight; Maximum 60 days

THEORETICAL COVERAGE: 425 square feet per gallon

CLEAN-UP: Use INTERLUX SPECIAL THINNER 216 for cleaning brushes and tools.

APPLICATION SYSTEMS

PREVIOUSLY PAINTED FIBERGLASS & WOOD: Remove all traces of loose paint and surface contamination. Sand thoroughly with 80-120 Grit Production Paper; wipe surface clean. Apply two coats of bottom paint.

NEW FIBERGLASS – No Sand Method: Wash entire surface with INTERLUX FIBERGLASS SOLVENT WASH 202 to remove wax and dirt, changing rags frequently. Repair scratches and dents with EPOXY SURFACING AND FAIRING COMPOUND 417A/418B; sand and clean repaired areas. Apply with brush or roller one thin coat of INTERLUX FIBERGLASS PRIMER AL200 to ensure paint adhesion. Do not spray. Allow to cure between 2-3 hours – no more, no less. Do not sand. Apply two coats of bottom paint.

Sanding Method: Clean entire surface with INTERLUX FIBERGLASS SOLVENT WASH 202 to remove wax and dirt, changing rags frequently. Sand entire surface with 80-120 Grit Production Paper; wipe clean. Apply two coats of bottom paint.

NEW & BARE WOOD: Sand well with 80-120 Grit Production Paper; wipe surface clean. Apply first coat of bottom paint reduced with INTERLUX SPECIAL THINNER 216 (10% maximum) to penetrate the grain of wood. Fair seams with SEAM COMPOUND 30. Apply second and third coats of bottom paint UNREDUCED.

PREVIOUSLY PAINTED STEEL: Remove all loose paint, rust and surface contamination by sanding or using a wire brush; wipe surface clean. Touch up bare spots by roughening with 80 Grit Production Paper then spot priming with 3 coats of INTERLUX UNDERWATER METAL PRIMER 360R; allow 3 hours for first coat to dry, 6 hours for the second, and overnight for the third. Apply two coats of bottom paint.

NEW STEEL: Sandblast to a near white finish; wipe surface clean. Immediately apply one thin coat of VINYLUX PRIMEWASH 353/354 to condition the surface; allow to dry a minimum of one hour, maximum of 24. Do not sand. Fill in all imperfections with EPOXY SURFACING AND FAIRING COMPOUND 417A/418B; sand filled areas smooth; wipe clean. Apply 3 coats of INTERLUX UNDERWATER METAL PRIMER 360R; allow 3 hours for the first coat to dry, 6 hours for the second, and overnight for the third. Do not apply 360R above the waterline. Apply two coats of bottom paint.

Color difference may occur between actual paint and color swatch on front of can.

[Subset B – Alternate Directions for Use for Pleasure Craft]

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PRODUCT DESCRIPTION: This product is a hard, high-strength antifouling designed for maximum antifouling performance in moderate to high fouling conditions. This product has the added benefit of excellent color homogeneity and stability. The fast dry formula of this product allows your boat to be painted and launched in the same day. This product is recommended for use on fiberglass, wood or properly primed steel and lead. Apply at least two full coats with brush, roller or spray. Do not apply when temperature is below 50°F (10°C).

COMPATIBILITY: This product is compatible with most other antifouling paints provided they are in sound condition and have been sanded. Soft antifouling paints and paints that are in poor condition will need to be removed or overcoated with Primocon® before applying this product.

V.O.C.: Less than 330 grams/liter
2.75 lbs./gallon) yields

THEORETICAL COVERAGE: 350 sq. ft./
gallon (2 mils dry film thickness)

THINNER: SPECIAL THINNER 216 or
BRUSHING LIQUID 333

DRY TIMES: Touch dry - 1 hour
77°F (25°C) Dry to overcoat - 4 hours minimum
Dry to launch - 8 hours minimum
60 days maximum

THINNING: Thin only when necessary Do not
exceed 10% maximum

APPLICATION TEMPERATURES: 50°F
(10°C)* and above (air and hull)

CLEAN-UP: SPECIAL THINNER 216 or
BRUSHING LIQUID 333

ESTIMATED DRY TIMES:

Temperature °F (°C)	Touch Dry	Overcoating Time Minimum	Immersion Time	
			Minimum	Maximum
50°F (10°C)	3 Hours	6 Hours	12 Hours	60 Days
60°F (15°C)	2 Hours	5 Hours	10 Hours	60 Days
75°F (24°C)	1 Hour	4 Hours	8 Hours	60 Days
95°F (35°C)	30 Minutes	2 Hours	6 Hours	60 Days

*If the air temperature falls below 50°F (10°C) during the 10 hour dry time extend the dry times to 36 hours minimum.

APPLICATION SYSTEMS

PREVIOUSLY PAINTED - GOOD CONDITION: Remove all traces of loose paint and contamination by sanding the entire surface with 80 grit sandpaper; wipe surface clean with Special Thinner 216. Apply at least 2 coats of this product.

PREVIOUSLY PAINTED - POOR CONDITION: Completely remove all old antifouling paint, using Interstrip® 299E. Sand and wipe clean with Fiberglass Solvent Wash 202.

BARE FIBERGLASS (POLYESTER OR VINYLESTER) - SURFACE PREPARATION:

BARE FIBERGLASS:

It is very important that bare fiberglass be properly prepared in order to prevent delamination of the antifouling paint. Begin by scrubbing the surface thoroughly with a stiff brush using Interlux All-Purpose Boat Soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry.

Remove mold release wax using one of the following products; Interlux Fiberglass Surface Prep or Interlux Fiberglass Solvent Wash following the product label instructions. To be certain that all of the contamination has been removed, run water over the surface. If the water beads up or separates, clean again. When the water sheets off, all contamination has been removed. After the surface has been properly cleaned, proceed with one of the application systems below.

BARE FIBERGLASS - NO SAND SYSTEM: Clean the surface following the preparation procedure described above. Apply one coat of Interprotect® 2000E or Fiberglass No Sand Primer YPA200 by brush or roller following the label instructions for applying the primer and overcoating with antifouling paint. Apply 2 coats of this product allowing for the appropriate dry times.

BARE FIBERGLASS - SANDING SYSTEM: Clean the surface following the preparation procedure above. Sand the entire surface with 80-grit sandpaper and wipe clean with Fiberglass Solvent Wash 202 to remove sanding residue. Repair any surface imperfections with Watertite YAV135. Sand and wipe clean. Apply two coats of this product allowing for appropriate dry times.

BARE WOOD: Sand the entire surface with 80-grit sandpaper, wipe surface clean with Interlux Special Thinner 216. Repair imperfections with Watertite YAV135. Sand and wipe clean. Apply the first coat of this product thinned 10% with Special Thinner 216 or Brush-Ease 433. Fill seams with Seam Compound 30 (if necessary). Apply two more coats of this product unthinned, allowing appropriate dry times.

UNDERWATER METALS: Contact the Interlux Technical Service Department at 1-800-468-7589 for full information on how to properly prime underwater metals. DO NOT USE ON ALUMINUM.

STORAGE AND DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.