


Intermatic



PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND
DOMESTIC ANIMALS

DANGER

KEEP OUT OF REACH OF CHILDREN

Corrosive. Causes eye irritation and skin burns. When handling wear full protective clothing, rubber gloves, goggles, face shield or other approved eye protection. May be fatal if swallowed or inhaled. Harmful if absorbed through skin. This product may be a dermal sensitizer. Avoid contact with skin, eyes or clothing. Remove and wash contaminated clothing before reuse. Avoid breathing vapor, spray mist, dust or chips from sanding or blasting. Wash thoroughly with soap and water after handling and before eating or smoking. Use with adequate ventilation.

FIRST AID: If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention immediately.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

If on skin, wash with plenty of soap and water. Get medical attention.

If in eyes, flush with water for at least 15 minutes. Get medical attention immediately.

If inhaled, remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention immediately.

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS: **FLAMMABLE!** Keep away from heat or open flame.

Intermooth
HISOL ST

Self polishing copoly
antifouling

PLUM BFA9

INGREDIENT STATEMENTS
AS PER ATTACHED SHEET

CONTAINS PETROLEUM DISTILLATE

KEEP OUT OF REACH OF CHILDREN

DANGER

SEE SIDE PANEL FOR ADDITIONAL
STATEMENTS.

EPA REG. NO. 2693-


NET 5 U. S. GALL

International Paint Co.

NEW YORK, N.Y. 10014 SAN FRANCISCO, CALIF. 94104

2693-128

International



DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labelling.

Intersmooth

HISOL SPC

**Self polishing copolymer
antifouling**

PLUM BFA954

**INGREDIENT STATEMENTS
AS PER ATTACHED SHEET**

NOTE - Wear protective clothing when product is used in confined areas or applied by spraying. While spraying, sanding or blasting wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

Container - Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved State and local procedures.

CONTAINS PETROLEUM DISTILLATES
KEEP OUT OF REACH OF CHILDREN

DANGER

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

EPA REG. NO. 2693-

NET 5 U. S. GALLONS

COMMERCIAL USE ONLY

EPA EST 2693-NJ-1

International Paint Company Inc.

BFA954/956

ACTIVE INGREDIENTS

| | |
|---|--------|
| TRIBUTYL TIN METHACRYLATE (AS PART OF A POLYMER) | 9.4 % |
| BIS (TRIBUTYL TIN) OXIDE | 0.5 % |
| CUPROUS OXIDE | 44.7 % |

INERT INGREDIENTS

45.4 %
100.0 %

ELEMENTAL TIN 3.2 %
ELEMENTAL COPPER 39.7 %

THIS PRODUCT CONTAINS 1.4 LBS. TRIBUTYL TIN METHACRYLATE (AS PART OF A POLYMER), 0.1 LBS. BIS (TRIBUTYL TIN) OXIDE, AND 6.5 LBS. CUPROUS OXIDE PER GALLON.