

<p style="text-align: center;">U.S. ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (WH-567) WASHINGTON, D.C. 20460</p> <p>NOTICE OF PESTICIDE: <input checked="" type="checkbox"/> REGISTRATION <input type="checkbox"/> REREGISTRATION <i>(Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)</i></p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; padding: 2px;">EPA REGISTRATION NO. 2693-132</td> <td style="width: 50%; padding: 2px;">DATE OF ISSUANCE 10 JAN 1986</td> </tr> <tr> <td colspan="2" style="padding: 2px;">TERM OF ISSUANCE</td> </tr> <tr> <td colspan="2" style="padding: 2px;">NAME OF PESTICIDE PRODUCT XIII 235/REA 540</td> </tr> </table>	EPA REGISTRATION NO. 2693-132	DATE OF ISSUANCE 10 JAN 1986	TERM OF ISSUANCE		NAME OF PESTICIDE PRODUCT XIII 235/REA 540	
EPA REGISTRATION NO. 2693-132	DATE OF ISSUANCE 10 JAN 1986						
TERM OF ISSUANCE							
NAME OF PESTICIDE PRODUCT XIII 235/REA 540							
<p>NAME AND ADDRESS OF REGISTRANT (Include ZIP code)</p> <div style="border: 1px solid black; padding: 10px; margin: 10px 0;"> <p style="margin: 0;">International Paint Co., Inc. 227 Morris Avenue Edison, New Jersey 07083</p> <p style="margin: 10px 0 0 40px;">Attn: Mr. Lee H. Jones</p> </div>							
<p>NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.</p>							
<p>On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.</p> <p>A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.</p> <p>Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.</p> <p>This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:</p> <ol style="list-style-type: none"> 1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data. 2. Make the labeling changes listed below before you release the product for shipment: <ol style="list-style-type: none"> a. Add the phrase "EPA Registration No. 2693-132". b. Since you removed the xylene from your formulation the pesticide disposal instructions given below the heading "Storage and Disposal" are acceptable. The instructions given below the heading "Pesticide Disposal", "Pesticide wastes are toxic etc" should be deleted. c. Add the sentence "Refer to Product Data Sheet for Application Instructions" below the sentence "It is a ____ labeling". 							
<p><input checked="" type="checkbox"/> ATTACHMENT IS APPLICABLE</p>							
SIGNATURE OF APPROVING OFFICIAL	DATE						

- d. The signal word "Warning" and the Child Hazard Warning "Keep Out of Reach of Children" must meet requirements (the whole label should be considered as the front panel) see 7a and 7b of "The Label" enclosure and the A-79 and front panel type size enclosures.
- e. The "Product Data Sheet" containing the Commercial Use Directions has been made part of your files. Please note that the "weight per gallon" should be the same on the data sheet as in the Confidential Statement of Formula.

3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,

John H. Lee
Product Manager (31)
Disinfectants Branch
Registration Division (TS-767C)

Enclosure

International



with COMMENTS
in EPA Letter Book

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING

KEEP OUT OF REACH OF CHILDREN

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT:

If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

If in eyes: Flush with plenty of soap and water. Get medical attention.

If on skin: Wash with plenty of soap and water. Get medical attention.

If inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARD

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARD

FLAMMABLE! Keep away from heat or open flame

XUU235/BRA540

Tin Free Eroding
Antifouling Paint

Active Ingredient	Percent
Cuprous Oxide	37.2
Inert Ingredients	62.8 100.00
Elemental Copper	32.9

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No.

2693-132

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

GENERAL DESCRIPTION
XUU235/BRA540 is an antifouling paint resistant to other marine fouling.

STORAGE & DISPOSAL

Do not contaminate water, food, or feed. Mixing is prohibited. Pesticide, spray mixture, or rinsate that cannot be used should be disposed of according to Federal, State, or local disposal authority. Triple rinse (or equivalent) and then dispose of rinsate. Consult Federal, State, or local authorities for approved alternative procedures.

PESTICIDE DISPOSAL

Pesticide wastes are toxic. Do not dispose of excess pesticide, rinsate, or other waste in a violation of Federal, State, or local law. These wastes cannot be disposed of in the open. Dispose of these wastes according to label instructions or to your State Pesticide or Environmental Control Agency, or the nearest authorized representative at the nearest office for guidance.

FOR COMMERCIAL USE ONLY

EPA REG. NO. 2693-
EPA EST. NO. 2693-NJ-1

NET FIVE U.S. GALLONS

International Paint Company Inc.

control the attachment of barnacles, seagrass, green weed and other fouling organisms in seawater and fresh water.

ACCEPTED
with COMMENTS
in EPA Letter Dated

JAN 10 1986

Insecticide, Fungicide, and Rodenticide Act
Control for the pesticide
registered under EPA Reg. No.

2693-132

Recommended Dry
Film Thickness
Theoretical Coverage 125 sq ft/gal to give 6 mils DFT
sq m/liter to give microns DFT
(DFT) Per Coat 6 mils : 150 microns
Dry Time Touch 2 Hours
@ 77°F (25°C) Hard 3 Hours
Overcoating Time (Min) 3 Hours
Overcoating Time (Max) 48 Hours
To Undock (Min) 4 Hours
To Undock (Max) 48 Hours
Color Red & colors
Finish Low Sheen
Storage Conditions Normal
Product Weight 15.1 lbs per US gallon
1.45 kgs per liter

Performance and Limitations

Performance (1) To maximize performance, minimum of two full coats at the recommended dry film thickness should be applied.

Limitations (1) Will crack on atmospheric exposure. Therefore, do not use on other than normal immersion surfaces.

(2) This is a scrubbable type antifouling. Therefore, mechanical cleaning devices can be used.

(3) Dry times are normally a function of humidity, ventilation, and temperature. The quotation of a single number at 77°F (25°C) is only a guideline and assumes standard conditions of 55% relative humidity and ventilation. Please consult your International Paint Marine Coatings Representative for more precise estimates under the specific conditions prevailing at the time of application.

surfaces. Remove all surface contaminants prior to application.

Application and Safety Precautions

Method of Application Brush, roller or spray
Thinning If necessary, use International GTAC04 or GTA007
Conventional Spray Gun DeVilbiss M3C or JGA
Fluid Tip E
Air Cap 78, 704 or 725
Pressures Atomizing Pressure
30-40 p.s.i.
(2.1-2.8 kg/sq cm)
Pot Pressure 10-20 p.s.i.
(0.7-1.4 kg/sq cm)
Airless Spray Tip Range 21-26 in.ou
Total output fluid pressure 2000-2500 p.s.i. (140-175 kg/sq cm)
Clean Up After use clean all equipment with international GTAC04 or GTA007 thinners

Safety Precautions Contains copper compound. Causes eye and skin irritation. When handling wear full protective clothing, rubber gloves, goggles, face shield or other approved eye protection. May be fatal if swallowed or inhaled. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Remove and wash contaminated clothing before reuse. Avoid breathing vapor and spray mist. Wash thoroughly with soap and water after handling and before eating or smoking. Use with adequate ventilation. FIRST AID: If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention immediately.

If on skin, wash with plenty of soap and water. Get medical attention. If in eyes, flush with water for at least 15 minutes. Get medical attention immediately. If inhaled, remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention immediately.

Avoid burning, welding, sanding or blasting dried film without appropriate protection.

Avoid smoking during application, eating or drinking in application area and the use of thinners to clean skin.

Since this product contains flammable materials, keep away from heat, sparks and open flames. No smoking should be permitted in the area.

Observe flash point precautions. Adequate ventilation must be maintained in enclosed areas to avoid explosion risks.

Prior to use—read labels on container and consult (OSHA) Material Safety Data Sheet for detailed instructions.

Warranty disclaimer. The technical data given herein has been compiled for your help and guidance and is based upon our experience and knowledge. However, as we have no control over the use to which this information is put, no warranty, express or implied, is intended or given. We assume no responsibility whatsoever for coverage, performance or damages, including injuries resulting from use of this information or of products recommended herein.