

PH 31 2693-135

143

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

FEB 26 1992

Courtaulds Coatings  
fka International Paint (USA), Inc.  
2270 Morris Avenue  
Union, NJ 07083

Attention: Raymond P. Gangi

Subject: Ultra-Kote  
EPA Registration No. 2693-135  
Amendment Dated January 28, 1991

The amendment referred to above submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable provided that you make the labeling changes below and submit five copies of final printed labeling.

- 1. Change the "If Swallowed" section of your Statement of Practical Treatment to read:

IF SWALLOWED: Drink promptly a large quantity of water.  
Avoid alcohol. Get medical attention.

- 2. Revise your storage and disposal statement to read as follows:

STORAGE AND DISPOSAL

Do not contaminate water, food, feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL

Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

CONTAINER DISPOSAL

Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved State and local procedures. If burned stay out of smoke.

CONCURRENCES

SYMBOL								
SURNAME								
DATE								

Dot 3

The heading "STORAGE AND DISPOSAL" must be of the same type size as the child hazard warning statement.

3. The misuse statement should be placed on your right panel immediately below the heading "Directions For Use." Delete the heading (i.e., Directions For Use) from the left panel of the label.
4. If applicable, indicate the minimum temperature at which the product should not be applied.
5. Change "overnight dry" to a specific number of hours.

A stamped copy of the label is enclosed for your records. If you have any questions concerning this letter, contact Marshall Swindell at (703) 305-6908.

Sincerely yours,



John H. Lee  
Product Manager 31  
Antimicrobial Programs Branch  
Registration Division (H7505C)

KEEP OUT OF REACH OF CHILDREN

# WARNING

See Side Panel for additional Precautionary Statements



# Interlux

# Ultra-Kote

EPA REG NO 2693-135  
EPA EST 2693-NJ-1

ACTIVE INGREDIENT	PERCENT
Cuprous Oxide	66.5%
Inert Ingredients	33.5%
	100%
Elemental Copper	58.36%

BEST AVAILABLE

ONE U.S. GALLON (3.785 LITERS)

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

FEB 26 1992

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, the pesticide registered under EPA Reg. No.

2693 135

## ULTRAKOTE ANTI FOULING BOTTOM PAINT DIRECTIONS FOR USE (CONTINUED)

**PRODUCT DESCRIPTION** ULTRAKOTE anti-fouling paint is the top of the line in antifouling paint technology. ULTRAKOTE is on free. Designed for maximum anti-fouling performance, ULTRAKOTE contains the highest concentration of the INTERLUX line. ULTRAKOTE is recommended for the hulls and transoms of pleasure boats, fishing boats, and agricultural boats. It will increase the rate of fouling. ULTRAKOTE has the same antifouling effect as the other Interlux antifouling paints, previously matched by ultra high lead copper antifouling.

**SURFACE PREPARATION** Surface must always be clean and dry prior to application. A painted surface must be wiped clean with 216 INTERLUX SPECIAL THINNER to remove any dirt or grease.

**GENERAL APPLICATION** For use on fiberglass, wood or properly primed metal surfaces. Apply a light to full coat with brush or spray.

**MIXING AND THINNING** Shake or mix well. For control of viscosity, thin with INTERLUX SPECIAL THINNER with 228 INTERLUX BRUSHING LIQUID. For use on bare wood thin 25% with 216 INTERLUX SPECIAL THINNER. For spray application thin up to 10% with 216 INTERLUX SPECIAL THINNER.

**THEORETICAL COVERAGE** 35 square feet per gallon.

**CLEAN UP** Use INTERLUX SPECIAL THINNER.

**ESTIMATED DRY TIMES** ULTRAKOTE is water resistant with a maximum dry time of 24 hours. For more information, see the ULTRAKOTE Maximum Dry Time chart on the side.

### APPLICATION SYSTEMS

**PREVIOUSLY PAINTED SURFACES** On previously painted surfaces, ULTRAKOTE should be applied over a compatible primer. If the surface is old, it is important that the old paint be removed. Wash the surface with 216 INTERLUX SPECIAL THINNER. If the surface is old, it is important that the old paint be removed. Wash the surface with 216 INTERLUX SPECIAL THINNER. If the surface is old, it is important that the old paint be removed. Wash the surface with 216 INTERLUX SPECIAL THINNER. If the surface is old, it is important that the old paint be removed. Wash the surface with 216 INTERLUX SPECIAL THINNER.

**BARE FIBERGLASS - NO SAND METHOD** Wash entire surface with 216 INTERLUX SPECIAL THINNER. Wash frequently. Repeat application if necessary to be sure all dirt is removed. Repair scratches and dents with 417A-418B EPOXY SURFACING & FAIRING COMPOUND. Sand the surface with 417A-418B EPOXY SURFACING & FAIRING COMPOUND. Apply a thin coat of AL210 INTERLUX FIBERGLASS PRIMER with brush or roller. Allow to dry. Apply a thin coat of ULTRAKOTE after the AL210 FIBERGLASS PRIMER has dried between 24 and 72 hours. NOTE: Apply a second coat of ULTRAKOTE after an overnight dry.

**BARE FIBERGLASS SANDING METHOD** Wash entire surface with 216 INTERLUX SPECIAL THINNER. Wash frequently. Repeat application. Repair scratches and dents with 417A-418B EPOXY SURFACING & FAIRING COMPOUND. Sand entire surface with 417A-418B EPOXY SURFACING & FAIRING COMPOUND. Apply a thin coat of ULTRAKOTE.

**BARE WOOD** Sand wet with 417A-418B EPOXY SURFACING & FAIRING COMPOUND. Wash with 216 INTERLUX SPECIAL THINNER. Wash frequently. Repeat application. Repair scratches and dents with 417A-418B EPOXY SURFACING & FAIRING COMPOUND. Apply a thin coat of ULTRAKOTE.

**ALUMINUM AND STEEL** Wash entire surface with 216 INTERLUX SPECIAL THINNER. Wash frequently. Repeat application. Repair scratches and dents with 417A-418B EPOXY SURFACING & FAIRING COMPOUND. Apply a thin coat of ULTRAKOTE.

## WARNING

### ENVIRONMENTAL HAZARDS

### PHYSICAL OR CHEMICAL HAZARD'S

**FLAMMABLE** Keep away from heat, sparks, or open flame.

### DIRECTIONS FOR USE

### STORAGE & DISPOSAL

International Paints

119500 Franca

119500 Franca

119500 Franca

119500 Franca

119500 Franca

119500 Franca

119500 Franca

119500 Franca