

PM 31

2693-135

5/22/97

14

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

MAY 22 1997

John P. Pazdera
Courtaulds Coatings Inc.
2270 Morris Avenue
Union, NJ. 07083


Subject: Ultra-Kote
EPA Registration No. 2693-135
Notification Per PR-Notice 95-2
Your Notification Dated May 9, 1997

Dear Mr. Pazdera:

This will acknowledge receipt of your notification to revise the Environmental Hazards section in accordance with PR Notice 93-10 and to add the "Product Descriptors" to the front panel submitted under the provisions of FIFRA section 3(c)9. Based on a review of the submitted material, the following comments apply.

The application is acceptable and the notification has been made a part of the records for this file.

Sincerely,



Marshall Swindell
Notification Coordinator
Antimicrobial Program Branch
Antimicrobial Division (7510W)

CONCURRENCES

SYMBOL	7510W						
SURNAME	P. Pazdera						
DATE	5/16/97						

284

Please read instructions on reverse before completing form.

Form Approved. OMB No. 2070-0060. Approval expires 05-31-98



United States
Environmental Protection Agency
Washington, DC 20460

<input type="checkbox"/>	Registration
<input type="checkbox"/>	Amendment
<input checked="" type="checkbox"/>	Other

OPP Identifier Number
245063

Application for Pesticide - Section I

1. Company/Product Number 2693-135	2. EPA Product Manager M. Swindell	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) Ultra-Kote	PM# 31	
5. Name and Address of Applicant (Include ZIP Code) Courtaulds Coatings Inc. 2270 Morris Avenue Union, NJ 07083 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3)(b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)
Notification - Minor Labeling Changes
- Expand Environmental Hazards section per PR Notice 93-10.
- Add Product Descriptors to front panel.

Section - III N/A

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes* <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Metal Plastic Glass Paper Other (Specify) _____		
* Certification must be submitted		If "Yes" Unit Packaging wgt. No. per container	If "Yes" Package wgt No. per container		
3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container		5. Location of Label Directions <input type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product	
6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled			<input type="checkbox"/> Other _____		

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name John P. Pazdera	Title Pesticide Registration Mgr.	Telephone No. (Include Area Code) 908-964-2288
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped)
2. Signature <i>John P. Pazdera</i>	3. Title Pesticide Registration Manager	
4. Typed Name John P. Pazdera	5. Date 5/9/97	



Ultra-Kote

- Excellent Protection for Severe Fouling Areas
- For Fiberglass, Wood or Steel Boats

KEEP OUT OF REACH OF CHILDREN

WARNING

See Side Panel for Additional Precautionary Statements



ONE U.S. GALLON
(3.785 L)

ACTIVE INGREDIENT	PERCENT
CUPROUS OXIDE	66.50%
INERT INGREDIENTS	33.50%
	100.00%

ELEMENTAL COPPER 66.50%

CONTAINS PETROLEUM DISTILLATES

EPA EST 2693-NJ-1

EPA REG NO. 2693-135

BEST AVAILABLE COPY

24 3/4

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. Wash thoroughly with soap and water after handling and before eating and smoking. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. When product is used in confined areas or applied by spraying, wear a respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health.

Statement of Practical Treatment: If in eyes: Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If on skin: Immediately remove contaminated clothing and wash with plenty of soap and water. Get medical attention. Wash contaminated clothing before reuse. If inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth. Get medical attention. If swallowed: Drink promptly a large quantity of water. Avoid alcohol. Get medical attention.

ENVIRONMENTAL HAZARD

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE Keep away from heat, sparks or open flame

GENERAL DESCRIPTION

ULTRA-KOTE antifouling bottom paint is an antifouling protective coating resistant to algae, barnacles and marine fouling.

NOTE:—Protective clothing and respirators should be used as described under Precautionary Statements.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. **PESTICIDE DISPOSAL:** Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act. **CONTAINER DISPOSAL:** Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved State and local procedures. If burned stay out of smoke.

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Courtauld's Coatings Inc. including surface preparation, proper application, and environmental conditions. Therefore, Courtauld's Coatings Inc. cannot guarantee the product's suitability for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. COURTAULD'S COATINGS INC SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use of this product, buyer agrees that the boat and its exclusive owner, if any, is limited to the refund of the purchase price or replacement of the product at Courtauld's Coatings Inc's option.

Interlux.

For information call 908-686-1300
Or write: Interlux, 2270 Morris Ave., Union, NJ 07083



ULTRA-KOTE® ANTIFOULING BOTTOM PAINT

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PRODUCT DESCRIPTION: ULTRA-KOTE antifouling paint is the top of the range epoxy ester, copper antifouling. ULTRA-KOTE is tin free. Designed for maximum antifouling performance, ULTRA-KOTE contains the highest copper loading in the INTERLUX line. ULTRA-KOTE is recommended for those areas of severe marine fouling or where pollution or agricultural run off increase the rate of fouling. ULTRA-KOTE has the added benefit of excellent color homogeneity and stability, previously unmatched by ultra high load copper antifouling.

SURFACE PREPARATION: Surface must always be clean and properly prepared prior to painting. All sanded surfaces must be wiped clean with 216 INTERLUX SPECIAL THINNER to remove sanding residue.

GENERAL APPLICATION: For use on fiberglass, wood or properly primed steel and lead. Apply at least two full coats with brush, roller or spray. Do not apply when temperature is below 50°F (10°C).

MIXING AND THINNING: Shake or mix well. Stir continuously while using. For brush or roller use, thin if necessary with 333 INTERLUX BRUSHING LIQUID. For use on bare wood, thin 15% with 216 INTERLUX SPECIAL THINNER. For spray application, thin up to 10% with 216 INTERLUX SPECIAL THINNER.

THEORETICAL COVERAGE: 350 square feet per gallon per coat.

CLEAN UP: INTERLUX SPECIAL THINNER 216.

ESTIMATED DRY TIMES: ULTRA-KOTE may be overcoated with itself after an overnight dry (16 hours). Prior to launch, allow to dry 16 hours. Maximum time to launch is 60 days.

APPLICATION SYSTEMS

PREVIOUSLY PAINTED SURFACES: Copolymer, vinyl and hard epoxy antifouling are the only suitable paints for overcoating with ULTRA-KOTE. It is important that these paints be in excellent condition to allow overcoating. Wash entire surface with 216 INTERLUX SPECIAL THINNER. Repeat application. Sand entire surface with 80 grit sandpaper to a clean, firmly attached surface. If a soft conventional antifouling paint is present, it must be removed. If there are excessive coats of old vinyl or hard epoxy antifouling on the surface to be painted, or weakness between or under these old coats, the "pulling" effect of ULTRA-KOTE may cause detachment. To prevent this from occurring, the excessive paint should be removed.

BARE FIBERGLASS - NO SAND METHOD: Wash entire surface with 202 FIBERGLASS SOLVENT WASH changing rags frequently. Repeat application if necessary to be sure all wax and mold release agents have been removed. Repair dents and scratches with 417A/418B EPOXY SURFACING & FAIRING COMPOUND; sand and clean repaired areas. Apply one thin coat of AL 200 INTERLUX FIBERGLASS PRIMER with brush or roller. Do not spray, do not sand. Apply first coat of ULTRA-KOTE after the AL 200 FIBERGLASS PRIMER has dried between 2-3 hours. **NO MORE-NO-LESS!** Apply second coat of ULTRA-KOTE after an overnight dry.

BARE FIBERGLASS SANDING METHOD: Wash entire surface with 202 FIBERGLASS SOLVENT WASH, changing rags frequently. Repeat application. Repair scratches and dents with 417A/418B EPOXY SURFACING & FAIRING COMPOUND. Sand entire surface with 80 grit production paper until a dull, matte appearance is obtained, wipe clean. Apply two coats of ULTRA-KOTE.

BARE WOOD: Sand well with 80 grit production paper; wipe surface clean. Apply first coat of ULTRA-KOTE after it has been thinned with 216 INTERLUX SPECIAL THINNER. Apply second coat (do not thin unless necessary) after an overnight dry.

ALUMINUM AND STEEL: Please contact the INTERLUX Technical Sales Department for full details on how to apply to steel and aluminum.

Rev. 4/97

BEST AVAILABLE COPY

7/17
FAC