

US ENVIRONMENTAL PROTECTION AGENCY
OFFICE OF PESTICIDES PROGRAMS
REGISTRATION DIVISION (75 767)
WASHINGTON, DC 20460

EPA REGISTRATION NO.
2693-140

DATE OF ISSUANCE
APR 08 1992

TERM OF ISSUANCE

NOTICE OF PESTICIDE: REGISTRATION
 Reregistration
(Under the Federal Insecticide, Fungicide,
and Rodenticide Act, as amended)

NAME OF PESTICIDE PRODUCT
Tri-Lux II Antifouling
490 Blue

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

Courtaulds Coatings
fka International Paint (USA), Inc.
2270 Morris Avenue
Union, NJ 07083

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an endorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit/cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.

2. Make the labeling changes listed below before you release the product for shipment:

- a. Add the phrase "EPA Registration No. 2693-140"
- b. Delete the phrase "tin free", this is an implied safety claim.
- c. If you do not intend to apply for alternate color formulations for this product in the near future you should delete the statement "available in a wide range of bright colors."

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL

DATE

3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



John H. Lee
Product Manager (31)
Antimicrobial Program Branch
Registration Division (H7505C)

Enclosures

BEST AVAILABLE

ACCEPTED
WITH COMMENTS
by EPA Label E-10

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
under EPA Reg. 152.10

0193-140

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
KEEP OUT OF REACH OF CHILDREN
WARNING**

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long sleeves, trousers and pants and hat. May be fatal if swallowed and inhaled. Do not breathe dust, vapors or spray mist. Wash hands thoroughly after use. Approved by the Ministry of Labour and Safety, Adm. Order 1000 and by the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after use.

Statement of Practical Treatment, if SWALLOWED: Drink plenty of water. Do not induce vomiting. If symptoms persist, get medical attention. If eye irritation persists, wash with water. If skin irritation persists, wash with soap and water.

ENVIRONMENTAL HAZARDS

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE

DIRECTIONS FOR USE

NOTE

GENERAL DESCRIPTION

STORAGE & DISPOSAL

PESTICIDE DISPOSAL

CONTAINER DISPOSAL

TRI-LUX II

PRODUCT DESCRIPTION: TRI-LUX II Antifouling Paint is a tin free, unique copolymer bottom paint. After TRI-LUX II forms a smooth racing finish. Although, specifically formulated for aluminum crafts and metal, compatible with fiberglass, wood, steel and lead. TRI-LUX II is ideal for aluminum outdrive units and outboard motor applications. Application instructions are followed. TRI-LUX II is very popular in inland fresh waters. Its hard paint finish.

SURFACE PREPARATION: Surface must always be clean and dry and properly prepared prior to painting. Clean with 216 INTERLUX SPECIAL THINNER to remove all sanding residue.

GENERAL APPLICATION: For use on aluminum, fiberglass, wood, steel and lead below the true waterline. A vent resistant roller or pure bristle brush. May be spray applied. Contact your INTERLUX Representative for more information.

MIXING AND THINNING: Shake or mix and stir continuously while using. When brushing or rolling, do not brush first coat on bare wood with 216 INTERLUX SPECIAL THINNER. In warmer environments 433 INTERLUX SPECIAL THINNER is recommended.

THEORETICAL COVERAGE: Depending on surface and condition, one gallon of TRI-LUX II will usually cover 350-400 sq. ft. of surface when brush applied.

CLEAN UP: Use 216 INTERLUX SPECIAL THINNER for cleaning paint brushes and equipment.

ESTIMATED DRY TIMES: TRI-LUX II may be overcoated with itself after 12 hours dry. Prior to launch, allow 3-5 days.

APPLICATION SYSTEMS

PREVIOUSLY PAINTED ALUMINUM: Remove all traces of loose paint and corrosion by sanding entire surface clean. Touch up bare spots by roughening metal with medium grit emery cloth. On aluminum hull metal followed by at least two full coats of TRI-LUX II.

BARE ALUMINUM: Small craft where sandblasting is not acceptable, i.e. aluminum pontoon boats, car top, etc. Apply INTERLUX SPECIAL THINNER to remove oil and grease. Uniformly roughen surface to a bright finish with 60 grit sandpaper. Clean of dust with 216 INTERLUX SPECIAL THINNER. Immediately apply one thin coat of 353-354 INTERLUX SPECIAL THINNER with 355 INTERLUX VINYLUX SOLVENT. Allow a minimum one hour dry and a maximum of 24 hours. Apply PRIMER. Apply at least two, preferably three coats observing the proper dry times between coats. Do not sand TRI-LUX II. We recommend that a different color of TRI-LUX II be applied for the first coat of a three coat system that the other two layers have worn away and that it is time to apply more TRI-LUX II.

On aluminum outdrive and lower units, apply at least two, preferably three, coats of 360 INTERLUX METAL as specified on label. Do not sand primer. Apply two coats of TRI-LUX II.

For large aluminum crafts capable of being sand blasted, contact your INTERLUX Representative for more information. For shafts, propellers, trim tabs, struts and thru hull fittings, these require special attention to improve adhesion. In all these areas the same as for bare aluminum but use three coats of 359 INTERLUX SPECIAL THINNER. The longevity of this system will probably not be equal to that of the remainder of the boat due to wear and tear.

PREVIOUSLY PAINTED FIBERGLASS AND WOOD - GOOD CONDITION: Remove all traces of loose paint and surface with 80 grit sandpaper. Apply surface primer. Apply two coats of TRI-LUX II.

BARE FIBERGLASS - NO SAND SYSTEM: Wash entire surface thoroughly with 216 INTERLUX SPECIAL THINNER. Apply INTERLUX SPECIAL THINNER with 355 INTERLUX VINYLUX SOLVENT. Allow a minimum one hour dry and a maximum of 24 hours. Apply PRIMER. Apply at least two, preferably three coats observing the proper dry times between coats. Do not sand TRI-LUX II. We recommend that a different color of TRI-LUX II be applied for the first coat of a three coat system that the other two layers have worn away and that it is time to apply more TRI-LUX II.

SANDING SYSTEM: Wash entire surface thoroughly with 216 INTERLUX SPECIAL THINNER. Apply surface primer. Apply two coats of TRI-LUX II. We recommend that a different color of TRI-LUX II be applied for the first coat of a three coat system that the other two layers have worn away and that it is time to apply more TRI-LUX II.

BARE WOOD: Sand entire surface thoroughly with 60 grit sandpaper. Apply surface primer. Apply two coats of TRI-LUX II. We recommend that a different color of TRI-LUX II be applied for the first coat of a three coat system that the other two layers have worn away and that it is time to apply more TRI-LUX II.

STEEL AND LEAD: Contact your INTERLUX Representative for specific details.

NOTE: TRI-LUX II is not recommended for use on leaded gasoline engines. Do not use TRI-LUX II on leaded gasoline engines. Do not use TRI-LUX II on leaded gasoline engines.

DISCLAIMER: The manufacturer makes no warranty, expressed or implied, for the use of this product in any application other than that for which it is intended. The user assumes all responsibility for the proper application of this product. The manufacturer shall not be held liable for any damage, injury or loss of property resulting from the use of this product in any application other than that for which it is intended.

ACTIVE INGREDIENTS	PERCENT
COPPER THIOCYANATE	22.86%
INERT INGREDIENTS	77.14%
	100.00%

ELEMENTAL COPPER 11.91%

CONTAINS PETROLEUM DISTILLATES

EPA EST 2093-NJ-1

EPA REG NO. 2093

Courtaulds Coatings Inc.
(International Paint)
2270 Morris Avenue, Union, NJ 07083 • (908) 681-1111
COURTAULDS COATINGS

BEST AVAILABLE