



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

July 22, 2021

Bathsheba Njuguna
PSRA Team Leader for,
International Paint, LLC
6001 Antoine Drive
Houston, TX 77091

Subject: Label Amendment – To add ABNs and make Minor Labeling Revisions
Product Name: INTERVIRON IVC BRA640 Red Antifouling
EPA Registration Number: 2693-142
Received Date: November 12, 2019
Decision Number: 00220695

Dear Ms. Njuguna:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. Pursuant to 40 CFR 156.10(a)(6) you must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under FIFRA and is subject to review by the Agency. See FIFRA section 2(p)(2). If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) lists examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process, FIFRA section 12(a)(1)(B). Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Assurance.

The following alternate brand names have been added to the product record:

- [ACT 4490U RED]
- [ACT 5590U GREEN]
- [ACT 6690U BLUE]
- [ACT 6696U DARK BLUE]
- [ACT 7740U GRAY WHITE]
- [ACT 7790U BLACK]
- [ACT 8890U BROWN]
- [INTERSPEED 640 POLISHING ANTIFOULING BRA640 RED]
- [INTERSPEED 640 POLISHING ANTIFOULING BRA641 BLUE]
- [INTERSPEED 640 POLISHING ANTIFOULING BRA642 BLACK]
- [INTERSPEED 640 POLISHING ANTIFOULING BRA643 GREEN]
- [INTERVIRON IVC – BLACK]
- [INTERVIRON IVC – BLUE]
- [INTERVIRON IVC – BROWN]
- [INTERVIRON IVC – GRAY]
- [INTERVIRON IVC – GREEN]
- [INTERVIRON IVC – RED]
- [PROGUARD ABLATIVE BLACK NAU993]
- [PROGUARD ABLATIVE BLUE NAU990]
- [PROGUARD ABLATIVE RED NAU992]
- [INTERLUX]
- [NAUTICAL]

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. If you have any questions, please contact Karen M. Leavy by phone at (703)-308-6237, or via email at Leavy.Karen@epa.gov.

Sincerely,



Aline Heffernan
Acting Product Manager Team 31
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

Enclosure

INTERVIRON IVC BRA 640 RED

[Eliminates Paint Build-Up and Heavy Sanding]

[Season Long Protection for Moderate to Heavy Fouling]

[Overcoats Existing Antifouling Paint]

[Reliable Performance at an Excellent Value]

[Season-Long Protection in Moderate to High Fouling Waters]

[Performance, value and reliability]

[Ablative Action – Eliminates Paint Build Up]

[FOR COMMERCIAL USE ONLY]

[For specific state registrations contact your International Representative]

ACCEPTED

Jul 22, 2021

Under the Federal Insecticide, Fungicide
and Rodenticide Act as amended, for the
pesticide registered under
EPA Reg. No. 2693-142

[Alternative Brand Names (ABNs):]

- [ACT 4490U RED]
 - [ACT 5590U GREEN]
 - [ACT 6690U BLUE]
 - [ACT 6696U DARK BLUE]
 - [ACT 7740U GRAY WHITE]
 - [ACT 7790U BLACK]
 - [ACT 8890U BROWN]
 - [INTERSPEED 640 POLISHING ANTIFOULING BRA640 RED]
 - [INTERSPEED 640 POLISHING ANTIFOULING BRA641 BLUE]
 - [INTERSPEED 640 POLISHING ANTIFOULING BRA642 BLACK]
 - [INTERSPEED 640 POLISHING ANTIFOULING BRA643 GREEN]
 - [INTERVIRON IVC – BLACK]
 - [INTERVIRON IVC – BLUE]
 - [INTERVIRON IVC – BROWN]
 - [INTERVIRON IVC – GRAY]
 - [INTERVIRON IVC – GREEN]
 - [INTERVIRON IVC – RED]
 - [PROGUARD ABLATIVE BLACK NAU993]
 - [PROGUARD ABLATIVE BLUE NAU990]
 - [PROGUARD ABLATIVE RED NAU992]
 - [INTERLUX]
 - [NAUTICAL]
-

[FRONT PANEL]

KEEP OUT OF REACH OF CHILDREN

WARNING

See side panel for additional Precautionary Statements

Active Ingredients:

Cuprous Oxide 41.97%

Inert Ingredients: 58.03%
100.00%

Copper as Metallic = 37.11%

Contains petroleum distillates.

EPA Reg. No. 2693-142

EPA Est. No. 2693-TX-1

NET CONTENTS: FIVE U.S. GALLONS (18.927 LITERS)

[DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of INTERNATIONAL PAINT, LLC., including surface preparations, proper application and environmental conditions. Therefore, INTERNATIONAL PAINT, LLC., cannot guarantee this product's suitability for your particular purpose of application. To the extent consistent with applicable law, INTERNATIONAL PAINT, LLC., EXPRESSLY DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE or otherwise that extend beyond the statements made on this label, and shall not be liable for special, incidental, or consequential damages resulting from the use or handling of this product, the exclusive remedy being the replacement of this product. To the extent consistent with applicable law, buyer/user assumes all risk of possession, handling, or use of this material when use and/or handling is contrary to label instructions.]

**International Paint, LLC.
6001 Antoine Drive
Houston, Texas 77091**

[Interlux.com]

[SIDE PANEL]

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

WARNING

May be fatal if swallowed or inhaled. Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. Do not breathe vapor or spray mist. While painting or sanding or sandblasting boat surfaces, wear a NIOSH approved particulate filter with any N, R, P filter with NIOSH approval number prefix TC-84A.; or a NIOSH approved powered air purifying respirator with an HE filter with NIOSH approval number prefix TC-21C.

Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

FIRST AID	
If Swallowed:	<ul style="list-style-type: none">• Call a poison control center or doctor immediately for treatment advice.• Have person sip a glass of water if able to swallow.• Do not induce vomiting unless told to do so by a poison control center or doctor.• Do not give anything by mouth to an unconscious person.
If on skin or clothing:	<ul style="list-style-type: none">• Take off contaminated clothing.• Rinse skin immediately with plenty of water for 15-20 minutes.• Call a poison control center or doctor for treatment advice.•
If inhaled:	<ul style="list-style-type: none">• Move person to fresh air.• If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.• Call a poison control, center or doctor for further treatment advice.
If in eyes:	<ul style="list-style-type: none">• Hold eye open and rinse slowly and gently with water for 15-20 minutes.• Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.• Call a poison control center or doctor for treatment advice.
OTHER: Have the product container or label with you when calling a poison control center or doctor or going for treatment. For medical emergencies, call the poison control center at 1-800-222-1222. For general information on this product, contact the National Pesticides Information Center (NPIC) at 1-800-858-7378, Monday through Friday, 8 AM to 12 PM PST, or at http://npic.orst.edu .	

Note to Physician: Contains petroleum distillate- vomiting may cause aspiration pneumonia.

ENVIRONMENTAL HAZARD

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and particulate generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System [NPDES] permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS

Flammable. Keep away from heat and open flame.

[SUBSET A – For Heavy Duty Marine Market]

PRODUCT DESCRIPTION: A high performance, tributyltin free, polishing antifouling resistant to algae, barnacles and other marine fouling. For use in fresh, salt and brackish waters. Prevents coating build-up. At subsequent drydocking's, it is only necessary to top up the system. Low VOC. This product is for industrial use and professional application only. Not for sale to the general public.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labelling.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE: Exposure to air and extremes of temperature must be avoided. Keep the container firmly closed. Keep out of direct sunlight. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING: Nonrefillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

[FOR CHEMICAL EMERGENCY, SPILL, LEAK, EXPOSURE OR ACCIDENT, CALL TOLL FREE: CHEMTREC 1-800-424-9300 (DAY OR NIGHT).]

PRODUCT INFORMATION:

Finish/Sheen: Semi-Gloss (ASTM D-523)

Converter: One pack

Volume Solids: 62% ± 2% (ASTM D-2697)

Mix Ratio: One pack

Flash Point: 79°F(26°C) (Setaflash) (ASTM D-3278)

Film Thickness: 4.0 mils (102 microns) dry specified equivalent to 6.5 mils (165 microns) wet. 4.0-5.0 mils (102 - 127 microns) dry practical range equivalent to 6.5-8.1 mils (165-206 microns) wet.

Theoretical Coverage: 248 sq. ft./gal. (4.0 mils(102 microns)) **Allow appropriate loss factors.**

APPLICATION DETAILS:

Method: Airless spray, brush or roller
 Thinner: Not recommended. If necessary, use GTA007, see thinning section.
 Cleaner: GTA007

Drying Time (hours)	(ASTM D) (1640 7.5.1)	Overcoating Interval by		Minimum Drying Time * before flooding (for 2x5 mil (125 microns) DFT (coats)
		Self	(ASTM D- 1640 7.8)	
Substrate Temp.	Touch	Minimum	Maximum	
41°F (5°C)	12	24	Indefinite	3 days
73°F (23°C)	6	12	Indefinite	2 days
95°F (35°C)	4	6	Indefinite	1 day

*Refer to your International Representative for minimum drying time before flooding at higher dry film thicknesses and to Limitations section for maximum recommended atmospheric exposure time before flooding.

REGULATORY DATA

VOC 3.21 lbs./gal. (385 g/l) as supplied.
 MIL SPEC MIL-P-24647B, Type I, CL IA, Gr A & B, Applications 1 & 2

SYSTEMS AND COMPATIBILITY: International should be consulted for detailed application advice, specification recommendations and as to the suitability of specific products on individual vessels.

LIMITATIONS: Apply in good weather when air and surface temperatures are above 35°F (2°C). Surface temperature must be at least 5°F (3°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40° and 100°F (4-38°C).

Prolonged atmospheric exposure of this product may detract from antifouling performance. Recommended maximum exposure time before flooding:

Temperate conditions 28 days
 Tropical conditions 7 days

These times may be extended under certain conditions. Contact your local International Representative for advice.

Technical and application data herein is for the purpose of establishing a general guideline of the coating and proper coating application procedures. Test performance results were obtained in a controlled laboratory environment and International makes no claim that the exhibited published test results, or any other tests,

accurately represent results actually found in all field environments. As application, environmental and design factors can vary significantly, due care should be exercised in the selection, verification of performance, and use of the coating.

SURFACE PREPARATION: Paint only clean, dry surfaces. Remove all grease, oil, soluble contaminants and other detrimental foreign matter by “solvent cleaning” (SSPC-SPI).

NEW CONSTRUCTION: Dependent on yard procedures, consult International.

UNPAINTED SURFACES: Prepare surface and apply recommended primer. Apply one or more coats of this product as specified. (Consult the relevant primer data sheet for surface preparation and overcoating information.)

RECOATING AND UPGRADING OF APPROVED SYSTEMS: Use controlled close high-pressure fresh water washing (3,000 psi, 211 kg./sq. cm.) to clean the entire area and remove any leached layer at the surface of the existing antifouling system. Repair corroded areas with the recommended anticorrosive primer and apply a spot coat of Interspeed 640 within the overcoating interval specified for the primer (consult relevant primer data sheet).

Apply the specified numbers of full coats of this product.

MIXING: This material is a one component coating. Always mix thoroughly with a power agitator before application.

APPLICATION: Apply by airless spray only. Application by other methods, brush or roller, may require more than one coat and is suggested for small areas only or initial stripe coating. Apply 6.5 mils (166 microns) wet which will yield 4.0 mils (102 microns) dry film thickness. Consult the following equipment recommendations or utilize suitable equal.

EQUIPMENT:

Brush: Use appropriate size China bristle brush.

Roller: Use All Purpose Roller Cover with 3/8” (9.5mm) pile smooth to medium. Prewash roller cover to remove loose fibers prior to use.

Airless Spray: Minimum 28:1 ratio pump; .021”-.026” (533-660 microns) orifice tip; 3/8” (9.5mm) ID high pressure material hose; 60 mesh tip filter.

THINNING: DO NOT THIN BEYOND YOUR STATE'S COMPLIANCY. Material is supplied at spray viscosity and normally does not need thinning. If thinning is necessary, thin up to a maximum of 4 ounces (118ml) per gallon (3.79 L) with International GTA007 Thinner.

WORK STOPPAGES & CLEAN UP: Clean all equipment immediately after use with International GTA007 Thinner. Spray equipment requires flushing with this solvent. It is good working practice to periodically flush out spray equipment during the course of the working day. Frequency will depend upon factors such as amount sprayed, temperature and elapsed time including work stoppages. Monitor material condition.

WELDING: In the event welding or flame cutting is performed on metal coated with this product, do so in accordance with instruction in ANSI/ASC Z49.1 “Safety in Welding and Cutting”.

SAFETY: This product is not to be used without reference to the current relevant Product Data Sheet and Material Safety Data Sheet (MSDS). Prior to use, obtain, consult and follow both the Material Safety and Product Data Sheets for this product for details concerning both product and health and safety information. Read and follow all precautionary notices on the Material Safety and Product Data Sheets and this container label. If you do not fully understand these warnings and instructions or if you cannot strictly comply with them, do not use this product. Proper ventilation and protective measures must be provided during application and drying to keep solvent vapor concentrations within safe limits and to protect against toxic or oxygen deficient hazards and/or flash fire. Actual safety measures are dependent on application methods and work environment. This safety information is not a substitute for that contained in the Material Safety and Product Data Sheets. Medical Advisory Number 1-800-854-6813.

[UN Shipping No: 1263]

[STORAGE: Store in cool, dry conditions.]

[SHELF LIFE: One year minimum from date of manufacture when maintained in protected storage at 40-100°F (4-38°C). Subject to reinspection thereafter.]

[All representations and statements concerning the product on this label are accurate to the best of International's knowledge. Any statements herein are not intended to be specific recommendations or warranties of any product, combination of products or fitness for any particular purpose. Any warranty, if given, or specific Terms and Conditions of Sale are contained in International's Terms and Conditions of Sale. You should request a copy of this document and review it carefully.]

[International and Interspeed are trademarks of the AkzoNobel Group of Companies.]

[Alternate Directions for Use] [SUBSET B – For Yacht Market]

PRODUCT DESCRIPTION: [ACT, alternate brand names, this product] uses Ablative Copolymer Technology to enable it to wash away with use, constantly exposing fresh and effective biocide. This Ablative Copolymer Technology also eliminates the build-up of old spent coatings and the heavy sanding needed to remove them. [ACT, alternate brand names, this product] provides season long protection against algae, barnacles and other forms of marine fouling in waters with moderate to heavy fouling. For use in fresh, salt and brackish waters.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labelling.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE: Exposure to air and extremes of temperature must be avoided. Keep the container firmly closed. Keep out of direct sunlight. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING: Nonrefillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

[FOR CHEMICAL EMERGENCY, SPILL, LEAK, EXPOSURE OR ACCIDENT, CALL TOLL FREE: CHEMTREC 1-800-424-9300 (DAY OR NIGHT).]

COMPATIBILITY: [Alternate brand names, ACT, this product] can be applied over most antifouling paints as long as the old coating is tightly adhered and in sound condition. When applying over conventional antifouling paints, thoroughly sand with [80,100, 120, 80-120] [grit, grade, grit wet and dry, grade wet or dry] sand paper. If applying over self-polishing typed copolymers antifouling, heavy sanding is required.

V.O.C: Less than 370 grams / liter

COATS REQUIRED: 2 coats.

THINNER: [Special Thinner 216, Special Thinner, Brush-Ease 433™, Antifouling Thinner, Yacht Thinner, Boat Thinner, Acetone]

DRY TIMES: Touch dry 1 hours 73°F (23°C) To Recoat – 12 hours

THINNING: Thin only if necessary.

To Launch – Minimum 16 hours

Do not exceed 10% by volume.

Maximum 60 days

CLEAN UP: [Special Thinner 216, Special Thinner, Brush-Ease 433™, Antifouling Thinner, Yacht Thinner, Boat Thinner, Acetone]

THEORETICAL COVERAGE: 455sq.ft/gal/coat

APPLICATION TEMPERATURE: 50°F (10°C) and above

APPLICATION SYSTEMS

PREVIOUSLY PAINTED SURFACES – GOOD CONDITION. Remove all traces of loose paint and contamination by sanding the entire surface with [80, 80-120, 100, 120] [grit, grade, wet or dry] sandpaper: wipe surface clean with [Special Thinner 216, Special Thinner, Thinner 216, Antifouling Thinner, Yacht Thinner, Boat Thinner, Acetone]. Apply 2 coats of [ACT, alternative brand name, this product].

PREVIOUSLY PAINTED SURFACES – POOR CONDITION: Completely remove all old antifouling paint [by paint stripper, sanding, abrasive media blasting, sanding or abrasive media blasting] for [fiberglass, epoxy, wood, or, sandblasting steel surfaces to a near white metal]. Proceed with application system for bare system below.

BARE FIBERGLASS – (POLYESTER or VINYLESTER)

It is very important that bare fiberglass be properly prepared in order to prevent delamination of the antifouling paint. Begin by scrubbing the surface thoroughly with a stiff brush using soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry.

Remove mold release wax using one of the following products: [Interlux Fiberglass Surface Prep YMA601V, Interlux Fiberglass Solvent Wash 202, Fiberglass Surface Prep YMA601V, Fiberglass Solvent Wash 202, Fiberglass Surface Prep, Solvent Wash, Acetone, Boat Prep] following the product label instructions. To be certain that all the contamination has been removed, run water over the surface; if the water beads up or separates, clean again. When the water sheets off, all contamination has been removed. After the surfaces has been properly cleaned, proceed with one of the application systems below.

BARE FIBERGLASS – NO SAND SYSTEM: Clean the surface using [Interlux Fiberglass Surface Prep YMA601V, Fiberglass Surface Prep, Boat Prep] following the preparation procedure described. Apply one coat of [InterProtect 2000E, InterProtect HS, InterProtect, Sandless Primer] following the label instructions for applying the primer and overcoating with antifouling paint. Apply 2 coats of [ACT, alternative brand name, this product] allowing for the appropriate dry times.

BARE FIBERGLASS – SANDING SYSTEM: Clean the surface following the preparations procedure described. Sand the entire surface with [80-120, 80, 100, 120] [grit, grade, wet or dry] sandpaper and wipe clean with [Interlux Fiberglass Solvent Wash 202, Fiberglass Solvent Wash 202, Fiberglass Solvent Wash, Solvent Wash,

Acetone, Boat Thinner, Interlux Fiberglass Surface Prep YMA601V, Fiberglass Surface Prep YMA601V, Fiberglass Surface Prep, Surface Prep, Boat Surface Prep] to remove sanding residue. Repair any surface imperfections with [Watertite, Watertite Epoxy Filler, Interfill, Interfill Epoxy Filler, Epoxy Filler, Boat Filler]. Sand and wipe clean. Apply 2 coats of [ACT, alternative brand name, this product] allowing for appropriate dry times.

BARE WOOD: Sand the entire surface with [80-120, 80, 100, 120] [grit, grade, wet or dry] sandpaper and wipe clean with [Special Thinner 216, Interlux Special Thinner 216, Special Thinner, Acetone, Fiberglass Solvent Wash 202, Interlux Fiberglass Solvent Wash 202, Solvent Wash, Boat Thinner]. Repair imperfections with [Watertite, Watertite Epoxy Filler, Interfill, Interfill Epoxy Filler]. Apply the first coat of this product thinned 10% with [Special Thinner 216, Interlux Special Thinner 216, Special Thinner, Acetone, Interlux Brush Ease 433, Brush Ease 433, Brush Ease]. Fill seams with [Seam Compound 30, Seam Compound, Seam Filler], if necessary. Apply 2nd coat of [ACT, alternative brand name, this product] unthinned, following the overcoating times.

UNDERWATER METALS: Contact the Interlux Technical Service Department at [Interlux.com, interluxtechnicalservice@akzonobel.com, 1-800-468-7589] for full information on how to properly prime underwater metals. DO NOT USE ON ALUMINUM.

[Interlux and the AkzoNobel logo are trademarks of Akzo Nobel.]

[Alternate Directions for Use] [SUBSET C – For Yacht Market]

PRODUCT DESCRIPTION: [Alternative brand name, Proguard Ablative, this product] is performance, value and reliability all in one. [Alternative brand name, Proguard Ablative, this product] is an all-purpose antifouling paint formulated to erode away with use reducing paint build-up. [Alternative brand name, Proguard Ablative, this product] provides season-long protection in moderate to high fouling waters and can be applied directly over most properly prepared antifouling paints. Recommended for use on the underwater areas of fiberglass, wood, and properly primed metal (except aluminum) boat hulls and can be used in fresh, salt and brackish waters.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labelling.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE: Exposure to air and extremes of temperature must be avoided. Keep the container firmly closed. Keep out of direct sunlight. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING: Nonrefillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

[FOR CHEMICAL EMERGENCY, SPILL, LEAK, EXPOSURE OR ACCIDENT, CALL TOLL FREE: CHEMTREC 1-800-424-9300 (DAY OR NIGHT).]

NOTE: Colors may fade or change above the waterline. Stir well before and during use, can be applied by brush, roller or spray. Do not use on aluminum.

COMPATIBILITY: [Alternative brand name, Proguard Ablative, this product] can be applied over most other antifouling paints provided the old coating is tightly adhered, is in sound condition and has been thoroughly sanded with 80 grit wet-or-dry sandpaper.

V.O.C.: Less than 330 grams/liter (2.75lbs./gal.)

THEORETICAL COVERAGE: 455 sq. ft/gal at 3.6 mils WFT and 2 mils DFT.

CLEAN UP: [Special thinner 216, Special Thinner, Boat Thinner, Brush Ease, Acetone or Xylene,¹].

THINNER: [Special thinner 216, Special Thinner, Boat Thinner, Brush Ease, Acetone or Xylene, ²] (thin only when necessary, do not exceed 10% by volume).

APPLICATION TEMPERATURE: 50°F (10°C)* and above (air and hull).

*If the air temperature falls below 50° F (10° C) during the dry time extend the dry times by 12 hours minimum.

ESTIMATED DRY TIMES:

Temperature	Touch Dry	Immersion	Over-Coating Time	Immersion Time
°F (°C)	Minimum	Minimum	Minimum	Maximum
50°F (10°C)	3 Hours	12 Hours	16 Hours	60 Days
77°F (25°C)	2 Hours	12 Hour	16 Hours	60 Days
95°F (35°C)	1 Hour	8 Hours	16 Hours	60 Days

PREPARATION/APPLICATION

BARE FIBERGLASS: It is very important that bare fiberglass be properly prepared in order to prevent delamination of the antifouling paint. Begin by scrubbing the surface thoroughly with a stiff brush using soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry.

Remove mold release wax using one of the following products: [Solvent Wash, Acetone, Boat Prep, Boat Thinner] following the product label instructions. To be certain that all the contamination has been removed, run water over the surface; if the water beads up or separates, clean again. When the water sheets off, all contamination has been removed. After the surfaces has been properly cleaned, proceed with one of the application systems below.

PREVIOUSLY PAINTED SURFACE - GOOD CONDITION:

Remove all traces of loose paint and contamination by sanding the entire surface with [80, 80-120, 100, 120] [grit, grade, wet or dry] sandpaper: wipe surface clean with [Antifouling Thinner, Yacht Thinner, Boat Thinner, Acetone]. Apply 2 coats of [Proguard Ablative, Alternative Brand Name, this product]

PREVIOUSLY PAINTED SURFACE - POOR CONDITION:

Completely remove all old antifouling paint [by paint stripper, sanding, abrasive media blasting, sanding or abrasive media blasting] for [fiberglass, epoxy, wood, or, sandblasting steel surfaces to a near white metal]. Proceed with application system for bare system.

BARE WOOD: Sand the entire surface with [80-120, 80, 100, 120] [grit, grade, wet or dry]; wipe surface clean with [Antifouling Thinner, Yacht Thinner, Boat Thinner, Acetone, Xylene, ¹] using the two-rag method before and after sanding. Apply the first coat of this product thinned 10% with [Antifouling Thinner, Yacht Thinner,

Boat Thinner, Acetone, Xylene, ^{2]} Apply one coat of [Proguard Ablative, alternative brand name, this product] allowing for appropriate dry times.

UNDERWATER METALS: Apply an approved underwater metal primer as per manufacturer's instructions. Apply two coats of This product allowing for appropriate dry times. Do not use on aluminum.

MAINTENANCE

Antifoulings are not effective under all conditions. Pollution, usage and natural occurrences can adversely affect an antifouling paint's performance. Therefore, we strongly suggest that the antifouling paints are checked regularly to make sure it is clean, and that no growth is occurring. The less a boat is used, and the longer the idle periods are the higher the chance of fouling. Properly functioning antifouling paints will repel hard growth and requires only occasional light wiping with a soft cloth or Scotch-Brite™ pad to remove slime. Aggressive cleaning of antifouling paints, using tools such as scrubbing pads and brushes, will shorten the effective life of the paint, and should only be used if necessary.

[¹ May not be an approved solvent for use in all areas.]

[² Thinning of this product may affect the V.O.C. compliance of this product.]

Please consult your local government regulations for recommendations for volatile organic compound (VOC) limits.