

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

JUL 23 1997

Courtaulds Coatings Inc.  
2270 Morris Avenue  
Union, NJ. 07083

Subject: Ultra-Kote 2669H Blue  
EPA Registration no. 2693-143  
Notification Per PR-Notice 95-2  
Your Notification Dated June 25, 1997

Dear Mr. Pazdera:

This will acknowledge receipt of your notification to add the "Product Descriptors" to the front panel submitted under the provisions of FIFRA section 3(c)9. Based on a review of the submitted material, the following comments apply.

The application is acceptable and the notification has been made a part of the records for this file.

Sincerely,

*Paul Hasty for*

Marshall Swindell  
Notification Coordinator  
Antimicrobial Program Branch  
Antimicrobial Division (7510W)

CONCURRENCES

SYMBOL	7510W						
SURNAME	P. Hasty						
DATE	7/22/97						

276

Please read instructions on reverse before completing form.

Form Approved. OMB No. 2070-0060. Approval expires 05-31-98



United States  
Environmental Protection Agency  
Washington, DC 20460

Registration  
 Amendment  
 Other

OPP Identifier Number  
245079

Application for Pesticide - Section I

1. Company/Product Number 2693-143	2. EPA Product Manager M. Swindell	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) Ultra-Kote 2669H Blue	PM# 31	
5. Name and Address of Applicant (Include ZIP Code) Courtaulds Coatings Inc. 2270 Morris Avenue Union, NJ 07083 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

Notification - Minor Labeling Changes  
- Add Product Descriptors to front panel

Section - III N/A


1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes* <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No		<input type="checkbox"/> Metal	<input type="checkbox"/> Plastic
* Certification must submitted		If "Yes" Unit Packaging wgt.	No. per container	<input type="checkbox"/> Glass	<input type="checkbox"/> Paper
		If "Yes" Package wgt	No. per container	<input type="checkbox"/> Other (Specify) _____	
3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container		5. Location of Label Directions <input type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product	
6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled			<input type="checkbox"/> Other _____		

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name John P. Pazdera	Title Pesticide Registration Mgr.	Telephone No. (Include Area Code) 908-964-2288
<b>Certification</b> I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped)
2. Signature <i>John P. Pazdera</i>	3. Title Pesticide Registration Manager	
4. Typed Name John P. Pazdera	5. Date 6/25/97	

CERTIFICATION FOR NOTIFICATION

"This notification is consistent with the provisions of PR Notice 95-2 and EPA regulations at 40 CFR 152.46, and no other changes have been made to the labeling or the confidential statement of formula for this product. I understand that it is a violation of 18 U.S.C. Sec. 1001 to willfully make any false statement to EPA. I further understand that if this notification is not consistent with the terms of PR Notice 95-2 and 40 CFR 152.46, this product may be in violation of FIFRA and I may be subject to enforcement action and penalties under sections 12 and 14 of FIFRA."

  
John P. Pazdera  
Pesticide Registration Manager

4 7 6

# *Ultra-Kote*

## *2669H Blue*

EXCELLENT PROTECTION FOR SEVERE FOULING AREAS  
FOR FIBERGLASS, WOOD OR STEEL BOATS

KEEP OUT OF REACH OF CHILDREN  
WARNING

See side panel for additional precautionary statements.

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

---

EPA Registration No. 2693-143

EPA Establishment No. 2693-NJ1

Active Ingredient:		
Cuprous Oxide	=	72.25%
Inert Ingredients:	=	27.75%
		<hr/>
		100.00%
Elemental Copper	=	64.10%

---

**PRECAUTIONARY STATEMENTS**

**WARNING**

**HAZARD TO HUMANS AND DOMESTIC ANIMALS:**

Causes eye irritation. Harmful if swallowed or absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

**STATEMENT OF PRACTICAL TREATMENT:**

**IF SWALLOWED:** Promptly drink large quantities of water. Avoid alcohol. Get medical attention.

**IF IN EYES:** Flush with plenty of water. Get medical attention if irritation persists.

**IF ON SKIN:** Wash with plenty of soap and water. Get medical attention if irritation persists.

**IF INHALED:** Remove victim to fresh air. If not breathing give artificial respiration, preferably mouth to mouth. Get medical attention.

**ENVIRONMENTAL HAZARD**

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**PHYSICAL OR CHEMICAL HAZARD**

Flammable. Keep away from heat and open flame.

**STORAGE AND DISPOSAL**

**PESTICIDE DISPOSAL:** Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State, or local disposal authorities.

**CONTAINER DISPOSAL:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in an approved landfill, or by other approved state and local alternative procedures.

6 7 6

## ULTRA-KOTE® 2669H BLUE ANTIFOULING BOTTOM PAINT

### DIRECTIONS FOR USE:

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

**PRODUCT DESCRIPTION:** ULTRA-KOTE® 2669H BLUE is a copper product for commercial and non-commercial use containing cuprous oxide. ULTRA-KOTE® also has excellent color stability. ULTRA-KOTE® can be applied to fiberglass, wood and properly prepared steel boat hulls. Use ULTRA-KOTE® where the fouling challenge is severe such as warm/tropical marine waters or in areas where runoff from the land causes higher algae and grass growth. ULTRA-KOTE® gives you protection no matter where you are.

**GENERAL APPLICATION:** ULTRA-KOTE® can be applied over most other antifouling paints, but it is important that these coatings be in excellent condition, well adhered to the hull and any loose or flaking paint has been removed. Soft antifouling paints should be removed. It is best to apply ULTRA-KOTE® between 50°F and 95° F.

**MIXING AND THINNING:** Shake or mix well. Stir continuously while using. For brush or roller use, thin if necessary with INTERLUX BRUSH-EASE 433. For use on bare wood, thin 15% with INTERLUX SPECIAL THINNER 216. For spray application, thin up to 10% with INTERLUX SPECIAL THINNER 216.

**THEORETICAL COVERAGE:** 450 square feet per gallon per coat.

**CLEAN UP:** INTERLUX SPECIAL THINNER 216 or INTERLUX BRUSH-EASE 433.

**ESTIMATED DRY TIMES:** ULTRA-KOTE® may be overcoated with itself after an overnight dry. Prior to launch, allow an overnight dry. Maximum time to launch is 60 days.

### APPLICATION SYSTEMS

**PREVIOUSLY PAINTED SURFACES:** Sand the entire surface with 80 grit sandpaper. Wipe the surface with INTERLUX SPECIAL THINNER 216. Apply two coats of ULTRA-KOTE®.

**BARE FIBERGLASS - NO SANDING METHOD:** Wash entire surface with FIBERGLASS SOLVENT WASH 202 changing rags frequently. Repeat application to be sure all wax and mold release agents have been removed. Repair dents and scratches with EPOXY SURFACING & FAIRING COMPOUND 417A/418B; sand and clean repaired areas. Apply one thin coat of INTERLUX FIBERGLASS PRIMER AL200 with brush or roller. Do not spray, do not sand. Apply first coat of ULTRA-KOTE® after the FIBERGLASS PRIMER AL200 has dried for two hours but no more than three. Apply second coat of ULTRA-KOTE after an overnight dry.

**BARE FIBERGLASS SANDING METHOD:** Wash entire surface with FIBERGLASS SOLVENT WASH 202, changing rags frequently to be sure all contamination is removed. Repair scratches and dents with EPOXY SURFACING & FAIRING COMPOUND 417A/418B. Sand entire surface with 80 grit production sandpaper until a dull, matte appearance is obtained, wipe clean. Apply two coat of ULTRA-KOTE®.

**BARE WOOD:** Sand well with 80 grit production paper, wipe surface clean. Apply first coat of ULTRA-KOTE® after it has been thinned 15% with INTERLUX SPECIAL THINNER 216. Apply second coat after an overnight dry. (Do not thin second coat unless necessary).

**UNDERWATER METALS:** Please contact the INTERLUX Technical Sales Department for full details on how to apply to underwater metals. Do not use on aluminum.

**DISCLAIMER:** The performance of any marine coating depends on many factors outside the control of Courtaulds Coatings Inc. including the surface preparation, proper application and the environmental conditions. Therefore, Courtaulds Coatings Inc. cannot guarantee the suitability of this product for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. COURTAULDS COATINGS INC. SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use, of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Courtaulds Coatings Inc.'s option.

Courtaulds Coatings Inc.  
400 S. 13th Street, Louisville, KY 40203

Union, NJ

Louisville, KY Montreal, Quebec

Houston, TX