

<p>US ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (TS 767) WASHINGTON, DC 20460</p> <p><b>NOTICE OF PESTICIDE:</b> <input type="checkbox"/> REGISTRATION <input type="checkbox"/> REREGERISTRATION</p> <p><i>(Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)</i></p>	<p>EPA REGISTRATION NO. <b>2693-144</b></p> <p>TERM OF ISSUANCE</p>	<p>DATE OF ISSUANCE <b>SEP 0 0 1991</b></p>
<p>NAME OF PESTICIDE PRODUCT <b>Ultra-Kote 2449H Red</b></p>		
<p>NAME AND ADDRESS OF REGISTRANT (Include ZIP code)</p> <p><b>Courtaulds Coatings Inc 400 South 13th Street Louisville, KY 40201</b></p>		
<p><b>NOTE:</b> Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.</p>		
<p>On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.</p> <p>A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.</p> <p>Registration is in no way to be construed as an endorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.</p> <p><b>This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:</b></p> <ol style="list-style-type: none"> <li>1. Submit/cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.</li> <li>2. Make the labeling changes listed below before you release the product for shipment:             <ol style="list-style-type: none"> <li>a. Add the phrase "EPA Registration No. 2693-144".</li> <li>b. Include the heading: Directions for Use.</li> <li>c. Delete the astericks in the ingredient section.</li> <li>d. Delete the word: Premium (1st paragraph-right panel). NOTE: Superlatives are not permitted on labels.</li> </ol> </li> </ol> <p><input checked="" type="checkbox"/> ATTACHMENT IS APPLICABLE</p>		
<p>SIGNATURE OF APPROVING OFFICIAL</p>		

e. Revise "...properly prepared steel hulls..." to read: "...properly prepared steel boat hulls..."

f. Revise "...warm or tropical waters or in areas..." to read: "...warm/tropical marine waters or ..."

g. Clarify these "...areas of runoff from the land..." Is this type of statement really necessary for antifouling marine boat bottom paints?

h. Delete the following comparison claims:

"...is the highest cuprous oxide content of all leading yacht antifouling paints.

"... makes ultra-kote the top of the line epoxy ester antifouling paint.

"...previously unmatched in high copper content antifouling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,

Marshall Swindell  
Acting Product Manager (31)  
Antimicrobial Program Branch  
Registration Division (H7505C)

CONCURRENCES							
SYMBOL							
SURNAME							
DATE							

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

SEP 6 6 1994

Order the Federal Insecticide,  
Fungicide, and Rodenticide  
Act amendments to the  
registered under EPA Reg. No.

2693-144

Inte

NOW!  
WITH MORE COPPER

**PRECAUTIONARY STATEMENTS**

**WARNING**

**HAZARD TO HUMANS AND DOMESTIC ANIMALS:**

Causes eye irritation. Harmful if swallowed or absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

**STATEMENT OF PRACTICAL TREATMENT:**

IF SWALLOWED: Promptly drink large quantities of water. Avoid alcohol. Get medical attention.  
IF IN EYES: Flush with plenty of water. Get medical attention if irritation persists.  
IF ON SKIN: Wash with plenty of soap and water. Get medical attention if irritation persists.  
IF INHALED: Remove victim to fresh air. If not breathing give artificial respiration, preferably mouth to mouth. Get medical attention.

**ENVIRONMENTAL HAZARD**

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**PHYSICAL OR CHEMICAL HAZARD**

Flammable. Keep away from heat and open flame.

**STORAGE AND DISPOSAL**

**PESTICIDE DISPOSAL:** Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide, spray mixture, or residue that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State, or local disposal authorities.

**CONTAINER DISPOSAL:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in an approved landfill, or by other approved state and local alternative procedures.

Ultra-  
2449H

KEEP OUT OF REACH

WARN

See side panel for additional p

NET CONTENTS: ONE U.S.

X<sup>®</sup>

## ULTRA-KOTE® RED 2449H ANTIFOULING BOTTOM PAINT

It is a violation of federal law to use this product in a manner inconsistent with its labeling.  
**PRODUCT DESCRIPTION:** ULTRA-KOTE® RED 2449H is a product for commercial and non-commercial use that has 76% cuprous oxide, which is the highest cuprous oxide content of all leading yacht antifouling paints. This copper content makes ULTRA-KOTE® the top of the line epoxy-ester antifouling paint. ULTRA-KOTE® also has excellent color stability previously unmatched in high copper content antifouling paints. ULTRA-KOTE® can be applied to fiberglass, wood and properly prepared steel hulls. Use ULTRA-KOTE® where the fouling challenge is severe such as warm or tropical waters or in areas where runoff from the land causes higher algae and grass growth. ULTRAKOTE® gives you premium protection no matter where you are.

**GENERAL APPLICATION:** ULTRAKOTE can be applied over most other antifouling paints, but it is important that these coatings be in excellent condition, well adhered to the hull and any loose or flaking paint has been removed. Soft antifouling paints should be removed. It is best to apply ULTRAKOTE between 50°F and 95°F.

**MIXING AND THINNING:** Shake or mix well. Stir continuously while using. For brush or roller use, thin if necessary with INTERLUX BRUSH-EASE 433. For use on bare wood, thin 15% with INTERLUX SPECIAL THINNER 216. For spray application, thin up to 10% with INTERLUX SPECIAL THINNER 216.

**THEORETICAL COVERAGE:** 450 square feet per gallon per coat.

**CLEAN UP:** INTERLUX SPECIAL THINNER 216 or INTERLUX BRUSH-EASE 433.

**ESTIMATED DRY TIMES:** ULTRAKOTE may be overcoated with itself after an overnight dry. Prior to launch, allow an overnight dry. Maximum time to launch is 60 days.

### APPLICATION SYSTEMS

**PREVIOUSLY PAINTED SURFACES:** Sand the entire surface with 80 grit sandpaper. Wipe the surface with INTERLUX SPECIAL THINNER 216. Apply two coats of ULTRAKOTE.

**BARE FIBERGLASS - NO SAND METHOD:** Wash entire surface with FIBERGLASS SOLVENT WASH 202 changing rags frequently. Repeat application to be sure all wax and mold release agents have been removed. Repair dents and scratches with EPOXY SURFACING & FAIRING COMPOUND 417A/418B, sand and clean repaired areas. Apply one thin coat of INTERLUX FIBERGLASS PRIMER AL200 with brush or roller. Do not spray, do not sand. Apply first coat of ULTRAKOTE after the FIBERGLASS PRIMER AL200 has dried for two hours but no more than three. Apply second coat of ULTRAKOTE after an overnight dry.

**BARE FIBERGLASS SANDING METHOD:** Wash entire surface with FIBERGLASS SOLVENT WASH 202, changing rags frequently to be sure all contamination is removed. Repair scratches and dents with EPOXY SURFACING & FAIRING COMPOUND 417A/418B. Sand entire surface with 80 grit production sandpaper until a dull, matte appearance is obtained, wipe clean. Apply two coats of ULTRAKOTE.

**BARE WOOD:** Sand well with 80 grit production paper; wipe surface clean. Apply first coat of ULTRAKOTE after it has been thinned 15% with INTERLUX SPECIAL THINNER 216. Apply second coat after an overnight dry. (Do not thin second coat unless necessary).

**UNDERWATER METALS:** Please contact the INTERLUX Technical Sales Department for full details on how to apply to underwater metals. Do not use on aluminum.

**DISCLAIMER:** The performance of any marine paint or coating depends on many factors outside the control of Courtauld's Coatings Inc. including surface preparation, proper application, and environmental conditions. Therefore, Courtauld's Coatings Inc. cannot guarantee the product's performance for your particular purpose or application. LIMITED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. COURTAULD'S COATINGS INC SHALL NOT UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase of this product, the buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Courtauld's Coatings Inc. discretion.

REV 05 94

EPA Registration No. 2693-			
EPA Establishment No. 2693-NJ1			
• Active Ingredient:			
Cuprous Oxide	=	76.00%	
• Inert Ingredients:	=	24.00%	
			100.00%
Elemental Copper	=	67.40%	

LITERS)

Courtauld's Coatings Inc.  
400 S. 13th Street, Louisville, KY 40203

Union, NJ

Louisville, KY

Montreal, Quebec

Houston, TX

Handwritten initials: "H. G. H."