

PM 31

2693-144

5/22/97

1/4

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

MAY 22 1997

John P. Pazdera  
Courtaulds Coatings Inc.  
2270 Morris Avenue  
Union, NJ. 07083

Subject: Ultra-Kote 2449H Red  
EPA Registration No. 2693-144  
Notification Per PR-Notice 95-2  
Your Notification Dated May 8, 1997

Dear Mr. Pazdera:

This will acknowledge receipt of your notification to add the "Product Descriptors" to the front panel submitted under the provisions of FIFRA section 3(c)9. Based on a review of the submitted material, the following comments apply.

The application is acceptable and the notification has been made a part of the records for this file.

Sincerely,



Marshall Swindell  
Notification Coordinator  
Antimicrobial Program Branch  
Antimicrobial Division (7510W)

CONCURRENCES

SYMBOL	7510W						
SURNAME	P. Hasty						
DATE	5/16/97						

PM 33

274

Please read instructions on reverse before completing form.

Form Approved. OMB No. 2070-0060. Approval expires 05-31-98



United States  
Environmental Protection Agency  
Washington, DC 20460

<input type="checkbox"/>	Registration
<input type="checkbox"/>	Amendment
<input checked="" type="checkbox"/>	Other

OPP Identifier Number  
245062

### Application for Pesticide - Section I

1. Company/Product Number 2693-144	2. EPA Product Manager M. Swindell	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) Ultra-Kote 2449H Red	PM# 31	
5. Name and Address of Applicant (Include ZIP Code) Courtaulds Coatings Inc. 2270 Morris Avenue Union, NJ 07083 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3)(b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

### Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

Notification - Minor Labeling Changes  
- Add Product Descriptors to front panel.

### Section - III N/A

1. Material This Product Will Be Packaged In:					
Child-Resistant Packaging <input type="checkbox"/> Yes* <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	2. Type of Container <input type="checkbox"/> Metal <input type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input type="checkbox"/> Other (Specify) _____		
* Certification must be submitted		If "Yes" Unit Packaging wgt.    No. per container	If "Yes" Package wgt    No. per container		
3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container		5. Location of Label Directions <input type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product	
6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled			<input type="checkbox"/> Other _____		

### Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name John P. Pazdera	Title Pesticide Registration Mgr.	Telephone No. (Include Area Code) 908-964-2288
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received  (Stamped)
2. Signature <i>John P. Pazdera</i>	3. Title Pesticide Registration Manager	
4. Typed Name John P. Pazdera	5. Date 5/8/97	

BEST AVAILABLE COPY



# Ultra-Kote

- Excellent Protection for Severe Fouling Areas
- For Fiberglass, Wood or Steel Boats

KEEP OUT OF REACH OF CHILDREN  
**WARNING**

See Side Panel for Additional Precautionary Statements

2449H  
RED

ONE U.S. GALLON  
(3.785 L)

ACTIVE INGREDIENT	PERCENT
CUPROUS OXIDE	76.00%
INERT INGREDIENTS	24.00%
ELEMENTAL COPPER 67.40%	100.00%

EPA EST 2693-NJ-1  
EPA REG NO. 2693-144

584  
27  
24

PRECAUTIONARY STATEMENTS  
**WARNING**  
KEEP OUT OF REACH OF CHILDREN

**HAZARD TO HUMANS AND DOMESTIC ANIMALS:**

Causes eye irritation. Harmful if swallowed or absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

**STATEMENT OF PRACTICAL TREATMENT**

**IF SWALLOWED:** Promptly drink large quantities of water. Never give anything by mouth to an unconscious person. Avoid alcohol. Get medical attention.

**IF IN EYES:** Flush with plenty of water. Get medical attention if irritation persists.

**IF ON SKIN:** Wash with plenty of soap and water. Get medical attention if irritation persists.

**IF INHALED:** Remove victim to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. Get medical attention.

**ENVIRONMENTAL HAZARD**

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**PHYSICAL OR CHEMICAL HAZARD**

Flammable. Keep away from heat and open flame.

**STORAGE AND DISPOSAL**

Do not contaminate water, food, feed by storage or disposal. Open dumping is prohibited. **PESTICIDE DISPOSAL:** Pesticide wastes are toxic. Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

**CONTAINER DISPOSAL:** Triple rinse (or equivalent). Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved State and local procedures. If burned stay out of smoke.

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Courtauld's Coatings Inc. including surface preparation, proper application, and environmental conditions. Therefore, Courtauld's Coatings Inc. cannot guarantee the product's suitability for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. COURTAULD'S COATINGS INC SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use of this product, buyer agrees that the sale and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Courtauld's Coatings Inc's option.

**X. Interlux**

For information call 908-686-1300  
Or write: Interlux, 2270 Morris Ave., Union, NJ 07088



**BEST AVAILABLE COPY**

**ULTRA-KOTE® 2449H RED ANTIFOULING BOTTOM PAINT**

**DIRECTION FOR USE:**

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

**PRODUCT DESCRIPTION:** ULTRA-KOTE® 2449H RED has been developed to provide excellent single season antifouling protection from shell and weed growth. With 76% cuprous oxide, this epoxy ester formula is recommended for use wherever the fouling challenge is severe, such as tropical marine waters, warm bays or tidal waters, or in areas where nutrient runoff from the land results in high algae and grass growth. ULTRA-KOTE® is formulated to offer the added benefits of excellent color stability and ease of mixing. ULTRA-KOTE® is compatible with most other antifouling paints. It can be used below the waterline in fresh, salt or brackish water on fiberglass, wood and properly primed metal boat hull and parts. Do not use on aluminum. This product is suitable for commercial and non-commercial applications.

**COMPATIBILITY:** ULTRA-KOTE® can be applied over most other antifouling paints, but it is important that these coatings be in excellent condition, well adhered to the hull and any loose or flaking paint has been removed. Soft antifouling paints should be removed. It is best to apply ULTRA-KOTE® between 50°F and 95°F. Shake or mix well. Stir continuously while using.

**V.O.C.:** Less than 219 grams/liter (1.8 lbs./gallon) as supplied.

**THINNER:** Brushing - BRUSH-EASE 433  
Spraying - SPECIAL THINNER 216

**THINNING:** Thin only when necessary. Do not exceed 10% by volume (15% on bare wood).

**CLEAN UP:** INTERLUX SPECIAL THINNER 216 or INTERLUX BRUSH-EASE 433.

**THEORETICAL COVERAGE:** 450 square feet per gallon per coat.

**DRYING TIMES:** Touch dry - 2 hours  
Dry to overcoat - 16 hours minimum\*  
Dry to launch - 18 hours minimum, 60 days maximum\*

**APPLICATION TEMPERATURE:** 50°F (10°C) and above\* (Air and Hull).

\*If either the air or hull temperature falls below 50°F (10°C) during the 16 hour dry time, extend the dry time and launch time to 36 hours minimum.

**APPLICATION SYSTEMS**

**PREVIOUSLY PAINTED SURFACES:** Sand the entire surface with 80 grit sandpaper. Wipe the surface with INTERLUX SPECIAL THINNER 216. Apply two coats of ULTRA-KOTE®.

**BARE FIBERGLASS - NO SAND METHOD:** Wash entire surface with INTERLUX FIBERGLASS SOLVENT WASH 202 changing rags frequently. Repeat application to be sure all wax and mold release agents have been removed. Repair dents and scratches with INTERLUX EPOXY SURFACING & FAIRING COMPOUND 417A/418B; sand and clean repaired areas. Apply one thin coat of INTERLUX FIBERGLASS AL200 PRIMER with brush or roller. Do not spray, do not sand. Apply first coat of ULTRA-KOTE® after an overnight dry.

**BARE FIBERGLASS SANDING METHOD:** Wash entire surface with INTERLUX FIBERGLASS SOLVENT WASH 202, changing rags frequently to be sure all contamination is removed. Repair scratches and dents with INTERLUX EPOXY SURFACING & FAIRING COMPOUND 417A/418B. Sand entire surface with 80 grit production sandpaper until a dull, matte appearance is obtained, wipe clean with INTERLUX FIBERGLASS SOLVENT WASH 202. Apply two coats of ULTRA-KOTE®, allowing an overnight dry between coats.

**BARE WOOD:** Sand well with 80 grit production sandpaper; wipe surface clean with INTERLUX SPECIAL THINNER 216. Fill minor voids and imperfections with INTERLUX EPOXY SURFACING & FAIRING COMPOUND 417A/418B. Apply first coat of ULTRA-KOTE® after it has been thinned 15% with INTERLUX SPECIAL THINNER 216. Fill seams, if necessary, with INTERLUX SEAM COMPOUND 30. Allow INTERLUX SEAM COMPOUND 30 to skin over for 24-48 hours before applying the second coat of ULTRA-KOTE®. Do not thin second coat of ULTRA-KOTE®.

**UNDERWATER METALS:** Please contact the INTERLUX Technical Sales Department 1-800-468-7589 for full details on how to apply to underwater metals. Do not use on aluminum.

Rev. 4/97

4/94  
Pete