

7/23/97

PM 31

2693-148

P9 1/6

Please read instructions on reverse before completing form.

Form Approved. OMB No. 2070-0060. Approval expires 05-31-98



United States
Environmental Protection Agency
Washington, DC 20460

| | |
|-------------------------------------|--------------|
| <input type="checkbox"/> | Registration |
| <input type="checkbox"/> | Amendment |
| <input checked="" type="checkbox"/> | Other |

OPP Identifier Number
245085

Application for Pesticide - Section I

| | | |
|---|--|--|
| 1. Company/Product Number 2693-148 | 2. EPA Product Manager M. Swindell | 3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted |
| 4. Company/Product (Name) Regatta Baltoplate Racing Finish 3950 Gray Metallic | PM# 31 | |
| 5. Name and Address of Applicant (Include ZIP Code) Courtaulds Coatings Inc. 2270 Morris Avenue Union, NJ 07083 <input type="checkbox"/> Check if this is a new address | 6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____ | |

Section - II

| | |
|--|--|
| <input checked="" type="checkbox"/> Amendment - Explain below. | <input type="checkbox"/> Final printed labels in response to Agency letter dated _____ |
| <input type="checkbox"/> Resubmission in response to Agency letter dated _____ | <input type="checkbox"/> "Me Too" Application. |
| <input checked="" type="checkbox"/> Notification - Explain below. | <input type="checkbox"/> Other - Explain below. |

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

- Notification: - Minor Labeling Changes
- Add Product Descriptors to front panel

Section - III N/A

| | | | | | |
|---|--|---|---|---|--|
| 1. Material This Product Will Be Packaged In: | | | | 2. Type of Container | |
| Child-Resistant Packaging <input type="checkbox"/> Yes* <input checked="" type="checkbox"/> No | Unit Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | Water Soluble Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | Metal Plastic Glass Paper Other (Specify) _____ | | |
| * Certification must be submitted | | If "Yes" Unit Packaging wgt. No. per container | If "Yes" Package wgt No. per container | | |
| 3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container | | 4. Size(s) Retail Container | | 5. Location of Label Directions <input type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product | |
| 6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled | | | <input type="checkbox"/> Other _____ | | |

Section - IV

| | | | | |
|--|--------------------------------------|---|--|--|
| 1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.) | | | 8. Date Application Received (Stamped) | |
| Name John P. Pazdera | Title Pesticide Registration Mgr. | Telephone No. (include Area Code) 908-964-2288 | | |
| 2. Signature <i>John P. Pazdera</i> | | | | |
| 3. Title Pesticide Registration Manager | | 4. Typed Name John P. Pazdera | | |
| 5. Date 7/1/97 | | | | |
| <p align="center">Certification</p> <p>I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.</p> | | | | |

JUL 23 1997

Courtaulds Coating Inc.
 2270 Morris Avenue
 Union, NJ. 07083

Subject: Regatta Baltoplate Racing Finish
 3950 Gray Metallic
 EPA Registration No. 2693-148
 Notification Per PR-Notice 95-2
 Your Notification Dated July 1, 1997

Dear Mr. Pazdera:

This will acknowledge receipt of your notification to add the "Product Descriptors" to the front panel submitted under the provisions of FIFRA section 3(c)9. Based on a review of the submitted material, the following comments apply.

The application is acceptable and the notification has been made a part of the records for this file.

Sincerely,



Marshall Swindell
 Notification Coordinator
 Antimicrobial Program Branch
 Antimicrobial Division (7510W)

CONCURRENCES

| | | | | | | | |
|---------|----------|--|--|--|--|--|--|
| SYMBOL | 7510W | | | | | | |
| SURNAME | P. Hasty | | | | | | |
| DATE | 7/22/97 | | | | | | |

REGATTA

BALTOPLATE RACING FINISH

ANTIFOULING BOTTOM PAINT FOR THE SERIOUS RACER

3950 Gray Metallic

[FOR PROFESSIONAL BOAT PAINT APPLICATORS]

- Hard Bottom Paint for All Waters
- Dependable Season Long Protection
- Overcoats Existing Antifouling Paint
- Super Value Bottom Paint.

| | |
|--------------------|----------|
| | % |
| ACTIVE INGREDIENT: | |
| Cuprous Oxide | = 41.15 |
| INERT INGREDIENTS: | = 58.85 |
| TOTAL | = 100.00 |
| Elemental Copper | = 37.25% |

Contains Petroleum Distillates

EPA Registration No. 2693-148 EPA Establishment No. 2693-NJ-1

**KEEP OUT OF REACH OF CHILDREN
WARNING**

See side panel for additional precautionary statements

Net Contents: ONE U.S. GALLON (3.785 LITERS)

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of Courtaulds Coatings Inc. including the surface preparation, proper application and the environmental conditions. Therefore, Courtaulds Coatings Inc. cannot guarantee the suitability of this product for your particular purpose or application. **IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. COURTAULDS COATINGS INC. SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.** By purchase or use, of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Courtaulds Coatings Inc.'s option.

Manufactured For Regatta Yacht Paint Co.

Courtaulds Coatings Inc.

400 S. 13th Street, Louisville, KY 40203

Union, NJ

Houston, TX

Louisville, KY

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
WARNING**

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Safety & Health Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Drink promptly a large quantity of water. Avoid alcohol. Get medical attention.
IF ON EYES: Flush eyes with plenty of water. Get medical attention.
IF ON SKIN: Wash with plenty of soap and water. Get medical attention.
IF INHALED: Remove victim to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARD

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD

Flammable. Keep away from heat and open flame.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, EXPOSURE OR ACCIDENT:
CALL TOLL FREE - CHEMTREC 1-800-424-9300 (DAY OR NIGHT)**

MEDICAL ADVISORY:

CONTACT YOUR LOCAL POISON CONTROL CENTER OR CALL 1-800-854-6813

**BALTOPLATE RACING FINISH
ANTIFOULING BOTTOM PAINT FOR THE SERIOUS RACER**

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

DIRECTIONS FOR USE CONT'D

PRODUCT DESCRIPTION: This product is a hard modified-epoxy antifouling paint developed to provide effective season long protection and ease of application. This product is recommended for use on the underwater areas of fiberglass, wood and properly primed metal (except aluminum) boat hulls. This product can be used in fresh, salt and brackish waters.

COMPATIBILITY: This product can be applied over most other antifouling paints provided they are adhering well to the surface and the surface has been cleaned and sanded. This product can be applied by brush, roller or spray.

V.O.C.: Less than 408 grams/liter (3.34 lbs./gallon).

THINNER: SPECIAL THINNER 216 or BRUSH-EASE 433.

THINNING: Thin only when necessary. Do not exceed 10% maximum.

CLEAN-UP: SPECIAL THINNER 216 or BRUSH-EASE 433.

THEORETICAL COVERAGE: 400 square feet/gallon yields 2 mils dry film thickness.

DRY TIMES: Touch dry - 2 hours.
77°F (25°C) Dry to overcoat - 10 hours minimum
Dry to launch - 10 hours minimum
60 days maximum

APPLICATION TEMPERATURE: 50°F (10° C)* and above (air and hull).

* If the air temperature falls below 50° F (10° C) during the 10 hour dry time, extend the dry times to 36 hours minimum.

APPLICATION SYSTEMS

PREVIOUSLY PAINTED - GOOD CONDITION: Remove all traces of loose paint and contamination by sanding the entire surface with 80 grit sandpaper, wipe surface clean with SPECIAL THINNER 216. Apply at least two coats of this product.

PREVIOUSLY PAINTED - POOR CONDITION: Completely remove all old antifouling paint, using FIBERGLASS PINTOFF 299 for fiberglass, PINTOFF 199 for wood, and by sandblasting to near white metal for steel. Follow application system for bare work below.

BARE FIBERGLASS (POLYESTER OR VINYLESTER)

SURFACE PREPARATION: It is very important that bare fiberglass be properly prepared to prevent delamination of the antifouling paint. Begin by scrubbing the surface thoroughly with soap and water using a stiff brush, or **INTERLUX ABRASIVE CLEANER YMA600**. Flush well with water. Wipe a small area with a clean cloth that has been wetted with **INTERLUX FIBERGLASS SOLVENT WASH 202**. While the surface is still wet remove with a clean dry cloth. Repeat this process until the entire surface has been cleaned. To be certain that all the contamination has been removed, run water over the surface. If the water beads up or separates, wipe again with **FIBERGLASS SOLVENT WASH 202**. When the water sheets off, all contamination has been removed. Sanding does not remove contamination. After the surface has been properly cleaned, proceed with the application system below.

BARE FIBERGLASS - NO SAND SYSTEM: Clean the surface following the preparation procedure above. Repair any surface imperfections using **INTERLUX EPOXY SURFACING AND FAIRING COMPOUND 417A/418B**. Sand and wipe clean. Apply one thin, continuous coat of **INTERLUX AL200 FIBERGLASS PRIMER** by brush or roller. **DO NOT SPRAY. DO NOT SAND.** Allow to cure a minimum of 2 hours but no more than 3 hours, and apply the first coat of this product. Apply a second coat allowing for the appropriate dry times.

BARE FIBERGLASS - SANDING SYSTEM: Clean the surface following the preparation procedure above. Sand the entire surface with 80 grit sandpaper and wipe clean with **FIBERGLASS SOLVENT WASH 202** to remove sanding residue. Repair any surface imperfections using **INTERLUX EPOXY SURFACING AND FAIRING COMPOUND 417A/418B**. Sand and wipe clean. Apply two coats of this product allowing for appropriate dry times.

BARE WOOD: Sand the entire surface with 80 grit sandpaper, wipe surface clean with **INTERLUX SPECIAL THINNER 216**. Repair imperfections with **INTERLUX EPOXY SURFACING AND FAIRING COMPOUND 417A/418B**. Sand and wipe clean. Apply the first coat of **PROLUX 240** thinned 10% with **SPECIAL THINNER 216** or **BRUSH-EASE 433**. Fill seams with **INTERLUX SEAM COMPOUND 30** (if necessary). Apply two more coats of this product unthinned, allowing the appropriate dry times.

UNDERWATER METALS: Contact the Technical Service Department at 1-800-468-7589 for full information on how to properly prime underwater metals. **DO NOT USE ON ALUMINUM.**

**FOR INFORMATION CALL 1-908-686-1300 OR WRITE TO:
2270 MORRIS AVENUE, UNION, NJ 07083**

