

P. 0. 31
9643 - 10
174

Mr. Theodore R. Hopper
Jotun Marine Coatings, Inc.
840 Key Highway
Baltimore, MD 21230

Jan 8 1983

Dear Mr. Hopper:

Subject: Antifouling Paint Label Improvement Program
95 Super Tropic Red Anti-Fouling
EPA Registration No. 2568-17
Your Submission of January 6, 1982

The amendment referred to above, submitted in connection with registration under FIFRA sec. 3(c)(7)(A), is acceptable, provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data.
2. Make the labeling changes listed below before you release the product for shipment bearing the amended labeling:
 - a. Delete DANGER on the front panel and replace it with WARNING.
 - b. Move "-17" to the EPA Registration No. The complete EPA Establishment Number must appear on the final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product bearing the amended labeling constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,

Richard F. Mountfort *RFM*
Product Manager (23)
Fungicide-Herbicide Branch
Registration Division (TS-767)

Enclosure

RD:MOUNTFORT:DCR-04197:WANG-2082C:pjb:Raven:479-2013:1/14/83

143

Page 4

A. LABEL FACE

95 SUPER TROPIC RED ANTI-FOULING

ACTIVE INGREDIENTS	
Cuprous Oxide	24.76%
INERT INGREDIENTS	<u>75.24%</u>
	100.00%

Copper as Metallic 23.41%

CONTAINS PETROLEUM DISTILLATES

KEEP OUT OF REACH OF CHILDREN

DANGER

SEE SIDE PANEL FOR ADDITIONAL

CAUTIONARY STATEMENTS

EPA Reg. No. 58
 EPA Est. No. 58-1

Net Contents 5 US Gallons
 18.925 Liters
 4.165 Imperial Gallons

ACCEPTED
with comments
JAN 18 1983 *RFM*
 Under the Federal Insecticide,
 Fungicide, and Rodenticide Act
 as amended, for the pesticide
 registered under EPA Reg. No. *2568-1-17*

170

1147
6
B

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS

WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding boat surface, wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. This product is for commercial use only.

FIRST AID

If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

If in eyes: Flush with plenty of water. Get medical attention.

If on skin: Wash with plenty of soap and water. Get medical attention.

If inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS

Flammable. Keep away from heat and open flame.

C. DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

95 Super Tropic is recommended for world wide use and will protect effectively against barnacles. Suitable primers must be used when this product is applied to a steel or aluminum hull; on fiberglass or wood proper surface preparation only is required.

Two coats of Arcanol Silvergray at a total film thickness of three mils is recommended for priming metal surfaces. After 4-6 hours drying time, the 95 Super Tropic may be applied by airless spray, brush, or roller at a rate of 2 to 3 mils per coat. Allow 6 hours drying time between coats at 60°F. Spreading rate at 2 mils is 450 sq. ft. per gallon. When desired film thickness is achieved allow at least 6 hours of drying before launching.

STORAGE and DISPOSAL

Pesticide spray mixture or solvent rinse that cannot be used according to label instructions must be disposed of according to federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

To dispose of container, triple rinse; then offer for reconditioning or recycling, or puncture and dispose of in a sanitary landfill or by other approved state and local procedures.