



U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs
Antimicrobials Division (7510C)
1200 Pennsylvania Avenue NW
Washington, D.C. 20460

EPA Reg. Number: 2693-170

Date of Issuance: SEP 19 2006

Term of Issuance:
Expiration Date: 10-30-07

Name of Pesticide Product:
Fiberglass Bottomkote with Biolux II-Black

NOTICE OF PESTICIDE:
[x] Registration
Reregistration

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

International Paint LLC
2270 Morris Avenue
Union, NJ 07083

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec 3(c)(7)(A) provided that you:

- 1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for re-registration of your product under FIFRA section 4.
2. This is a time-limited registration. The Agency is still in the process of completing the Environmental Risk Assessment need to support the antifouling use pattern. The Agency is now extending your time-limited to October 30, 2007

Signature of Approving Official:

Handwritten signature of Marshall Swindell

Marshall Swindell
Product Manager Team-33
Regulatory Management Branch I
Antimicrobials Division (7510P)

Date:

SEP 19 2006

3. This conditional registration will expire automatically on October 30, 2007. If you fail to satisfy the conditions imposed in the registration, EPA may issue a Notice to Cancel under Section 6 (e) of FIFRA.
4. Make the labeling changes listed below before you release the product for shipment
 - a) Revise the "EPA Registration No to read, "EPA Reg. No. 2693-170"
 - b) Add the following statement as a foot note to your ingredient statement:
This product contain petroleum distillate"
 - c) Add the word "**Combustible**" to the Chemical Hazard statement
5. Submit three (3) copies of your final printed labeling before distributing or selling the product bearing the revised labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

Sincerely,



Marshall Swindell
Product Manager 33
Regulatory Branch I
Antimicrobials Division (7510P)

3 8 7

FIBERGLASS BOTTOMKOTE with BIOLUX II - Black

- Contains Irgarol
- Irgarol Improves Antifouling Performance by Reducing Slime
- Proven All Purpose Antifouling Protection
- Overcoats Existing Antifouling Paint

ACCEPTED
with COMMENTS
EPA Letter Dated:

KEEP OUT OF REACH OF CHILDREN

SEP 19 2006

CAUTION

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

See side panel for additional precautionary statements

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

2693-170

EPA Registration No. 2693-
EPA Establishment No. 2693-NJ-1

Active Ingredients:

Cuprous Oxide	= 42.75%
N-Cyclopropyl-N'-(1,1-dimethylethyl)-6-(methylthio)-1,3,5-triazine-2,4-diamine	= 0.49%
Inert Ingredients:	= 56.76%
	100.00%
Copper as Metallic	= 37.93%

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of International Paint LLC including the surface preparation, proper application and the environmental conditions. Therefore, International Paint LLC cannot guarantee the suitability of this product for your particular purpose or application. **IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT LLC SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.** By purchase or use, of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint LLC's option.

International Paint LLC
2270 Morris Avenue
Union, NJ 07083

4 2 7
ACCEPTED
with COMMENTS
EPA Letter Dated

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

SEP 19 2006

Under the Federal Insecticide,
Fungicide, and Rodenticide Act, as
amended, for the pesticide,
registered under EPA Reg. No.

CAUTION

Harmful if absorbed through skin or inhaled. Causes moderate eye irritation. Avoid contact with eyes, skin or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. Avoid breathing spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Safety & Health Administration and the National Institute of Occupational Safety & Health. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash clothing before reuse. May pose an aspiration pneumonia hazard.

FIRST AID

IF SWALLOWED: Call a Poison Control Center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a Poison Control Center or doctor. Do not give anything by mouth to an unconscious person.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. Call a Poison Control Center or doctor for treatment advice.

IF ON SKIN AND CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a Poison Control Center or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, give artificial respiration preferably mouth-to-mouth if possible. Call a Poison Control Center or doctor for further treatment advice.

In case of emergency call 1-800-854-6813. Have the product container or label with you when calling a Poison Control Center or doctor or going in for treatment.

ENVIRONMENTAL HAZARD

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

5 8 7

PHYSICAL OR CHEMICAL HAZARD

Do not use or store near heat or open flame.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

ACCEPTED
with COMMENTS
EPA Letter Dated:

SEP 19 2006

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended for the pesticide,
registered under EPA Reg. No.

2693-170

6 8 7

NO. 11111
with COMMENTS
EPA Letter Dated:

FIBERGLASS BOTTOMKOTE WITH BIOLUX II

PRODUCT DESCRIPTION: Fiberglass Bottomkote with Biolux II is a hard modified-epoxy antifouling paint that provides excellent season long protection. Fiberglass Bottomkote with Biolux II contains cuprous oxide and Irgarol. The Irgarol works to control weed, slime and algae fouling while the cuprous oxide works to control shell fouling such as barnacles and zebra mussels. This keeps the bottom of your boat cleaner longer. The fast dry formula of Fiberglass Bottomkote with Biolux II allows it to be painted and launched in the same day. Fiberglass Bottomkote with Biolux II can be applied over any other antifouling paint and can also be wet sanded and burnished to a smooth racing finish.

SEP 19 2006

Fiberglass is the Federal Insecticide, and Rodenticide Act, amended, for the pesticide registered under EPA Reg. No.

2693-170

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with it's labeling.

V.O.C.: Less than 400 grams/liter (3.34 lbs./gallon)

THEORETICAL COVERAGE: 400 sq. ft./ gallon yields 2 mils dry film thickness.

THINNER: SPECIAL THINNER 216 or BRUSH-EASE 433 77°F (25°C)

DRY TIMES: Touch dry - 1 hour
Dry to overcoat - 4 hours minimum
Dry to launch - 8 hours minimum
60 days maximum

THINNING: Thin only when necessary
Do not exceed 10% maximum.

CLEAN-UP: SPECIAL THINNER 216 or BRUSH-EASE 433

APPLICATION TEMPERATURE: 50°F (10°C)* and above (air and hull)

Temperature F°/C°	Touch Dry	Overcoating Time		Immersion Time	
		Minimum	Maximum	Minimum	Maximum
50°F (10°C)	3 hrs	6 hrs	60 days	12 hrs	60 days
60°F (15°C)	2 hrs	5 hrs	60 days	10 hrs	60 days
75°F (24°C)	1 hr	4 hrs	60 days	8 hrs	60 days
95°F (35°C)	30 Min	3 hrs	60 days	6 hrs	60 days

*If the air temperature falls below 50°F (10°C) during the dry time, extend the dry times to 36 hours minimum.

PREPARATION

PREVIOUSLY PAINTED - GOOD CONDITION: Remove all traces of loose paint and contamination by sanding the entire surface with 80 grit sandpaper, wipe surface clean with Special Thinner 216. Apply at least two coats of Fiberglass Bottomkote with Biolux II.

PREVIOUSLY PAINTED - POOR CONDITION: Completely remove all old antifouling paint, using Interstrip® 299E. Follow application system for bare work below.

BARE FIBERGLASS (POLYESTER OR VINYLESTER) - SURFACE PREPARATION: Begin by scrubbing the surface thoroughly with a stiff brush using Interlux All Purpose Boat Soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry. Remove mold release wax using one of the following methods.

The preferred method of cleaning gelcoat is to apply Fiberglass Surface Prep YMA601 with a maroon, 3M, Scotch-Brite® pad and scrub well. Flush with fresh water or wipe off with a clean, wet cloth ensuring that no traces of Fiberglass Surface Prep remain.

An alternate method would be to dampen cheesecloth with Interlux Fiberglass Solvent Wash 202. Wipe thoroughly to remove all surface contamination and cleaners. Wipe off with a clean, dry rag before liquid dries. Wipe only a few square feet at a time and change rags frequently.

To be certain the contamination has been removed, run water over the surface. If the water beads up or separates, repeat one of the above methods. When the water sheets off, all contamination has been removed. Sanding does not remove contamination.

After the surface has been properly cleaned, proceed with the application system below.

BARE FIBERGLASS - NO SAND SYSTEM: After the surface has been cleaned as described above - apply one thin continuous coat of Interlux Fiberglass No Sand Primer YPA200. Please refer to label directions for application. Allow appropriate dry time and apply the first coat of Fiberglass Bottomkote with Biolux II.

BARE FIBERGLASS - SANDING SYSTEM: After the surface has been cleaned as described above - Sand entire surface with 80-grit sandpaper until flat matte finish is obtained. Remember to change sandpaper frequently. Wipe off sanding residue with Fiberglass Solvent Wash 202. Apply two coats of **Fiberglass Bottomkote with Biolux II** allowing for appropriate dry times.

BARE WOOD: Sand entire underwater surface with 80-grit sandpaper; wipe surface clean with Interlux Brush-Ease 433 or Special Thinner 216. Repair imperfections with Watertite; sand and wipe clean. Apply first coat of **Fiberglass Bottomkote with Biolux II** reduced 10% with Brush-Ease 433 or Special Thinner 216 to penetrate into the wood. If necessary, fill seams with Interlux Seam Compound 30. Apply second and third coats of **Fiberglass Bottomkote with Biolux II** unreduced. Allow proper dry times between coats.

UNDERWATER METALS: Contact the Interlux Technical Service Department at 1-800-468-7589 for full information on how to properly prime underwater metals. DO NOT USE ON ALUMINUM.

APPLICATION

Apply two coats of **Fiberglass Bottomkote with Biolux II** (three coats on bare wood) allowing for the appropriate dry times

HINTS

Fiberglass Bottomkote with Biolux II can be applied over existing antifouling paint as long as the old coating is tightly adhered and is in sound condition.

Soft antifouling paints will need to be removed or overcoated with Primocon before applying **Fiberglass Bottomkote with Biolux II**.

Color difference may occur between actual paint and color swatch on front of can.

ACCEPTED
with COMMENTS
EPA Letter Dated:

SEP 19 2006

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended

2693-170