

US ENVIRONMENTAL PROTECTION AGENCY
OFFICE OF PESTICIDES PROGRAMS
REGISTRATION DIVISION (75-767)
WASHINGTON, DC 20460

EPA REGISTRATION NO.
2693-172

DATE OF ISSUANCE

APR 19 1994

TERM OF ISSUANCE

NOTICE OF PESTICIDE: REGISTRATION
 REREGISTRATION

(Under the Federal Insecticide, Fungicide,
and Rodenticide Act, as amended)

NAME OF PESTICIDE PRODUCT

Aquarius Antifouling
Bottom Paint 568 Navy Blue

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

Courtaulds Coatings Inc
400 South 13th Street
Louisville, KY 40201

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit/cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.

2. Make the labeling changes listed below before you release the product for shipment:

- a. Add the phrase "EPA Registration No. 2693-172".
- b. Include the heading: Net Contents.
- c. Delete the word: Percentage (ingredient section)
- d. Delete the phrase: environmentally friendly.

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL

DATE

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

- 2 -

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



Marshall Swindell
Acting Product Manager (31)
Antimicrobial Program Branch
Registration Division (H7505C)

CONCURRENCES

SYMBOL							
SURNAME							
DATE							

3 of 5

New

APR 19 1994

Unac.
Fungicide, and...
amended, for the pesticide
registered under EPA Reg. No.
2693-172

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
KEEP OUT OF REACH OF CHILDREN
WARNING**

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. While spraying and/or sanding boat surfaces, wear a face mask and respirator jointly approved by the Mining Enforcement and Safety Administration and by the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT: IF SWALLOWED: Drink promptly large quantities of water. Avoid alcohol. Get immediate medical attention.
IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Get medical attention.
IF ON SKIN: Wash with plenty of soap and water. Get medical attention.
IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARDS
This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

DIRECTIONS FOR USE
It is a violation of Federal law to use this product in a manner inconsistent with its labeling. **NOTE:** Protective clothing and respirators should be used as described under Precautionary Statements.

GENERAL DESCRIPTION
This product is an antifouling protective coating resistant to algae, barnacles, zebra mussels and other marine fouling. For use on boat hulls which are used in fresh, salt and brackish waters. For both commercial and non-commercial use.

STORAGE & DISPOSAL
Do not contaminate water, food or feed by storage or disposal.
PESTICIDE DISPOSAL: Pesticide wastes are toxic. Open dumping is prohibited. Pesticide spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State, or Local Disposal Authorities. **CONTAINER DISPOSAL:** Triple rinse (or equivalent) and dispose of in an approved land fill. Consult Federal, State, or Local Disposal Authorities for approved alternative procedures.

56

KEEP
NE

BEST AVAILABLE COPY

4 of 5

Interlux®

568 NAVY BLUE

Active Ingredient:
Cuprous Oxide

Inert Ingredients

ELEMENTAL COPPER 37.9%
EPA REG NO. 2003
EPA EST. NO. 2003-NJ-1

Pen
46.
53.
100.

BEST AVAILABLE COPY

5 7 5

DIRECTIONS FOR USE CONTINUED AQUARIUS ANTIFOULING BOTTOM PAINT

PRODUCT DESCRIPTION: AQUARIUS ANTIFOULING is an environmentally friendly bottom paint since it is water based not solvent based. It is an acrylic latex containing cuprous oxide for fouling protection.

AQUARIUS ANTIFOULING dries quickly to a smooth, extremely durable finish with exceptional abrasion resistance. AQUARIUS ANTIFOULING provides excellent protection against many or most fouling growth. Do not use on aluminum hulls or outdrives.

SURFACE PREPARATION AND COMPATIBILITY: Surface preparation directions must be followed exactly in order to ensure adhesion. Surfaces must be clean and dry prior to painting. AQUARIUS ANTIFOULING is compatible with most generic antifoulings. It is important that any primer or antifouling be in good condition prior to overcoating.

GENERAL APPLICATION PROCEDURES: Apply at least two full coats of AQUARIUS ANTIFOULING by brush or roller (sponge type preferred). Do not apply thin coats, the life of any antifouling is relative to the thickness applied. As a water based paint, never apply AQUARIUS ANTIFOULING at temperatures below 50°F. Always keep from freezing. If necessary, AQUARIUS ANTIFOULING can be reduced with small increments (up to 10% by volume) of tap water to ease application.

MIXING INSTRUCTIONS: Shake and mix well. Stir continuously while using. Thin only if necessary. Do not remove from original container unless poured in a plastic or glass jar.

DRY AND LAUNCH TIMES: Minimum dry time between coats is 3 hours. There is no maximum. Minimum time to launch after the second coat is applied is 36 hours, no maximum.

THEORETICAL COVERAGE: 300 square feet per gallon per coat.

CLEAN-UP: Water.

APPLICATION SYSTEMS

PREVIOUSLY PAINTED SURFACES: AQUARIUS ANTIFOULING is suitable over most generic antifoulings provided they are in good condition. Wipe down surface with 433 INTERLUX BRUSH EASE to remove contamination. Sand entire surface with 80-120 grit sandpaper to a clean surface. Wipe down with the same solvent to remove sanding dust. Apply AQUARIUS ANTIFOULING.

NEW SURFACES - FIBERGLASS - NO-SAND METHOD: Wash down entire surface using 202 FIBERGLASS SOLVENT WASH. Apply solvent, rubbing into surface to soften mold release agent. Before solvent dries, use clean rags to wipe down to remove release agent and solvent. Numerous rags will be necessary to avoid spreading of release agent. Once dry, apply one coat of AL-200 FIBERGLASS PRIMER with brush or roller. Follow instructions carefully. Allow 2 hours dry time but no more than 3 hours and apply the first of two coats of AQUARIUS ANTIFOULING.

NEW SURFACE - FIBERGLASS - SANDING METHOD: Clean hull as above but sand with 80-120 grit sandpaper instead of priming. Wash off sanding dust with 202 FIBERGLASS CLEANER, allow to dry and apply first of two coats of AQUARIUS ANTIFOULING.

NEW SURFACES - WOOD: Sand with 80-120 grit sandpaper. Wipe off sanding dust with 216 THINNER, allow to dry. First coat of AQUARIUS ANTIFOULING should be reduced with 15-20% tap water. Apply two additional, unreduced coats.

METAL SURFACES: Do not use on aluminum. For steel surface recommendations, contact your local COURTAULDS COATINGS representative.

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Courtaulds Coatings Inc including surface preparation, proper application, and environmental conditions. Therefore, Courtaulds Coatings Inc cannot guarantee this product's suitability for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. COURTAULDS COATINGS INC SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Courtaulds Coatings Inc's option.

Ingredient	Percent
Cuprous Oxide	48.45%
Acrylic Resin	53.55%
TOTAL COPPER	100.00%

PA REG NO. 2893
PA EST. NO. 2893-NJ-1

Courtaulds Coatings Inc.
 400 S. 13th Street, Louisville, KY 40203
 Union, N.J. Louisville, KY Houston, TX Montreal, Quebec

BEST AVAILABLE COPY