

2693-174

02/03/2004

115

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

FEB 03 2004

International Paint Inc.
2270 Morris Avenue
Union, N. J. 07083

Attention: John P. Pazdera
Pesticide Registration Manager

Subject: Tri-Lux II Aerosol 490A Blue
EPA Registration No. 2693-174
Amendment Dated January 6, 2004

This will acknowledge receipt of your notification to add a Product Descriptor to the front panel of the label, submitted under the provisions of FIFRA Section 3(c)(9). Based on a review of the submitted material, the following comments apply.

The notification is in compliance with PR Notice 98-10 and is acceptable. This information has been made a part of your file.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely



Marshall Swindell
Product Manager (33)
Regulatory Management Branch 1
Antimicrobials Division (7510C)

CONCURRENCES

SYMBOL								
SURNAME								
DATE								

Please read instructions on reverse before completing form.

Form Approved, OMB No. 2070-0060, Approval expires 2-28-95



United States
Environmental Protection Agency
Washington, DC 20460

<input type="checkbox"/>	Registration
<input type="checkbox"/>	Amendment
<input checked="" type="checkbox"/>	Other

OPP Identifier Number

Application for Pesticide - Section I

1. Company/Product Number 2693-174	2. EPA Product Manager M. Swindell	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) Tri-Lux II Aerosol 490A Blue	PM# 33	
5. Name and Address of Applicant (Include ZIP Code) International Paint Inc. 2270 Morris Ave. Union, NJ 07083 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3)(b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)
Notification - Minor Labeling Changes: Add Product Descriptor, add trade names for recommended primer, make changes requested in Agency letter dated 7/15/03.

Section - III *N/A*

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No		<input type="checkbox"/> Metal	<input type="checkbox"/> Plastic
Certification must submitted	If "Yes" Unit Packaging wgt.	No. per container	If "Yes" Package wgt	No. per container	<input type="checkbox"/> Glass
					<input type="checkbox"/> Paper
					<input type="checkbox"/> Other (Specify) _____
3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container		5. Location of Label Directions <input type="checkbox"/>	
6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled			<input type="checkbox"/> Other _____		

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name John P. Pazdera	Title Pesticide Registration Manager	Telephone No. (Include Area Code) 908-964-2288
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped)
2. Signature <i>John P. Pazdera</i>	3. Title Pesticide Registration Manager	
4. Typed Name John P. Pazdera	5. Date 1/6/04	

Tri-Lux II Aerosol 490A Blue

COPOLYMER ANTIFOULING PAINT Paint for Outdrives, Outboards & Props

EPA Registration No.2693-174

EPA Establishment No. 2693-NJ-1

Active Ingredient:		
Cuprous Thiocyanate	=	9.16%
Inert Ingredients:	=	90.84%
		100.00%

Contains Petroleum Distillates

KEEP OUT OF REACH OF CHILDREN WARNING

See side panel for additional Precautionary Statements

12 Fluid Ounces

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of International Paint Inc. including the surface preparation, proper application and the environmental conditions. Therefore, International Paint Inc. cannot guarantee the suitability of this product for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT INC. SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint Inc.'s option.

International Paint Inc.
2270 Morris Ave.
Union, NJ 07083

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
WARNING
KEEP OUT OF REACH OF CHILDREN**

Causes eye irritation. Harmful if swallowed or absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.

FIRST AID

If swallowed:

- Immediately call a poison control center or doctor.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give any liquid to the person.
- Do not give anything by mouth to an unconscious person.

If on skin or clothing

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

If inhaled:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

If in eyes:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

Other: Have the product container or label with you when calling a poison control center or doctor or going for treatment.

Note to Physician: Contains petroleum distillate – vomiting may cause aspiration pneumonia.

PHYSICAL OR CHEMICAL HAZARD

Extremely flammable. Content under pressure. Keep away from heat, sparks, open fire or heated surfaces. Do not puncture or incinerate container. Exposure to temperatures above 130 degrees F may cause bursting.

ENVIRONMENTAL HAZARD

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

Do not contaminate water, food, feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

CONTAINER DISPOSAL: Do not puncture or incinerate. A completely empty can can be disposed of with household trash. Wrap in paper before disposing.

TRI-LUX II AEROSOL **Copolymer Antifouling Paint**

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PRODUCT DESCRIPTION:

TRI-LUX II AEROSOL antifouling paint is formulated specifically for aluminum outboards, outdrives and aluminum boat hulls in underwater areas. When applied over properly primed metal TRI-LUX II AEROSOL will provide excellent antifouling protection.

TRI-LUX II is a true polishing copolymer that washes away with use, preventing buildup of old coatings. TRI-LUX II is for use in fresh, salt and brackish water.

APPLICATION SYSTEMS:

BARE ALUMINUM: Sand with medium grit emery cloth to a bright metal finish. Apply one thin coat of VINYL-LUX PRIMEWASH 353/354 that has been thinned 25% with VINYL-LUX SOLVENT 355. Allow to dry one hour, but no more than twenty-four hours, and apply the first coat of [INTERLUX OUTBOARD AND OUTDRIVE AEROSOL PRIMER 370; INTERLUX PRIMOCON YPA985] to the entire underwater surface. Do not apply primer or TRI-LUX II AEROSOL above the true waterline. After applying at least 2 coats of primer, apply TRI-LUX II AEROSOL as specified below.

PREVIOUSLY PAINTED (with antifouling paint): Sand with 80 grit sandpaper. Wipe off sanding residue with INTERLUX SPECIAL THINNER 216. Re-sand any areas where the bare aluminum is exposed with medium grit emery cloth and wipe clean. Immediately apply [INTERLUX OUTBOARD AND OUTDRIVE AEROSOL PRIMER 370; INTERLUX PRIMOCON YPA985] to bare areas. Apply at least two full coats of primer to the entire underwater surface. Do not apply primer or TRI-LUX II above the true waterline. Apply TRI-LUX II AEROSOL as specified below.

FACTORY PAINTED SURFACES (Underwater Surface Only): Wipe surface clean with INTERLUX SPECIAL THINNER 216 to remove contaminants. Sand the surface with 120 grit production sandpaper. Wipe the surface again with INTERLUX SPECIAL THINNER 216 to remove sanding residue. Apply at least 2 coats of [INTERLUX OUTBOARD AND OUTDRIVE PRIMER 370; INTERLUX PRIMOCON YPA985] allowing appropriate dry times. After an overnight drying, apply at least one full can of TRI-LUX II AEROSOL as specified below. Do not apply primer or TRI-LUX II AEROSOL above the true waterline.

TRI-LUX II AEROSOL APPLICATION

- 1) Shake can well, listen for rattle of mixing ball. Continue shaking for at least one minute.
- 2) Hold container about 12-16 inches from unit when applying paint. TRI-LUX II AEROSOL will be touch dry in about 30 minutes.
- 3) Apply contents of one can for each outdrive/outboard. Allow a minimum of 6 hours at 75 degrees F or 12 hours at 50 degrees F dry time between coats.
- 4) Be sure paint is completely dry before immersion; leave a minimum of 12 hours at 75 degrees or 16 hours at 50 degrees F prior to launch. There is no maximum launch time.
- 5) Clean up – use INTERLUX SPECIAL THINNER 216.