

2693-176

03/13/2007

1/5

MAR 13 2007

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, D.C. 20460



Office of Pesticide Programs

International Paint, LLC  
2270 Morris Avenue  
Union, N. J. 07083

Attention: John P. Pazdera  
Pesticide Registration Manager

Subject: Interclene XMH127 Red  
EPA Registration No. 2693-176  
Amendment Dated December 6, 2006

The amendment, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, is acceptable.

- In Response to PR Notice 2001-1

A stamped copy of the "accepted" product labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely

A handwritten signature in black ink, appearing to read "M Swindell".

Marshall Swindell  
Product Manager 33  
Regulatory Management Branch 1  
Antimicrobials Division (7510P)

Enclosure

FRONT PANEL

INTERCLEN  
XMH127 RED

ANTI FOULING PAINT

Active Ingredient:		
Cuprous Oxide	= 21.31%	EPA Registration No. 2693-176
Inert Ingredients:	= 78.69%	
	<u>100.00%</u>	EPA Establishment No. 2693-TX-1
Copper as Metallic	= 19.28%	

Contains Petroleum Distillates.

KEEP OUT OF REACH OF CHILDREN

WARNING

See side panel for additional precautionary statements

**ACCEPTED**  
with **COMMENTS**  
EPA Letter Dated:

**MAR 13 2007**

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
Registered under EPA Reg. No.

**2693-176**

Net Contents: FIVE U.S. GALLONS (18.927 LITERS)

**DISCLAIMER:** The performance of any marine coating depends on many factors outside the control of International Paint LLC including the surface preparation, proper application and the environmental conditions. Therefore, International Paint LLC cannot guarantee the suitability of this product for your particular purpose or application. **IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT LLC SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.** By purchase or use, of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint LLC's option.

International Paint LLC  
2270 Morris Ave.  
Union, NJ 07083

LEFT PANEL

PRECAUTIONARY STATEMENTS  
WARNING  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

**FIRST AID**

**If Swallowed:**

- Immediately call a poison control center or doctor.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give any liquid to the person.
- Do not give anything by mouth to an unconscious person.

ACCEPTED  
with COMMENTS  
EPA Letter Dated:

MAR 13 2007

**If on skin or clothing:**

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No.

2693-176

**If inhaled:**

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

**If in eyes:**

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

**Other:** Have the product container or label with you when calling a poison control center or doctor or going for treatment.

**Note to Physician:** Contains petroleum distillate - vomiting may cause aspiration pneumonia.

**ENVIRONMENTAL HAZARD:**

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**PHYSICAL OR CHEMICAL HAZARD:**

Do not use or store near heat or open flame.

**STORAGE AND DISPOSAL:**

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

Pesticide Disposal: Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State, or local disposal authorities.

Container Disposal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

**ACCEPTED  
with COMMENTS  
EPA Letter Dated:**

**MAR 13 2007**

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

**2693-176**

ACCEPTED  
with COMMENTS  
EPA Letter Dated:

RIGHT PANEL

INTERCLENE XMH SERIES

MAR 13 2007

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.  
2693-176

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

GENERAL DESCRIPTION:

This product is an antifouling protective coating resistant to algae, barnacles and other marine fouling in fresh, sea and brackish waters on steel boat hulls. This product is for commercial and non-commercial use.

**SURFACE PREPARATION AND COMPATIBILITY:** Surface preparation directions must be followed exactly in order to ensure adhesion. Surface must always be clean and dry prior to painting.

**GENERAL APPLICATION PROCEDURES:** Airless spray is recommended: Tip Size 21-26 thou. inch. Pump ratio of 30:1 or greater. For small areas, brush or roller may be used but multiple coats may be required to achieve the required dry film thickness. It is recommended to apply by airless spray one (1) or two (2) full coats of this product.

**MIXING AND THINNING INSTRUCTIONS:** Mix thoroughly with power mixer prior to application. This coating is designed to be applied without thinning. Should thinning be necessary consult your International representative prior to altering this coating.

**CLEAN-UP:** For tools, equipment, etc., use INTERNATIONAL GTA007.

**MINIMUM DRY AND LAUNCHING TIMES:** Minimum drying time between coats is 8 hours, and before launching is 12 to 16 hours depending on paint thickness at a temperature of 73°F.

**THEORETICAL COVERAGE:** 497 square feet per gallon, per coat at 2.0 mils D.T.F. Consult your International representative for practical application coverage. Practical square foot coverage per gallon per coat is directly proportional to surface, application techniques and climatic conditions.

APPLICATION SYSTEMS

**EXISTING ANTIFOULING SYSTEMS – GOOD CONDITION:** High pressure fresh water wash with a minimum of 2500 p.s.i. and/or scrape to remove all marine growth, slime, salts, etc. Spot blast all areas of corrosion to a Near White Metal Standard of SSPC-SP10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

**POOR HULL CONDITIONS:** For "optimum" results, blast entire area to a Near White Metal Standard SSPC-SP10-85. Apply an approved underwater anticorrosive system.

**NEW SHIP CONSTRUCTION:** Blast entire area to a Near White Metal Standard SSPC-SP10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.