# UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460



# United States: Environmental Protection Office of Pesticide Programs Agency

International Paints, LLC 2270 Morris Avenue Union, N. J. 07083

FEB 17 2010

Attention: John P. Pazdera

Pesticide Registration Manager

Subject: Interclene XMH127 RED

EPA Registration No. 2693-176 Notification Dated January 28, 2010

This will acknowledge receipt of your notification, submitted under the provisions of FIFRA Section 3(c)(9).

# **Proposed Notification**

- To revise Storage and Disposal statement per PR Notice 2007-4

# **General Comments**

Based on a review of the submitted material, the following comments apply:

The Notification is in compliance with PR Notice 98-10 and is acceptable. This information has been added to your file.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.


Sincerely

Marthe Leny por Marshall Swindell

Product Manager (33)

Regulatory Management Branch 1 Antimicrobials Division (7510P)

to a consideration of the state		N.	P			Zo
<b>\$EPA</b>	Environmenta	United States I Protection Agrington, DC 20460	ency	Reg	No. 2070-0060 Istration endment er	OPP Identifier Number
		Application for	Pesticide - Se	ction I		
. Company/Product Number 2693-176			2. EPA Product M M. Swindell			
. Company/Product (Nar Interclene XMH127 R			<b>PM#</b> 33	_		None Restricted
International Paint LI 2270 Morris Ave. Union NJ 97083	Applicant <i>(Include ZIP Co</i> )  LC  this is a new address	ode)	(b)(i), my producto: EPA Reg. No.	et is similar or		FIFRA Section 3(c)(3) mposition and labeling
		Sa	Product Name			
Notification - Expl	lain below.  itional page(s) if necessar torage and Disposal sta	ry. (For section I and S	Other - E	etter dated * Application. Explain below.		
		Sec	ction - III			
Yes* No If "Yes" No. per If "Yes" No. per				Yes Metal Plastic Glass No. per Paper		
Label	nts Information  Container	4. Size(s) Retail Cont	ainer	On	of Label Direction Label Labeling accom	
3. Manner in Which Label is Affixed to Product Lithograph Paper glued Stencifed			Ot	ther		
			tion - IV			
. Contact Point <i>(Compl</i>	lete items directly below t	for identification of ind	ividual to be contacte	ed, if necessary	, to process this	application.)
ohn P. Pazdera  Title Pestic			ide Regis. Manager	egis. Manager  Telephone No. (Include Area Constitution of the Second Const		
i certify that the st lacknowledge that both under applica	tatements I have made or It any knowingly false or r Ible law.	Certification n this form and all attac misleading statement n	chments thereto are nay be punishable by	true, accurate a fine or impriso	ccoccoc ind complete.conment or	8. Date Application Received % (Stamped)
Signature John P. Pazdera 3. Title Pest				<del> </del>	00	0 00
	v r. razaeri	2 3. Title Pestici	ide Registration Ma	anager	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	



Mr. Marshall Swindell Product Manager 33 Regulatory Management Branch 1 **Antimicrobial Division** Office of Pesticide Programs (7504P) U.S. EPA Room S-4900, One Potomac Yard 2777 South Crystal Drive Arlington, VA 22202-4501

Via Federal Express

January 28, 2010

Re: Interclene XMH127 Red EPA Reg. No. 2693-176

Notification-Response to PR Notice 2007-4

Dear Mr. Swindell:


The enclosed Notification pertains to our product Interclene XMH127 Red, EPA Reg. No. 2693-176. Specifically, we wish to make the following label change:

Revise the Storage and Disposal statement in accord with PR Notice 2007-4. No other changes are being made.

As this is an Agency-initiated amendment, no registration service fee is required.

In support of this application, please find enclosed:

- Application for Amendment Form (8570-1)
- Five (5) copies of revised labeling
- Copy of EPA stamped label dated 3/13/07 and letter dated 2/28/08
- Certification Statement



4068

Mr. Marshall Swindell January 28, 2010 Page 2

Please do not hesitate to contact me at 908-964-2288 if there are any questions concerning this submission.

Very truly yours,

John P. Pazdera

Pesticide Registration Manager

JPP/cd

Enclosures

50f8

# FRONT PANEL

INTERCLENE XMH127 RED

\_\_\_\_\_\_

# ANTIFOULING PAINT

Active Ingredient:

Cuprous Oxide

= 21.31%

EPA Registration No. 2693-176

Inert Ingredients:

= 78.69%

EPA Establishment No. 2693-TX-1

100.00%

Copper as Metallic

= 18.93%

Contains Petroleum Distillates.

# KEEP OUT OF REACH OF CHILDREN

# WARNING

See side panel for additional precautionary statements

Net Contents: FIVE U.S. GALLONS (18.927 LITERS)

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of International Paint LLC including the surface preparation, proper application and the environmental conditions. Therefore, International Paint LLC cannot guarantee the suitability of this product for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT LLC SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use, of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint LLC's option.

International Paint LLC 2270 Morris Ave. Union, NJ 07083

100fg

# LEFT PANEL

# PRECAUTIONARY STATEMENTS WARNING HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

# **FIRST AID**

## If Swallowed:

- Immediately call a poison control center or doctor.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give any liquid to the person.
- Do not give anything by mouth to an unconscious person.

# If on skin or clothing:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

## If inhaled:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

## If in eyes:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

Other: Have the product container or label with you when calling a poison control center or doctor or going for treatment.

**Note to Physician:** Contains petroleum distillate – vomiting may cause aspiration pneumonia.

# ENVIRONMENTAL HAZARD:

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

## PHYSICAL OR CHEMICAL HAZARD:


Combustible. Do not use or store near heat or open flame.

# STORAGE AND DISPOSAL:

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

**PESTICIDE DISPOSAL**: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.



8088

## RIGHT PANEL

# INTERCLENE XMH SERIES

## **DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

# **GENERAL DESCRIPTION:**

This product is an antifouling protective coating resistant to algae, barnacles and other marine fouling in fresh, sea and brackish waters on steel boat hulls. This product is for commercial and non-commercial use.

SURFACE PREPARATION AND COMPATIBILITY: Surface preparation directions must be followed exactly in order to ensure adhesion. Surface must always be clean and dry prior to painting.

GENERAL APPLICATION PROCEDURES: Airless spray is recommended: Tip Size 21-26 thou. inch. Pump ratio of 30:1 or greater. For small areas, brush or roller may be used but multiple coats may be required to achieve the required dry film thickness. It is recommended to apply by airless spray one (1) or two (2) full coats of this product.

MIXING AND THINNING INSTRUCTIONS: Mix thoroughly with power mixer prior to application. This coating is designed to be applied without thinning. Should thinning be necessary consult your International representative prior to altering this coating.

CLEAN-UP: For tools, equipment, etc., use INTERNATIONAL GTA007.

MINIMUM DRY AND LAUNCHING TIMES: Minimum drying time between coats is 8 hours, and before launching is 12 to 16 hours depending on paint thickness at a temperature of 73°F.

THEORETICAL COVERAGE: 497 square feet per gallon, per coat at 2.0 mils D.T.F. Consult your International representative for practical application coverage. Practical square foot coverage per gallon per coat is directly proportional to surface, application techniques and climatic conditions.

# APPLICATION SYSTEMS

EXISTING ANTIFOULING SYSTEMS – GOOD CONDITION: High pressure fresh water wash with a minimum of 2500 p.s.i. and/or scrape to remove all marine growth, slime, salts, etc. Spot blast all areas of corrosion to a Near White Metal Standard of SSPC-SP10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

POOR HULL CONDITIONS: For "optimum" results, blast entire area to a Near White Metal Standard SSPC-SP10-85. Apply an approved underwater anticorrosive system.

NEW SHIP CONSTRUCTION: Blast entire area to a Near White Metal Standard SSPC-SP10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.