Pm	31	2693	- 177	Page	13
US ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (TS-767) WASHINGTON, DC 20460		2693-17 TERM OF ISSUANCE	DATE OF ISSUANCE.	34	
NOTICE OF PESTICIDE: REGISTRATION			NAME OF PESTICIDE PRODUCT		
(Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)			Interclene XMH242 Red		
NAME AND ADDRESS OF REGISTRANT (Include ZIP code)					
۲			コ		
Courtaulds Coatings Inc 400 South 13th Street Louisville, KY 40201					
L			٦		
NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.					
On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.					
A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.					
Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.					
This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:					
1. Submit/cite all data required for registration/ reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.					
2. Make the labeling changes listed below before you release the product for shipment:					
a. Add the phrase "EPA Registration No. 2693-177".					
b. The heading: "Directions for Use" must be placed directly above the misuse statement on the right panel.					
c. Delete "Structures". (right panel).					
d. Include the heading: Net Contents.					
e. Revise the phrase: "Elemental copper" to read: Copper as metallic% Note: Recalculate your percentage; it may not be 38.30%					
ATTACHMENT IS APPLICABLE					
SIGNATURE OF APPROVI	JG OFFICIAL			DATE	

- 2 -

f. Inlude the following two subheadings to appear within the Storage and Disposal section.

> Pesticide Disposal Container Disposal

- g. Clearly indicate whether this product is for "Commercial Use Only" or "Non-Commercial Use only" or both.
- h. Clearly indicate that this product is be used on boat hulls.
- i. Clearly indicate the boat hull construction material: ie steel boat hulls.
- j. Revise the statement: "Flammable. Keep away from heat and open flame" to read: Do not use or store near heat or open flame.

Note: This is based upon the data submitted for this product.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,

Marshall Swindell Acting Product Manager (31) Antimicrobial Program Branch Registration Division (H7505C)

CONCURRENCES SYMBOL SURNAME DATE OFFICIAL FILE COPY

ACCUPTED
with COMMENTS
in EPA Denor Dates:

FRONT PANEL

INTERCLENE XMH242 RED

ANTIFOULING PAINT

SEP 1 9 1994

Under the federal insections. Functions, and Rederations Art rus amended, for the postfolds rucks where are Reg. No. 2693-177

Active Ingredient:

Cuprous Oxide

= 27.73%

EPA Registration No.

2693-

Inert Ingredients:

= 72.27%

EPA Establishment No. 2693-Tx-1

100.00%

Elemental Copper = 38.30%

Contains Petroleum Distillates.

KEEP OUT OF REACH OF CHILDREN

WARNING

See side panel for additional precautionary statements

FIVE U.S. GALLONS (18.927 LITERS)

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of Courtaulds Coatings Inc. including the surface preparation, proper application and the environmental conditions. Therefore, Courtaulds Coatings Inc. cannot guarantee the suitability of this product for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. COURTAULDS COATINGS INC. SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use, of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Courtaulds Coatings Inc.'s option.

Courtaulds Coatings Inc. 400 S. 13th Street, Louisville, KY 40203

Union, NJ,

Houston, TX

Montreal, Quebec



with COMMENTS in EPA Letter Dated:

RIGHT PANEL

INTERCLENE XMH SERIES

SEP 1 9 1994

Under the Foreign Inscribite, Fungicide, and Reducticide Act. 124 Appendix Under EPA Reg. No. 2693-777

It is a violation of Federal use this product "Hangard, manager and inconsistent with its labeling."

**Register under EFA Reg. No.

GENERAL DESCRIPTION:

This product is an antifouling protective coating resistant to algae, barnacles and other marine fouling in fresh, sea and brackish waters on steel

DIRECTIONS FOR USE:

SURFACE PREPARATION AND COMPATIBILITY: Surface preparation directions must be followed exactly in order to ensure adhesion. Surface must always be clean and dry prior to painting. GENERAL APPLICATION PROCEDURES: Airless spray is recommended: Tip Size 21-26 thou. inch. Pump ratio of 30:1 or greater., For small areas, brush or roller may be used but multiple coats may be required to achieve the required dry film thickness. It is recommended to apply by airless spray one (1) or two (2) full coats of this product.

MIXING AND THINNING INSTRUCTIONS: Mix thoroughly with power mixer prior to application. This coatings is designed to be applied

MIXING AND THINNING INSTRUCTIONS: Mix thoroughly with power mixer prior to application. This coatings is designed to be applied without thinning. Should thinning be necessary consult your International representative prior to altering this coating. CLEAN UP: For tools, equipment, etc., use INTERNATIONAL GTA007. MINIMUM DRY AND LAUNCHING TIMES: Minimum drying time between coats is 8 hours, and before launching is 12 to 16 hours depending on paint thickness at a temperature of 73°F.

THEORETICAL COVERAGE: 497 square feet per gallon, per coat at 2.0 mils D.T.F. Consult your International representative for practical application coverage. Practical square foot coverage per gallon, per coat is directly proportional to surface, application techniques and climatic conditions.

APPLICATION SYSTEMS

EXISTING ANTIFOULING SYSTEMS - GOOD CONDITION: High pressure fresh water wash with a minimum of 2500 p.s.i. and/or scrape to remove all marine growth, slime, salts, etc. Spot blast all areas of corrosion to a Near White Metal Standard of SSPC-SP10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system. POOR HULL CONDITIONS: For "optimum" results, blast entire area to a Near White Metal Standard SSPC-SP10-85. Apply an approved underwater anticorrosive system.

NEW SUIP CONSTRUCTION: Blast entire area to a Near White Metal Standard SSPC-SP10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.



in EPA Letter Dated:

SEP 1 9 1994

LEFT PANEL

PRECAUTIONARY STATEMENTS WARNING

Under the Foderal Insocioida a siculation and Rodenticide Act see abranded, for the pesticide presidented under EPA Reg. 116.

HAZARUS TO HUMAN AND DOMESTIC ANIMALS 2693-/77
Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sailing or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT:

IF SWALLOWED: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

IF IN EYES: Flush with plenty of water. Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove victim to fresh air. If not breathing give artificial respiration, preferably mouth-to mouth. Get medical attention.

ENVIRONMENTAL HAZARD:

This material is toxic to firm. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters urless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD:

Flammable. Keep away from heat and open flame.

STORAGE AND DISPOSAL:

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State, or local disposal authorities.

Container: Triple rinse (or equivalent). Then offer for cecycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

