

US ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (75-767) WASHINGTON, DC 20460 NOTICE OF PESTICIDE: <input checked="" type="checkbox"/> REGISTRATION <input type="checkbox"/> REREGISTRATION <i>(Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)</i>	EPA REGISTRATION NO. 2693-178	DATE OF ISSUANCE SEP 19 1994
	TERM OF ISSUANCE	
	NAME OF PESTICIDE PRODUCT Interspeed BWA360 Red	

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

Courtaulds Coatings Inc
 400 South 13th Street
 Louisville, KY 40201

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit/cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.
2. Make the labeling changes listed below before you release the product for shipment:
 - a. Add the phrase "EPA Registration No. 2693-178".
 - b. The heading: "Directions for Use" must be placed directly above the misuse statement on the right panel.
 - c. Delete "Structures". (right panel).
 - d. Include the heading: Net Contents.
 - e. Revise the phrase: "Elemental copper" to read: Copper as metallic ___%

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL	DATE
---------------------------------	------

2 9 5

- 2 -

f. Include the following two subheadings to appear within the Storage and Disposal section.

Pesticide Disposal
Container Disposal

g. Clearly indicate whether this product is for "Commercial Use Only" or "Non-Commercial Use only" or both.

h. Clearly indicate that this product is be used on boat hulls.

i. Clearly indicate the boat hull construction material: ie steel boat hulls.

j. Revise the statement: "Flammable. Keep away from heat and open flame" to read: Do not use or store near heat or open flame.

Note: This is based upon the data submitted for this product.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



Marshall Swindell
Acting Product Manager (31)
Antimicrobial Program Branch
Registration Division (H7505C)

CONCURRENCES

SYMBOL							
SURNAME							
DATE							

3 9 5

FRONT PANEL

ACCEPTED
with COMMENTS
in EPA Letter Datch

INTERSPEED
BWA360 RED

SEP 19 1994

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.

2693-178

ANTIFOULING PAINT

Active Ingredient:		
Cuprous Oxide	= 38.19%	EPA Registration No. 2693-
Inert Ingredients:	= 61.81%	EPA Establishment No. 2693-Tx-1
	<u>100.00%</u>	
Elemental Copper	= 34.57%	

Contains Petroleum Distillates.

KEEP OUT OF REACH OF CHILDREN

WARNING

See side panel for additional precautionary statements

FIVE U.S. GALLONS (18.927 LITERS)

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of Courtaulds Coatings Inc. including the surface preparation, proper application and the environmental conditions. Therefore, Courtaulds Coatings Inc. cannot guarantee the suitability of this product for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. COURTAULDS COATINGS INC. SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use, of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Courtaulds Coatings Inc.'s option.

Courtaulds Coatings Inc.
400 S. 13th Street, Louisville, KY 40203

Union, NJ,

Houston, TX

Montreal, Quebec

BEST AVAILABLE COPY

495

ACCEPTED
with COMMENTS
in EPA Letter Dated:

SEP 19 1994

RIGHT PANEL

INTERSPEED BWA SERIES

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No.

2693-178

GENERAL DESCRIPTION:

This product is an antifouling protective coating resistant to algae, barnacles and other marine fouling in fresh, sea and brackish waters on steel [REDACTED]

DIRECTIONS FOR USE:

SURFACE PREPARATION AND COMPATIBILITY: Surface preparation directions must be followed exactly in order to ensure adhesion. Surface must always be clean and dry prior to painting.

GENERAL APPLICATION PROCEDURES: Airless spray is recommended: Tip Size 21-26 thou. inch. Pump ratio of 30:1 or greater., For small areas, brush or roller may be used but multiple coats may be required to achieve the required dry film thickness. It is recommended to apply by airless spray one (1) or two (2) full coats of this product.

MIXING AND THINNING INSTRUCTIONS: Mix thoroughly with power mixer prior to application. This coatings is designed to be applied without thinning. Should thinning be necessary consult your International representative prior to altering this coating.

CLEAN UP: For tools, equipment, etc., use INTERNATIONAL GTA007.

MINIMUM DRY AND LAUNCHING TIMES: Minimum drying time between coats is 8 hours, and before launching is 16 hours at a temperature of 73°F.

THEORETICAL COVERAGE. 497 square feet per gallon, per coat at 2.0 mils D.T.F. Consult your International representative for practical application coverage. Practical square foot coverage per gallon, per coat is directly proportional to surface, application techniques and climatic conditions.

APPLICATION S STEMS

EXISTING ANTIFOULING SYSTEMS - GOOD CONDITION: High pressure fresh water wash with a minimum of 2500 p.s.i. and/or scrape to remove all marine growth, slime, salts, etc. Spot blast all areas of corrosion to a Near White Metal Standard of SSPC-SP10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

POOR HULL CONDITIONS: For "optimum" results, blast entire area to a Near White Metal Standard SSPC-SP10-85. Apply an approved underwater anticorrosive system.

NEW SHIP CONSTRUCTION: Blast entire area to a Near White Metal Standard SSPC-SP10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

BEST AVAILABLE COPY

595
ACCEPTED
with COMMENTS
in EPA Letter Dated:

SEP 19 1994

2693-178
Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.

LEFT PANEL

PRECAUTIONARY STATEMENTS
WARNING

HAZARDS TO HUMAN AND DOMESTIC ANIMALS

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT:

IF SWALLOWED: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

IF IN EYES: Flush with plenty of water. Get medical attention.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove victim to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARD:

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD:

Flammable. Keep away from heat and open flame.

STORAGE AND DISPOSAL:

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State, or local disposal authorities.

Container: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

BEST AVAILABLE COPY