

INTERSPEED BWA360 RED

FOR COMMERCIAL USE ONLY

Active Ingredient:	
CUPROUS OXIDE	38.19%
Inert Ingredients:	<u>61.81%</u>
	100.00%

COPPER AS METALLIC = 34.57%

Contains petroleum distillates.

KEEP OUT OF REACH OF CHILDREN WARNING



See side panel for additional Precautionary Statements

EPA Reg. No.: 2693-178

EPA Est. No.: 2693-NJ-1

For specific state registrations contact your International Representative

**NET CONTENTS:
FIVE U.S. GALLONS (18.927 LITERS)**



**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
WARNING**

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

FIRST AID

If Swallowed:

- Immediately call a poison control center or doctor.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give any liquid to the person.
- Do not give anything by mouth to an unconscious person.

If on skin or clothing:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

If inhaled:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

If in eyes:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

Other: Have the product container or label with you when calling a poison control center or doctor or going for treatment.

Note to Physician: Contains petroleum distillate - vomiting may cause aspiration pneumonia.

ENVIRONMENTAL HAZARDS:

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD:



Do not use or store near heat or open flame.

STORAGE AND DISPOSAL:

Do not contaminate water, food or feed by storage or disposal.

PESTICIDE DISPOSAL: Pesticide, spray mixture, or rinsate that cannot be used according to label instructions must be disposed of according to applicable Federal, state or local procedures.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures



DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

This product is for industrial use and professional application only. Not for sale to the general public.

PRODUCT DESCRIPTION: A modified vinyl antifouling used to control the attachment of barnacles, weed and other fouling organisms in sea water and fresh water.

PRODUCT INFORMATION

Finish/Sheen	Semi-Gloss (ASTM D-523)
Converter	One pack
Volume Solids	62% ± 2% (ASTM D-2697)
Mix Ratio	One pack
Flash Point	89°F (32°C) (Setaflash) (ASTM D-3278)
Film Thickness	2 mils (51 microns) dry specified equivalent to 3.2 mils (82 microns) wet; 2.0-3.0 mils (51-76 microns) dry practical range equivalent to 3.2-4.8 mils (82-123 microns) wet
Theoretical Coverage	497 sq. ft./gal. (2.0 mils (51 microns) DFT) Allow appropriate loss factors.

APPLICATION DETAILS

Method	Airless spray, brush or roller
Thinner	Not recommended. If necessary use GTA007, see thinning section.
Cleaner	GTA007



Drying Time (hours)	(ASTM D 1640 7.5.1) Substrate Temperature Touch	Overcoating Interval by Self (ASTM D-1640 7.8)		Minimum drying time* before flooding
		Minimum	Maximum	
41° F(5°C)	8	8	Indefinite	24
73°F (23°C)	3	3	Indefinite	12
95°F (35°C)	2	2	Indefinite	12

* Refer to Limitations section for maximum recommended atmospheric exposure time before flooding.

REGULATORY DATA

VOC: 2.8 lb/gal (340 g/l) as supplied (EPA Method 24)

SYSTEMS AND COMPATIBILITY: International should be consulted for detailed application advice, specification recommendations and as to the suitability of specific products on individual vessels.




LIMITATIONS

Apply in good weather when air and surface temperatures are above 35°F (2°C). Surface temperature must be at least 5°F (3°C) above dew point. For optimum application properties bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40° and 100°F (4-38°C).

Prolonged atmospheric exposure of this product may detract from antifouling performance. Recommended maximum exposure time before flooding:

- Temperate conditions 28 days
- Tropical conditions 7 days



Technical and application data herein is for the purpose of establishing a general guideline of the coating and proper coating application procedures. Test performance results were obtained in a controlled laboratory environment and International makes no claim that the exhibited published test results, or any other tests, accurately represent results actually found in all field environments. As application, environmental and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of the coating.

SURFACE PREPARATION

Paint only clean, dry surfaces. Remove all grease, oil, soluble contaminants and other detrimental foreign matter by "solvent cleaning" (SSPC-SP1).

New Construction: Dependent on yard procedures, consult International.

Unpainted surfaces: Prepare surface and apply recommended primer. Apply one or more coats of Interclene® 140 as specified. (Consult the relevant primer data sheet for surface preparation and overcoating information).


Maintenance: Use controlled close high pressure fresh water washing (3,000 psi, 211 kg/sq.cm.) to clean the entire area, and remove any leached layer at the surface of the existing antifouling system.

Repair corroded areas with the recommended anticorrosive primer and apply Interclene® 140 within the overcoating interval specified for the primer (consult relevant primer data sheet for surface preparation and overcoating information). Apply the specified number of full coats of Interclene® 140.

MIXING: This material is a one component coating. Always mix thoroughly with a power agitator before application.

APPLICATION

Apply by airless spray only. Application by other methods, brush or roller, may require more than one coat and is suggested for small areas only. Apply 3.2 mils (82 microns) wet which will yield 2.0 mils (51 microns) dry film thickness. Consult the following equipment recommendations or utilize suitable equal.



Equipment

Brush: Use appropriate size China bristle brush.

Roller: Use All Purpose Roller Cover with 3/8" (9.5mm) smooth to medium nap. Prewash roller cover to remove loose fibers prior to use.

Airless Spray: Minimum 30:1 ratio pump; .021" - .026" (533-660 microns) orifice tip; 3/8" (9.5mm) ID high pressure material hose. 60 mesh tip filter.

THINNING

DO NOT THIN BEYOND YOUR STATES COMPLIANCY. Material is supplied at spray viscosity and normally does not need thinning. If thinning is necessary, thin up to a maximum of 4 ounces (118 ml) per gallon (3.79 ℓ) with International GTA007 Thinner.

WORK STOPPAGES AND CLEANUP

Clean all equipment immediately after use with International GTA007 Thinner. Spray equipment requires flushing with this solvent. It is good working practice to periodically flush out spray equipment during the course of the working day. Frequency will depend upon factors such as amount sprayed, temperature and elapsed time including work stoppages. Monitor material condition.

WELDING

In the event welding or flame cutting is performed on metal coated with this product, do so in accordance with instruction in ANSI/ASCZ49. 1 "Safety in Welding and Cutting".

SAFETY



This product is not to be used without reference to the current relevant Product Data Sheet and Material Safety Data Sheet (MSDS). Prior to use, obtain, consult and follow both the Material Safety and Product Data Sheets for this product for details concerning both product and health and safety information. Read and follow all precautionary notices on the Material Safety and Product Data Sheets and their container label. If you do not fully understand these warnings and instruction or if you cannot strictly comply with them, do not use this product. Proper ventilation and protective measures must be provided during application and drying to keep solvent vapor concentrations within safe limits and to protect against toxic or oxygen deficient hazards and/or flash fire. Actual safety measures are dependent on application methods and work environment. This safety information is not a substitute for that contained in the Material Safety and Product Data Sheets.

Medical Advisory Number: 1-800-854-6813.

UN Shipping No: 1263

STORAGE: *Store in cool, dry conditions.*

Shelf Life: One year minimum from date of manufacture when maintained in protected storage at 40-100°F (4-38°C). Subject to reinspection thereafter.



6 8 6

All representations and statements concerning the product on this label are accurate to the best of International's knowledge. Any statements herein are not intended to be specific recommendations or warranties of any product, combination of products or fitness for any particular purpose. Any warranty, if given, or specific Terms and Conditions of Sale are contained in International's Terms and Conditions of Sale. You should request a copy of this document and review it carefully.

International Paint Inc.
2270 Morris Ave., Union, NJ 07083

ACCEPTED
JUN 23 2013
Under the Federal Insecticide, Fungicide, and
Rodenticide Act as amended, for the
pesticide, registered under
EPA Reg. No. 2693-178

