

PM

31

2693-179

Page 1 of 5

<p>U.S. ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (75 767) WASHINGTON, DC 20460</p> <p>NOTICE OF PESTICIDE: <input checked="" type="checkbox"/> REGISTRATION <input type="checkbox"/> REREISTRATION (Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)</p>	<p>EPA REGISTRATION NO. 2693-179</p> <p>TERM OF ISSUANCE</p> <p>NAME OF PESTICIDE PRODUCT Fiberglass Bottomkote 999 Bronze</p>	<p>DATE OF ISSUANCE MAR 21 1995</p>
<p>NAME AND ADDRESS OF REGISTRANT (Include ZIP code)</p> <p>Courtaulds Coatings, Inc. 400 South 13th Street P.O. Box 1439 Louisville, KY 40201-1439</p>		
<p>NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.</p>		
<p>On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.</p> <p>A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.</p> <p>Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.</p>		
<p>This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:</p>		
<ol style="list-style-type: none">1. Submit/cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.2. Make the labeling changes listed below before you release the product for shipment:<ol style="list-style-type: none">a. Add the phrase "EPA Registration No. 2693-179"b. Delete the phrase "tin free", this is an implied safety claim.c. Revise your storage and disposal statement to read as follows:<p style="text-align: center;">STORAGE AND DISPOSAL</p>Do not contaminate water, food, feed by storage or disposal. Open dumping is prohibited.<p style="text-align: center;">PESTICIDE DISPOSAL</p>Pesticide wastes are toxic. Paint that cannot be used according to label instructions must be disposed of		
<p>SIGNATURE OF APPROVING OFFICIAL</p>		<p>DATE</p>

2 of 5

according to federal, state or local procedures under the Resources Conservation and Recovery Act.

CONTAINER DISPOSAL

Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved State and local procedures. If burned stay out of smoke.

The heading "STORAGE AND DISPOSAL" must be of the same type size as the child hazard warning statement.

3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



Marion Johnson
Product Manager (31)
Antimicrobial Program Branch
Registration Division (7505C)

Enclosures

3 of 5

EPA Registration No. 2693-

EPA Establishment No. 2693-NJ1

Active Ingredient	=	
Metallic Copper	=	28.32%
Inert Ingredients	=	71.68%
		<hr/> 100.00%

ACCEPTED
with COMMENTS
in EPA Letter Dated:

MAR 21 1995

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.

2693-179

FIBERGLASS BOTTOMKOTE

999 Bronze

KEEP OUT OF REACH OF CHILDREN

WARNING

See side panel for additional precautionary statements

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

44 45

PRECAUTIONARY STATEMENTS

WARNING

HAZARD TO HUMANS AND DOMESTIC ANIMALS:

Causes eye irritation. Harmful if swallowed or absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT:

IF SWALLOWED: Promptly drink large quantities of water. Avoid alcohol. Get medical attention.

IF IN EYES: Flush with plenty of water. Get medical attention if irritation persists.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention if irritation persists.

IF INHALED: Remove victim to fresh air. If not breathing give artificial respiration, preferably mouth to mouth. Get medical attention.

ENVIRONMENTAL HAZARD

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD

Flammable. Keep away from heat and open flame.

STORAGE AND DISPOSAL

PESTICIDE DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State, or local disposal authorities.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in an approved landfill, or by other approved state and local alternative procedures.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

MAR 21 1995

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.

2693-179

DIRECTION FOR USE:

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

PRODUCT DESCRIPTION: For all types of fiberglass, wood and steel boat hulls. Specially formulated to apply over most types of antifouling paint and for boats that are frequently removed from water and subjected to rough usage. Provides extended antifouling protection and a smooth, hard finish. This product can be used in salt, fresh and brackish waters. This product is for commercial and non-commercial use only.

GENERAL APPLICATION: Stir thoroughly. Apply by brush or roller 2 unthinned coats of Interlux Fiberglass Bottomkote, for best results, 3 coats of Interlux Fiberglass Bottomkote are recommended.

THEORETICAL COVERAGE: 350 square feet per gallon.

CLEAN UP: INTERLUX SPECIAL THINNER 216.

ESTIMATED DRY TIMES: For overcoating, minimum 2 hours, recommended 8 hours, maximum 72 hours.

IMMERSION: Minimum 4 hours, recommended 24 hours, maximum 72 hours.

APPLICATION SYSTEMS

SURFACE PREPARATION: If previous antifouling paint is in good condition, wash down with fresh water, degrease with Interlux Brushing Liquid 333 if required, sand surface lightly and apply Interlux Fiberglass Bottomkote as directed. Otherwise, remove all old paint mechanically and/or use Interlux Pintoff 199 or 299 as appropriate. Do not burn off. Proceed as for new work.

NEW WORK: Fiberglass: Wipe down fiberglass with Interlux Solvent Wash 202. Apply one thin coat of Interlux Fiberglass Primer AL200. Overcoat primer within 2-3 hours, no more, no less. Apply second coat of Interlux Fiberglass Bottomkote observing overcoating times. For osmosis repair and prevention, use the Interlux Interprotect System. **Wood:** Sand wood and wipe surface clean. Thin first coat of Interlux Fiberglass Bottomkote 20% with Interlux Special Thinner 216. Apply second coat of Interlux Fiberglass Bottomkote observing overcoating times. **Steel, Lead:** Etch by blasting or grinding with 36 grit paper to provide a good profile. Apply 4-5 coats of Interlux Interprotect 2000E. Apply Interlux Fiberglass Bottomkote following the dry times listed below. Apply second coat of Interlux Fiberglass Bottomkote observing overcoating times.

Temperature (°C)	Hours between last coat of INTERPROTECT 2000E and antifouling paint
10-16 C	7-9 hours
16-27 C	5-7 hours
27-33 C	3-5 hours

Beyond these times, sand with 80 grit paper or apply another coat of INTERPROTECT 2000E before application of the antifouling coating. **Aluminum:** Use Interlux Tri-Lux II.

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of Courtaulds Coatings Inc. including the surface preparation, proper application and the environmental conditions. Therefore, Courtaulds Coatings Inc. cannot guarantee the suitability of this product for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. COURTAULDS COATINGS INC. SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. purchase or use of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Courtaulds Coatings Inc.'s option.

Courtauld's Coatings Inc.
400 S. 13th Street, Louisville, KY 40203

Union, NJ

Louisville, KY

Houston, TX

ACCEPTED
with COMMENTS
in EPA Letter Dated:

MAR 21 1995

Under the authority of the
Federal Insecticide, Fungicide and
Rodenticide Act, for the purpose
registered under EPA Reg. No.

2693-179