

PM

31

2693-179

page 1 of 2

RECD EPA/GPP/DPD2

'96 JUN -7 A8:12

ACCEPTED

DEC 19 1996

Under The Federal Insecticide, Fungicide and  
Rodenticide Act, as amended, for the  
pesticide registered under  
EPA Reg. No. 2693-179


## PRECAUTIONARY STATEMENTS

**WARNING****HAZARDS TO HUMANS AND DOMESTIC ANIMALS:**

Causes eye irritation. Harmful if swallowed or absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

**STATEMENT OF PRACTICAL TREATMENT:**

**IF SWALLOWED:** Promptly drink large quantities of water. Avoid alcohol. Get medical attention.

**IF IN EYES:** Flush with plenty of water. Get medical attention if irritation persists.

**IF ON SKIN:** Wash with plenty of soap and water. Get medical attention if irritation persists.

**IF INHALED:** Remove victim to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. Get medical attention.

**ENVIRONMENTAL HAZARD**

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**PHYSICAL OR CHEMICAL HAZARD**

Flammable. Keep away from heat and open flame.

**STORAGE AND DISPOSAL**

Do not contaminate water, food, feed by storage or disposal. Open dumping is prohibited.

**PESTICIDE DISPOSAL:** Pesticide wastes are toxic. Paint that cannot be used according to label instructions must be disposed of according to federal, state, or local procedures under the Resources Conservation and Recovery Act.

**CONTAINER DISPOSAL:** Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved state and local procedures. If burned stay out of smoke.

**FIBERGLASS BOTTOMKOT****999 BRONZE****KEEP OUT OF REACH OF CHILDREN****WARNING**

See side panel for additional precautionary statements.

**NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)**

ACCEPTED

DEC 19 1996

Under The Federal Insecticide, Fungicide and  
Rodenticide Act, as amended, for the  
pesticide registered under  
EPA Reg. No. 2693-179

KOTE®

DISCLAIMER: The performance of this product is dependent upon the quality of the surface to which it is applied. Interlux® makes no warranty, expressed or implied, for the use of this product on any surface other than that for which it is specifically designed. The user assumes all liability for the use of this product on any surface other than that for which it is specifically designed. Interlux® makes no warranty, expressed or implied, for the use of this product on any surface other than that for which it is specifically designed. The user assumes all liability for the use of this product on any surface other than that for which it is specifically designed.

EPA Reg. No. 2693-179  
EPA Est. No. 2693-179

ACTIVE  
INGREDIENT  
25.00%  
Other Ingredients  
75.00%

# FIBERGLASS BOTTOMKOTE® 999 BRONZE

**PRODUCT DESCRIPTION:** FIBERGLASS BOTTOMKOTE® 999 BRONZE combines season long protection against fouling organisms with a hard, smooth racing finish. FIBERGLASS BOTTOMKOTE® 999 BRONZE uses an acrylic resin to provide ease of application and a hard finish that is compatible with most other types of antifouling paints. It also can be hauled out and trailered (on a short term basis) without losing its antifouling capability. FIBERGLASS BOTTOMKOTE® 999 BRONZE can also be wet sanded and burnished to provide an even smoother surface for racing sailboats or powerboats. FIBERGLASS BOTTOMKOTE® 999 BRONZE is for use below the waterline on fiberglass, wood and properly primed underwater metal boat hulls and parts (except aluminum). FIBERGLASS BOTTOMKOTE® 999 BRONZE is effective in fresh or low fouling saltwater on barnacles, and zebra mussels.

## DIRECTION FOR USE:

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

**COMPATIBILITY:** FIBERGLASS BOTTOMKOTE® 999 BRONZE can be applied over most other hard antifouling paints, but it is important that these coatings be in excellent condition, well adhered to the hull and any loose or flaking paint must be removed. Soft antifouling paints must be removed.

**V.O.C.:** Less than 600 grams/liter.

**THINNER:** SPECIAL THINNER 216  
BRUSH-EASE 433

**THINNING:** Thin only if necessary. Maximum 10%.

**CLEAN UP:** SPECIAL THINNER 216  
BRUSH-EASE 433

**THEORETICAL COVERAGE:** 300 sq. ft./gal. yields 1 mils D.F.T.

**DRY TIMES:** Touch Dry 1 hour minimum.

77°F (25°C): Overcoat 2 hours minimum.  
Launch 8 hours minimum 60 day maximum.

\*Under good drying conditions paint may be overcoated after 2 hours, however it is best to allow an overnight dry to assure complete solvent evaporation. Lower temperature result in longer dry and launch times.

**APPLICATION TEMPERATURES:** 50°F (10°C) and above (air and hull).

## APPLICATION SYSTEMS

**PREVIOUSLY PAINTED SURFACES - Good Condition:** Remove all traces of loose paint and contamination by sanding the entire surface well with 80-120 grit production paper; wipe surface clean. Apply two coats of bottom paint.

**Poor Condition:** Completely remove all old paint with INTERLUX® FIBERGLASS PINTOFF® 299 for fiberglass, INTERLUX® PINTOFF® 199 for wood and by sandblasting steel surfaces to a near white metal. Proceed with application system for bare work as described below.

**BARE FIBERGLASS - No Sand System:** Wash entire surface thoroughly with INTERLUX® FIBERGLASS SOLVENT WASH 202, changing rags frequently. Before liquid dries, wipe clean with a dry cloth. (Be sure all wax and other contaminants are removed). Repair imperfections with INTERLUX® EPOXY SURFACE & FAIRING COMPOUND 417A/418B; sand and wipe clean. Apply one thin continuous coat of INTERLUX® NO SAND PRIMER AL200 with brush or roller. Do not spray, do not sand. Allow to cure between 2-3 hours - no more, no less. Apply two coats of bottom paint.

**Sanding System:** Wash entire surface thoroughly with INTERLUX® FIBERGLASS SOLVENT WASH 202, changing rags frequently. Before liquid dries, wipe clean with a dry cloth. (Be sure all wax and other contaminants are removed). Repair imperfections with INTERLUX® EPOXY SURFACE & FAIRING COMPOUND 417A/418B; sand and wipe clean. Sand entire gelcoat well with 80-120 grit production paper until a flat, matte finish is obtained; wipe surface clean. Apply two coats of bottom paint.

**BARE WOOD:** Sand entire surface thoroughly to a smooth finish with 80 grit production paper; wipe surface clean. Repair imperfections with INTERLUX® EPOXY SURFACE & FAIRING COMPOUND 417A/418B; sand and wipe clean. Apply first coat of bottom paint reduced with INTERLUX® SPECIAL THINNER 216 (10% maximum) to penetrate the porous grain. Fair seams with INTERLUX® SEAM COMPOUND 30. Apply second and third coats of bottom paint unthinned.

**BARE STEEL:** Sandblast surface to a near white metal; remove blast residue with broom and air hose. Within one hour of blasting apply the first coat of INTERPROTECT® 2000E/2001E. If application of INTERPROTECT® 2000E/2001E cannot be applied within one hour after blasting, apply one thin coat of VINYLUX® PRIMEWASH 353/354, that has been thinned 25% with VINYLUX® SOLVENT 355, prior to application of INTERPROTECT® 2000E/2001E. Apply at least 4 coats of INTERPROTECT® 2000E/2001E to reach a minimum dry paint film thickness of 10 mils. If sanding is necessary to smooth INTERPROTECT® 2000E/2001E, apply at least 15 mils of dry paint film thickness prior to sanding. If fairing is necessary, apply INTERLUX® EPOXY SURFACE & FAIRING COMPOUND 417A/418B or VC-WATERITITE between first and second coats of INTERPROTECT® 2000E/2001E.

Rev. 6/95

**Interlux.** For information call 908-686-1300  
Or write: Interlux, 2270 Morris Ave., Union, NJ 07083



400 S. 13th Street, Louisville, KY 40203

Union, NJ • Louisville, KY • Montreal, Quebec • Houston, TX