



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

April 26, 2021

Bathsheba Njuguna
PSRA Team Leader for,
International Paint, LLC
6001 Antoine Drive
Houston, TX 77091

Subject: Label Amendment – Minor Labeling Revisions
Product Name: FiberGlass BottomKote 999 Bronze
EPA Registration Number: 2693-179
Received Date: November 20, 2019
Decision Number: 557979

Dear Njuguna:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. Pursuant to 40 CFR 156.10(a)(6) you must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under FIFRA and is subject to review by the Agency. See FIFRA section 2(p)(2). If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) lists examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process, FIFRA section 12(a)(1)(B). Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Assurance.

The following alternate brand names have been added to the product record:

- FiberGlass BottomKote Racing Bronze
- Interlux FiberGlass BottomKote Racing Bronze
- FiberGlass BottomKote
- BottomKote
- BottomKote Racing Bronze
- FiberGlass Racing Bronze
- Racing BottomKote
- Racing Bronze Antifouling
- Racing Antifouling
- FiberGlass Racing
- BottomKote Racing

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. If you have any questions, please contact Karen M. Leavy by phone at (703)-308-6237, or via email at Leavy.Karen@epa.gov.

Sincerely,



Aline Heffernan
Acting Product Manager Team 31
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

Enclosure: Stamped Label

FIBERGLASS BOTTOMKOTE®
RACING BRONZE
999 BRONZE

ACCEPTED

Apr 26, 2021

Under the Federal Insecticide, Fungicide
and Rodenticide Act as amended, for the
pesticide registered under
EPA Reg. No. 2693-179

Alternative Brand Names (ABNs):

- [FIBERGLASS BOTTOMKOTE RACING BRONZE Y999 BRONZE]
- [FIBERGLASS BOTTOMKOTE RACING BRONZE]
- [INTERLUX FIBERGLASS BOTTOMKOTE RACING BRONZE]
- [FIBERGLASS BOTTOMKOTE]
- [BOTTOMKOTE]
- [BOTTOMKOTE RACING BRONZE]
- [FIBERGLASS RACING BRONZE]
- [RACING BOTTOMKOTE]
- [RACING BRONZE ANTIFOULING]
- [RACING ANTIFOULING]
- [FIBERGLASS RACING]
- [BOTTOMKOTE RACING]

[GRAPHICS]

AkzoNobel

Interlux



Micron, Interlux, InterProtect and the AkzoNobel
logo are trademarks of AkzoNobel. © AkzoNobel [XXXX- year label is printed].

Active Ingredient:

Metallic Copper: 28.32%

Other Ingredients: 71.68%
100.00%

EPA Reg. No. 2693-179

EPA Est. No. 2693 -TX-1

KEEP OUT OF REACH OF CHILDREN

WARNING

See side panel for additional Precautionary Statement

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of International Paint LLC including surface preparation, proper application, and environmental conditions. Therefore, International Paint LLC cannot guarantee this product's suitability for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT LLC SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES when not used as directed. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint LLC's option.

International Paint, LLC.
6001 Antoine Drive
Houston, Texas 77091

[Interlux.com]

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if inhaled. Do not breathe vapor or spray mist. While painting or sanding or sandblasting boat surfaces, wear a NIOSH approved particulate filter with any N, R, P filter with NIOSH approval number prefix TC-84A.; or a NIOSH approved powered air purifying respirator with an HE filter with NIOSH approval number prefix TC-21C. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.

FIRST AID	
If Swallowed:	<ul style="list-style-type: none">• Call a poison control center or doctor immediately for treatment advice.• Have person sip a glass of water if able to swallow.• Do not induce vomiting unless told to do so by a poison control center or doctor.• Do not give anything by mouth to an unconscious person.
If on skin or clothing:	<ul style="list-style-type: none">• Take off contaminated clothing.• Rinse skin immediately with plenty of water for 15-20 minutes.• Call a poison control center or doctor for treatment advice.•
If inhaled:	<ul style="list-style-type: none">• Move person to fresh air.• If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.• Call a poison control, center or doctor for further treatment advice.
If in eyes:	<ul style="list-style-type: none">• Hold eye open and rinse slowly and gently with water for 15-20 minutes.• Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.• Call a poison control center or doctor for treatment advice.
Have the product container or label with you when calling a poison control center or doctor or going for treatment. For medical emergencies, call the poison control center at 1-800-222-1222. For general information on this product, contact the National Pesticides Information Center (NPIC) at 1-800-858-7378, Monday through Friday, 8 AM to 12 PM PST, or at http://npic.orst.edu .	

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD

Flammable. Keep away from heat, sparks or open flames.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE: Exposure to air and extremes of temperature must be avoided. Keep the container firmly closed. Keep out of direct sunlight. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING: Nonrefillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

[Fiberglass Bottomkote® Racing Bronze Y999]

[Alternative brand names, this product]

PRODUCT DESCRIPTION: [Alternative brand names, this product] combines season long protection against fouling organisms with a hard, smooth racing finish. [Alternative brand names, this product] uses an acrylic resin to provide ease of application and a hard finish that is compatible with most other types of antifouling paints. It also can be hauled out and trailered (on a short-term basis) without losing its antifouling capability. [Alternative brand names, this product] can also be wet sanded and burnished to provide an even smoother surface for racing sailboats or powerboats. [Fiberglass Bottomkote® Racing Bronze Y999], [Alternative brand names, this product] is for use below the waterline on fiberglass, wood and properly primed underwater metal boat hulls and parts (except aluminum). [Fiberglass Bottomkote® Racing Bronze Y999], [Alternative brand names, this product] is effective in fresh or low fouling saltwater on barnacles, and zebra mussels.

DIRECTIONS FOR USE:

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

COMPATIBILITY: [Alternative Brand Name, this product] can be applied over most antifouling paints as long as the old coating is tightly adhered and in sound condition. When applying over conventional antifouling paints, thoroughly sand with [80,100, 120, 80-120] [grit, grade, grit wet and dry, grade wet or dry] sand paper. If applying over self-polishing typed copolymers antifoulings, heavy sanding is required. Soft antifouling paints must be removed.

V.O.C.: Less than 660 grams/liter.

THINNER: [Interlux® Special Thinner 216, Special Thinner]
[Interlux® Brush-Ease 433,
[Yacht Thinner, Boat Thinner, Acetone]

THINNING: Thin only if necessary. Maximum 10%.

CLEAN UP:

Interlux® Special Thinner 216, Special Thinner]
[Interlux® Brush-Ease 433,
[Yacht Thinner, Boat Thinner, Acetone]

THEORETICAL COVERAGE: 300 sq. ft./gal. yields 1 mils D.F.T.

DRY TIMES: Touch Dry 1 hour minimum.

77°F (25°C) Overcoat 2 hours minimum*.

Launch 4 hours minimum 60 day maximum.

*Under good drying conditions paint may be overcoated after 2 hours, however it is best to allow an overnight dry to assure complete solvent evaporation. Lower temperature result in longer dry and launch times.

APPLICATION TEMPERATURES: 50°F (10°C) and above (air and hull).

APPLICATION SYSTEMS

PREVIOUSLY PAINTED SURFACES - GOOD CONDITION: Remove all traces of loose paint and contamination by sanding the entire surface with [80, 80-120, 100, 120] [grit, grade, wet or dry] sandpaper: wipe surface clean with [Special Thinner 216, Special Thinner, Thinner 216, Yacht Thinner, Boat Thinner, Acetone]. Apply 2 coats of [alternative brand name, this product].

POOR CONDITION Completely remove all old antifouling paint [by paint stripper, sanding, abrasive media blasting, sanding or abrasive media blasting] for [fiberglass, epoxy, wood, or, sandblasting steel surfaces to a near white metal]. Proceed with application system for bare system below.

Bare Fiberglass - Surface Preparations [Polyester, Vinyl ester, Epoxy][Polyester, Vinyl ester and Epoxy]: It is very important that bare fiberglass be properly prepared in order to prevent delamination of the antifouling paint. Begin by scrubbing the surface thoroughly with a stiff brush using soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry. Remove mold release wax using one of the following products: [Interlux Fiberglass Surface Prep YMA601V, Interlux Fiberglass Solvent Wash 202, Fiberglass Surface Prep YMA601V, Fiberglass Solvent Wash 202, Fiberglass Surface Prep, Solvent Wash, Acetone, Boat Prep] following the product label instructions. To be certain that all the contamination has been removed, run water over the surface; if the water beads up or separates, clean again. When the water sheets off, all contamination has been removed. After the surfaces has been properly cleaned, proceed with one of the application systems below.

BARE FIBERGLASS - NO SAND SYSTEM: Clean the surface following the preparation procedure described. Apply one coat of [InterProtect 2000E, InterProtect HS, InterProtect, Sandless Primer] following the label instructions for applying the primer and overcoating with antifouling paint. Apply 2 coats of antifouling allowing for the appropriate dry times.

SANDING SYSTEM: Clean the surface following the preparations procedure described. Sand the entire surface with [80-120, 80, 100, 120] [grit, grade, wet or dry] sandpaper and wipe clean with [Interlux Fiberglass Solvent Wash 202, Fiberglass Solvent Wash 202, Fiberglass Solvent Wash, Solvent Wash, Acetone, Boat Thinner, Interlux Fiberglass Surface Prep YMA601V, Fiberglass Surface Prep YMA601V, Fiberglass Surface Prep, Surface Prep, Boat Surface Prep] to remove sanding residue. Repair any surface imperfections with [Watertite, Watertite Epoxy Filler, Epoxy Filler, Boat Filler]. Sand and wipe clean. Apply 2 coats of [alternative brand name, this product] allowing for appropriate dry times.

BARE WOOD: Sand the entire surface with [80-120, 80, 100, 120] [grit, grade, wet or dry] sandpaper and wipe clean with [Special Thinner 216, Interlux Special Thinner 216, Special Thinner, Acetone, Fiberglass Solvent Wash 202, Interlux Fiberglass Solvent Wash 202, Solvent Wash, Boat Thinner]. Repair imperfections with [Watertite, Watertite Epoxy Filler, Epoxy Filler]. Apply the first coat of this product thinned 10% with [Special Thinner 216, Interlux Special Thinner 216, Special Thinner, Acetone, Interlux Brush Ease 433, Brush Ease 433, Brush Ease]. Fill seams with [Seam Compound 30, Seam Compound, Seam Filler], if necessary. Apply 2nd coat of this product unthinned, following the overcoating times.

BARE STEEL: Sandblast to a near white finish; wipe surface clean with clean airline or broom. Immediately apply one coat of [InterProtect 2000E, Interlux InterProtect 2000E, Interlux InterProtect HS, InterProtect HS, InterProtect] thinned 15% with [Interlux 2333n, Interlux 2316n, Brushing Reducer 2333n, Spray Reducer 2316n]. Fill in all imperfections with [Interlux Watertite Epoxy Filler, Watertite Epoxy Filler, Interlux Interfill Epoxy Filler, Interfill Epoxy Filler, Interlux Epoxy Filler, Epoxy Filler]. Sand filled areas smooth; wipe clean. Apply 3 coats of [InterProtect 2000E, Interlux InterProtect 2000E, Interlux InterProtect HS, InterProtect HS, InterProtect, Primocon, Interlux Primocon, Underwater Metal Primer, Metal Primer, Boat Metal Primer]. Apply 2 coats of antifouling paint.

FOR INFORMATION CALL 1-713-682-1711 OR WRITE TO: 6001 Antoine Drive, Houston TX 77091

Color difference may occur between actual paint and color swatch on front of can.

[Fiberglass Bottomkote and the AkzoNobel logo are trademarks of AkzoNobel. © AkzoNobel] [current year].