



U.S. ENVIRONMENTAL PROTECTION AGENCY  
Office of Pesticide Program  
Registration Division (H7505C)  
401 "M" St., S.W.  
Washington, D.C. 20460

EPA Reg.  
Number:

2693-190

Date of Issuance:

JUN 15 2005

NOTICE OF PESTICIDE:  
  X   Registration  
      Reregistration

(under FIFRA, as amended)

Term of Issuance: Expiration  
Date 06/15/06

Name of Pesticide Product:

MICRON CSC SUPER WITH  
BIO-LUX BLUE

Name and Address of Registrant (include ZIP Code):

International Paint, Inc.  
2270 Morris Avenue  
Union, NJ 07083

**Note:** Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency request all registrants of similar product to submit such data; and submit acceptable response required for reregistration of your product under FIFRA section 4.

The Agency is currently reviewing additional information submitted by your supplier. Therefore, we are extending this limited registration to June 15, 2006.

Signature of Approving Official:

Marshall Swindell,  
Product Manager 33  
Regulatory Management Branch I  
Antimicrobials Division (7510C)

Date:

JUN 15 2005

2/0

2. This conditional registration will expire automatically on June 15, 2006. If you fail to satisfy the conditions imposed in the registration, EPA may issue a Notice To Cancel under Section 6(e) of FIFRA.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,



Marshall Swindell  
Product Manager 33  
Regulatory Management Branch I  
Antimicrobials Division (7510C)

Enclosure

3/6

**MICRON CSC® SUPER  
with BIO-LUX™**

- Bio-Lux Blocks Slime
- Bio-Lux Boosts Performance by Controlling Slime
- ~~Biocidal~~ Antifouling Protection for All Conditions
- Multi-Season, Self-Polishing, No Paint Buildup

**BLUE**

**KEEP OUT OF REACH OF CHILDREN**

**CAUTION**

See side panel for additional precautionary statements

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

JUN 15 2005

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

2693-190

EPA Registration No. 2693-190  
EPA Establishment No. 2693-NJ

**Active Ingredients:**

Cuprous Oxide	= 38.62%
N-Cyclopropyl-N'-(1,1-dimethylethyl)-6- (methylthio)-1,3,5-triazine-2,4-diamine	= 2.00%
Inert Ingredients:	= 59.38%
	100.00%
Copper as Metallic	= 34.03%

**DISCLAIMER:** The performance of any marine coating depends on many factors outside the control of International Paint Inc. including the surface preparation, proper application and the environmental conditions. Therefore, International Paint Inc. cannot guarantee the suitability of this product for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT INC. SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use, of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint Inc.'s option.

**International Paint Inc.**

**Union, NJ**

JUN 15 2005

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

**PRODUCT DESCRIPTION:** MICRON CSC® SUPER with BIO-LUX™ is a multi-2693-196  
season, Controlled Solubility Copolymer antifouling paint that is specially formulated  
with two biocides - cuprous oxide and a booster called BIO-LUX™. The cuprous oxide  
works best against shell fouling, while the BIO-LUX™ booster helps protect against  
weed, slime and algae growth. MICRON CSC® SUPER with BIO-LUX™ washes  
away (polishes) at a controlled rate similar to a bar of soap, resulting in a reduced build-  
up of old coatings and minimized sanding at reapplication. This technology also allows  
the boat to be hauled and launched without recoating. MICRON CSC® SUPER with  
BIO-LUX™ is for use below the waterline on fiberglass, wood and properly primed  
metal boat hulls and parts, in fresh, salt and brackish waters. Do not use on aluminum.

### DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its  
labeling.

**COMPATIBILITY:** MICRON CSC® SUPER with BIO-LUX™ can be applied over  
most hard, conventional antifouling paints as long as the old coating is tightly adhered, is  
in sound condition, and has been thoroughly sanded with 80 grit wet-or-dry sandpaper.  
MICRON CSC® SUPER with BIO-LUX™ should not be applied over MICRON  
33®, MICRON 44® or soft antifouling paints. These old coatings should be removed.

**V.O.C.:** Less than 400 grams/liter  
(3.33 lbs./gallon)

**THINNING:** Thin only when necessary.  
Do not exceed 10% by volume.

**DRY TIMES:** Touch dry- 2 hours  
77°F (25°C) Dry to overcoat - 16 hours minimum\*  
Dry to launch - 16 hours minimum \*

**THINNER:** Brushing- BRUSH-EASE 433  
Spraying- SPECIAL THINNER 216

**THEORETICAL COVERAGE:** 440 sq.ft./gallon  
Yields 2 mils dry film thickness

**CLEAN-UP:** SPECIAL THINNER 216 or  
BRUSH-EASE 433

**APPLICATION TEMPERATURES:** 50°F (10°C) and above. (Air and hull)

\* If either hull or air temperature falls below 50°F (10°C) during the 16 hour dry time  
extend the dry time to a minimum of 36 hours.

### APPLICATION SYSTEMS

Shake or mix well prior to use. Apply at least two full coats (3 coats on bare wood) of  
MICRON CSC® SUPER with BIO-LUX™ by brush or solvent resistant 3/8" nap  
roller. Do not apply thin coats. Keep in mind that the life of the paint is directly related to  
the amount of paint applied. If during application the brush pulls or the roller drags, use  
INTERLUX® BRUSH-EASE 433 to improve handling. Certain areas of the hull  
experience faster polishing than the other areas. These areas include the waterline, the  
leading edge of the keel, the rudder and the bow stem. It is suggested that an additional  
coat of paint be applied to these areas to insure that the MICRON CSC® SUPER with  
BIO-LUX™ does not wash away before the other areas of the bottom.

**PREVIOUSLY PAINTED SURFACES - GOOD CONDITION:** Remove all traces of loose paint and contamination by sanding the entire surface well with 80 grit wet-or-dry sandpaper; wipe surface clean with INTERLUX® SPECIAL THINNER 216. Apply at least 2 coats of MICRON CSC® SUPER with BIO-LUX™ allowing proper dry times.

**PREVIOUSLY PAINTED SURFACES - POOR CONDITION:** Completely remove all antifouling paint with INTERLUX® INTERSTRIP 299E for fiberglass or wood and by sandblasting steel surfaces to a near white metal. Proceed with application for bare work described below.

**BARE FIBERGLASS - SURFACE PREPARATION (POLYESTER OR VINYL-ESTER):** It is very important that bare fiberglass be prepared properly to prevent delamination of antifouling paint. Scrub the surface thoroughly with soap and water using a stiff bristled brush. Flush well with fresh water. When the surface is dry, wipe a small area with a clean cloth that has been wetted with INTERLUX® FIBERGLASS SOLVENT WASH 202. While the surface is still wet remove with a clean dry cloth. Repeat this process until the entire surface has been cleaned. To be certain that all wax and other contaminants have been removed, run water over the surface. If the water beads up or separates, wipe again with FIBERGLASS SOLVENT WASH 202. When the water sheets off, all contamination has been removed. Sanding does not remove contamination. After the surface has been properly cleaned, proceed with the application systems below.

**BARE FIBERGLASS - NO SAND SYSTEM:** Clean the surface following the preparation procedure described above. Repair any surface imperfections with INTERLUX® INTERPROTECT WATERTITE V135. Sand the repaired areas and wipe clean. Apply one thin continuous coat of INTERLUX BONDKOTE 200 FIBERGLASS PRIMER®. Follow the BONDKOTE 200 label directions for overcoating, apply at least 2 coats of MICRON CSC® SUPER with BIO-LUX™. Allow proper dry times between coats.

**BARE FIBERGLASS - SANDING SYSTEM:** Clean the surface following the preparation procedure described above. Repair any surface imperfections using INTERLUX® INTERPROTECT WATERTITE V135. Sand and wipe clean. Sand the entire surface with 80 grit sandpaper until a flat, matte finish is obtained. Wipe the sanding residue off the surface with FIBERGLASS SOLVENT WASH 202. Apply at least two coats of MICRON CSC® SUPER with BIO-LUX™.

**BARE WOOD:** Sand entire underwater surface with 80 grit sandpaper; wipe surface clean with INTERLUX® BRUSH-EASE 433. Repair imperfections with INTERLUX® INTERPROTECT WATERTITE V135; sand and wipe clean. Apply first coat of MICRON CSC® SUPER with BIO-LUX™ reduced 10% with BRUSH-EASE 433 to penetrate into the wood. Fill seams with INTERLUX® SEAM COMPOUND 30. Apply second and third coats of MICRON CSC® SUPER with BIO-LUX™ unreduced. Allow proper dry times between coats.

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

JUN 15 2005

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,

6/6

**UNDERWATER METALS:** Contact the Interlux Technical Service Department at 1-800-468-7589 for details on how to properly prime underwater metals. Do not use on aluminum.

**Color difference may occur between actual paint and color swatch on front of can.**

**INTERLUX®** For information call 908-686-1300

Or write Interlux 2270 Morris Avenue, Union, NJ 07083

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

JUN 15 2005

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

2693-190