

2693-191

3-9-2000

1/6



U.S. ENVIRONMENTAL PROTECTION AGENCY  
Office of Pesticide Programs  
Registration Division (H7505C)  
401 "M" St., S.W.  
Washington, D.C. 20460

EPA Reg. Number:

2693-191

Date of Issuance:

MAR - 9 2000

NOTICE OF PESTICIDE:

- Registration
- Reregistration

Term of Issuance: Conditional

Name of Pesticide Product: Micron 33  
OutDrive Spray 464A White

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

International Paint, Inc.  
2270 Morris Avenue  
Union, N.J. 07083

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration/ reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.

2. Make the following label changes:

- a. Revise the EPA Registration Number to read, "EPA Reg. No. "2693-191".

Signature of Approving Official:

Marshall Swindell, PM 33  
Regulatory Management Branch I  
Antimicrobial Division (7510C)

Date:

MAR - 9 2000

2/6

Page 2  
EPA Registration No. 2693-191

3. Submit two (2) copies of the revised final printed labeling before you release the product for shipment.

The Confidential Statements of Formula for one basic and two alternate formulations, dated August 10, 1999 are in compliance with PR Notice 91-2 and are acceptable.

A stamped copy of the label is enclosed for your records.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely,



Marshall Swindell  
Product Manager 33  
Regulatory Management Branch 1  
Antimicrobial Division (7510C)

Enclosure

3/6

**MICRON 33  
OUTDRIVE SPRAY  
464A White**

**COPOLYMER ANTIFOULING PAINT  
FOR OUTBOARDS & OUTDRIVES**

ACTIVE INGREDIENTS	PERCENT
Tributyltin Methacrylate (as part of a polymer)	4.020
Bis (tributyltin) Oxide	0.057
Cuprous Thiocyanate	5.310
Inert Ingredients	<u>90.613</u>
	100.000

Elemental Tin 1.3%  
Elemental Copper 2.7%

EPA REG. NO. 2693-  
EPA EST. 2693-NJ-1

Contains Petroleum Distillates

**ACCEPTED  
with COMMENTS  
in EPA Letter Dated:**

**MAR - 9 2000**  
Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

**KEEP OUT OF REACH OF CHILDREN  
DANGER**

See Side Panel For Additional Precautionary Statements

**2693-191**

**NET WT. 19.75 OZ. (560 GRAMS)**

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

4/16

**Micron 33 Outdrive Spray 464A White**  
**COPOLYMER ANTIFOULING PAINT**

**DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

This product may only lawfully be used on aluminum outdrives and outboards. It is unlawful to use this product on non-aluminum hulled vessels less than 82 feet (25 meters) in length (on deck) except for the outboard motor or lower drive unit of such vessels. Users must comply with all applicable OSHA requirements.

**PRODUCT DESCRIPTION:** MICRON OUTDRIVE SPRAY antifouling paint is formulated specifically for aluminum outboards, outdrives and aluminum boat hulls in underwater areas. When applied over properly primed metal MICRON 33 OUTDRIVE SPRAY will provide excellent antifouling protection. MICRON 33 OUTDRIVE SPRAY is a true polishing copolymer that washes away with use, preventing buildup of old coatings. MICRON 33 OUTDRIVE SPRAY is for use in fresh, salt and brackish water.

**APPLICATION SYSTEMS**

**BARE ALUMINUM:** Sand with medium grit emery cloth to a bright metal finish. Apply one thin coat of VINYLUX® PRIMEWASH 353/354 that has been thinned 25% with VINYLUX® SOLVENT 355. Allow to dry one hour but no more than twenty-hour hours and apply the first coat of INTERLUX® OUTBOARD AND OUTDRIVE AEROSOL PRIMER 370 to the entire underwater surface. Do not apply primer or MICRON 33 OUTDRIVE SPRAY above the true waterline. After applying at least 2 coats of primer, apply MICRON 33 OUTDRIVE SPRAY as specified below.

**PREVIOUSLY PAINTED (With Antifouling Paint):** Sand with 80 grit sandpaper. Wipe off sanding residue with INTERLUX® SPECIAL THINNER 216. Resand any areas where the bare aluminum is exposed with medium grit emery cloth and wipe clean. Immediately apply INTERLUX® OUTBOARD AND OUTDRIVE AEROSOL PRIMER 370 to bare areas. Apply at least two full coats of primer to the entire underwater surface. Do not apply primer or MICRON 33 OUTDRIVE SPRAY above the true waterline. Apply MICRON 33 OUTDRIVE SPRAY as specified below.

**FACTORY PAINTED SURFACES (Underwater Surface Only):** Wipe surface clean with INTERLUX® SPECIAL THINNER 216 to remove contaminants. Sand the surface with 120 grit production sandpaper. Wipe the surface again with INTERLUX® SPECIAL THINNER 216 to remove sanding residue. Apply at least 2 coats of INTERLUX® OUTBOARD AND OUTDRIVE AEROSOL PRIMER 370, allowing appropriate dry times. After an overnight dry apply at least one full can of MICRON 33 OUTDRIVE SPRAY as specified below. Do not apply primer or MICRON 33 OUTDRIVE SPRAY above the true waterline.

**ACCEPTED**  
with **COMMENTS**  
in EPA Letter Dated:

MAR - 9 2000

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

2693-191

**MICRON 33 OUTDRIVE SPRAY APPLICATION**

- 1) Shake can well, listen for rattle of mixing ball. Continue shaking for at least one minute.
- 2) Hold container about 12-16 inches from unit when applying paint. MICRON 33 OUTDRIVE SPRAY will be touch dry in about 30 minutes.
- 3) Apply contents of one can for each outdrive/outboard. Allow a minimum of 6 hours at 75°F or 12 hours at 50°F dry time between coats.
- 4) Be sure paint is completely dry before immersion, leave a minimum of 12 hours at 75°F or 16 hours at 50°F prior to launch.
- 5) Clean up -- use INTERLUX® SPECIAL THINNER 216.

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:  
MAR - 9 2000

**PRECAUTIONARY STATEMENTS**  
**DANGER**

**HAZARDS TO HUMANS AND DOMESTIC ANIMALS:**

Corrosive. Causes eye irritation and skin burns. When handling wear full protective clothing, rubber gloves, goggles, face shield or other approved eye protection. May be fatal if swallowed or inhaled. Harmful if absorbed through skin. This product may be dermal sensitizer. Avoid contact with skin, eyes or clothing. Remove and wash contaminated clothing before reuse. Avoid breathing of vapor, spray mist, dust or chips from sanding or blasting. While spraying, sanding or blasting wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health.

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 2693-191


**STATEMENT OF PRACTICAL TREATMENT**

- IF SWALLOWED:** Promptly drink large quantities of water. Avoid alcohol. Get medical attention.
- IF IN EYES:** Flush with plenty of water. Get medical attention if irritation persists.
- IF ON SKIN:** Wash with plenty of soap and water. Get medical attention if irritation persists.
- IF INHALED:** Remove victim to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. Get medical attention.

**ENVIRONMENTAL HAZARD**

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent to sewer system without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**PHYSICAL OR CHEMICAL HAZARD:** Extremely Flammable. Content under pressure. Keep away from heat, sparks, open fire or heated surfaces. Do not puncture or incinerate container. Exposure to temperatures above 130°F may cause bursting,



6/6

### STORAGE AND DISPOSAL

Do not contaminate water, food, feed by storage or disposal. Open dumping is prohibited.

**PESTICIDE DISPOSAL:** Pesticide wastes are toxic. Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

**CONTAINER DISPOSAL:** Do not puncture or incinerate. A completely empty can can be disposed of with household trash. Wrap in paper before disposing.

**DISCLAIMER:** The performance of any marine paint or coating depends on many factors outside the control of Interlux including surface preparation, proper application, and environmental conditions. Therefore, Interlux cannot guarantee this product's suitability for your particular purpose or application. **IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. INTERLUX SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.** By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Interlux's option.



For information call 908-686-1300  
Or write: Interlux, 2270 Morris Ave., Union, NJ 07083

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

1/99

MAR - 9 2000

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.  
2693-191