

2693-192

02/01/2005

1/8

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

International Paint, Inc.
2270 Morris Ave.
Union, NJ 07083

FEB -1 2005

Attention: Mr. John P. Pazdera

Subject: **Ultra with Bio-lux Blue**
EPA Registration No. 2693-192
Amendment Application Date: January 4, 2004
EPA Received Date: January 5, 2004

This will acknowledge receipt of your notification, submitted under the provisions of FIFRA section 3 (c) 9. Based on a review of the material, the following comment apply.


- The following product descriptor is acceptable to add on the front panel:
"Contains Teflon for Added Durability, Easy Cleaning and Reduce Drag"
- The following product descriptors are not acceptable and considered misleading:
"Biolux Blocks Slime" This is a misleading statement concerning the effective of the product as a pesticide.
"Teflon only by DuPont" This statement is a comparison with other teflon products.

This application and has been made a part of the records for this file.

CONCURRENCES							
SYMBOL							
SURNAME							
DATE							

If you have any comments or questions concerning this letter, please contact me at (703) 308-6341 or Portia Jenkins at (703) 308-6230.

Sincerely,



Marshall Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510C)

33

3/8



Marine and Protective Coatings

January 4, 2005

Via Federal Express

Mr. Marshall Swindell
 Product Manager (33)
 Regulatory Management Branch I
 Antimicrobials Division (7504C)
 U.S. EPA
 Room 266A, Crystal Mall 2
 1801 South Bell Street
 Arlington, VA 22202-4501

Re: Ultra with Bio-Lux Blue
 EPA Reg. No. 2693-192
 Notification – Minor Labeling Changes

Dear Mr. Swindell:

The enclosed Notification pertains to our product Ultra with Bio-Lux Blue, EPA Reg. No. 2693-192. Specifically, we wish to make the following label changes:

- Add the product descriptors “Biolux Blocks Slime”, “Contains Teflon for Added Durability, Easy Cleaning and Reduced Drag” and “Teflon only by DuPont” to the front panel.

Enclosed, therefore, please find:

- EPA Form 8570-1
- Copy of EPA approved label dated 9/15/04
- Five (5) copies of labels bearing the revisions noted above
- Certification Statement


Please do not hesitate to contact me at 908-964-2288 if there are any questions concerning this submission.

Very truly yours,

John P. Pazdera
 Pesticide Registration Manager

JPP/cd

Enclosures



International Paints Inc.
 2270 Morris Avenue
 Union, New Jersey 07085
 USA
 Tel: (800) 681-1481
 Fax: (908) 688-1545

4/8



Please read instructions on reverse before completing form.

Form Approved. OMB No. 2070-0060

	United States Environmental Protection Agency Washington, DC 20480	<input type="checkbox"/> Registration <input type="checkbox"/> Amendment <input checked="" type="checkbox"/> Other	OPP Identifier Number
--	---	--	-----------------------

Application for Pesticide - Section I

1. Company/Product Number 2693-192	2. EPA Product Manager M. Swindell	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) Ultra with Bio-Lux Blue	PM# 33	
5. Name and Address of Applicant (Include ZIP Code) International Paint Inc. 2270 Morris Ave. Union, NJ 07083 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

Notification - Minor Labeling Changes
- Addition of Product Descriptors to Front Panel

Section - III *N/A*

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No		<input type="checkbox"/> Metal <input type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input type="checkbox"/> Other (Specify) _____	
* Certification must be submitted		If "Yes" Unit Packaging wgt. No. per container	If "Yes" Package wgt No. per container		
3. Location of Net Contents Information		4. Size(s) Retail Container		5. Location of Label Directions	
<input type="checkbox"/> Label <input type="checkbox"/> Container				<input type="checkbox"/> _____	
6. Manner in Which Label is Affixed to Product				<input checked="" type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled <input type="checkbox"/> Other _____	

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name John P. Pazdera	Title Pesticide Registration Manager	Telephone No. (Include Area Code) 908-964-2288
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped)
2. Signature 	3. Title Pesticide Registration Mgr.	
4. Typed Name John P. Pazdera	5. Date 1/4/05	

ULTRA™ with BIOLUX™

BLUE

- Teflon® only by DuPont
- Contains Biolux to resist slime
- High Copper Antifouling for Ultimate Protection
- Teflon® Added for Durability and Easy Cleaning
- Biolux Boosts Antifouling Performance by Controlling Slime
- Biolux Blocks Slime
- Contains Teflon® for Added Durability, Easy Cleaning and Reduced Drag

KEEP OUT OF REACH OF CHILDREN

WARNING

See side panel for additional precautionary statements

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)


EPA Registration No. 2693-192
EPA Establishment No. 2693-NJ

Active Ingredients:

Cuprous Oxide	= 66.65%
N-Cyclopropyl-N'-(1,1-dimethylethyl)-6-(methylthio)-1,3,5-triazine-2,4-diamine	= 1.59%

Inert Ingredients:	= 31.76%
	100.00%

Copper as Metallic	= 59.2%
--------------------	---------



DISCLAIMER: The performance of any marine coating depends on many factors outside the control of International Paint Inc. including the surface preparation, proper application and the environmental conditions. Therefore, International Paint Inc. cannot guarantee the suitability of this product for your particular purpose or application. **IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED.** INTERNATIONAL PAINT INC. SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use, of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint Inc.'s option.

International Paint Inc.

Union, NJ

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
WARNING**

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

FIRST AID

If Swallowed:

- Call a poison control center or doctor immediately for treatment advice.
- Have person sip a glass of water if able to swallow.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give anything by mouth to an unconscious person.

If on skin or clothing:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

If inhaled:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

If in eyes:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

Other: Have the product container or label with you when calling a poison control center or doctor or going for treatment.

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD: Flammable. Keep away from heat, sparks and open flame.

STORAGE AND DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Open dumping is prohibited. Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local procedures.

PRODUCT DESCRIPTION: Ultra™ with Biolux™ provides excellent long term protection from shell and weed fouling. Ultra™ with Biolux™ contains a very high loading of cuprous oxide and an organic boosting biocide called Biolux™. The cuprous oxide works best against shell fouling such as barnacles and zebra mussels and the Biolux™ booster works to control slime and algae fouling. Ultra™ with Biolux™ also contains Teflon® for added durability and easy cleaning. Ultra™ with Biolux™ is recommended for use wherever the fouling challenge is severe, and can be used in fresh, salt and brackish water on fiberglass, wood and properly primed metal boat hulls and parts. Do not use on aluminum. Ultra™ with Biolux™ can be applied over hard well sanded antifouling paint. Even though Ultra™ with Biolux™ has a very high loading of cuprous oxide it has excellent color stability and resists changing color at the waterline.

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

COMPATIBILITY: Ultra™ with Biolux™ can be applied over any other hard antifouling paint after sanding the surface. Soft antifouling paints will need to be removed or overcoated with Underwater Primer 360R before applying Ultra™ with Biolux™.

V.O.C.: Less than 290 grams/liter (2.40 lbs./gallon)	THEORETICAL COVERAGE: 530 sq. ft./ gallon yields 2 mils dry film thickness.
THINNER: Special Thinner 216 or Brush-Ease 433	DRY TIMES: Touch dry - 2 hours 77°F (25°C) Dry to overcoat - 16 hours minimum Dry to launch - 16 hours minimum 60 days maximum
THINNING: Thin only when necessary Do not exceed 10% maximum.	APPLICATION TEMPERATURE: 50°F (10°C)* and above (air and hull)
CLEAN-UP: Special Thinner 216 or Brush-Ease 433	

*If either the air or hull temperature falls below 50°F (10°C) during the 16 hour dry time extend the dry times to 36 hours minimum.

APPLICATION SYSTEMS

PREVIOUSLY PAINTED - GOOD CONDITION: Remove all traces of loose paint and contamination by sanding the entire surface with 80 grit sandpaper, wipe surface clean with Special Thinner 216. Apply at least two coats of Ultra™ with Biolux™.

PREVIOUSLY PAINTED - POOR CONDITION: Completely remove all old antifouling paint, using Interstrip 299E. Sand and wipe clean with Fiberglass Solvent Wash 202.

BARE FIBERGLASS - (POLYESTER OR VINYLESTER)

SURFACE PREPARATION: It is very important that bare fiberglass be properly prepared to prevent delamination of the antifouling paint. Scrub the surface thoroughly with soap and water using a stiff brush. Flush well with water. Wipe a small area with a clean cloth that has been wetted with Interlux® Fiberglass

Solvent Wash 202. While the surface is still wet remove with a clean dry cloth. Repeat this process until the entire surface has been cleaned. To be certain that all of the contamination has been removed, run water over the surface. If the water beads up or separates, wipe again with Fiberglass Solvent Wash 202. When the water sheets off, all contamination has been removed. Sanding does not remove contamination. After the surface has been properly cleaned, proceed with the application system below.

BARE FIBERGLASS - NO SAND SYSTEM: Clean the surface following the preparation procedure above. Repair any surface imperfections using Interlux® Interprotect® Watertite® V135. Sand and wipe clean. Apply one thin, continuous coat of Interlux No Sand Primer by brush or roller. Follow application directions for primer and apply the first coat of Ultra™ with Biolux™. Apply a second coat allowing for the appropriate dry times.

BARE FIBERGLASS - SANDING SYSTEM: Clean the surface following the preparation procedure above. Sand the entire surface with 80 grit sandpaper and wipe clean with Fiberglass Solvent Wash 202 to remove sanding residue. Repair any surface imperfections with Interlux® Interprotect® Watertite® V135. Sand and wipe clean. Apply two coats of Ultra™ with Biolux™ allowing for appropriate dry times.

BARE WOOD: Sand the entire surface with 80 grit sandpaper, wipe surface clean with Interlux® Special Thinner 216. Repair imperfections with Interlux® Interprotect® Watertite® V135. Sand and wipe clean. Apply the first coat of Ultra with Biolux thinned 10% with Special Thinner 216 or Brush-Ease 433. Fill seams with Interlux® Seam Compound 30 (if necessary). Apply two more coats of Ultra with Biolux unthinned, allowing the appropriate dry times.

UNDERWATER METALS: Contact the Interlux® Technical Service Department at 1-800-468-7589 for full information on how to properly prime underwater metals. DO NOT USE ON ALUMINUM.

Teflon® is a trademark of DuPont. Only DuPont makes TEFLON.