

2693-198

11/29/2010

1/7



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, D.C. 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

International Paint LLC
2270 Morris Avenue
Union, NJ 07083

NOV 29 2010

Attention:
John Pazdera
Pesticide Registration Manager
Interlux/International

Subject: VC 17M with Bio-Lux Red
EPA Registration Number: 2693-198
Agency Initiated Action (Extends expiring time-limited approvals)

This letter conditionally extends the approval date to 06/15/2012, for the following label use categories which received time-limited approval until 06/15/2006 in the letter dated 06/15/2005.

This approval extension is conditionally granted providing:

1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for re-registration of your product under FIFRA section 4.
2. The Company must submit and/or cite all data required for registration of the product under FIFRA sec. 3 (c) (5) when the Agency requests all registrants of similar product to submit such data; and submit an acceptable response required for reregistration of your product under FIFRA section 4.

* Your release for shipment of the product constitutes acceptance of these conditions. A stamped copy of the accepted label is attached for your records.

The Agency also reminds the Company that this product ought to have received a time-limited approval on or before 06/15/2006, as per the original notice of registration. The Agency reminds the Agent that the burden of tracking the requirements of a conditional registration and

requesting additional time-limited approval falls on the Agent. It is their responsibility to ensure that all registered products have an up to date label and Agency approval letter at all times.

A stamped copy of the label stamped "accepted with comments" is enclosed for your records.

If you have any questions concerning this letter, please contact Abigail Downs at (703) 305-5259.

Sincerely,



Marshall Swindell
Product Manager (33)
Regulatory Management Branch I
Antimicrobials Division (7510P)

3/17

VC 17m with Biolux Red

Part A (Base) of a Two Part Antifouling Paint System

Teflon – Only by DuPont
Biolux Blocks Slime
Low Friction, Thin Film Antifouling
Biolux Boosts Performance by Controlling Slime

KEEP OUT OF REACH OF CHILDREN

DANGER

**Copper Powder Bag (Part B) Inside Cap (Copper Powder = 99.00%)
Mix Powder and Liquid Before Use
Mix Only with Part B – Copper Powder V901 (EPA Reg. No. 2693-195)**

ACTIVE INGREDIENT:

N-Cyclopropyl-N'-(1,1-Dimethyl-ethyl) = 2.38%
-6-(Methylthio)-1,3,5-triazine-2,4-Diamine

INERT INGREDIENTS:

= 97.62%
TOTAL = 100.00%

EPA Registration No. 2693-198

EPA Establishment No. 2693-NJ-1

See side panel for additional precautionary statements

Net Contents: 0.75 U.S. QUART (0.710 LITERS)

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of International Paint Inc. including the surface preparation, proper application and the environmental conditions. Therefore, International Paint Inc. cannot guarantee the suitability of this product for your particular purpose or application. **IMPLIED WARRANTIES OF FITNESS OF A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT INC. SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.** By purchase or use, of the product, buyer agrees that the sold and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product as International Paint Inc.'s option.

International Paint Inc.
2270 Morris Avenue
Union, NJ 07083

NOV 29 2010

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No.

2693-198

4/7

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

DANGER

Corrosive. Causes irreversible eye damage or skin burns. Harmful if absorbed through skin. Do not get in eyes, on skin or on clothing. Wear goggles, face shield, or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Wear protective clothing and rubber gloves. Prolonged or frequently repeated skin contact may cause allergic reaction in some individuals. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Remove contaminated clothing and wash clothing before reuse.

FIRST AID

(Applies to both products below individually)

- VC17m with Biolux – Red (EPA Reg. No. 2693-198)
- VC17m with Biolux - Copper Powder V901 (EPA Reg. No. 2693-195)

IF SWALLOWED: Call a Poison Control Center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to by a Poison Control Center or doctor. Do not give anything by mouth to an unconscious person.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. Call Poison Control Center or doctor for treatment advice.

IF ON SKIN AND CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a Poison Control Center or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, give artificial respiration preferably mouth-to-mouth if possible. Call a Poison Control Center or doctor for further treatment advice.

In case of emergency call 1-800-854-6813. Have the product container or label with you when calling a Poison Control Center or doctor or going in for treatment.

NOV 29 2010

Under the Federal Insecticide, Fungicide, and Rodenticide Act, this product is registered under EPA Reg. No. 2693-198

ENVIRONMENTAL HAZARDS:

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS

Flammable. Keep away from heat and open flame.

STORAGE AND DISPOSAL:

Do not contaminate water, food, or feed by storage and disposal. Open dumping is prohibited.

Pesticide Disposal: Pesticide or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

Container Disposal: Triple rinse (or equivalent) and dispose of in an approved landfill. Consult Federal, State, or local disposal authorities for approved alternative procedure.

For Chemical Emergency, Spill, Leak, Exposure or Accident, Call Toll Free – Day or Night: Chemtrec 1-800-424-9300. Medical Advisory: Contact your Local Poison Control Center or call 1-800-854-6813.

ACCEPTED
with COMMENTS
in EPA Letter Dets 4

NOV 29 2010

Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
amended, for the pesticide
registered under EPA Reg. No.

2093-198

VC® 17m with Biolux

Product Description

VC® 17m with Biolux is a friction reducing, low drag, high performance antifouling paint formulated with "Teflon". When applied the **VC 17m with Biolux** will immediately give a thin, super smooth, racing finish, that would normally take days of tiresome sanding. **VC 17m with Biolux** incorporates the Biolux™ technology along with the metallic copper to achieve complete protection against zebra mussels, teredo worms, weed, algae and slime fouling. This is especially helpful in freshwater or low fouling saltwater. The applied thickness of **VC 17m with Biolux** is eight times thinner than traditional paint which virtually eliminates film build-up.

Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Preparation

BARE FIBERGLASS (POLYESTER OR VINYLESTER): - Scrub the surface thoroughly with soap and water using a stiff brush. Flush well with fresh water. Use **INTERLUX® Fiberglass Solvent Wash 202** to remove any wax or other contaminants from the surface.

- **SANDING SYSTEM:** Matte sand with 320-grit sandpaper. Wipe again with **Fiberglass Solvent Wash 202**.

- **NON-SANDING SYSTEM:** Clean as above. Apply one coat of **No-Sand Primer** and follow the overcoating times.

BARE WOOD: Sand smooth with 80-100-grit sandpaper, and wipe with **INTERLUX® SPECIAL THINNER 216**.

UNDERWATER METALS: Underwater metals must be primed to avoid contact with copper bottom paints. DO NOT USE ON ALUMINUM. Grind or sandblast to bright metal, clean thoroughly with **SPECIAL THINNER 216** and overcoat within one hour with **VC TAR**. Apply 3-5 additional coats of **VC TAR** taking care to follow the label directions. If you cannot apply **VC TAR** within one hour of blasting, apply one thin coat of **INTERLUX® VINYL-LUX® PRIMEWASH 353/354** prior to application of **VC TAR**.

PREVIOUSLY PAINTED: GOOD CONDITION

- **WITH VC 17m:** Clean with fresh water. Sand any loose or flaking paint with 320 grit sandpaper and wipe off sanding residue with **VC17m THINNER V172**.

- **HARD ANTIFOULING:** Due to the porosity of hard antifouling paints, it needs to be sanded several times to reach an acceptable surface for application of **VC 17m with Biolux**.

NOV 29 2010
in EPA Letter 2010

Under the Federal Insecticide, Fungicide and Rodenticide Act, amended for the registration under 2693-198

Begin sanding with 80 grit sandpaper and work through the sandpaper grades until a final sanding with 320 grit sandpaper is reached. Wipe the surface with **SPECIAL THINNER 216** to remove sanding residue.

- **SOFT ANTIFOULING:** Soft antifouling paints should be removed prior to application of **VC 17m with Biolux**.

PREVIOUSLY PAINTED: POOR CONDITION - Remove all antifouling paint and proceed with system for bare surface.

Application

MIXING: **VC 17m with Biolux** is a two-part product that must be mixed prior to use. Mix **VC 17m with Biolux** Part A Base with Part B copper V901 (found in bag under the cap). Mix thoroughly. Stir occasionally during application.

APPLICATION: **VC 17m with Biolux** is applied with a short nap roller or solvent resistant foam roller, 4-6" wide or an electric airless spray gun.

Low fouling, cold saltwater: Three coats the first season and two coats each season to follow.

Freshwater: Two coats the first season and one coat each season after

COLOR: **VC 17m with Biolux** changes color after several weeks of immersion.

V407 (Red): At application – Reddish copper bronze. Changes to bright burnt red.

Hints

1. When rolling, pour only small amounts into a steel roller tray
2. Roll quickly and in one direction only
3. When spraying make sure that the nozzle is not more than 6-8 inches from the hull.
4. Do not use conventional spray equipment as this may result in dry spray
5. Use **VC17m Thinner V172** if needed, 10% by volume maximum
6. **VC 17m with Biolux** covers 85 sq. ft./ quart

Dry Time Table

Temperature		Touch Dry	Overcoating Time		Launch Time	
F°	C°		Minimum	Maximum	Minimum	Maximum
41	5	5 min	10 min	N/A	20 min	N/A
59	15	5 min	10 min	N/A	20 min	N/A
73	23	3 min	10 min	N/A	15 min	N/A
95	35	2 min	10 min	N/A	10 min	N/A

In EPA Letter Dated:

NOV 29 2010

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No

2693-198