



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Program
Registration Division (H7505C)
401 "M" St., S.W.
Washington, D.C. 20460

EPA Reg. Number:

Date of Issuance:

2693-199

AUG 27 2003

NOTICE OF PESTICIDE:
 Registration
 Reregistration

Term of Issuance: Expiration
Date 01/15/04

Name of Pesticide Product:

Trilux with Biolux
Black

Under FIFRA, as amended

Name and Address of Registrant (include ZIP Code):

International Paint, Inc.
2270 Morris Avenue
Union, NJ 07083

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency request all registrants of similar product to submit such data; and submit acceptable response required for reregistration of your product under FIFRA section 4.

This product was first granted a time limited registration subject to our completion of an environmental risk assessment. We have completed our risk assessment and find we have concerns regarding the potential for Irgarol to impact aquatic plants, especially seagrass beds which are important as a nursery area and habitat for higher order species. We are concern that Irgarol is showing a trend to be an environmental problem. In order to allow you time to address our concerns we are extending this time limited registration to January 15, 2004. You were provided a copy of our risk assessment with a letter dated August 20, 2003.

Signature of Approving Official:

Marshall Swindell,
Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510C)

Date:

AUG 27 2003

2. Revise the First Aid statements to read:

"FIRST AID

IF SWALLOWED: Call a Poison Control Center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a Poison Control Center or doctor. Do not give anything by mouth to an unconscious person.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. Call a Poison Control Center or doctor for treatment advice.

IF ON SKIN AND CLOTHING: Take off contaminated clothing. Rinse skin immediately plenty of water for 15-20 minutes. Call a Poison Control Center or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or and ambulance, give artificial respiration preferably mouth-to-mouth if possible. Call a Poison Control Center or doctor for further treatment advice.


In case of emergency all (insert toll-free emergency number) Have the product container or label with you when call a Poison Control Center or doctor or going in for treatment

3. This conditional registration will expire automatically on January 15, 2004. If you fail to satisfy the conditions imposed in the registration, EPA may issue a Notice To Cancel under Section 6(e) of FIFRA.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely, yours,



Marshall Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510C)

Enclosure

3/0

ACCEPTED
with COMMENTS
EPA Letter Dated:

AUG 27 2003

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

2693-199

TRILUX with BIOLUX BLACK

KEEP OUT OF REACH OF CHILDREN

WARNING

See side panel for additional Precautionary Statements

Net Contents: 12 ounces

EPA Registration No. 2693-

EPA Establishment No. 2693-NJ-1

Active Ingredients:

Cuprous Thiocyanate	=	8.60%
N-Cyclopropyl-N'- (1,1-Dimethylethyl)-6- (Methylthio)-1,3,5-triazine -2,4- Diamine	=	0.86%

Inert Ingredients:	=	<u>90.54%</u>
		100.00%

Copper as Metallic 4.48%

Contains Petroleum Distillates

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of International Paint Inc. including the surface preparation, proper application and the environmental conditions. Therefore International Paint Inc. cannot guarantee the suitability of this product for your particular purpose or application. **IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED.** INTERNATIONAL PAINT INC. SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use, of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint Inc.'s option.

INTERNATIONAL PAINT INC.
2270 Morris Avenue
Union, NJ 07083

410

ACCEPTED
with COMMENTS
EPA Letter Dated:

**PRECAUTIONARY STATEMENTS
WARNING
HAZARD TO HUMANS AND DOMESTIC ANIMALS**

AUG 27 2003
Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide
registered under EPA Reg. No.
2693-199

Causes eye irritation. Harmful if swallowed or absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT

If swallowed:

- Call a poison control center or doctor immediately for treatment advice.
- Have person sip a glass of water if able to swallow.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give anything by mouth to an unconscious person.

If on skin or clothing:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes
- Call a poison control center or doctor for treatment advice.

If inhaled:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

If in eyes:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

Other: Have the product container or label with you when calling a poison control center or doctor or going for treatment.

PHYSICAL OR CHEMICAL HAZARD

Extremely flammable. Content under pressure. Keep away from heat, sparks, open fire or heated surfaces. Do not puncture or incinerate container. Exposure to temperatures above 130 degrees F may cause bursting.

ENVIRONMENTAL HAZARD

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

Do not contaminate water, food, feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

CONTAINER DISPOSAL: Do not puncture or incinerate. A completely empty can can be disposed of with household trash. Wrap in paper before disposing.

ACCEPTED
with COMMENTS
EPA Reg. No. Dated:

AUG 27 2003

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 2693-199

6/6
 ACCEPTED
 with COMMENTS
 EPA Letter Dated:

AUG 27 2003

Under the Federal Insecticide,
 Fungicide, and Rodenticide Act as
 amended, for the pesticide,
 EPA Reg. No.

3693-199

Trilux with Biolux Aerosol

Trilux[®] with Biolux[®] Aerosol antifouling paint is formulated specifically for aluminum outboards, outdrives and aluminum hulls in underwater areas. When applied over properly primed metal Trilux[®] with Biolux[®] Aerosol will provide good antifouling protection. Biolux[®] Technology is used to control slime growth. Trilux[®] with Biolux[®] Aerosol is for use in fresh, salt and brackish water. Trilux[®] with Biolux[™] Aerosol also contains Teflon[®] for added durability and easy cleaning.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

FOR ALUMINUM OUTBOARDS, OUTDRIVES AND HULLS

BARE ALUMINUM: Sand with medium grit emery cloth and apply Viny-Lux Primewash 353/354. Apply 1 full can of Outboard & Outdrive Aerosol Primer 370.

PREVIOUSLY PAINTED - with Trilux[®] with Biolux[®] Aerosol: Sand with 80 grit sandpaper then apply Trilux[®] with Biolux[®] Aerosol as specified below.

PREVIOUSLY PAINTED – with Factory Paint or other Antifouling Paint - Sand with 80 grit sandpaper. Wipe clean and apply 1 full can of Aerosol Primer 370. Then apply 1 full can of Trilux[®] with Biolux[®] Aerosol as specified below. Apply Trilux[®] with Biolux[®] Aerosol only after priming with Outboard & Outdrive Aerosol Primer 370.

1. Shake can, listen for mixing ball & continue shaking for at least 1 minute.
2. Hold container 12"-16" from unit.
3. Apply contents of 1 can for each Outdrive/Outboard. It will be touch dry in about 30 minutes. Allow a minimum of 6 hours at 75°F or 12 hours at 50°F dry time between coats.
4. For application to hulls, apply 2-3 coats. Allow proper dry times.
5. Be sure paint is completely dry before immersion, allow minimum of 12 hours at 75°F or 16 hours at 50°F prior to launch.

For clean up - use Special Thinner 216.

COVERAGE – One can covers 22 sq. ft.

Do not apply primer or Trilux[®] with Biolux[®] Aerosol above the true waterline.

For best antifouling protection, use entire can of primer and Trilux[®] with Biolux[®] Aerosol for each lower unit.

Do not apply to tin-based paint such as Micron[®]33, Micron 33 Aerosol, Micron 44 or Tri-Lux IIT. Do not use above the true waterline.