
 <p align="center"> <b>U.S. ENVIRONMENTAL PROTECTION AGENCY</b>  Office of Pesticide Programs  Antimicrobials Division (7510C)  1200 Pennsylvania Avenue NW  Washington, D.C. 20460 </p> <p align="center"> <b>NOTICE OF PESTICIDE:</b>  <input checked="" type="checkbox"/> Registration  <input type="checkbox"/> Reregistration </p> <p>(under FIFRA, as amended)</p>	EPA Reg. Number: 2693-202	Date of Issuance: JUN 14 2006
	Term of Issuance: Expiration Date: 6-30-07	
	Name of Pesticide Product: CSC Plus - Blue	
Name and Address of Registrant (include ZIP Code):  International Paint, Inc. 2270 Morris Avenue Union, NJ 07083		
Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.		
<p>On the basis of information furnished by the registrant, the above named pesticide is hereby registered/re-registered under the Federal Insecticide, Fungicide and Rodenticide Act.</p> <p>Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.</p> <p>This product is conditionally registered in accordance with FIFRA sec 3(c)(7)(A) provided that you:</p> <ol style="list-style-type: none"> <li>1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for re-registration of your product under FIFRA section 4.</li> <li>2. This is a time-limited registration. The Agency is still in the process of completing the Environmental Risk Assessment need to support the antifouling use pattern. The Agency is now extending your time-limited to June 30, 2007</li> </ol>		
Signature of Approving Official:  Marshall Swindell Product Manager Team-33 Regulatory Management Branch I Antimicrobials Division (7510P)	Date:  JUN 14 2006	

3. This conditional registration will expire automatically on June 30, 2007. If you fail to satisfy the conditions imposed in the registration, EPA may issue a Notice to Cancel under Section 6 ( e ) of FIFRA.
4. Submit three (3) copies of your final printed labeling before distributing or selling the product bearing the revised labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

Sincerely,



Marshall Swindell  
Product Manager 33  
Regulatory Branch I  
Antimicrobials Division (7510C)

3 7 6

# CSC PLUS

ACCEPTED  
with COMMENTS  
EPA Letter Dated:

- Bio-Lux Blocks Slime
- Bio-Lux Boosts Performance by Controlling Slime
- Antifouling Protection for All Conditions
- Multi-Season, Self-Polishing, No Paint Buildup

JUN 14 2006

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

BLUE

2693-202

KEEP OUT OF REACH OF CHILDREN

CAUTION

See side panel for additional precautionary statements

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

EPA Registration No. 2693-  
EPA Establishment No. 2693-NJ

Active Ingredients:

Cuprous Oxide	= 38.62%
N-Cyclopropyl-N'-(1,1-dimethylethyl)-6-(methylthio)-1,3,5-triazine-2,4-diamine	= 2.00%
Inert Ingredients:	= 59.38%
	100.00%
Copper as Metallic	= 34.03%

**DISCLAIMER:** The performance of any marine coating depends on many factors outside the control of International Paint Inc. including the surface preparation, proper application and the environmental conditions. Therefore, International Paint Inc. cannot guarantee the suitability of this product for your particular purpose or application. **IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT INC. SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.** By purchase or use, of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint Inc.'s option.

International Paint Inc.

Union, NJ

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**CAUTION**

Harmful if absorbed through skin or inhaled. Causes moderate eye irritation. Avoid contact with eyes, skin or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. Avoid breathing spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Safety & Health Administration and the National Institute of Occupational Safety & Health. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash clothing before reuse. May pose an aspiration pneumonia hazard.

**STATEMENT OF PRACTICAL TREATMENT**

**IF SWALLOWED:** Call a physician or Poison Control Center. Do not induce vomiting. Do not give anything by mouth to an unconscious person. Avoid alcohol.  
**IF IN EYES:** Flush eyes with plenty of water. Call a physician if irritation persists.  
**IF ON SKIN:** Wash with plenty of soap and water. Get medical attention.  
**IF INHALED:** Remove victim to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. Get medical attention.

**ENVIRONMENTAL HAZARD**

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**PHYSICAL OR CHEMICAL HAZARD**

Do not use or store near heat or open flame.

**STORAGE AND DISPOSAL**

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

**PESTICIDE DISPOSAL:** Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

**CONTAINER DISPOSAL:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

**ACCEPTED  
with COMMENTS  
EPA Letter Dated:**

JUN 14 2006

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No.

2695-202

**PRODUCT DESCRIPTION:** CSC PLUS is a multi-season, Controlled Solubility Copolymer antifouling paint that is specially formulated with two biocides - cuprous oxide and a booster called BIO-LUX™. The cuprous oxide works best against shell fouling, while the BIO-LUX™ booster helps protect against weed, slime and algae growth. CSC PLUS washes away (polishes) at a controlled rate similar to a bar of soap, resulting in a reduced build-up of old coatings and minimized sanding at reapplication. This technology also allows the boat to be hauled and launched without recoating.. CSC PLUS is for use below the waterline on fiberglass, wood and properly primed metal boat hulls and parts. in fresh, salt and brackish waters. Do not use on aluminum.

**DIRECTIONS FOR USE:**

It is a violation of Federal law to use this product in a manner inconsistent with its' labeling.

**COMPATIBILITY:** CSC PLUS can be applied over most hard, conventional antifouling paints as long as the old coating is tightly adhered, is in sound condition, and has been thoroughly sanded with 80 grit wet-or-dry sandpaper. CSC PLUS should not be applied over MICRON 33®, MICRON 44® or soft antifouling paints. These old coatings should be removed..

**V.O.C.:** Less than 400 grams/liter  
(3.33 lbs./gallon)

**THINNING:** Thin only when necessary.  
Do not exceed 10% by volume.

**DRY TIMES:** Touch dry- 2 hours  
77°F (25°C) Dry to overcoat - 16 hours minimum\*  
Dry to launch - 16 hours minimum \*

**THINNER:** Brushing- BRUSH-EASE 433  
Spraying- SPECIAL THINNER 216

**THEORETICAL COVERAGE:** 440 sq.ft./gallon  
Yields 2 mils dry film thickness

**CLEAN-UP:** SPECIAL THINNER 216 or  
BRUSH-EASE 433

**APPLICATION TEMPERATURES:** 50°F (10°C) and above. (Air and hull)  
\* If either hull or air temperature falls below 50°F (10°C) during the 16 hour dry time extend the dry time to a minimum of 36 hours.

**APPLICATION SYSTEMS**

Shake or mix well prior to use. Apply at least two full coats (3 coats on bare wood) of CSC PLUS by brush or solvent resistant 3/8" nap roller. Do not apply thin coats. Keep in mind that the life of the paint is directly related to the amount of paint applied. If during application the brush pulls or the roller drags, use INTERLUX ® BRUSH-EASE 433 to improve handling. Certain areas of the hull experience faster polishing than the other areas. These areas include the waterline, the leading edge of the keel, the rudder and the bow stem. It is suggested that an additional coat of paint be applied to these areas to insure that the CSC PLUS does not wash away before the other areas of the hull.

ACCEPTED  
VIA COMMENTS  
EPA Letter Dated:

JUN 14 2006

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

2693 - 200

6 7 6

**PREVIOUSLY PAINTED SURFACES - GOOD CONDITION:** Remove all traces of loose paint and contamination by sanding the entire surface well with 80 grit wet-or-dry sandpaper; wipe surface clean with INTERLUX® SPECIAL THINNER 216. Apply at least 2 coats of CSC PLUS allowing proper dry times.

**PREVIOUSLY PAINTED SURFACES - POOR CONDITION:** Completely remove all antifouling paint with INTERLUX® INTERSTRIP 299E for fiberglass or wood and by sandblasting steel surfaces to a near white metal. Proceed with application for bare work described below.

**BARE FIBERGLASS - SURFACE PREPARATION (POLYESTER OR VINYL-ESTER):** It is very important that bare fiberglass be prepared properly to prevent delamination of antifouling paint. Scrub the surface thoroughly with soap and water using a stiff bristled brush. Flush well with fresh water. When the surface is dry, wipe a small area with a clean cloth that has been wetted with INTERLUX® FIBERGLASS SOLVENT WASH 202. While the surface is still wet remove with a clean dry cloth. Repeat this process until the entire surface has been cleaned. To be certain that all wax and other contaminants have been removed, run water over the surface. If the water beads up or separates, wipe again with FIBERGLASS SOLVENT WASH 202. When the water sheets off, all contamination has been removed. Sanding does not remove contamination. After the surface has been properly cleaned, proceed with the application systems below.

ACCEPTED  
with COMMET  
in EPA Letter Date

JUN 14 2006

**BARE FIBERGLASS - NO SAND SYSTEM:** Clean the surface following the preparation procedure described above. Repair any surface imperfections with INTERLUX® INTERPROTECT WATERTITE V135. Sand the repaired area Under the Federal Insecticide, Fungicide, and Rodenticide Act amended for the pesticide, registered under EPA Reg. No. 2695-202 wipe clean. Apply one thin continuous coat of INTERLUX BONDKOTE 200 FIBERGLASS PRIMER®. Follow the BONDKOTE 200 label directions for overcoating, apply at least 2 coats of CSC PLUS. Allow proper dry times between coats.

**BARE FIBERGLASS - SANDING SYSTEM:** Clean the surface following the preparation procedure described above. Repair any surface imperfections using INTERLUX® INTERPROTECT WATERTITE V135. Sand and wipe clean. Sand the entire surface with 80 grit sandpaper until a flat, matte finish is obtained. Wipe the sanding residue off the surface with FIBERGLASS SOLVENT WASH 202. Apply at least two coats of CSC PLUS.

**BARE WOOD:** Sand entire underwater surface with 80 grit sandpaper; wipe surface clean with INTERLUX® BRUSH-EASE 433. Repair imperfections with INTERLUX INTERPROTECT WATERTITE V135; sand and wipe clean. Apply first coat of CSC PLUS reduced 10% with BRUSH-EASE 433 to penetrate into the wood. Fill seams with INTERLUX® SEAM COMPOUND 30. Apply second and third coats of CSC PLUS unreduced. Allow proper dry times between coats.

**UNDERWATER METALS:** Contact the Interlux Technical Service Department at 1-800-468-7589 for details on how to properly prime underwater metals. Do not use on aluminum.

Color-difference may occur between actual paint and color swatch on front of can.

INTERLUX® For information call 908-686-1300