2693-205 6/15/2	2005	Page 17
U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Pesticide Program Registration Division (H7505C)	EPA Reg. Number:	Date of Issuance:
401 "M" St., S.W. Washington, D.C. 20460	2693-205	JUN 1 5 2005
NOTICE OF PESTICIDE:	<sup>Term of Issuance:</sup> Expiration Date 06/15/06	
under FIFRA, as amended).	Name of Pesticide Product:	
	ULTRA PLUS - BLUE	
ame and Address of Registrant (include ZIP Code): International Paint, Inc. 2270 Morris Avenue Union, NJ 07083		
ote: Changes in labeling differing in substance from that accepted in a submitted to and accepted by the Registration Division prior to use correspondence on this product always refer to the above SPA registratic	of the label in comm	a registration must merce. In any
n the basis of information furnished by the registrant, the above named egistered/reregistered under the Federal Insecticide, Fungicide and Rod	d pesticide is heret denticide Act.	ру
egistration is in no way to be construed as an endorsement or recommend n order to protect health and the environment, the Administrator, on hi ancel the registration of a pesticide in accordance with the Act. The ith the registration of a product under this Act is not to be construed xclusive use of the name or to its use if it has been covered by others	is motion, may at ar acceptance of any r d as giving the regi	ny time suspend or name in connection
This product is conditionally register 'IFRA sec. 3(c)(7)(A) provided that you:	ed in accord	lance with
1. Submit and/or cite all data requir our product under FIFRA sec. 3( c ) (5) wh ll registrants of similar product to submi cceptable response required for reregistra nder FIFRA section 4.	en the Agend t such data,	cy request ; and submit
The Agency's is currently reviewing a o complete Environmental Risk Assessment f xtending this time limited registration to	or Irgarol.	We are
gnature of Approving Official:	Date:	
Maundell	JUN 1	

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,

Marshall Swindell Product Manager 33 Regulatory Management Branch I Antimicrobials Division (7510C)

Enclosure

376

ACCEPTED with COMPLENTS in EPA Letter Dated:

JUN 1 5 2005

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No.

1693-205

# **ULTRA PLUS**

#### BLUE

Contains Biolux to resist slime

High Copper Antifouling for Ultimate Protection

Teflon® Added for Durability and Easy Cleaning

Biolux Boosts Antifouling Performance by Controlling Slime

KEEP OUT OF REACH OF CHILDREN

## WARNING

See side panel for additional precautionary statements

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

EPA Registration No. 2693- 10 205 EPA Establishment No. 2693-NJ

Active Ingredients:

Cuprous Oxide N-Cyclopropyl-N'-(1,1-dimethylethyl)-6- (methylthio)-1,3,5-triazine-2,4-diamine	= 66.65% = 1.59%
Inert Ingredients:	= <u>31.76%</u> 100.00%
Copper as Metallic	= 59.2%

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of International Paint Inc. including the surface preparation, proper application and the environmental conditions. Therefore, International Paint Inc. cannot guarantee the suitability of this product for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTIBILITY ARE EXCLUDED. INTERNATIONAL PAINT INC. SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use, of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint Inc.'s option.

## International Paint Inc.

### Union, NJ

with COMMENTS in EPA Letter Dated:

# PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS WARNING

JUN 1 5 2005 Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 26 9-3-205

f . .

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton whit, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

## STATEMENT OF PRACTICAL TREATMENT

**IF SWALLOWED:** Promptly drink large quantities of water. Avoid alcohol. Get medical attention.

IF IN EYES: Flush eyes with plenty of water. Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Get medical attention. IF INHALED: Remove victim to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD: Flammable. Keep away from heat, sparks and open flame.

STORAGE AND DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

<u>PESTICIDE DISPOSAL</u>: Pesticide wastes are toxic. Open dumping is prohibited. Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

<u>CONTAINER DISPOSAL</u>: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local procedures.

PRODUCT DESCRIPTION: Ultra Plus provides excellent long term protection from shell and weed fouling. Ultra Plus contains a very high loading of cuprous oxide and an organic boosting biocide called Biolux™. The cuprous oxide works best against shell fouling such as barnacles and zebra mussels and the Biolux™ booster works to control slime and algae fouling. Ultra Plus also contains Teflon® for added durability and easy cleaning. Ultra Plus is recommended for use wherever the fouling challenge is severe, and can be used in fresh, salt and brackish water on fiberglass, wood and properly primed metal boat hulls and parts. Do not use on aluminum. Ultra Plus can be applied over hard well sanded antifouling paint. Even though Ultra Plus has a very high loading of cuprous oxide it has excellent color stability and resists changing color at the

• waterline.

••••••

#### DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

\*COMPATIBILITY: Ultra Plus can be applied over any other hard antifouling paint after sanding the surface. Soft antifouling paints will need to be removed or overcoated with Underwater Primer 360R before applying Ultra Plus.

V.O.C.: Less than 290 grams/liter (2.40 lbs./gallon) THEORETICAL COVERAGE: 530 sq. ft./ gallon yields 2 mils dry film thickness.

THINNER: Special Thinner 216 or Brush-Ease 433 DRY TIMES: Touch dry - 2 hours 77°F (25°C) Dry to overcoat - 16 hours minimum Dry to launch - 16 hours minimum 60 days maximum

THINNING: Thin only when necessary Do not exceed 10% maximum.

CLEAN-UP: Special Thinner 216 or Brush-Ease 433 APPLICATION TEMPERATURE: 50°F (10°C)\* and above (air and hull)

"If either the air or hull temperature falls below 50°F (10°C) during the 16 hour dry time extend the dry times to 36 hours minimum.

## APPLICATION SYSTEMS

PREVIOUSLY PAINTED - GOOD CONDITION: Remove all traces of loose paint and contamination by sanding the entire surface with 80 grit sandpaper, wipe surface clean with Special Thinner 216. Apply at least two coats of Ultra Plus.

PREVIOUSLY PAINTED - POOR CONDITION: Completely remove all old antifouling paint, using Interstrip 299E. Sand and wipe clean with Fiberglass Solvent Wash 202.

ACCEPTED with COMMENTS in EPA Level Dutic:

576

JUN 1 5 2005 Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 2693 - 205

## BARE FIBERGLASS - (POLYESTER OR VINYLESTER)

SURFACE PREPARATION: It is very important that bare fiberglass be properly prepared to prevent delamination of the antifouling paint. Scrub the surface thoroughly with soap and water using a stiff brush. Flush well with water. Wipe a small area with a clean cloth that has been wetted with Interlux® Fiberglass Solvent Wash 202. While the surface is still wet remove with a clean dry cloth. Repeat this process until the entire surface has been cleaned. To be certain that all of the contamination has been removed, run water over the surface. If the

water beads up or separates, wipe again with Fiberglass Solvent Wash 202. When the water sheets off, all contamination has been removed. <u>Sanding does</u> not remove contamination. After the surface has been properly cleaned, proceed with the application system below.

BARE FIBERGLASS - NO SAND SYSTEM: Clean the surface following the preparation procedure above. Repair any surface imperfections using Interlux® Interprotect® Watertite® V135. Sand and wipe clean. Apply one thin, continuous coat of Interlux No Sand Primer by brush or roller. Follow application directions for primer and apply the first coat of Ultra Plus. Apply\_a second coat allowing for the appropriate dry times.

BARE FIBERGLASS - SANDING SYSTEM: Clean the surface following the preparation procedure above. Sand the entire surface with 80 grit sandpaper and wipe clean with Fiberglass Solvent Wash 202 to remove sanding residue. Repair any surface imperfections with Interlux® Interprotect® Watertite® V135. Sand and wipe clean. Apply two coats of Ultra Plus allowing for appropriate dry times.

BARE WOOD: Sand the entire surface with 80 grit sandpaper, wipe surface clean with Interlux® Special Thinner 216. Repair imperfections with Interlux® Interprotect® Watertite® V135. Sand and wipe clean. Apply the first coat of Ultra with Biolux thinned 10% with Special Thinner 216 or Brush-Ease 433. Fill seams with Interlux® Seam Compound 30 (if necessary). Apply two more coats of Ultra with Biolux unthinned, allowing the appropriate dry times.

UNDERWATER METALS: Contact the Interlux® Technical Service Department at 1-800-468-7589 for full information on how to properly prime underwater metals. <u>DO NOT USE ON ALUMINUM.</u>

Teflon® is a trademark of DuPont. Only DuPont makes TEFLON.

ACCEPTED with COMMENTS in EPA Letter Dated:

676

JUN 1 5 2005

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, recistered under EPA Reg. No.

2693-205