



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Program
Registration Division (H7505C)
401 "M" St., S.W.
Washington, D.C. 20460

EPA Reg. Number:

2693-209

Date of Issuance:

JUN 15 2005

NOTICE OF PESTICIDE:
 X Registration
 Reregistration

Term of Issuance: Expiration
Date 06/15/06

Name of Pesticide Product:

Fiberglass Bottomkote
ACT with Biolux - BLUE

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

International Paint, Inc.
2270 Morris Avenue
Union, NJ 07083

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency request all registrants of similar product to submit such data; and submit acceptable response required for reregistration of your product under FIFRA section 4.

The Agency is currently reviewing additional information submitted by your supplier. Therefore, we are extending this limited registration to June 15, 2006.

Signature of Approving Official:

Marshall Swindell,
Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510C)

Date:

JUN 15 2005

2. This conditional registration will expire automatically on June 15, 2006. If you fail to satisfy the conditions imposed in the registration, EPA may issue a Notice To Cancel under Section 6(e) of FIFRA.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,



Marshall Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510C)

Enclosure

FIBERGLASS BOTTOMKOTE ACT with BIOLUX - 3 8 7

Blue

- Ablative Copolymer Technology with Biolux
- Contains Biolux
- Biolux Boosts Antifouling Performance by Controlling Slime
- Overcoats Existing Antifouling Paint
- Eliminates Paint Build Up and Heavy Sanding

KEEP OUT OF REACH OF CHILDREN

CAUTION

See side panel for additional precautionary statements

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

EPA Registration No. 2693-
EPA Establishment No. 2693-NJ-1

Active Ingredients:

Cuprous Oxide	= 41.97%
N-Cyclopropyl-N'-(1,1-dimethylethyl)-6-(methylthio)-1,3,5-triazine-2,4-diamine	= 0.98%
Inert Ingredients:	= 57.05%
	100.00%
Copper as Metallic	= 37.24%

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of International Paint Inc. including the surface preparation, proper application and the environmental conditions. Therefore, International Paint Inc. cannot guarantee the suitability of this product for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT INC. SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use, of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint Inc.'s option.

ACCEPTED
with **COMMENTS**
in EPA Letter Dated:

International Paint Inc.
2270 Morris Avenue
Union, NJ 07083

JUN 15 2005
Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.
2693-209

4 3 7

ACCEPTED
with COMMENTS
in EPA Letter Dated:

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

JUN 15 2005
Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.
1693-289

CAUTION

Harmful if absorbed through skin or inhaled. Causes moderate eye irritation. Avoid contact with eyes, skin or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. Avoid breathing spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Safety & Health Administration and the National Institute of Occupational Safety & Health. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash clothing before reuse. May pose an aspiration pneumonia hazard.

FIRST AID

IF SWALLOWED: Call a Poison Control Center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a Poison Control Center or doctor. Do not give anything by mouth to an unconscious person.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. Call a Poison Control Center or doctor for treatment advice.

IF ON SKIN AND CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a Poison Control Center or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, give artificial respiration preferably mouth-to-mouth if possible. Call a Poison Control Center or doctor for further treatment advice.

In case of emergency call 1-800-854-6813. Have the product container or label with you when calling a Poison Control Center or doctor or going in for treatment.

ENVIRONMENTAL HAZARD

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

5 8 7
ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUN 15 2005

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

2693-209

PHYSICAL OR CHEMICAL HAZARD

Do not use or store near heat or open flame.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PRODUCT DESCRIPTION

Fiberglass Bottomkote® ACT with Biolux® uses Ablative Copolymer Technology to enable it to wash away with use. This Ablative Copolymer Technology also eliminates the build-up of old spent coatings and the heavy sanding needed to remove them. Fiberglass Bottomkote® ACT with Biolux® also uses Biolux® Technology to boost antifouling performance by blocking slime. It provides excellent protection against barnacles, algae, slime zebra mussels and other forms of marine fouling in waters with moderate to heavy fouling and can be used in fresh, salt and brackish waters.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

PREPARATION

PREVIOUSLY PAINTED – GOOD CONDITION: Remove all traces of loose paint and contamination by sanding the entire surface with 80-grit sandpaper, wipe surface clean with Special Thinner 216.

PREVIOUSLY PAINTED – POOR CONDITION: Completely remove all old antifouling paint, using Interstrip 299E. Sand and wipe clean with Fiberglass Solvent Wash 202.

BARE FIBERGLASS – (POLYESTER OR VINYLESTER)

SURFACE PREPARATION: It is very important that bare fiberglass be properly prepared to prevent delamination of the antifouling paint. Scrub the surface thoroughly with soap and water using a stiff brush. Flush well with water. Wipe a small area with a clean cloth that has been wetted with Interlux® Fiberglass Solvent Wash 202. While the surface is still wet remove with a clean dry cloth. Repeat this process until the entire surface has been cleaned. To be certain that all of the contamination has been removed, run water over the surface. If the water beads up or separates, wipe again with Fiberglass Solvent Wash 202. When the water sheets off, all contamination has been removed.

Sanding does not remove contamination. After the surface has been properly cleaned, proceed with the application system below.

687

TEMPERATURE F°/C°	TOUCH DRY	OVERCOATING TIME		IMMERSION TIME	
		Minimum	Maximum	Minimum	Maximum
50/10	3 hrs	12 hrs	60 days	24 hrs	60 days
60/15	2 hrs	10 hrs	60 days	20 hrs	60 days
75/24	1 hr	6 hrs	60 days	16 hrs	60 days
95/35	30 min	4 hrs	60 days	8 hrs	60 days

* If either the hull or air temperature falls below 50°F (10°C) during the 12 hour dry time, extend the dry times to 36 hours minimum.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUN 15 2005

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

2693-209

BARE FIBERGLASS – NO SAND SYSTEM: Clean the surface following the preparation procedure above. Repair any surface imperfections using Interlux® Watertite® V135. Sand and wipe clean. Apply one thin, continuous coat of Interlux No Fiberglass No Sand Primer YPA200 by brush or roller. Follow application directions for primer and apply the first coat of Fiberglass Bottomkote® ACT with Biolux®.

BARE FIBERGLASS – SANDING SYSTEM: Clean the surface following the preparation procedure above. Sand the entire surface with 80-grit sandpaper and wipe clean with Fiberglass Solvent Wash 202 to remove sanding residue. Repair any surface imperfections with Interlux® Watertite® V135. Sand and wipe clean.

BARE WOOD: Sand the entire surface with 80-grit sandpaper, wipe surface clean with Interlux® Special Thinner 216. Repair any imperfections with Interlux® Watertite® V135. Sand and wipe clean. Apply the first coat of Fiberglass Bottomkote® ACT with Biolux thinned 10% with Special Thinner 216 or Brush-Ease 433. Fill seams with Interlux® Seam Compound 30 (if necessary).

UNDERWATER METALS: Contact the Interlux® Technical Service Department at 1-800-468-7589 for full information on how to properly prime underwater metals. **DO NOT USE ON ALUMINUM.**

APPLICATION

Apply two coats of Fiberglass Bottomkote® ACT with Biolux® allowing for the appropriate dry times.

HINTS

- Fiberglass Bottomkote ACT with Biolux® can be applied over existing antifouling paint as long as the old coating is tightly adhered and is in sound condition.
- Soft antifouling paints will need to be removed or overcoated with Primocon before applying Fiberglass Bottomkote ACT with Biolux®.

V.O.C.: Less than 370 grams/liter
(2.40 lbs./gallon)

THEORETICAL COVERAGE: 455 sq. ft./gallon
yields 2 mils dry film thickness.

THINNER: SPECIAL THINNER 216 or
BRUSH-EASE 433

DRY TIMES: Touch dry – 1 hour
77°F (25°C) Dry to overcoat – 12 hours minimum
Dry to launch – 12 hours minimum
60 days maximum

THINNING: Thin only when necessary
Do not exceed 10% maximum.

CLEAN-UP: SPECIAL THINNER 216 or
BRUSH-EASE 433

APPLICATION TEMPERATURE: 50°F (10°C)*
and above (air and hull)

**ACCEPTED
with COMMENTS
in EPA Letter Dated:
JUN 15 2005**

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

2693-209