

International Paint, Inc.
2270 Morris Avenue
Union, NJ 07083

AUG 18 2005

Attention: John Pazdera


Subject: **Fiberglass Bottomkote ACT with Biolux - Blue**
EPA Registration No. 2693-209
Amendment Application Date: July 11, 2005
EPA Received Date: July 13, 2005

The labeling referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. A stamped copy is enclosed for your records.

- Add an alternate set of Use Directions - "Subset B"

Please note, this product is conditional registered that will expire automatically on June 15, 2006.

Sincerely yours,



Marshall Swindell
Product Manager (33)
Regulatory Management Branch I
Antimicrobials Division (7510C)

Enclosure

CONCURRENCES

SYMBOL							
SURNAME							
DATE							

FIBERGLASS BOTTOMKOTE ACT with BIOLUX – Blue

2/8

- Exceptional Multi-Season Ablative Antifouling
- Season-to-Season Antifouling Protection
- Igarol Improves Antifouling Performance by Reducing Slime
- Overcoats Existing Antifouling Paint
- Eliminates Paint Build Up and Sanding
- Controlled Polishing for Power or Sail
- Contains Organic Boosting Biocide to Fight Slime

KEEP OUT OF REACH OF CHILDREN

CAUTION

See side panel for additional precautionary statements

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

EPA Registration No. 2693-
EPA Establishment No. 2693-NJ-1

Active Ingredients:

Cuprous Oxide	= 41.97%
N-Cyclopropyl-N'-(1,1-dimethylethyl)-6-(methylthio)-1,3,5-triazine-2,4-diamine	= 0.98%
Inert Ingredients:	= 57.05%
	100.00%
Copper as Metallic	= 37.24%

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of International Paint LLC including the surface preparation, proper application and the environmental conditions. Therefore, International Paint LLC cannot guarantee the suitability of this product for your particular purpose or application. **IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT LLC SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.** By purchase or use, of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint LLC's option.

ACCEPTED
with COMMENTS
EPA Letter Dated:

International Paint LLC
2270 Morris Avenue
Union, NJ 07083

AUG 18 2005
Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

CAUTION

Harmful if absorbed through skin or inhaled. Causes moderate eye irritation. Avoid contact with eyes, skin or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. Avoid breathing spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Safety & Health Administration and the National Institute of Occupational Safety & Health. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash clothing before reuse. May pose an aspiration pneumonia hazard.

FIRST AID

IF SWALLOWED: Call a Poison Control Center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a Poison Control Center or doctor. Do not give anything by mouth to an unconscious person.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. Call a Poison Control Center or doctor for treatment advice.

IF ON SKIN AND CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a Poison Control Center or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, give artificial respiration preferably mouth-to-mouth if possible. Call a Poison Control Center or doctor for further treatment advice.

In case of emergency call 1-800-854-6813. Have the product container or label with you when calling a Poison Control Center or doctor or going in for treatment.

ENVIRONMENTAL HAZARD

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board Regional Office of the EPA.

**ACCEPTED
with COMMENTS
EPA Letter Dated:**

AUG 18 2005

**Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,**

registered under EPA Reg. No.
2693-28

PHYSICAL OR CHEMICAL HAZARD

Do not use or store near heat or open flame.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

**ACCEPTED
with COMMENTS
EPA Letter Dated:**

AUG 18 2005

**Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.**

2693-209

[Subset A – Use Directions for Pleasure Craft]

5/8

PRODUCT DESCRIPTION: Fiberglass Bottomkote ACT with Biolux uses Ablative Copolymer Technology to provide excellent season-to-season protection. Ablative Copolymer Technology enables it to wear away with use and eliminates the build-up of old spent coatings and the heavy sanding needed to remove them. **Fiberglass Bottomkote ACT with Biolux** contains cuprous oxide and Irgarol. The Irgarol works to control weed, slime and algae fouling while the cuprous oxide works to control shell fouling such as barnacles and zebra mussels. This keeps the bottom of your boat cleaner longer. It provides excellent protection against all forms of marine fouling in waters with moderate to heavy fouling and can be used in fresh, salt and brackish waters.

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with it's labeling.

V.O.C.: Less than 370 grams/liter (3.08 lbs./gallon)	THEORETICAL COVERAGE: 455 sq. ft./ gallon yields 2 mils dry film thickness.
THINNER: SPECIAL THINNER 216 or BRUSH-EASE 433	DRY TIMES: Touch dry - 1 hour 77°F (25°C) Dry to overcoat - 12 hours minimum Dry to launch - 12 hours minimum
THINNING: Thin only when necessary Do not exceed 10% maximum.	
CLEAN-UP: SPECIAL THINNER 216 or BRUSH-EASE 433	APPLICATION TEMPERATURE: 50°F (10°C)* and above (air and hull)

ACCEPTED
with COMMENTS
EPA Letter Dated:

TEMPERATURE °F (°C)	TOUCH DRY	OVERCOATING	IMMERSION
		TIME	TIME
		Minimum	Minimum
50°F (10°C)	3 Hours	16 Hours	16 Hours
60°F (15°C)	2 Hours	12 Hours	12 Hours
77°F (25°C)	1 Hour	12 Hours	12 Hours
95°F (35°C)	30 Minutes	8 Hours	8 Hours

AUG 18 2005
Under the Federal Insecticide,
Fungicide, and Rodenticide Act
amended, for the pesticide,
registered under EPA Reg. No.
2693-209

* If either the air temperature falls below 50°F (10°C) during the 16 hour dry time, extend the dry times to 36 hours minimum.

PREPARATION

PREVIOUSLY PAINTED - GOOD CONDITION: Remove all traces of loose paint and contamination by sanding the entire surface with 80-grit sandpaper, wipe surface clean with Special Thinner 216.

PREVIOUSLY PAINTED - POOR CONDITION: Completely remove all old antifouling paint, using Interstrip 299E. Sand and wipe clean with Fiberglass Solvent Wash 202

BARE FIBERGLASS (POLYESTER OR VINYLESTER) - SURFACE

PREPARATION: Begin by scrubbing the surface thoroughly with a stiff brush using Interlux All Purpose Boat Soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry. Remove mold release wax using one of the following methods.

The preferred method of cleaning gelcoat is to apply Fiberglass Surface Prep YMA601 with a maroon, 3M, Scotch-Brite® pad and scrub well. Flush with fresh water or wipe off with a clean, wet cloth ensuring that no traces of Fiberglass Surface Prep remain.

An alternate method would be to dampen cheesecloth with Fiberglass Solvent Wash 202. Wipe thoroughly to remove all surface contamination and cleaners. Wipe off with a clean, dry rag before liquid dries. Wipe only a few square feet at a time and change rags frequently.

6/8

To be certain the contamination has been removed, run water over the surface. If the water beads up or separates, repeat one of the above methods. When the water sheets off, all contamination has been removed. Sanding does not remove contamination. After the surface has been properly cleaned, proceed with the application system below.

BARE FIBERGLASS - NO SAND SYSTEM: Clean the surface following the preparation procedure above. Repair any surface imperfections using Watertite YAV135. Sand and wipe clean. Apply one thin, continuous coat of No Fiberglass No Sand Primer YPA200 by brush or roller. Follow application directions for primer and apply the first coat of **Fiberglass Bottomkote ACT with Biolux**.

BARE FIBERGLASS - SANDING SYSTEM: Clean the surface following the preparation procedure above. Sand the entire surface with 80-grit sandpaper and wipe clean with Fiberglass Solvent Wash 202 to remove sanding residue. Repair any surface imperfections with Watertite YAV135. Sand and wipe clean.

BARE WOOD: Sand the entire surface with 80-grit sandpaper, wipe surface clean with Interlux Special Thinner 216. Repair any imperfections with Watertite YAV135. Sand and wipe clean. Apply the first coat of **Fiberglass Bottomkote ACT with Biolux** thinned 10% with Special Thinner 216 or Brush-Ease 433. Fill seams with Seam Compound 30 (if necessary). Then apply 2 full coats unreduced of **Fiberglass Bottomkote ACT with Biolux**.

UNDERWATER METALS: Contact the Interlux Technical Service Department at 1-800-468-7589 for full information on how to properly prime underwater metals. **DO NOT USE ON ALUMINUM.**

APPLICATION

Apply two coats of **Fiberglass Bottomkote ACT with Biolux** allowing for the appropriate dry times

HINTS

Fiberglass Bottomkote ACT with Biolux can be applied over existing antifouling paint as long as the old coating is tightly adhered and is in sound condition.

Soft antifouling paints will need to be removed or overcoated with Primocon before applying **Fiberglass Bottomkote ACT with Biolux**.

Color difference may occur between actual paint and color swatch on front of can.

ACCEPTED
with **COMMENTS**
EPA Letter Dated:

AUG 18 2005

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

2693-209

[Subset B – Alternate Use Directions for Pleasure Craft]

PRODUCT DESCRIPTION: Fiberglass Bottomkote ACT with Biolux is a multi-season, antifouling paint that is formulated with two biocides that provides effective protection against barnacles, slime, algae and hydroids. It is recommended for boats that are used in high fouling salt or fresh water areas, or which remain in the water for prolonged periods between haul outs. Fiberglass Bottomkote ACT with Biolux wears away, resulting in a reduced build-up of old coatings and minimized sanding at reapplication. This also allows the boat to be hauled and launched without recoating. Fiberglass Bottomkote ACT with Biolux is for use below the waterline on fiberglass, wood and properly primed metal boat hulls and parts, in fresh, salt and brackish waters. Do not use on aluminum.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its' labeling.

COMPATIBILITY: Fiberglass Bottomkote ACT with Biolux can be applied over most hard, conventional antifouling paints as long as the old coating is tightly adhered, is in sound condition, and has been thoroughly sanded with 80-grit wet-or-dry sandpaper.

V.O.C.: Less than 370 grams/liter (3.08 lbs./gallon) **THINNING:** Thin only when necessary. Do not exceed 10% maximum

DRY TIMES: Touch dry- 1 hour **THINNER:** Brushing- Brush-Ease 433 **ACCEPTED COMMENTS**
77°F (25°C) Dry to overcoat - Spraying- Special Thinner **EPA Letter Dated:**
12 hours minimum*
Dry to launch - 12 hours minimum *

THEORETICAL COVERAGE: 455 sq.ft. /gallon Yields 2 mils dry film thickness **AUG 18 2005**
CLEAN-UP: Special Thinner 216 or Brush-Ease 433 **Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 2693-209**

APPLICATION TEMPERATURES: 50°F (10°C) and above. (Air and hull)
* If either hull or air temperature falls below 50°F (10°C) during the 16-hour dry time extend the dry time to a minimum of 36 hours.

APPLICATION SYSTEMS

Shake or mix well prior to use. Apply at least two full coats (3 coats on bare wood) of Fiberglass Bottomkote ACT with Biolux by brush or solvent resistant 3/8" nap roller. Do not apply thin coats. Keep in mind that the life of the paint is directly related to the amount of paint applied. If during application the brush pulls or the roller drags, use Brush-Ease 433 to improve handling. Certain areas of the hull experience faster polishing than the other areas, these areas include the waterline, the leading edge of the keel, the rudder and the bow stem. It is suggested that an additional coat of paint be applied to these areas to insure that the Fiberglass Bottomkote ACT with Biolux does not wash away before the other areas of the bottom.

PREVIOUSLY PAINTED SURFACES - GOOD CONDITION: Remove all traces of loose paint and contamination by sanding the entire surface well with 80 grit wet-or-dry sandpaper; wipe surface clean with Special Thinner 216. Apply at least 2 coats of Fiberglass Bottomkote ACT with Biolux, allowing proper dry times.

PREVIOUSLY PAINTED SURFACES - POOR CONDITION: Completely remove all antifouling paint with Interstrip® 299E. Proceed with application for bare fiberglass described below.

8/8

BARE FIBERGLASS - SURFACE PREPARATION (POLYESTER OR VINYL-ESTER): Begin by scrubbing the surface thoroughly with a stiff brush using Interlux Boat Soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry. Remove mold release wax using one of the following methods.

The preferred method of cleaning gelcoat is to apply Fiberglass Surface Prep YMA601 with a maroon, 3M, Scotch-Brite® pad and scrub well. Flush with fresh water or wipe off with a clean, wet cloth ensuring that no traces of Fiberglass Surface Prep remain.

An alternate method would be to dampen cheesecloth with Fiberglass Solvent Wash 202. Wipe thoroughly to remove all surface contamination and cleaners. Wipe off with a clean, dry rag before liquid dries. Wipe only a few square feet at a time and change rags frequently.

To be certain the contamination has been removed, run water over the surface. If the water beads up or separates, repeat one of the above methods. When the water sheets off, all contamination has been removed. Sanding does not remove contamination. After the surface has been properly cleaned, proceed with the application system below.

BARE FIBERGLASS - NO SAND SYSTEM: After the surface has been prepared as described above – apply one thin continuous coat of Fiberglass No Sand Primer YPA200. Please refer to label directions for application. Apply two coats minimum of compatible Interlux, antifouling paint. Apply at least two coats of Fiberglass Bottomkote ACT with Biolux.

BARE FIBERGLASS - SANDING SYSTEM: After the surface has been prepared as described above – Sand entire surface well with 80-grit sandpaper until flat matte finish is obtained. Remember to change sandpaper frequently. Wipe off sanding residue with Fiberglass Solvent Wash 202. Apply two coats minimum of Fiberglass Bottomkote ACT with Biolux.

BARE WOOD: Sand entire underwater surface with 80-grit sandpaper; wipe surface clean with Brush-Ease 433. Repair imperfections with Watertite; sand and wipe clean. Apply first coat of Fiberglass Bottomkote ACT with Biolux reduced 10% with Brush-Ease 433 to penetrate into the wood. Fill seams with Seam Compound 30. Apply second and third coats of Fiberglass Bottomkote ACT with Biolux unreduced. Allow proper dry times between coats.

UNDERWATER METALS: Contact the Interlux Technical Service Department for details on how to properly prime underwater. Do not use on aluminum.

**ACCEPTED
with COMMENTS
EPA Letter Dated:**

AUG 18 2005

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

2693-209