
 <p>U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Pesticide Program Registration Division (H7505C) 401 "M" St., S.W. Washington, D.C. 20460</p> <p>NOTICE OF PESTICIDE: <u>  X  </u> Registration <u>      </u> Reregistration</p> <p>(under FIFRA, as amended)</p>	EPA Reg. Number:  2693-212	Date of Issuance:  JUL 7 2004
	Term of Issuance: Expiration Date 09/15/04	
	Name of Pesticide Product:  Super Epoxycop with Irgarol - Blue	
Name and Address of Registrant (include ZIP Code):  International Paint, Inc. 2270 Morris Avenue Union, NJ 07083		
<p><b>Note:</b> Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.</p> <p>On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.</p> <p>Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.</p> <p>This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:</p> <ol style="list-style-type: none"> <li>1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency request all registrants of similar product to submit such data; and submit acceptable response required for reregistration of your product under FIFRA section 4.</li> </ol> <p>Please note that the active ingredient (Irgarol 1051) contained in your product formulations was previously registered for antifoulant use on a time limited conditional basis. The time limited registration was granted to allow the manufacturer, Ciba Geigy to resolve various environmental risk concerns. So far all antifouling paint product containing Irgarol 1051 have been granted time limited registrations only, which are due to expire on September 15, 2004, It is probable that all these registrations will be granted a time extension beyond the expiration date in the near future. Please contact you sales representative from Ciba Geigy for additional information.</p> <ol style="list-style-type: none"> <li>2. Add the phase, EPA Registration No.2693-212 to your label before you release your product for shipment.</li> </ol>		
Signature of Approving Official:    Marshall Swindell, Product Manager 33 Regulatory Management Branch I Antimicrobials Division (7510C)	Date:  JUL 7 2004	

3. Make the following labeling revisions:

Revise the Physical Or Chemical Hazard to read:

Combustible. Do not use or store near heat or open flame

Add the following statement as a footnote to the ingredient statement


Contains Petroleum Distillate

4. This conditional registration will expire automatically on September 15, 2004. If you fail to satisfy the conditions imposed in the registration, EPA may issue a Notice To Cancel under Section 6(e) of FIFRA.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,



Marshall Swindell  
Product Manager 33  
Regulatory Management Branch I  
Antimicrobials Division (7510C)

Enclosure

# SUPER EPOXYCOP with IRGAROL - Blue

3/6

- with Irgarol
- Irgarol Blocks Slime
- Irgarol Boosts Performance by Controlling Slime
- Antifouling Protection for All Conditions
- Multi-Season, Self-Polishing, No Paint Buildup
- Use on fiberglass, wood and steel hulls
- Irgarol controls slime

**KEEP OUT OF REACH OF CHILDREN**

**ACCEPTED  
with COMMENTS  
in EPA Letter Dated:**

JUL 07 2004

**CAUTION**

See side panel for additional precautionary statements

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

2693-212

EPA Registration No. 2693-  
EPA Establishment No. 2693-NJ-1

**Active Ingredients:**

Cuprous Oxide	= 55.00%
N-Cyclopropyl-N'-(1,1-dimethylethyl)-6-(methylthio)-1,3,5-triazine-2,4-diamine	= 0.98%
<b>Inert Ingredients:</b>	= 44.02%
	100.00%
 Copper as Metallic	 = 48.80%

**DISCLAIMER:** The performance of any marine coating depends on many factors outside the control of International Paint Inc. including the surface preparation, proper application and the environmental conditions. Therefore, International Paint Inc. cannot guarantee the suitability of this product for your particular purpose or application. **IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED.** INTERNATIONAL PAINT INC. SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use, of the product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint Inc.'s option.

**International Paint Inc.  
2270 Morris Avenue  
Union, NJ 07083**

4/6  
ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

JUL 07 2004

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

2693-212

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**CAUTION**

Harmful if absorbed through skin or inhaled. Causes moderate eye irritation. Avoid contact with eyes, skin or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. Avoid breathing spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Safety & Health Administration and the National Institute of Occupational Safety & Health. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash clothing before reuse. May pose an aspiration pneumonia hazard.

**FIRST AID**

**IF SWALLOWED:** Call a Poison Control Center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a Poison Control Center or doctor. Do not give anything by mouth to an unconscious person.

**IF IN EYES:** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. Call a Poison Control Center or doctor for treatment advice.

**IF ON SKIN AND CLOTHING:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a Poison Control Center or doctor for treatment advice.

**IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, give artificial respiration preferably mouth-to-mouth if possible. Call a Poison Control Center or doctor for further treatment advice.

In case of emergency call 1-800-854-6813. Have the product container or label with you when calling a Poison Control Center or doctor or going in for treatment.

**ENVIRONMENTAL HAZARD**

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

5/0  
ACCEPTED  
with COMMENTS—  
in EPA Letter Dated:

JUL 6 7 2004

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

## PHYSICAL OR CHEMICAL HAZARD

Do not use or store near heat or open flame.

## STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

**PESTICIDE DISPOSAL:** Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

**CONTAINER DISPOSAL:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

**PRODUCT DESCRIPTION:** This product is a premium ablative antifouling coating that provides effective multi-season protection for boats that are used in high fouling salt or fresh water areas on boat bottoms only. The combination of cuprous oxide and Irgarol, an anti-slime additive, provides excellent antifouling protection for boats in all waters. The combination of two biocides, cuprous oxide and Irgarol, an anti-slime additive, provides multi-season antifouling protection against barnacles, zebra mussels, hydroids, algae and slime for boats in salt or fresh water on boat bottoms only. It releases these biocides by the constant exposure of new paint film to the water. It is compatible over most all types of properly prepared bottom paints. Do not use on aluminum hulls.

**DIRECTIONS FOR USE:** It is a violation of federal law to use this product in a manner inconsistent with it's labeling.

**SURFACE PREPARATION:** Surface must always be clean, dry and properly prepared prior to painting. Failure to do so will lead to eventually blistering and/or peeling. All sanded surfaces must be wiped clean with [West Marine Model 329591 Reducer/Thinner; Interlux Fiberglass Solvent Wash 202] to remove sanding residue.

**GENERAL APPLICATION:** For use on boats below the true waterline. Can be brushed or rolled on fiberglass, wood, steel and previously painted surfaces per application systems below. DO NOT USE ON ALUMINUM. Apply at least three (3) coats for best performance, as the life of the paint is proportional to the number of coats applied.

**MIXING AND THINNING:** Shake or mix thoroughly and stir continuously while using. Thin when necessary with [West Marine Model 329591 Reducer/Thinner; Interlux Special Thinner 216; Brush-Ease 433].

**THEORETICAL COVERAGE:** Depending on surface and conditions, one gallon of bottom paint will usually cover over 350 square feet of surface when brushed or rolled.

**CLEAN UP:** Use [West Marine Model 329591 Reducer/Thinner; Interlux Special Thinner 216] for cleaning equipment and paint brushes.

**ESTIMATED DRY TIMES:** Bottom paints are designed for overcoating after an overnight dry. Prior to launching, allow a minimum dry of overnight and maximum of 60 days. If drying conditions are poor, or if paint was applied too thickly, longer periods of drying will be required. Fresh coats of paint must be thoroughly dry before overcoating.

2693-212

**YEARLY REPAINTING:** Scrub bottom clean at haul-out. Repaint only if old paint is sound and tight; if not, remove it by sanding or with paint remover. If old paint is rough, sand it with 100-150-grit sandpaper. Prepare seams, nicks and chips as below. Spot coat any scuffs with antifoulant. Apply three (3) coats of antifoulant.

**ON BARE WOOD:** Sand bare wood with 80-grit sandpaper. Repair imperfections with an epoxy filler and fairing compound. Apply first coat of bottom paint reduced 10% with [West Marine Model 329591 Reducer/Thinner; Interlux Special Thinner 216; Brush-Ease 433] to penetrate the porous grain. Fair seams with underwater seam compound. Apply second and third coats of antifoulant.

**ON BARE FIBERGLASS:** Dewax by washing with [West Marine Model 329591 Reducer/Thinner; Interlux Special Thinner 216; Brush-Ease 433]; remove dissolved wax at once with clean paper towels or rags: repeat. Sand thoroughly to a dull flat finish with 80-grit sandpaper. Fill any chips or dings with an epoxy filler and fairing compound, allow to dry and sand. Apply 2 to 3 coats of antifouling paint.

**ON BARE STEEL:** Sandblast surface to a near white metal: remove blast residue with a broom and air hose. Wipe off with [West Marine Model 329591 Reducer/Thinner; Interlux Special Thinner 216; Brush-Ease 433]. Do not sand. Fill in any imperfections with fairing compound. Sand smooth and wipe clean. Apply 3 coats of high quality marine primer, followed by three (3) coats of antifoulant.

**DISCLAIMER:** The performance of any marine paint or coating depends on many factors outside the control of our company including surface preparation, proper application, and environmental condition. Therefore, we cannot guarantee this product's suitability for your particular purpose or application. Implied warranties or fitness for a particular purpose and of merchantability are excluded. We shall not, under any circumstances, be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product, at the company's option.

ACCEPTED  
with COMMENTS  
to EPA Lease District

JUL 07 2004

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended for the pesticide  
registered under EPA Reg. No.

2693-212