

2693-215

12/31/2007

1/7



U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs  
Antimicrobials Division (7510C)  
1200 Pennsylvania Avenue NW  
Washington, D.C. 20460

EPA Reg. Number:  
2693-215

Date of Issuance:  
**DEC 31 2007**

Term of Issuance:  
Conditional

Name of Pesticide Product:  
Ultra P - Blue

NOTICE OF PESTICIDE:

Registration  
 Reregistration

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

International Paint, LLC  
2270 Morris Avenue  
Union, N. J. 07083

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for re-registration of your product under FIFRA section 4.
2. Make the labeling changes listed below before you release the product for shipment:
  - a. Revise the "EPA Registration Number to read, "EPA Reg. No. 2693-215".

Signature of Approving Official:

Marshall Swindell  
Product Manager Team-33  
Regulatory Management Branch I  
Antimicrobials Division (7510P)

Date:

**DEC 31 2007**

b. Antifouling paint products formulated using Preventol A5-S are limited to application by paint brush or paint roller; do not apply paints containing Preventol A5-S using an airless spray paint method.

c. Indicate in the use directions "Antifouling paint products formulated using Preventol A5-S are limited to use by Do-It-Yourself users/residential users". Use of Preventol A5-S containing antifouling paint products is limited to boats no larger than 300 ft<sup>2</sup>. Typical boat sizes that fall into this category are  
**14 ft Boat** - The surface area of the hull of a 14 ft boat with a 5 ft beam is ~70 ft<sup>2</sup>  
**20 ft Boat** - The surface area of the hull of a 20 ft boat with a 8 ft beam is ~160 ft<sup>2</sup>  
**30 ft Boat** - The surface area of the hull of a 30 ft boat with a 10 ft beam is ~300 ft<sup>2</sup>

3. In support of your application you must submit the following additional information:

- A Monitoring Study which addresses nitrosamine formation as associated with the antifoulant use pattern during actual use of the product. The time frame for submitting the Monitoring Study will be determined after the required Monitoring Protocol has been reviewed and accepted by the agency.
- A Monitoring Study Protocol must be submitted to the Agency for approval prior to initiation of the Monitoring Study. The protocol must be submitted by March 1, 2008.

4. Submit two (2) copies of your final printed labeling before distributing or selling the product bearing the revised labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



Marshall Swindell  
Product Manager 33  
Regulatory Management Branch I  
Antimicrobials Division (7510P)

Enclosure: (Stamped Label)

# Ultra P – Blue

Active Ingredients:

Cuprous Oxide	64.65%
Tolyfluanid	1.64%

Inert Ingredients:

	<u>33.71%</u>
	100.00%

**COPPER AS METALLIC = 57.42%**

Contains petroleum distillates.

**ACCEPTED  
with COMMENTS  
EPA Letter Dated:**

**DEC 31 2007**

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

2693-215

**KEEP OUT OF REACH OF CHILDREN**

**DANGER**

- See side panel for additional Precautionary Statement-

EPA Reg. No.: 2693-ERL

EPA Est. No.: 2693-NJ-1

**NET CONTENTS:  
ONE U.S. GALLON (3.785 LITERS)**

**International Paint LLC  
2270 Morris Avenue  
Union, NJ 07083**

4  
7

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS  
DANGER**

Causes eye damage or skin burns. Harmful if swallowed or inhaled. Do not get in eyes, on skin or on clothing. Do not breathe dust or vapor. While sanding or sandblasting boat surfaces, wear a mask or respirator jointly approved by the Mine Safety and Health Administration and the National Institute for Occupational Safety and Health. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Wear protective clothing such as protective eyewear (safety glasses, goggles, or face shield), chemical resistant gloves, long sleeved cotton shirt, long pants, and hat. Remove contaminated clothing and wash clothing before reuse. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

**FIRST AID**

**If Swallowed:**

- Immediately call a poison control center or doctor.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give **any** liquid to the person.
- Do not give anything by mouth to an unconscious person.

**If on skin or clothing:**

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes
- Call a poison control center or doctor for treatment advice.

**If inhaled:**

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

**If in eyes:**

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

**Other:** Have the product container or label with you when calling a poison control center or doctor or going for treatment.

**Note to Physician:** Contains petroleum distillate – vomiting may cause aspiration pneumonia.

ACCEPTED  
with COMMENTS  
EPA Letter Dated:

DEC 3, 2007

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

2693-215

**ENVIRONMENTAL HAZARDS:** This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**PHYSICAL OR CHEMICAL HAZARD:** Combustible: Do not use or store near heat or open flame.

**STORAGE AND DISPOSAL:** Do not contaminate water, food or feed by storage or disposal.

**PESTICIDE DISPOSAL:** Pesticide wastes are toxic. Open dumping is prohibited. Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

**CONTAINER DISPOSAL:** Triple rinse (or equivalent) and dispose of in an approved landfill. Consult Federal, State or local disposal authorities for approved alternative procedures.

ACCEPTED  
with COMMENTS  
EPA Letter Dated:  
DEC 31 2007

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.  
2693-215

## ULTRA P

**PRODUCT DESCRIPTION:** In the most troublesome fouling situations, where waters are warmer, land runoff is greater and slime-causing algae are rampant, Ultra P rises to the challenge. Interlux has combined a very high load of cuprous oxide to combat shell fouling with Biolux technology to fight weed and slime growth. Biolux keeps the bottom clean from weed and algae fouling and the copper then works better at keeping shell fouling such as barnacles and zebra mussels from attaching to the bottom. Ultra P is recommended for use where the fouling challenge is severe. Such as warm or tropical waters or in areas where the runoff from the land causes higher algae and grass growth. It can be used in fresh, salt and brackish water on fiberglass, wood and properly primed metal boat hulls and parts. Do not use on aluminum. **ULTRA P** can be applied over hard well-sanded antifouling paint. Even though **ULTRA P** has a very high loading of cuprous oxide it has excellent color stability and resists changing color at the waterline.

### DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

**COMPATIBILITY:** **ULTRA P** can be applied over any other hard antifouling paint after sanding the surface. Soft antifouling paints will need to be removed or overcoated with Underwater Primer 360R before applying **ULTRA P**.

**VOC:** Less than 290 grams/liter (2.40 lbs./gallon)

**DRY TIMES:** Touch dry – 2 hours

77°F (25°C) Dry to overcoat – 16 hours minimum

Dry to launch – 16 hours minimum  
60 days maximum

**THINNING:** Thin only when necessary.

Do not exceed 10% maximum.

**THINNER:** Special Thinner 216™ or  
Brush-Ease 433™

**CLEAN-UP:** Special Thinner 216™ or  
Brush-Ease 433™.

**THEORETICAL COVERAGE:** 530 SQ.FT./GALLON. Yields 2 mils dry film thickness.

**APPLICATION TEMPERATURES:** 50°F (10°C)\* and above. (Air and hull)

\* If either the air or hull temperature falls below 50°F (10°C) during the 16-hour dry time extend the dry time to 36 hours minimum.

**ULTRA P** should not be spray applied.

### APPLICATION SYSTEMS

**PREVIOUSLY PAINTED - GOOD CONDITION:** Remove all traces of loose paint and contamination by sanding the entire surface with 80 grit sandpaper; wipe surface clean with Special Thinner 216™. Apply at least 2 coats of **ULTRA P** by brush or solvent resistant 3/8" nap roller.

**PREVIOUSLY PAINTED SURFACES - POOR CONDITION:** Completely remove all old antifouling paint using Interstrip® 299E. Sand and wipe clean with Fiberglass Solvent Wash 202™.

**BARE FIBERGLASS (POLYESTER OR VINYLESTER) - SURFACE PREPARATION:** It is very important that bare fiberglass be properly prepared to prevent delamination of antifouling paint. Scrub the surface thoroughly with soap and water using a stiff brush. Flush well with water. Wipe a small area with a clean cloth that has been wetted with Interlux® Fiberglass Solvent Wash 202™. While the surface is still wet remove with a clean dry cloth. Repeat this process until the entire surface has been cleaned. To be certain that all of the contamination has been removed, run water over the surface. If the water beads up or separates, wipe again with Fiberglass Solvent Wash 202™. When the water sheets off, all contamination has been removed. Sanding does not remove contamination. After the surface has been properly cleaned, proceed with the application system below.

**BARE FIBERGLASS - NO SAND SYSTEM:** Clean the surface following the preparation procedure described above. Repair any surface imperfections using Interlux® Interprotect® Watertite® V135. Sand and wipe clean. Apply one thin continuous coat of Interlux® No Sand Primer YPA200 by brush or roller. Follow application directions for primer and apply the first coat of **ULTRA P**. Apply a second coat allowing for the appropriate dry times.

ACCEPTED  
with COMMENTS  
EPA Letter Dated:  
DEC 31 2007  
Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.  
2693-215

**BARE FIBERGLASS - SANDING SYSTEM:** Clean the surface following the preparation procedure described above. Sand the entire surface with 80 grit sandpaper and wipe clean with Fiberglass Solvent Wash 202™ to remove sanding residue. Repair any surface imperfections using Interlux® Interprotect® Watertite® V135. Sand and wipe clean. Apply 2 coats of **ULTRA P** allowing for appropriate dry times.

**BARE WOOD:** Sand the entire surface with 80 grit sandpaper; wipe surface clean with Interlux® Special Thinner 216™. Repair imperfections with Interlux® Interprotect® Watertite® V135. Sand and wipe clean. Apply the first coat of **ULTRA P** thinned 10% with Special Thinner 216™ or Brush-Ease 433™. Fill seams with Interlux® Seam Compound 30 (if necessary). Apply two more coats of **ULTRA P** unthinned, allowing appropriate dry times.

**UNDERWATER METALS:** Contact the Interlux® Technical Service Department at 1-800-468-7589 for full information on how to properly prime underwater metals. **DO NOT USE ON ALUMINUM.**

Teflon® is a trademark of DuPont. Only DuPont makes TEFLON.

FOR CHEMICAL EMERGENCY, SPILL, LEAK, EXPOSURE OR ACCIDENT, CALL TOLL FREE: CHEMTREC 1-800-424-9300 (DAY OR NIGHT) MEDICAL ADVISORY: CONTACT YOUR LOCAL POISON CONTROL CENTER OR CALL 1-800-854-6813.

ACCEPTED  
with COMMENTS  
EPA Letter Dated:

DEC 31, 2007

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

2693-215