

2693-215

5210912009

1/6

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, D.C. 20460



United States
Environmental Protection
Agency

Office of Pesticide Programs

International Paints, LLC
2270 Morris Avenue
Union, N. J. 07083

FEB - 9 2009

Attention: John P. Pazdera
Pesticide Registration Manager

Subject: Ultra P - Blue
EPA Registration No. 2693-215
Amendment Dated December 16, 2008

The amendment, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, to revise the "Directions for Use" and Product Description" sections, is acceptable, provided that you make the label changes.

- In the product description, indicate what type of boats this product will be used on (e.g., ships, commercial, pleasure craft, etc.).

Submit two (2) copies of the final printed label for our review. A stamped copy of the "accepted" label is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely

A handwritten signature in black ink that reads "Marshall Swindell".

Marshall Swindell
Product Manager (33)
Regulatory Management Branch 1
Antimicrobials Division (7510P)

Enclosure

Ultra P – Blue

Active Ingredients:

Cuprous Oxide	64.65%
Tiolyfluonid	1.64%

Inert Ingredients:

<u>33.71%</u>
100.00%

COPPER AS METALLIC = 57.42%

Contains petroleum distillates.

ACCEPTED
with COMMENTS
EPA Letter Dated:

FEB - 9 2009

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No. *2693-215*

KEEP OUT OF REACH OF CHILDREN

DANGER

- See side panel for additional Precautionary Statement-

EPA Reg. No.: 2693-215

EPA Est. No.: 2693-NJ-1

**NET CONTENTS:
ONE U.S. GALLON (3.785 LITERS)**

**International Paint LLC
2270 Morris Avenue
Union, NJ 07083**

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
DANGER**

Causes eye damage or skin burns. Harmful if swallowed or inhaled. Do not get in eyes, on skin or on clothing. Do not breathe dust or vapor. While sanding or sandblasting boat surfaces, wear a mask or respirator jointly approved by the Mine Safety and Health Administration and the National Institute for Occupational Safety and Health. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Wear protective clothing such as protective eyewear (safety glasses, goggles, or face shield), chemical resistant gloves, long sleeved cotton shirt, long pants, and hat. Remove contaminated clothing and wash clothing before reuse. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

FIRST AID

If Swallowed:

- Immediately call a poison control center or doctor.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give **any** liquid to the person.
- Do not give anything by mouth to an unconscious person.

**ACCEPTED
with COMMENTS
EPA Letter Dated:**

FEB - 9 2009

If on skin or clothing:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes
- Call a poison control center or doctor for treatment advice.

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 2693-215

If inhaled:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

If in eyes:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

Other: Have the product container or label with you when calling a poison control center or doctor or going for treatment.

Note to Physician: Contains petroleum distillate – vomiting may cause aspiration pneumonia.

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD: Combustible: Do not use or store near heat or open flame.

STORAGE AND DISPOSAL: Do not contaminate water, food or feed by storage or disposal.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Open dumping is prohibited. Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

CONTAINER DISPOSAL: Triple rinse (or equivalent) and dispose of in an approved landfill. Consult Federal, State or local disposal authorities for approved alternative procedures.

ACCEPTED
with COMMENTS
EPA Letter Dated:

FEB - 9 2009

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No. 2693-215

ULTRA P

PRODUCT DESCRIPTION: **ULTRA P** is an ultra strong formula for high fouling areas that provides excellent long-term antifouling protection. Where the fouling challenge is severe such as warm or tropical waters or in areas where the runoff from the land causes higher algae and grass growth, **ULTRA P** rises to the challenge. Biolux® technology reduces slime and increases antifouling performance. The fast dry formula of **Ultra P** allows your boat to be painted and launched in the same day. It can be used in fresh, salt and brackish water on fiberglass, wood and properly primed metal boat hulls and parts. Do not use on aluminum. **ULTRA P** can be applied over hard well-sanded antifouling paint. **ULTRA P** has excellent color stability and resists changing color at the waterline.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

COMPATIBILITY: **ULTRA P** can be applied over any other hard antifouling paint after sanding the surface. Soft antifouling paints will need to be removed or overcoated with Primocon YPA984 before applying **ULTRA P**.

VOC: Less than 290 grams/liter (2.40 lbs./gallon)

DRY TIMES: Touch dry - 1 hour

77°F (25°C) Dry to overcoat - 2 hours minimum

Dry to launch - 8 hours minimum

60 days maximum

THINNING: Thin only when necessary.

Do not exceed 10% maximum.

THINNER: Special Thinner 216™ or

Brush-Ease 433™

CLEAN-UP: Special Thinner 216™ or

Brush-Ease 433™.

ACCEPTED
with COMMENTS
EPA Letter Dated:

FEB - 9 2009

THEORETICAL COVERAGE: 500 SQ.FT./GALLON. Yields 2 mils dry film thickness.

APPLICATION TEMPERATURES: 50°F (10°C)* and above. (Air and hull).

If either the air or hull temperature falls below 50°F (10°C) during the dry time extend the dry times to a minimum.

Apply **ULTRA P** by brush or solvent resistant 3/8" nap roller. Do not apply by airless spray.

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 2693-715

APPLICATION SYSTEMS

PREVIOUSLY PAINTED - GOOD CONDITION: Remove all traces of loose paint and contamination by sanding the entire surface with 80 grit sandpaper; wipe surface clean with Special Thinner 216™. Apply at least 2 coats of **ULTRA P**.

PREVIOUSLY PAINTED SURFACES - POOR CONDITION: Completely remove all old antifouling paint using Interstrip® 299E. Sand and wipe clean with Fiberglass Solvent Wash 202.

BARE FIBERGLASS:

It is very important that bare fiberglass be properly prepared to remove the mold release wax completely to prevent delamination of the antifouling paint. Begin by scrubbing the surface thoroughly with soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry.

Remove mold release wax using one of the following Interlux products. Fiberglass Surface Prep YMA601 or Fiberglass Solvent Wash 202 following the product label instructions. To be certain that all of the contamination has been removed, run water over the surface. If the water beads up or separates, clean again. When the water sheets off, all contamination has been removed. After the surface has been properly cleaned, proceed with one of the application systems below.

BARE FIBERGLASS - NO SAND SYSTEM:

Clean the surface following the preparation procedure above. Repair any surface imperfections using Interlux Watertite filler. Sand and wipe clean. Apply one coat, using one of the following Interlux products InterProtect® 2000 or No Sand Primer YPA200, following the label instructions for applying the primer and overcoating with antifouling paint. Apply two coats of **Ultra P**, allowing for the appropriate dry times.

BARE FIBERGLASS - SANDING SYSTEM:

Clean the surface following the preparation procedure above for bare fiberglass. Sand the entire surface with 80-grit sandpaper until a flat matte finish is obtained. Wipe the sanding residue off the surface with Interlux Special Thinner 216. Repair any surface imperfections with Interlux Watertite. Sand and wipe clean. Apply two coats of **Ultra P** allowing for appropriate dry times.

6
6

BARE WOOD: Sand the entire surface with 80 grit sandpaper; wipe surface clean with Interlux® Special Thinner 216™. Repair imperfections with Watertite® V135. Sand and wipe clean. Apply the first coat of **ULTRA P** thinned 10% with Special Thinner 216™ or Brush-Ease 433™. Fill seams with Interlux® Seam Compound 30 (if necessary). Apply two more coats of **ULTRA P** unthinned, allowing appropriate dry times.

UNDERWATER METALS: Contact the Interlux® Technical Service Department at 1-800-468-7589 for full information on how to properly prime underwater metals. **DO NOT USE ON ALUMINUM.**

Color difference may occur between actual paint and color swatch on front of can.

ACCEPTED
with COMMENTS
EPA Letter Dated:

FEB - 9 2009

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No. 2693-215