



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

September 18, 2020

Vanessa Villagran
PSRA Specialist for, International Paint, LLC
6001 Antoine Drive
Houston, TX 77091

Subject: Label Amendment – Minor Labeling Revisions
Product Name: Trilux 44-White
EPA Registration Number: 2693-220
Application Date: April 13, 2020
Decision Number: 565865

Dear Ms. Villagran:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. You must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) lists examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Assurance.

Page 2 of 2
EPA Reg. No. 2693-220
Decision No. 565865

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. If you have any questions, please contact Karen M. Leavy by phone at (703)-308-6237, or via email at Leavy.Karen@epa.gov.



Eric Miederhoff
Product Manager 31
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

Enclosure

Trilux 44 – White

[Antifouling Paint]

[Copper Free Antifouling]

[Alternate Brand Names]

[INTERSPEED 5640 BLACK BZA646/5]

[INTERSPEED 5640 BLUE BZA647/5]

[INTERSPEED 5640 RED BZA645/5]

[PACIFICA PLUS]

[PACIFICA PLUS YBB260 BLUE]

[PACIFICA PLUS YBB261 GREEN]

[PACIFICA PLUS YBB262 RED]

[PACIFICA PLUS YBB263 BLACK]

[PACIFICA PLUS YBB264 GRAY WHITE]

[TRILUX 44 ANTIFOULING PAINT – WHITE]

[Graphics]

AkzoNobel



VC, Interlux and the AkzoNobel logo are trademarks of AkzoNobel. © AkzoNobel [XXXX- year label is printed].



Interlux and the AkzoNobel logo are trademarks of Akzo Nobel.

ACCEPTED

09/18/2020

Under the Federal Insecticide, Fungicide
and Rodenticide Act as amended, for the
pesticide registered under
EPA Reg. No. 2693-220

[FRONT PANEL]

KEEP OUT OF REACH OF CHILDREN

DANGER

See side panel for additional Precautionary Statement

Active Ingredients:

1H-Pyrrole-3-carbonitrile, 4-bromo -2-(4-chlorophenyl)-5-(trifluoromethyl) 3.90%

Zinc 2-Pyridinethiol 1-Oxide* 4.12%

Other Ingredients: 91.98%

100.00%

Contains petroleum distillates.

*Zinc Pyrithione

EPA Reg No.: 2693-220

EPA Est. No.: 2693- TX-1

[DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of INTERNATIONAL PAINT, LLC., including surface preparations, proper application and environmental conditions. Therefore, INTERNATIONAL PAINT, LLC., cannot guarantee this product's suitability for your particular purpose of application. To the extent consistent with applicable law, INTERNATIONAL PAINT, LLC., EXPRESSLY DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE or otherwise that extend beyond the statements made on this label, and shall not be liable for special, incidental, or consequential damages resulting from the use or handling of this product, the exclusive remedy being the replacement of this product. To the extent consistent with applicable law, buyer/user assumes all risk of possession, handling, or use of this material when use and/or handling is contrary to label instructions.]

**INTERNATIONAL PAINT LLC
6001 Antoine Drive, Houston, TX 77091**

**NET CONTENTS:
ONE GALLON (3.785 LITERS)**

[SIDE PANEL]

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
KEEP OUT OF REACH OF CHILDREN
DANGER**

Corrosive. Causes irreversible eye damage or skin burns. Harmful if absorbed through skin. Do not get in eyes, on skin or on clothing. Harmful if swallowed or inhaled. Do not breathe dust, vapor or spray mist. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

Residential (non-commercial) users are advised to wear chemical resistant gloves, protective eyewear (goggles, safety glasses, or face shield), long sleeved shirt and long pants, socks and shoes. In addition to these minimum PPE, commercial users must wear a disposable coverall with hood and chemical resistant footwear.

While removing existing paint by sanding or blasting, or applying new antifoulant paint, commercial users must wear a minimum of an NIOSH-approved elastomeric half mask respirator with organic vapor (OV) cartridges and a combination N, R, or P filter; OR a NIOSH-approved gas mask with OV canisters; OR a NIOSH-approved powered air-purifying respirator with OV cartridges and combination HE filters.

Residential (non-commercial) users are advised to wear the same respirators, cartridges, and prefilters as required by commercial users.

FIRST AID	
IF IN EYES:	<ul style="list-style-type: none">• Hold eye open and rinse slowly and gently with water for 15-20 minutes.• Remove contact lenses, if present, after the first 5 minutes, and then continue rinsing.• Call a Poison Control Center or doctor for treatment advice.
IF SWALLOWED:	<ul style="list-style-type: none">• Immediately call a poison control center or doctor.• Do not induce vomiting unless told to do so by a poison control center or doctor.• Do not give any liquid to the person.• Do not give anything by mouth to an unconscious person.
IF ON SKIN OR CLOTHING:	<ul style="list-style-type: none">• Take off contaminated clothing.• Rinse skin immediately with plenty of water for 15-20 minutes.• Call a poison control center or doctor for treatment advice.
IF INHALED:	<ul style="list-style-type: none">• Move a person to fresh air.• If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.• Call a poison control center or doctor for further treatment advice.
OTHER: Have the product container or label with you when calling a poison control center or doctor or going for treatment. For medical emergencies, call the poison control center at 1-800-222-1222. For general information on this product, contact the National Pesticides Information Center (NPIC) at 1-800-858-7378, Monday through Friday, 8 AM to 12 PM PST, or at http://npic.orst.edu .	

Note to Physician: Contains petroleum distillate – vomiting may cause aspiration pneumonia.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and particulate generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD:

FLAMMABLE. Keep away from heat and open flame.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE: Exposure to air and extremes of temperature must be avoided. Keep the container firmly closed. Keep out of direct sunlight. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING: Nonrefillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

[For Chemical Emergency, Spill, Leak, Exposure or Accident, Call Toll Free – Day or Night – CHEMTREC 1-800-424-9300. Medical Advisory Number – Contact your Local Poison Control Center or Call 1-800-854-6813.]

[Subset A] [Commercial Use]

DIRECTIONS FOR USE: It is a violation of federal law to use this product in a manner inconsistent with its labeling.

SURFACE PREPARATION AND COMPATIBILITY: Surface preparation directions must be followed exactly in order to insure adhesion. Surface must always be clean and dry prior to painting.

GENERAL APPLICATION PROCEDURES: Apply using an airless sprayer. Tip Size 21-26 thou inch, pump ratio of 30:1 or greater. For small areas, brush or roller may be used, but multiple coats may be required to achieve the required dry film thickness. It is recommended to apply by airless spray one (1) or two (2) full coats of this product.

MIXING AND THINNING INSTRUCTIONS: Mix thoroughly with power mixer prior to application. This coating is designed to be applied without thinning. Should thinning be necessary, consult your International representative prior to altering this coating.

CLEAN UP: For tools, equipment, etc., use INTERNATIONAL GTA007.

MINIMUM DRY AND LAUNCHING TIMES: Minimum drying time between coats is 6 hours, and before launching is 6 hours at 73° F.

THEORETICAL COVERAGE: 186 square feet per gallon, per coat at 5.0 mils DFT. Consult your International representative for practical application coverages. Practical square foot coverage per gallon, per coat is directly proportional to surface, application techniques and climatic conditions.

APPLICATION SYSTEMS

EXISTING ANTIFOULING SYSTEMS – GOOD CONDITION: High pressure fresh water wash with a minimum of 2500 p.s.i. and/or scrape to remove all marine growth, slime, salts, etc. Spot blast all areas of corrosion to a Near White Metal Standard of SSPC-SP10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

POOR CONDITION: For “optimum” results, blast entire area to Near White Metal Standard of SSPC-SP10-85. Apply an approved underwater anticorrosive system.

NEW SHIP CONSTRUCTION: Blast entire area to a Near White Metal Standard of SSPC-SP10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

WOOD AND NON-FERROUS SURFACES: Use surface preparation and primers as specified by the Navy.

Subset B [Pleasure Craft]

PRODUCT DESCRIPTION: [Trilux 44, Alternate Brand Name, this product, it] is a copper free antifouling that provides excellent protection from shell and weed fouling. It uses Biolux® technology to block slime and Ecomea to ward off barnacles and zebra mussels. The fast dry formula of [Trilux 44, Alternate Brand Name, this product, it] allows the boat to be painted and launched quickly and its abrasive action reduces paint build up and helps to improve fuel efficiency. [Trilux 44, Alternate Brand Name, this product, it] is available in bright colors and is suitable for use on all boats including fiberglass, aluminum, wood, and steel and can be used in all waters. [Trilux 44, Alternate Brand Name, this product, it] can be brush or roller applied.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

GENERAL APPLICATION PROCEDURES

For applications by residential (non-commercial) users: Do not apply by airless spray. Do not apply more than one coat of this product within 24 hours. Apply only in outdoor, non-enclosed spaces.

Apply 2-3 coats of [Trilux 44, Alternate Brand Name, this product, it] by brush or solvent resistant 3/8" nap roller. **Do not apply thin coats.** Keep in mind that the life of the paint is directly related to the amount of paint applied. Certain areas of the hull, such as the leading edge of the keel and rudder, the waterline and bow stem polish faster than other areas. On these areas we suggest an additional coat of paint to ensure that the [Trilux 44, Alternate Brand Name, this product, it] does not polish away before other areas of the bottom.

Approximate time it will take to paint your boat

Boat Size	Application Time
14'	40 minutes per coat
20'	1 Hour 20 Minutes
30'	2 Hours 40 Minutes per coat

THEORETICAL COVERAGE: 528 ft ² /gal (2 mils dry film thickness)	V.O.C.: Less than 330 grams/liter (2.75 lbs./gallon)
THINNER: [Special Thinner 216, Interlux Special Thinner 216, Special Thinner, Acetone, Interlux Brush Ease 433, Brush Ease 433, Brush Ease, Acetone, Boat Thinner]	THINNING: Do not exceed 10% by volume

Temperature °F (°C)	Touch Dry	Overcoating Time		Immersion Time	
	MIN	MIN	MAX	MIN	MAX
41°F (5°C)	6 hrs	12 hrs	NA	18 hrs	NA
50°F (10°C)	3 hrs	6 hrs	NA	9 hrs	NA
73°F (23°C)	2 hrs	4 hrs	NA	6 hrs	NA
95°F (35°C)	1 h	2 hrs	NA	4 hrs	NA

*If the air temperature falls below 41°F (5°C) during the 4 hour dry time extend the dry time to 24 hours minimum.

COMPATIBILITY: [Trilux 44, Alternate Brand Name, this product, it] is compatible with most other antifouling paints and can be applied after sanding the surface.

PREPARATION

BARE FIBERGLASS: It is very important that bare fiberglass be properly prepared to remove the mold release wax completely to prevent delamination of the antifouling paint. Begin by scrubbing the surface thoroughly with a stiff brush using soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry.

Remove mold release wax using one of the following Interlux products. [Interlux Fiberglass Surface Prep YMA601V, Interlux Fiberglass Solvent Wash 202, Fiberglass Surface Prep YMA601V, Fiberglass Solvent Wash 202, Fiberglass Surface Prep] following the product label instructions. To be certain that all of the contamination has been removed, run water over the surface. If the water beads up or separates, clean again. When the water sheets off, all contamination has been removed. After the surfaces has been properly cleaned, proceed with one of the application systems below.

BARE FIBERGLASS – NO SAND SYSTEM: Clean the surface following the preparation procedure above. Repair any surface imperfections using [Watertite, Watertite Epoxy Filler, Epoxy Filler]. Sand and wipe clean. Apply one coat, using one of the following Interlux products [Interprotect® 2000E InterProtect HS, InterProtect], following the label instructions for applying the primer and overcoating with antifouling paint.

BARE FIBERGLASS – SANDING SYSTEM: Clean the surface following the preparation procedure above. Repair any surface imperfections using [Watertite, Watertite Epoxy Filler, Epoxy Filler]. Sand and wipe clean. After the surface has been cleaned sand with [80-120, 80, 100, 120] [grit, grade, wet or dry] sandpaper until a flat, matte finish has been obtained. Wipe off the sanding residue with [Interlux Fiberglass Surface Prep YMA601V, Interlux Fiberglass Solvent Wash 202, Fiberglass Surface Prep YMA601V, Fiberglass Solvent Wash 202, Fiberglass Surface Prep].

BARE WOOD: Sand entire surface thoroughly to a smooth finish with [80-120, 80, 100, 120] [grit, grade, wet or dry] sandpaper. Clean off the sanding residue. Prime with Primocon® thinned 10% with [Special Thinner 216, Interlux Special Thinner 216, Special Thinner, Acetone, Interlux Brush Ease 433, Brush Ease 433, Brush Ease, Acetone, Boat Thinner] or thin first coat of [Trilux 44, Alternate Brand Name, this product] 10-15% with [Special Thinner 216, Interlux Special Thinner 216, Special Thinner, Acetone, Interlux Brush Ease 433, Brush Ease 433, Brush Ease, Acetone, Boat Thinner]. Apply two more coats of this product unthinned, allowing appropriate dry times.

ALUMINUM & UNDERWATER METALS – Contact the Interlux Technical Service Department at [Interlux.com, interluxtechnicalservice@akzonobel.com, 1-800-468-7589] for full information on how to properly prime underwater metals.

PREVIOUSLY PAINTED SURFACES

In Good Condition: Remove all contamination. Sand the entire surface with [80-120, 80, 100, 120] [grit, grade, wet or dry] sandpaper; remove sanding residue.

In Poor Condition: Completely remove all old antifouling paint. Sand and wipe clean with **[Interlux Fiberglass Solvent Wash 202, Fiberglass Surface Prep YMA601V, Fiberglass Surface Prep, Fiberglass Solvent Wash]**.

APPLICATION

After the surface has been properly prepared and cleaned as above, apply two coats of **[Trilux 44, Alternate Brand Name, this product]** (3 on bare wood) by brush or roller (Residential users). Commercial (non-residential) users may apply **[Trilux 44, Alternate Brand Name, this product, it]** by airless spray while wearing the proper personal protective equipment.

NOTE: Important: Do not apply **[Trilux 44, Alternate Brand Name, this product, it]** above the true waterline.