



U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs
Antimicrobials Division (7510C)
1200 Pennsylvania Avenue NW
Washington, D.C. 20460

EPA Reg. Number:
2693-223

Date of Issuance:
OCT 3 2007

Term of Issuance: Time Limited-
Expires on September 28th,
2008

Name of Pesticide Product: Trilux
ABF-White

NOTICE OF PESTICIDE:

- Registration
- Reregistration

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

International Paint LLC
2270 Morris Ave.
Union, NJ 07083

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for re-registration of your product under FIFRA section 4.

2. Make the labeling changes listed below before you release the product for shipment:

- a. Add the phrase "EPA Registration Number 2693-223."

Signature of Approving Official:

Dennis H Edwards for
Marshall Swindell
Product Manager-33
Regulatory Management Branch I
Antimicrobials Division (7510P)

Date:

OCT 03 2007

3. The restrictions must be placed at the beginning of the Directions for Use section to read as follows:
 1. Do not apply by airless sprayer
 2. Do not apply more than one coat of the product within 24 hours
 3. Apply only in outdoor, non-enclosed spaces
4. Submit the Storage and Stability and Corrosion Characteristic studies at the end of the one year study.


The Confidential Statement of Formula dated February 14th, 2006, is acceptable.

5. Submit three (3) copies of the final printed label prior to releasing this product for sale.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



Marshall Swindell
Product Manager 33
Regulatory Branch I
Antimicrobials Division (7510P)

Enclosure: (Stamped Labeling)

3 8 7

Trilux ABF - White

Active Ingredient:

Zinc 2-Pyridinethiol 1-Oxide* 4.80%

Inert Ingredients: 95.20%
100.00%

* Zinc Pyrithione

KEEP OUT OF REACH OF CHILDREN

DANGER

- See side panel for additional Precautionary Statements

EPA Reg. No.: 2693-

EPA Est. No.: 2693-NJ-1

NET CONTENTS:
ONE U.S. GALLON (3.785 LITERS)

ACCEPTED
with COMMENTS
in EPA Letter Dated:

OCT 03 2007

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

2693-223

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
KEEP OUT OF REACH OF CHILDREN
DANGER**

Corrosive. Causes irreversible eye damage or skin burns. Harmful if absorbed through skin. Do not get in eyes, on skin or on clothing. Harmful if swallowed or inhaled. Do not breathe dust, vapor or spray mist. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

Residential (non-commercial) users are advised to wear chemical resistant gloves, protective eyewear (goggles, safety glasses, or face shield), long-sleeved shirt and long pants, socks and shoes. In addition to these minimum PPE, commercial users must wear a disposable coverall with hood and chemical resistant footwear.

While removing existing paint by sanding or blasting, or applying new antifoulant paint, commercial users must wear a respirator with an **organic vapor removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number TC-14G), or a NIOSH approved full face respirator with an organic vapor removing cartridge with a P100 prefilter.** Residential (non-commercial) users are advised to wear the same respirators, cartridges, and prefilters as required by commercial users.

**ACCEPTED
with COMMENTS
in EPA Letter Dated:**

OCT 03 2007

**Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No. 2695-223**

FIRST AID

If Swallowed:

- Immediately call a poison control center or doctor.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give any liquid to the person.
- Do not give anything by mouth to an unconscious person.

If on skin or clothing:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes
- Call a poison control center or doctor for treatment advice.

If inhaled:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

If in eyes:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

Other: Have the product container or label with you when calling a poison control center or doctor or going for treatment.

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL: Do not contaminate water, food or feed by storage or disposal.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Open dumping is prohibited. Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

CONTAINER DISPOSAL: Triple rinse (or equivalent) and dispose of in an approved landfill. Consult Federal, State or local disposal authorities for approved alternative procedures.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

OCT 03 2007

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

2695-223

Trilux® ABF

PRODUCT DESCRIPTION: Trilux® ABF is a slow wearing, water-based, copper free antifouling that uses Biolux® Technology for the controlled release of biocide to control fouling. Trilux® ABF wears away with use providing long term antifouling protection for your boat. The performance of Trilux® ABF is directly related to the amount of paint applied. The low VOC formula meets the most stringent regulations and can be used in any air quality management district. Trilux® ABF was developed for use on aluminum hulled vessels but can be used on fiberglass, aluminum, wood and steel surfaces. Trilux® ABF is for use on recreational or commercial vessels below the waterline on underwater boat hulls and parts in fresh, salt and brackish water and can be brush roller or spray applied. Trilux® ABF can be applied over most other antifouling paints provided they are in good condition and have been cleaned and sanded. Follow the application instructions for previously painted surfaces.

DIRECTIONS FOR USE: It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

GENERAL APPLICATION PROCEDURES

Apply at least 2-3 full coats of Trilux® ABF by brush or solvent resistant 3/8" nap roller. Do not apply thin coats. Keep in mind that the life of the paint is directly related to the amount of paint applied. Certain areas of the hull, such as the leading edge of the keel and rudder, the waterline and the bow stem polish faster than other areas. On these areas we suggest an additional coat of paint to insure that the Trilux® ABF does not polish away before other areas of the bottom (Thin film thickness may lead to premature fouling).

PREPARATION

PREVIOUSLY PAINTED SURFACES - In Good Condition: Rinse with fresh water and allow surface to dry. Abrade with 80-grit sandpaper. Remove sanding residue by wiping clean with Special Thinner 216.

In Poor Condition: Remove all previous coatings using Interstrip 299E and prime the substrate.

BARE ALUMINUM - On small craft where sandblasting is not practical, i.e. aluminum pontoon boats, car top boats etc.; Wipe bare metal with Special Thinner 216 to remove oil and grease. Uniformly sand surface to a bright finish with medium grit emery cloth. Wipe surface clean of dust. Immediately apply one thin coat of Viny-Lux Primewash 353 thinned 25% with Viny-Lux Solvent 355. Allow to dry a minimum of one hour but no more than twenty-four hours then apply Interprotect 2000E. Apply 1-2 coats of Interprotect 2000E. Be sure to follow dry times on the Interprotect 2000E label. When complete, apply at least three coats of Trilux® ABF. If dry times for Interprotect 2000E cannot be followed, use the following alternate system. Apply 2-3 coats of Primocon over the Viny-Lux Primewash. On riveted and welded areas, apply a minimum of 3 coats of Primocon. Finish with at least three coats of Trilux® ABF.

ALUMINUM-PREVIOUSLY PAINTED WITH A FACTORY FINISH: Wipe surface clean with Special Thinner 216 to remove contaminants. Sand the surface with 120-grit sandpaper. Wipe the surface again with Special Thinner 216, to remove sanding residue. Immediately spot prime any bare areas with Primocon. Apply at least two full coats of Primocon (three coats to riveted areas), to the entire bottom, allowing appropriate dry times. After an overnight dry apply at least three coats of Trilux® ABF.

BARE FIBERGLASS: Begin by scrubbing the surface thoroughly with a stiff brush using Interlux General Purpose Boat Soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry. Remove mold release wax using one of the following methods. Apply Low VOC Fiberglass Solvent Wash 202v or Fiberglass Surface Prep YMA601 with a maroon, 3M Scotch-Brite® pad and scrub well. Flush with fresh water or wipe off with a clean, wet cloth ensuring that no traces of Fiberglass Surface Prep remain.

OR

Dampen cheesecloth with Interlux Fiberglass Solvent Wash 202. Wipe thoroughly to remove all surface contamination and cleaners. Wipe off with a clean, dry rag before liquid dries. Wipe only a few square feet at a time and change rags frequently. To be certain the contamination has been removed, run water over the surface. If the water beads up or separates, repeat one of the above

ACCEPTED
WITH COMMENTS
EPA Letter Dated:
OCT 23 2007
Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.
2693-223

methods. When the water sheets off, all contamination has been removed. Repair all scratches, nicks and dings by sanding those areas with 80-grit sand paper then remove the sanding residue using Fiberglass Solvent Wash 202. Fill the repair areas with Interlux Watertite Epoxy Filler.

- **No Sand System:** Clean surface as above. Apply one thin, continuous coat of Interlux® Fiberglass No Sand Primer YPA200 with brush or roller. Do not spray; do not sand. Follow directions on the Fiberglass No-Sand Primer Label and apply 2 coats of **Trilux® ABF** allowing the appropriate dry times.

BARE WOOD: Sand entire surface thoroughly to a smooth finish with 80-grit sandpaper. Clean off the sanding residue using Special Thinner 216 on a damp rag. Prime with 1 coat of Primocon. Apply three coats of **Trilux® ABF**.

BARE METAL: Prime with Viny-Lux Primewash 353 followed by Interprotect 2000E or Primocon. Apply three coats of **Trilux® ABF**.

UNDERWATER METALS INCLUDING SHAFTS, PROPELLERS, TRIM TABS, STRUTS AND THRU-HULL FITTINGS:

These areas require special attention to initial surface preparation in order to improve adhesion. Treat these areas the same as bare aluminum. The longevity of this system will probably not be equal to that of the remainder of the boat due to the RPM's these parts withstand. For more details contact Interlux Technical Service at 1-800-468-7589.

APPLICATION

For applications by residential (non-commercial) users:

- Do not apply by airless spray
- Do not apply more than one coat of this product within 24 hours
- Apply only in outdoor, non-enclosed spaces

Apply three coats of **Trilux® ABF** by brush or roller.

THINNER: Special Thinner 6216

COVERAGE: 400 sq. ft./ Gallon

DRY TIME: 6 hours @ 73°F. If cooler, wait longer.

BARE FIBERGLASS: Apply a minimum of three coats of **Trilux® ABF**.

BARE WOOD: Prime with Primocon or apply the first coat of **Trilux® ABF** reduced with Special Thinner 216 (10% maximum) to penetrate the porous grain. Fill seams with Seam Compound 30. Apply second and third coats of **Trilux® ABF** unreduced.

PREVIOUSLY PAINTED FIBERGLASS AND WOOD - GOOD CONDITION: Apply three coats of **Trilux® ABF**.

IMPORTANT: Do not apply Primocon or **Trilux® ABF** above the true waterline.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

OCT 03 2007
Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

2693-223