



U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs
Antimicrobials Division (7510C)
1200 Pennsylvania Avenue NW
Washington, D.C. 20460

EPA Reg. Number: 2693-225

Date of Issuance: OCT 21 2008

Term of Issuance: Conditional

Name of Pesticide Product: Latenac II Antifouling RED

NOTICE OF PESTICIDE:
[x] Registration
[] Reregistration

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

International Paint, LLC
2270 Morris Avenue
Union, N. J. 07083

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec 3(c)(7)(A) provided that you:

- 1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for re-registration of your product under FIFRA section 4.
2. Make the labeling changes listed below before you release the product for shipment:
a. Revise the "EPA Registration Number to read, "EPA Reg. No. 2693-225".

Signature of Approving Official:

Marshall Swindell
Product Manager Team-33
Regulatory Management Branch I
Antimicrobials Division (7510P)

[Handwritten signature of Marshall Swindell]

Date:

OCT 21 2008


3. Submit three (3) copies of your final printed labeling before distributing or selling the product bearing the revised labeling.

4. The Basic and Alternate Confidential Statements of Formulas (CSFs) dated September 5, 2008 are in compliance with PR Notice 91-2, agree with the label and are acceptable.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label stamped "accepted with comments" is enclosed for your records.

Sincerely,



Marshall Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510P)

Enclosure: (Stamped Label)

Latenac II Antifouling Red

Dependable Season Long Protection
Fast Dry, Paint and Launch the Same Day
Compatible Over Most Antifouling Paints

Active Ingredient:		
Cuprous Oxide	= 33.40%	EPA Registration No. 2693-
Inert Ingredients:	= 66.60%	
	100.00%	EPA Establishment No. 2693-NJ-1
Copper as Metallic	= 29.66%	

Contains Petroleum Distillates.

KEEP OUT OF REACH OF CHILDREN

WARNING

See side panel for additional precautionary statements

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of International Paint LLC, including the surface preparation, proper application and the environmental conditions. Therefore, International Paint LLC cannot guarantee the suitability of this product for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT LLC SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use of the product buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at the discretion of International Paint LLC.

International Paint LLC
2270 Morris Avenue
Union, New Jersey, 07083

ACCEPTED
with COMMENTS
EPA Letter Dated:
OCT 21 2008

Under the Federal Insecticide,
Fungicide and Rodenticide Act as
amended, for the purposes
registered under EPA Reg. No.
2693-225

[Subset A – For use on Pleasure Craft]

PRODUCT DESCRIPTION:

This product is performance, value and reliability all in one. The fast dry formula allows the boat to be painted and launched in the same day and can be applied directly over most properly prepared antifouling paints. This product is recommended for use on the underwater areas of fiberglass, wood, and properly primed metal (except aluminum) boat hulls. It can be used in fresh, salt and brackish waters.

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

COMPATIBILITY: This product can be applied over most other antifouling paints provided the old coating is tightly adhered, is in sound condition and has been thoroughly sanded with 80 grit wet-or-dry sandpaper.

V.O.C.: Less than 480 grams/liter. (4.0 lbs./gal.)	THEORETICAL COVERAGE: 400 sq. ft./gal. yields 2 mils dry film thickness
THINNER: Interlux Special Thinner 216 or Interlux Brush Ease 433	THINNING: Thin only when necessary. Do not to exceed 10% maximum.
CLEAN UP: Interlux Special Thinner 216 or Interlux Brush Ease 433	APPLICATION TEMPERATURE: 50°F (10°C)* and above (air and hull).

ESTIMATED DRY TIMES:

Temperature	Touch Dry	Overcoating Time	Immersion Time	
			Minimum	Maximum
°F (°C)		Minimum	Minimum	Maximum
50°F (10°C)	3 Hours	6 Hours	12 Hours	60 Days
60°F (15°C)	2 Hours	5 Hours	10 Hours	60 Days
75°F (24°C)	1 Hour	4 Hours	8 Hours	60 Days
95°F (35°C)	30 Minutes	2 Hours	6 Hours	60 Days

*If the air temperature falls below 50°F (10°C) during the dry time extend the dry times by 12 hours minimum.

ACCEPTED
with COMMENTS
EPA Letter Dated:

OCT 21 2011

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No.

2693-225

PREPARATION

PREVIOUSLY PAINTED SURFACES - GOOD CONDITION:

Remove all traces of loose paint and contamination by sanding the entire surface with 80 grit wet-or-dry sandpaper; wipe surface clean with Interlux Special Thinner 216. Apply at least 2 coats of this product.

PREVIOUSLY PAINTED SURFACES - POOR CONDITION:

Completely remove all old antifouling paint, using Interlux Interstrip 299E for fiberglass, and wood, and by sandblasting to near white metal for steel. Follow application systems below.

BARE FIBERGLASS:

It is very important that bare fiberglass be properly prepared to prevent delamination of the antifouling paint. Begin by scrubbing the surface thoroughly with a stiff brush using Interlux All-Purpose Boat Soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry.

Remove mold release wax using one of the following Interlux products. Fiberglass Surface Prep YMA601 or Fiberglass Solvent Wash 202 following the product label instructions. To be certain that all of the contamination has been removed, run water over the surface. If the water beads up or separates, clean again. When the water sheets off, all contamination has been removed. After the surface has been properly cleaned, proceed with one of the application systems below.

APPLICATION SYSTEMS

BARE FIBERGLASS - NO SAND SYSTEM:

Clean the surface following the preparation procedure above. Apply one coat, of Interlux InterProtect® 2000 or YPA200 Fiberglass No-Sand Primer following the label instructions for applying the primer and overcoating with antifouling paint. Apply two coats of this product, allowing for the appropriate dry times.

BARE FIBERGLASS - SANDING SYSTEM:

Clean the surface following the preparation procedure above for bare fiberglass. Sand the entire surface with 80-grit sandpaper until a flat matte finish is obtained. Wipe the sanding residue off the surface with Interlux Fiberglass Solvent Wash 202. Sand and wipe clean. Apply two coats of this product allowing for appropriate dry times.

ACCEPTED
with COMMENTS
EPA Logo

OCT 21 2008

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No.

2693-225

BARE WOOD:

Sand the entire surface with 80-grit sandpaper. Wipe the sanding residue off the surface with Interlux Special Thinner 216. Apply the first coat of this product thinned 10% with Special Thinner 216 or Brush-Ease 433. Fill seams with Interlux Seam Compound 30 (if necessary). Apply two more coats of this product unthinned, allowing for the appropriate dry times.

UNDERWATER METALS:

Contact the Interlux Technical Service Department at 1-800-468-7589 for full information on how to properly prime underwater metals. DO NOT USE ON ALUMINUM.

COLOR DIFFERENCE MAY OCCUR BETWEEN ACTUAL PAINT AND COLOR SWATCH ON FRONT OF CAN.

ACCEPTED
with COMMENTS
EPA Letter Dated:

OCT 21 2008

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

2693-225

[Subset B: Alternate Directions for Use for Pleasure Craft]

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PRODUCT DESCRIPTION: This product uses Micron technology to provide excellent, long lasting antifouling protection against all types of fouling. These products are designed to wear away (polish) at a controlled rate similar to a bar of soap. As a result there will be a reduced buildup of old coatings and minimized sanding at reapplication. In addition, this technology allows the boat to be hauled and relaunched the following season without repainting. This product dries to bright colors. It will provide excellent antifouling longevity against all types of algae, weeds, barnacles, and other shell fouling. This product can be used below the waterline in fresh, salt or brackish water on fiberglass, wood and properly primed metal boat hull and parts. Do not use on aluminum.

COMPATIBILITY: This product can be applied over most antifouling paints as long as the old coating is tightly adhered, is in sound condition, and has been thoroughly sanded with 80 grit wet-or-dry sandpaper. Soft antifouling paints will need to be removed or overcoated with Primocon® before applying.

VOC: Less than 385 grams/liter (3.21 lbs./gallon) as supplied	THINNING: Thin only when necessary. Do not exceed 10% by volume.
DRY TIMES: Touch Dry - 2 hours At 77°F (25°C) Dry to overcoat - 16 hours minimum* Dry to launch - 16 hours minimum*	THINNER: Brushing - Brush-Ease 433™ Spraying - Special Thinner 216™
THEORETICAL COVERAGE: 495 sq.ft./gallon. Yields 2 mils dry film thickness.	CLEAN-UP: Special Thinner 216™ or Brush-Ease 433™
APPLICATION TEMPERATURES: 50°F (10°C) and above. (Air and hull) * If either hull or air temperature falls below 50°F (10°C) during the 16 hour dry time extend the dry time to a minimum of 36 hours.	

ACCEPTED
 With COMMENTS
 EPA Letter Dated:
 OCT 21 2003
 2693-205
 Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended or the pesticide registered under EPA Reg. No.

APPLICATION SYSTEMS

GENERAL APPLICATION PROCEDURES: Shake or mix well prior to use. Apply at least 2 full coats (3 coats on bare wood) of this product by brush or solvent resistant 3/8" nap roller. Do not apply thin coats. Keep in mind that the life of the paint is directly related to the amount of paint applied. If during application, brush pulls or roller drags, use Interlux Brush-Ease 433™ to improve handling. Certain areas of hull experience faster polishing than other areas. These areas include the waterline, the leading edge of the keel and rudder, and the bow stem. On these areas, it is suggested that an additional coat of paint be applied to insure that this product does not wash away before the other areas of the bottom.

PREVIOUSLY PAINTED SURFACES - GOOD CONDITION: Remove all traces of loose paint and contamination by sanding the entire surface well with 80-grit wet or dry sandpaper; wipe surface clean with Interlux Special Thinner 216™. Apply at least 2 coats of this product, allowing proper dry times.

PREVIOUSLY PAINTED SURFACES - POOR CONDITION: Completely remove all old antifouling paint with Interlux Interstrip® 299E for fiberglass, wood and by sandblasting steel surfaces to a near white metal. Proceed with application system for bare work as described below.

BARE FIBERGLASS:

It is very important that bare fiberglass be properly prepared to completely remove the mold release wax in order to prevent delamination of the antifouling paint. Begin by scrubbing the surface thoroughly with a stiff brush using Interlux All-Purpose Boat Soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry.

Remove mold release wax using one of the following Interlux Fiberglass Surface Prep or Interlux Fiberglass Solvent Wash following the product label instructions. To be certain that all of the contamination has been removed, run water over the surface. If the water beads up or separates, clean again. When the water sheets off, all contamination has been removed. After the surface has been properly cleaned, proceed with one of the application systems below.

BARE FIBERGLASS - NO SAND SYSTEM: Clean the surface following the preparation procedure above. Apply one coat of Interlux InterProtect® 2000 or Interlux No Sand Primer YPA200, following the label instructions for applying the primer, and overcoating with antifouling paint. Apply two coats of this product, allowing for the appropriate dry times.

BARE FIBERGLASS - SANDING SYSTEM: Clean the surface following the preparation procedure described above. Repair any surface imperfections using Watertite Epoxy Filler. Sand and wipe clean. Sand the entire surface with 80-grit sandpaper until a flat matte finish is obtained. Wipe the sanding residue off the surface with Fiberglass Solvent Wash 202™. Apply at least 2 coats of this product.

BARE WOOD: Sand entire surface thoroughly with 80 grit production sandpaper; wipe surface clean with Interlux Brush-Ease 433™. Repair imperfections with Watertite Epoxy Filler; sand and wipe clean. Apply first coat of this product reduced with Interlux Brush-Ease 433™ (10% maximum). Fill seams with Interlux Seam Compound 30 between first and second coats of this product.

UNDERWATER METALS: Contact the Interlux Technical Service Department at 1-800-468-7589 for full details on how to properly prime underwater metals. Do not use on aluminum.

NOTE: This product may change color at the waterline.

Color difference may occur between actual paint and color swatch on front of can.

ACCEPTED
with COMMENTS
EPA Letter Dated:
OCT. 21 2008
Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.
2693-225