



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

October 8, 2019

Bathsheba Njuguna
PSRA Team Leader
International Paint, LLC
6001 Antoine Drive, Houston, TX 77091

Subject: Notification per PRN 98-10 – Revise dry time on the Label
Product Name: LATENAC II ANTIFOULING RED
EPA Registration Number: 2693-225
Application Date: July 27, 2018
Decision Number: 543217

Dear Ms. Njuguna:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

If you have any questions, you may contact Mohammad Alavi at (703) 347-0522 or via email at Alavi.mohammad@epa.gov.

Sincerely,

A handwritten signature in blue ink that reads "E. Miederhoff".

Eric Miederhoff
Product Manager 31
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

Latenac II Antifouling Red

- [Dependable Season Long Protection]
- [Fast Dry, Paint and Launch the Same Day]
- [Compatible Over Most Antifouling Paints]
- [Antifouling Performance for All Conditions]
- [Multi-Season, Self-Polishing, No Build-Up]
- [Haul & Relaunch Without Repainting]
- [High Solids Formulation]

NOTIFICATION

2693-225

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

10/08/2019

Alternate Brand Names:

[MICRON CSC HS]
[MICRON CSC HS YBC580 BLUE]
[MICRON CSC HS YBC581 GREEN]
[MICRON CSC HS YBC582 RED]
[MICRON CSC HS YBC583 BLACK]
[MICRON CSC HS YBC584 SHARK WHITE]
[MICRON CSC HS YBC586 DARK BLUE]

Active Ingredient:

Cuprous Oxide = 33.40% EPA Registration No. 2693-225

Inert Ingredients: = 66.60%
100.00% EPA Establishment No. 2693 TX-1

Copper as Metallic = 29.66%

Contains Petroleum Distillates.

KEEP OUT OF REACH OF CHILDREN

WARNING

See side panel for additional precautionary statements

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of International Paint LLC, including the surface preparation, proper application and the environmental conditions. Therefore, International Paint LLC cannot guarantee the suitability of this product for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT LLC SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use of the product buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at the discretion of International Paint LLC.

International Paint, LLC.
6001 Antoine Drive
Houston, TX 77091

Interlux.com

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
WARNING**

WARNING: Causes eye irritation. Causes skin irritation. May be fatal if swallowed. May be fatal if inhaled. Do not breathe vapor or spray mist. Do not get in eyes, on skin, or on clothing. May be fatal if absorbed through skin. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Wear protective clothing such as chemically protective gloves, long-sleeved shirt, long pants, and hat. While spraying paint or sanding or sand blasting boat surfaces, wear a minimum of a NIOSH-approved elastomeric half mask respirator with organic vapor (OV) cartridges and combination N₁, R, or P filters; OR a NIOSH-approved gas mask with OV canisters; OR a NIOSH-approved powered air purifying respirator with OV cartridges and combination HE filters. Remove and wash contaminated clothing before reuse.

FIRST AID	
If swallowed:	<ul style="list-style-type: none"> • Call a poison control center or doctor immediately for treatment advice. • Have person sip a glass of water if able to swallow. • Do not induce vomiting unless told to do so by a poison control center or doctor. • Do not give anything by mouth to an unconscious person.
If on skin or clothing:	<ul style="list-style-type: none"> • Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15-20 minutes. • Call a poison control center or doctor for treatment advice.
If inhaled:	<ul style="list-style-type: none"> • Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. • Call a poison control center or doctor for further treatment advice.
If in eyes:	<ul style="list-style-type: none"> • Hold eye open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. • Call a poison control center or doctor for treatment advice.
Other:	<ul style="list-style-type: none"> • Have the product container or label with you when calling a poison control center or doctor or going for treatment. For medical emergencies, call the poison control center at 1-800-222-1222. • For general information on this product, contact the National Pesticides Information Center (NPIC) at 1-800-858-7378, Monday through Friday, 8 AM to 12 PM PST, or at http://npic.orst.edu.

Note to Physician: Contains petroleum distillate - vomiting may cause aspiration pneumonia.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and particulate generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD: Flammable. Keep away from heat and open flame.

STORAGE AND DISPOSAL:

Do not contaminate water, food, feed by storage or disposal. Open dumping is prohibited.

STORAGE: Exposure to air and extremes of temperature must be avoided. Keep the container firmly closed. Keep out of direct sunlight. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING: Nonrefillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

[Subset A – For use on Pleasure Craft]

PRODUCT DESCRIPTION:

This product is performance, value and reliability all in one. The fast dry formula allows the boat to be painted and launched in the same day and can be applied directly over most properly prepared antifouling paints. This product is recommended for use on the underwater areas of fiberglass, wood, and properly primed metal (except aluminum) boat hulls. It can be used in fresh, salt and brackish waters.

COMPATIBILITY: This product can be applied over most other antifouling paints provided the old coating is tightly adhered, is in sound condition and has been thoroughly sanded with 80 grit wet-or-dry sandpaper.

V.O.C.: Less than 330 grams/liter. (2.75 lbs./gal/)	THEORETICAL COVERAGE: 400 sq. ft. /gal. yields 2 mils dry film thickness
THINNER: Interlux Special Thinner 216 or Interlux Brush Ease 433	THINNING: Thin only when necessary. Do not to exceed 10% maximum.
CLEAN UP: Interlux Special Thinner 216 or Interlux Brush Ease 433	APPLICATION TEMPERATURE: 50°F (10°C)* and above (air and hull).

ESTIMATED DRY TIMES:

Temperature °F (°C)	Touch Dry	Overcoating Time Minimum	Immersion Time	
			Minimum	Maximum
50°F (10°C)	3 Hours	6 Hours	12 Hours	60 Days
60°F (15°C)	2 Hours	5 Hours	10 Hours	60 Days
75°F (24°C)	1 Hour	4 Hours	8 Hours	60 Days
95°F (35°C)	30 Minutes	2 Hours	6 Hours	60 Days

*If the air temperature falls below 50°F (10°C) during the dry time extend the dry times by 12 hours minimum.

PREPARATION

PREVIOUSLY PAINTED SURFACES – GOOD CONDITION:

Remove all traces of loose paint and contamination by sanding the entire surface with 80 grit wet-or-dry sandpaper; wipe surface clean with Interlux Special Thinner 216. Apply at least 2 coats of this product.

PREVIOUSLY PAINTED SURFACES - POOR CONDITION:

Completely remove all old antifouling paint, using Interlux Interstrip 299E for fiberglass, and wood, and by sandblasting to near white metal for steel. Follow application systems below.

BARE FIBERGLASS:

It is very important that bare fiberglass be properly prepared to prevent delamination of the antifouling paint. Begin by scrubbing the surface thoroughly with a stiff brush using Interlux All-Purpose Boat Soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry.

Remove mold release wax using one of the following Interlux products. [Fiberglass Surface Prep YMA601 or Fiberglass Solvent Wash 202] following the product label instructions. To be certain that all of the contamination has been removed, run water over the surface. If the water beads up or separates, clean again. When the water sheets off, all contamination has been removed. After the surface has been properly cleaned, proceed with one of the application systems below.

APPLICATION SYSTEMS

BARE FIBERGLASS - NO SAND SYSTEM:

Clean the surface following the preparation procedure above. Apply one coat, of [Interlux InterProtect® 2000 or YPA200 Fiberglass No-Sand Primer] following the label instructions for applying the primer and overcoating with antifouling paint. Apply two coats of this product, allowing for the appropriate dry times.

BARE FIBERGLASS - SANDING SYSTEM:

Clean the surface following the preparation procedure above for bare fiberglass. Sand the entire surface with 80-grit sandpaper until a flat matte finish is obtained. Wipe the sanding residue off the surface with Interlux Fiberglass Solvent Wash 202. Sand and wipe clean. Apply two coats of this product allowing for appropriate dry times.

BARE WOOD:

Sand the entire surface with 80-grit sandpaper. Wipe the sanding residue off the surface with Interlux Special Thinner 216. Apply the first coat of this product thinned 10% with Special Thinner 216 or Brush-Ease 433. Fill seams with Interlux Seam Compound 30 (if necessary). Apply two more coats of this product unthinned, allowing for the appropriate dry times.

UNDERWATER METALS:

Contact the Interlux Technical Service Department at 1-800-468-7589 for full information on how to properly prime underwater metals. DO NOT USE ON ALUMINUM.

COLOR DIFFERENCE MAY OCCUR BETWEEN ACTUAL PAINT AND COLOR SWATCH ON FRONT OF CAN.

[Subset B: Alternate Directions for Use for Pleasure Craft]

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PRODUCT DESCRIPTION: This product is a high solids formulation antifouling that uses Micron technology to provide excellent, long lasting antifouling protection. Micron products are designed to wear away (polish) at a controlled rate similar to a bar of soap which results in reduced buildup of old coatings and minimized sanding at reapplication.

This also allows the boat to be hauled and relaunched the following season without repainting. This product dries quickly so that can be overcoated and launched quickly. It also dries with bright crisp colors. It will provide excellent antifouling longevity against all types of algae, weeds, barnacles, and other shell fouling. This product can be used below the waterline in fresh, salt or brackish water on fiberglass, wood and properly primed metal boat hull and parts. Do not use on aluminum.

COMPATIBILITY: This product can be applied over most antifouling paints as long as the old coating is tightly adhered, is in sound condition, and has been thoroughly sanded with 80 grit wet-or-dry sandpaper. Soft antifouling paints will need to be removed or overcoated with Primocon® before applying. For additional information consult the Interlux Compatibility Chart.

VOC: Less than 330 grams/liter (2.75 lbs. /gallon) as supplied	THINNING: Thin only when necessary. Do not exceed 10% by volume. Do not thin in restricted Air Quality Management Districts.
DRY TIMES: Touch Dry - 2 hours At 77°F (25°C) Dry to overcoat - 6 hours minimum* Dry to launch – 8 hours minimum*	THINNER: Brushing – [Brush-Ease 433™ Spraying - Special Thinner 216™]
THEORETICAL COVERAGE: 335 sq. ft. /gallon. Yields 3 mils dry film thickness.	
APPLICATION TEMPERATURES: 50°F (10°C) and above. (Air and hull). * If either hull or air temperature falls below 50°F (10°C) during the 16 hour dry time extend the dry time to a minimum of 36 hours.	

APPLICATION SYSTEMS

GENERAL APPLICATION PROCEDURES: Shake or mix well prior to use. Apply at least 2 full coats (3 coats on bare wood) of this product by brush or solvent resistant 3/8" nap roller. Do not apply thin coats. Keep in mind that the life of the paint is directly related to the amount of paint applied. If during application, brush pulls or roller drags, use Interlux Brush-Ease 433™ to improve handling. Certain areas of hull experience faster polishing than other areas. These areas include the waterline, the leading edge of the keel and rudder, and the bow stem. On these areas, it is suggested that an additional coat of paint be applied to insure that this product does not wear away before the other areas of the bottom.

PREVIOUSLY PAINTED SURFACE - GOOD CONDITION: Remove all traces of loose paint and contamination by sanding the entire surface well with 80-grit wet or dry sandpaper; wipe surface clean. Apply at least 2 coats of this product, allowing proper dry times.

PREVIOUSLY PAINTED SURFACES - POOR CONDITION: Completely remove all old antifouling paint with Interlux Interstrip® 299E for fiberglass, wood and by sandblasting steel surfaces to a near white metal. Proceed with application system for bare work as described below.

BARE FIBERGLASS: It is very important that bare fiberglass be properly prepared to completely remove the mold release wax in order to prevent delamination of the antifouling paint. Begin by scrubbing the surface thoroughly with a stiff brush using soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry.

Remove mold release wax using one of the following [Interlux Fiberglass Surface Prep YMA601, Fiberglass Solvent Wash 202V or Interlux Fiberglass Solvent Wash 202] following the product label instructions. To be certain that all of the contamination has been removed, run water over the surface. If the water beads up or separates, clean again. When the water sheets off, all contamination has been removed. After the surface has been properly cleaned, proceed with one of the application systems below.

BARE FIBERGLASS - NO SAND SYSTEM: Clean the surface following the preparation procedure above. Apply one coat of [Interlux InterProtect® 2000 or Interlux No Sand Primer YPA200,] following the label instructions for applying the primer, and overcoating with antifouling paint. Apply two coats of this product, allowing for the appropriate dry times.

BARE FIBERGLASS - SANDING SYSTEM: Clean the surface following the preparation procedure described above. Repair any surface imperfections using Watertite Epoxy Filler. Sand and wipe clean. Sand the entire surface with 80-grit sandpaper until a flat matte finish is obtained. Wipe the sanding residue off the surface with Fiberglass Solvent Wash 202™. Apply at least 2 coats of this product.

BARE WOOD: Sand entire surface thoroughly with 80 grit production sandpaper; wipe surface clean. Repair imperfections with Watertite Epoxy Filler; sand and wipe clean. Apply first coat of this product reduced with Interlux Brush-Ease 433™ (10% maximum). Fill seams with Interlux Seam Compound 30 between first and second coats of this product.

UNDERWATER METALS: Contact the Interlux Technical Service Department at 1-800-468-7589 for full details on how to properly prime underwater metals. Do not use on aluminum.

NOTE: This product may change color at the waterline.

Color difference may occur between actual paint and color swatch on front of can.