



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION

February 14, 2022

Vanessa Villagran  
Product Safety & Regulatory Affairs (PSRA),  
Akzo Nobel  
6001 Antoine Drive  
Houston, TX 77091  
USA

Subject: Label Amendment – To revise the product labeling  
Product Name: Trilux 33 Aerosol-Black  
EPA Registration Number: 2693-226  
Application Date: February 18, 2020  
Decision Number: 00219928

Dear Ms. Villagran:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. You must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) lists examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Assurance.

The following alternate brand names have been added to the product record:

- \*[TRILUX® 33® 063A BLACK]
- \*[TRILUX® 33® 064A GRAY]
- \*[TRILUX® 33® 068A WHITE]
- \*[TRILUX® 33®]
- \*[TRILUX® 33® ANTIFOULING]

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. If you have any questions, please contact Karen M. Leavy by phone at (703)-308-6237, or via email at [Leavy.Karen@epa.gov](mailto:Leavy.Karen@epa.gov).

Sincerely,



For Eric Miederhoff  
Product Manager Team 31  
Regulatory Management Branch I  
Antimicrobials Division (7510P)  
Office of Pesticide Programs

Enclosure: Stamped Label

# Trilux 33 Aerosol - Black

[Antifouling]  
[Paint for Outdrives, Outboards & Props]  
[Biolux Blocks Slime]

---

Active Ingredients:

Cuprous Thiocyanate	6.54%
Zinc 2-Pyridinethiol 1-Oxide*	1.33%

Other Ingredients:	<u>92.13%</u>
	100.00%

**COPPER AS METALLIC = 3.42%**

Contains petroleum distillates.

\* Zinc Pyrithione

EPA Reg. No.: 2693-226

EPA Est. No.: 2693- TX-1

**ACCEPTED**

Feb 14, 2022

---

**Alternate Brand Names (ABNs):**

- [TRILUX® 33® 063A BLACK]
- [TRILUX® 33® 064A GRAY]
- [TRILUX® 33® 068A WHITE]
- [TRILUX® 33®]
- [TRILUX® 33® ANTIFOULING]

Under the Federal Insecticide, Fungicide  
and Rodenticide Act as amended, for the  
pesticide registered under  
EPA Reg. No. 2693-226

---

[GRAPHICS]

**AkzoNobel**

 **Interlux**

 Trilux, Biolux, Interlux and the AkzoNobel logo are trademarks of AkzoNobel. © AkzoNobel  
[XXXX- year label is printed].

 Interlux and the AkzoNobel logo  
are trademarks of Akzo Nobel.

[FRONT PANEL]

**KEEP OUT OF REACH OF CHILDREN**

**DANGER**

See side panel for additional Precautionary Statement

[Note to Reviewer: In accordance with 40 CFR 156.68(d), all first aid statements, as prescribed, will appear on the front panel of the product label.]

<b>FIRST AID</b>	
<b>If swallowed:</b>	<ul style="list-style-type: none"><li>• Call a poison control center or doctor immediately for treatment advice.</li><li>• Do not give any liquid to the person.</li><li>• Do not induce vomiting unless told to do so by a poison control center or doctor.</li><li>• Do not give anything by mouth to an unconscious person.</li></ul>
<b>If on skin or clothing:</b>	<ul style="list-style-type: none"><li>• Take off contaminated clothing.</li><li>• Rinse skin immediately with plenty of water for 15-20 minutes</li><li>• Call a poison control center or doctor for treatment advice.</li></ul>
<b>If inhaled:</b>	<ul style="list-style-type: none"><li>• Move person to fresh air.</li><li>• If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.</li><li>• Call a poison control center or doctor for further treatment advice.</li></ul>
<b>If in eyes:</b>	<ul style="list-style-type: none"><li>• Hold eye open and rinse slowly and gently with water for 15-20 minutes.</li><li>• Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.</li><li>• Call a poison control center or doctor for treatment advice.</li></ul>
<b>Other:</b> Have the product container or label with you when calling a poison control center or doctor or going for treatment. For medical emergencies, call the poison control center at 1-800-222-1222. For general information on this product, contact the National Pesticides Information Center (NPIC) at 1-800-858-7378, Monday through Friday, 8 AM to 12 PM PST, or at <a href="http://npic.orst.edu">http://npic.orst.edu</a> .	

**Note to Physician:** Contains petroleum distillates. Vomiting may cause aspiration pneumonia.

**[DISCLAIMER:** The performance of any marine paint or coating depends on many factors outside the control of INTERNATIONAL PAINT, LLC., including surface preparations, proper application and environmental conditions. Therefore, INTERNATIONAL PAINT, LLC., cannot guarantee this product's suitability for your particular purpose of application. To the extent consistent with applicable law, INTERNATIONAL PAINT, LLC., EXPRESSLY DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE or otherwise that extend beyond the statements made on this label, and shall not be liable for special, incidental, or consequential damages resulting from the use or handling of this product, the exclusive remedy being the replacement of this product. To the extent consistent with applicable law, buyer/user assumes all risk of possession, handling, or use of this material when use and/or handling is contrary to label instructions.]

International Paint LLC  
6001 Antoine Drive  
Houston, TX 77091

[Interlux.com]

NET CONTENTS: 12 ounces

**[SIDE PANEL]**

**PRECAUTIONARY STATEMENTS**  
**HAZARD TO HUMANS AND DOMESTIC ANIMALS**  
**KEEP OUT OF REACH OF CHILDREN**  
**DANGER**

Corrosive. Causes skin burns. Causes substantial but temporary eye injury. Harmful if absorbed through skin, swallowed or inhaled. Avoid contact with skin, eyes, or clothing. Avoid breathing vapor or spray mist. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the restroom. Wear chemical resistant (such as nitrile or butyl) gloves, long-sleeved shirt, long pants, socks, and shoes. For overhead exposure, wear chemical-resistant headgear. Wear protective eyewear (goggles, safety glasses, or face shield). While spraying paint or sanding or sandblasting boat surfaces,). Wear a minimum of a NIOSH-approved particulate filtering facepiece respirator with any N, R or P filter; OR a NIOSH-approved elastomeric particulate respirator with any N, R or P filter; OR a NIOSH-approved powered air purifying respirator with HE filters. Remove and wash contaminated clothing before reuse.

**ENVIRONMENTAL HAZARDS**

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and particulate generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**PHYSICAL OR CHEMICAL HAZARDS**

Extremely flammable. Contents under pressure. Keep away from heat, sparks, open fire or heated surfaces. Do not puncture or incinerate container. Exposure to temperatures above 130 degrees F may cause bursting.

**[Trilux® 33]**  
**[Alternate Brand Name]**

[Trilux® 33®, this product] antifouling paint is formulated specifically for aluminum outboards, outdrives and aluminum hulls in underwater areas. [Trilux® 33®, this product] uses two biocides and Biolux® Technology for protection from all types of fouling. Biolux® Technology is used to control slime growth. [Trilux® 33®, this product] is for use in fresh, salt and brackish water.

**DIRECTIONS FOR USE**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

**STORAGE AND DISPOSAL**

Do not contaminate water, food or feed by storage or disposal.

**STORAGE:** Exposure to air and extremes of temperature must be avoided. Keep the container firmly closed. Keep out of direct sunlight. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition.

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**CONTAINER HANDLING:** Nonrefillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

[For Chemical Emergency, Spill, Leak, Exposure or Accident, Call Toll Free – Day or Night – CHEMTREC 1-800-424-9300. Medical Advisory Number – Contact your Local Poison Control Center or Call 1-800-854-6813.]

**FOR ALUMINUM OUTBOARDS, OUTDRIVES AND HULLS**

**BARE ALUMINUM** - Sand with [medium, course] grit emery cloth to bright metal, remove sanding residue with a [clean broom or airline] and immediately apply 1 full can of [Primocon YPA985 primer, Primocon Primer, Underwater Metal Primer], following overcoating times.

**PREVIOUSLY PAINTED - with [Trilux® 33®, this product]:** Sand with [80, 100] grit sandpaper then apply [Trilux® 33®] as specified below.

**PREVIOUSLY PAINTED - with Factory Paint or other Antifouling Paint:** Sand with [80,100] grit sandpaper. Wipe clean and apply 1 full can of [Primocon, Primocon YPA985 primer, Primocon, Underwater Metal Primer]. Then 1 full can of [Trilux®33®] as specified below.

## APPLICATION

Apply [Trilux® 33®, this product] only after priming with [Primocon, Primocon YPA985 primer, Underwater Metal Primer].

1. Shake can, listen for mixing ball & continue shaking for at least 2 minutes. It is best to shake in an up and down motion. IF CAN IS NOT SHAKEN PROPERLY CLOGGING OF THE TIP MAY RESULT.
2. Hold container 12-16" from unit.
3. Apply contents of 1 can for each Outdrive/Outboard. It will be touch dry in about 30 minutes. Allow a minimum of 6 hours at 75° or 12 hours at 50°F dry time between coats.
4. For application to hulls, apply 2-3 coats. Allow proper dry times.
5. Be sure paint is completely dry before immersion. Allow a minimum of 12 hours at 75°F or 16 hours at 50°F prior to launch.

**For Clean-up** - use [Special Thinner 216, Special Thinner, Yacht Thinner, Antifouling Thinner, Boat Thinner, Acetone]

**COVERAGE** - One can of [Trilux® 33®, this product] will cover 22 square feet. For best antifouling protection, use entire can of primer and [Trilux® 33®, this product] for each lower unit.

When finished spraying, invert can and spray until the nozzle is cleared. Do not apply primer or [Trilux® 33®, this product] above the true waterline.

[MADE IN THE USA]