



U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs
Antimicrobials Division (7510C)
1200 Pennsylvania Avenue NW
Washington, D.C. 20460

EPA Reg. Number: 2693-228

Date of Issuance: JAN 15 2010

Term of Issuance: Conditional

Name of Pesticide Product: Uni-Kote HT - Black

NOTICE OF PESTICIDE:
[x] Registration
Reregistration

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

International Paint, LLC
2270 Morris Avenue
Union, N. J. 07083

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec 3(c)(7)(A) provided that you:

- 1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for re-registration of your product under FIFRA section 4.
2. Make the labeling changes listed below before you release the product for shipment:
a. Revise the "EPA Registration Number to read, "EPA Reg. No.0 2693-228".

Signature of Approving Official:

Marshall Swindell
Product Manager Team-33
Regulatory Management Branch I
Antimicrobials Division (7510P)

[Handwritten signature of Marshall Swindell]

Date:

JAN 15 2010

b. Under the "Hazard to Humans and Domestic Animals" section of the product label, change "Mining Enforcement and Safety Administration" to read "Mine Safety and Health Administration (MSHA)."

c. The "Physical or Chemical Hazard" section of the label must be changed to the following hazard statement since the flash point of this product is 80°F.

"Fammable. Keep away from heat and open flame"

d. Delete the words "Hybrid Technology" wherever it may appear on the label. Implied claims of Heightened efficacy of a pesticide product by itself or as compared with another product or device are false and misleading.

e. Delete the word "new" in the Product Description.

3. Please note that the one year room temperature storage stability (830.6317) and corrosion characteristics (830.6320) are upgradeable upon submission of the results of these studies within one (1) year from the date of this Notice of Registration.


4. Submit two (2) copies of your final printed labeling before distributing or selling the product bearing the revised labeling.

5. The Basic and Alternate (white) Confidential Statements of Formulas (CSFs) dated September 21, 2009 are acceptable.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A copy of the stamped "accepted" label and a copy of the Product Chemistry review is enclosed for your records.

Sincerely,



Marshall Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510P)

Enclosures

Uni-Kote HT - Black

~~Hybrid Technology for All Surfaces~~
Fast dry, paint and launch the same day

Active Ingredient:		
Cuprous Oxide	= 25.00%	EPA Registration No. 2693-
Inert Ingredients:	= <u>75.00%</u>	
	100.00%	EPA Establishment No. 2693-NJ-1
Copper as Metallic = 22.20%		

Contains Petroleum Distillates.

ACCEPTED
with **COMMENTS**
EPA Letter Dated:
JAN 15 2010

KEEP OUT OF REACH OF CHILDREN

WARNING

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No.

See side panel for additional precautionary statements

2693-228

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of International Paint LLC, including the surface preparation, proper application and the environmental conditions. Therefore, International Paint LLC cannot guarantee the suitability of this product for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT LLC SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use of the product buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at the discretion of International Paint LLC.

International Paint LLC
2270 Morris Avenue
Union, New Jersey 07083

4/8

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
WARNING**

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes, or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

FIRST AID

If Swallowed:

- Immediately call a poison control center or doctor.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give any liquid to the person.
- Do not give anything by mouth to an unconscious person.

If on skin or clothing:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

If inhaled:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

If in eyes:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

Other: Have the product container or label with you when calling a poison control center or doctor or going for treatment.

Note to Physician: Contains petroleum distillate – vomiting may cause aspiration pneumonia.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD: Do not use or store near heat or open flame.

ACCEPTED
with COMMENTS
EPA Letter Dated:

015 2010

Under the Federal Insecticide, Fungicide, and Plant Repellent Act as amended, for the pesticide registered under EPA Reg. No.

2693-228

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Non-refillable container. Do not reuse or refill this container. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container 1/4 full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

ACCEPTED
with COMMENTS
EPA Label Dated:

JAN 15 2010

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended by the FIFRA Re-
authorized Act, the pesticide
registered under EPA Reg. No.

2693-228

Uni-Kote HT

PRODUCT DESCRIPTION: Uni-Kote HT (~~Hybrid Technology~~) is a ~~new~~ ~~technology~~ antifouling that delivers the benefits of both hard and abrasive antifouling paints. ~~Like~~ Uni-Kote HT offers the durability and scrub-ability of a ~~hard~~ hard paint, it has a slow polishing mechanism built-in, that continuously renews the active surface and avoids the heavy build-up of paint layers much like an abrasive paint. ~~Hybrid Technology~~ minimizes paint run-off/dischage in water and during haul-out procedures. Developed to provide a durable finish with fast drying properties, Uni-Kote HT aims to provide effective season-long protection for all power and sailboats. Uni-Kote HT is recommended for use on the underwater areas of fiberglass, wood, and properly primed metal (except aluminum) boat hulls and can be painted and launched the same day. Uni-Kote HT is recommended for use in all waters.

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

COMPATIBILITY: Uni-Kote HT can be applied over most other antifouling paints provided the old coating is tightly adhered, is in sound condition and has been thoroughly sanded with 80 grit wet-or-dry sandpaper. Uni-Kote HT can be applied by brush, roller or spray.

V.O.C.: Less than 465 grams/liter. (3.9 lbs. /gal.).	THEORETICAL COVERAGE: 400 sq. ft./gal at 2 mils dry film thickness.
THINNER: Interlux Special Thinner 216 or Interlux Brush Ease 433.	THINNING: Thin only when necessary. Do not to exceed 10% maximum.
CLEAN UP: Special Thinner 216 or Brush Ease 433.	APPLICATION TEMPERATURE: 50°F (10°C)* and above (air and hull).

ESTIMATED DRY TIMES:

Temperature	Touch Dry	Overcoating Time	Immersion Time	
			Minimum	Maximum
50°F (10°C)	3 Hours	6 Hours	12 Hours	60 Days
60°F (15°C)	2 Hours	5 Hours	10 Hours	60 Days
75°F (24°C)	1 Hour	4 Hours	8 Hours	60 Days
95°F (35°C)	30 Minutes	2 Hours	6 Hours	60 Days

*If the air temperature falls below 50°F (10°C) during the dry time extend the dry times by 12 hours minimum.

CREDITED
 COMMENTS
 Date:
JAN 15 2010
 Under the Federal Insecticide,
 Fungicide, and Rodenticide Act as
 amended, this pesticide,
 registered under EPA Reg. No.
 2623-228

PREPARATION

PREVIOUSLY PAINTED SURFACES - GOOD CONDITION:

Remove all traces of loose paint and contamination by sanding the entire surface with 80 grit wet-or-dry sandpaper; wipe surface clean with Special Thinner 216. Apply at least 2 coats of **Uni-Kote HT**.

PREVIOUSLY PAINTED SURFACES - POOR CONDITION:

Completely remove all old antifouling paint, using Interlux Interstrip 299E for fiberglass, and wood, and by sandblasting or grinding to near white metal for steel. Follow application systems below.

BARE FIBERGLASS:

It is very important that bare fiberglass be properly prepared to prevent delamination of the antifouling paint. Remove mold release wax and surface contamination by using one of the following Interlux products: Fiberglass Surface Prep YMA601 or Fiberglass Solvent Wash 202 following the product label instructions. Fill any surface imperfections with Interlux Watertite YAV135 following the label instructions. After the surface has been properly cleaned, proceed with one of the application systems below.

APPLICATION SYSTEMS

BARE FIBERGLASS - NO SAND SYSTEM:

Clean the surface following the preparation procedure above. Apply one coat, of Interlux InterProtect® 2000 or Fiberglass No-Sand Primer YPA200 following the label instructions for applying the primer and over coating with antifouling paint. Apply two coats of **Uni-Kote HT**, allowing for the appropriate dry times.

BARE FIBERGLASS - SANDING SYSTEM:

Clean the surface following the preparation procedure above for bare fiberglass. Sand the entire surface with 80-grit sandpaper until a flat matte finish is obtained. Wipe the sanding residue off the surface with Fiberglass Solvent Wash 202. Sand and wipe clean. Apply two coats of **Uni-Kote HT** allowing for appropriate dry times.

BARE FIBERGLASS - BLISTER PREVENTION SYSTEM:

Apply the InterProtect system for the prevention of blisters. Contact the Interlux Technical Service Department at 1-800-468-7589 or visiting yachtpaint.com for complete instructions on the application of the InterProtect system.

ACCEPTED
with COMMENTS
Interlux
Date: **JAN 15 2010**
Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.
2693-228

8/8

BARE WOOD:

Sand the entire surface with 80-grit sandpaper. Wipe the sanding residue off the surface with Special Thinner 216. Apply the first coat of **Uni-Kote HT** thinned 10% with Special Thinner 216 or Brush-Ease 433. Fill seams with Interlux Seam Compound 30 (if necessary). Apply two more coats of **Uni-Kote HT** unthinned, allowing for the appropriate dry times.

UNDERWATER METALS:

Contact the Interlux Technical Service Department at 1-800-468-7589 for full information on how to properly prime underwater metals or steel hulls. More systems and information available on www.yachtpaint.com. **DO NOT USE ON ALUMINUM.**

COLOR DIFFERENCE MAY OCCUR BETWEEN ACTUAL PAINT AND COLOR SWATCH ON FRONT OF CAN.

ACCEPTED
with COMMENTS
Date: _____

JAN 15 2010
Under Federal Insecticide,
Fungicide, and Rodenticide Act as
amended for the pesticide,
registered under EPA Reg. No.
2693-228