



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

February 13, 2020

Bathsheba Njuguna
PSRA Team Leader
International Paint, LLC
6001 Antoine Drive
Houston, TX 77091

Subject: Label Amendment – Multiple changes to various parts of label, add Sub-label B
Product Name: UNI-KOTE HT - BLACK
EPA Registration Number: 2693-228
Application Date: December 20, 2019
Decision Number: 559076

Dear Njuguna:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. You must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance

Page 2 of 2
EPA Reg. No. 2693-228
Decision No. 559076

with FIFRA section 6. If you have any questions, you may contact Joseph Daniels at (703) 347-8669 or via email at Daniels.joseph@epa.gov.

Sincerely,



Eric Miederhoff
Product Manager 31
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

Enclosure

Uni-Kote HT – Black

[Dual resin technology]
[Universal for use on all power and sailboats]
[Durable coating yet minimizes paint build up]
[Fast dry, paint and launch the same day]

ACCEPTED

02/13/2020

Under the Federal Insecticide, Fungicide
and Rodenticide Act as amended, for the
pesticide registered under
EPA Reg. No. 2693-228


Alternate Brand Names:

[ABLATIVE PLUS PREMIUM ANTIFOULING PAINT]
[FIBERGLASS BOTTOMKOTE NT YBB349 RED]
[FIBERGLASS BOTTOMKOTE NT YBB359 GREEN]
[FIBERGLASS BOTTOMKOTE NT YBB369 BLUE]
[FIBERGLASS BOTTOMKOTE NT YBB379 BLACK]
[INTERLUX FIBERGLASS BOTTOMKOTE NT YBB349 RED]
[INTERLUX FIBERGLASS BOTTOMKOTE NT YBB359 GREEN]
[INTERLUX FIBERGLASS BOTTOMKOTE NT YBB369 BLUE]
[INTERLUX FIBERGLASS BOTTOMKOTE NT YBB379 BLACK]
[ABLATIVE PLUS PREMIUM ANTIFOULING PAINT]

[GRAPHICS]

AkzoNobel

Interlux

 Micron, Interlux, InterProtect and the AkzoNobel
logo are trademarks of AkzoNobel. © AkzoNobel [XXXX- year label is printed].

FRONT PANEL

KEEP OUT OF REACH OF CHILDREN

WARNING

See side panel for additional precautionary statements

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

Active Ingredient:

Cuprous Oxide = 25.00%

Other Ingredients: = 75.00%
100.00%

Copper as Metallic = 22.20%

Contains Petroleum Distillates.

EPA Registration No. 2693-228

EPA Establishment No. 2693- TX-1

[DISCLAIMER]

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of INTERNATIONAL PAINT, LLC., including surface preparations, proper application and environmental conditions. Therefore, INTERNATIONAL PAINT, LLC., cannot guarantee this product's suitability for your particular purpose of application. To the extent consistent with applicable law, INTERNATIONAL PAINT, LLC., EXPRESSLY DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE or otherwise that extend beyond the statements made on this label, and shall not be liable for special, incidental, or consequential damages resulting from the use or handling of this product, the exclusive remedy being the replacement of this product. To the extent consistent with applicable law, buyer/user assumes all risk of possession, handling, or use of this material when use and/or handling is contrary to label instructions.

International Paint LLC
6001 Antoine Drive
Houston, TX 77091

[Interlux.com]

SIDE PANEL

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS WARNING

May be fatal if swallowed or inhaled. Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. Do not breathe vapor or spray mist. While painting or sanding or sandblasting boat surfaces, wear a NIOSH approved particulate filter with any N, R, P filter with NIOSH approval number prefix TC-84A.; or a NIOSH approved powered air purifying respirator with an HE filter with NIOSH approval number prefix TC-21C.

Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove contaminated clothing and wash clothing before reuse.

FIRST AID	
If Swallowed:	<ul style="list-style-type: none">• Call a poison control center or doctor immediately for treatment advice.• Have person sip a glass of water if able to swallow.• Do not induce vomiting unless told to do so by a poison control center or doctor.• Do not give anything by mouth to an unconscious person.
If inhaled:	<ul style="list-style-type: none">• Move person to fresh air.• If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.• Call a poison control, center or doctor for further treatment advice.
If in eyes:	<ul style="list-style-type: none">• Hold eye open and rinse slowly and gently with water for 15-20 minutes.• Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.• Call a poison control center or doctor for treatment advice.
If on skin or clothing:	<ul style="list-style-type: none">• Take off contaminated clothing.• Rinse skin immediately with plenty of water for 15-20 minutes.• Call a poison control center or doctor for treatment advice.
Have the product container or label with you when calling a poison control center or doctor or going for treatment. For medical emergencies, call the poison control center at 1-800-222-1222. For general information on this product, contact the National Pesticides Information Center (NPIC) at 1-800-858-7378, Monday through Friday, 8 AM to 12 PM PST, or at http://npic.orst.edu .	

Note to Physician: Contains petroleum distillate – vomiting may cause aspiration pneumonia.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD: Flammable. Keep away from heat and open flame.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE: Exposure to air and extremes of temperature must be avoided. Keep the container firmly closed. Keep out of direct sunlight. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING: Nonrefillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

[Subset A]

[Uni-Kote HT]

PRODUCT DESCRIPTION: [Uni-Kote HT] uses a dual resin technology that provides a universal durable, fast dry antifouling paint that delivers the benefits of both hard and polishing antifouling paints for use on all power and sailboats. The universal formula of [Uni-Kote HT] has durability of a traditional hard paint but has a slow polishing mechanism built-in that continuously smooths and renews the active surface avoiding the heavy build-up of paint layers much like a polishing paint. The fast-dry formula allows the boat to be painted and launched in the same day. Uni-Kote HT provides clean stable colors for effective season-long protection. [Uni-Kote HT] is recommended for use on the underwater areas of fiberglass, wood, and properly primed metal (except aluminum) boat hulls. It can be used in fresh, salt and brackish waters.

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

COMPATIBILITY: [Uni-Kote HT] can be applied over most other antifouling paints provided the old coating is tightly adhered, is in sound condition and has been thoroughly sanded with 80 grit wet-or-dry sandpaper. [Uni-Kote HT] can be applied by brush, roller or spray.

V.O.C.: Less than 465 grams/liter. (3.9 lbs. /gal.).	THEORETICAL COVERAGE: 400 sq. ft./gal at 2 mils dry film thickness.
THINNER: Interlux Special Thinner 216 or Interlux Brush Ease 433.	THINNING: Thin only when necessary. Do not to exceed 10% maximum.
CLEAN UP: Special Thinner 216 or Brush Ease 433.	APPLICATION TEMPERATURE: 50°F (10°C)* and above (air and hull).

ESTIMATED DRY TIMES:

Temperature °F (°C)	Touch Dry	Overcoating Time Minimum	Immersion Time	
			Minimum	Maximum
50°F (10°C)	3 Hours	6 Hours	12 Hours	60 Days
60°F (15°C)	2 Hours	4 Hours	10 Hours	60 Days
75°F (24°C)	1 Hour	2 Hours	6 Hours	60 Days
95°F (35°C)	30 Minutes	1 Hours	3 Hours	60 Days

*If the air temperature falls below 50°F (10°C) during the dry time extend the dry times by 12 hours minimum.

PREPARATION

PREVIOUSLY PAINTED SURFACES - GOOD CONDITION:

Remove all traces of loose paint and contamination by sanding the entire surface with 80 grit wet-or-dry sandpaper; wipe surface clean with Special Thinner 216. Apply at least 2 coats of [Uni-Kote HT].

PREVIOUSLY PAINTED SURFACES - POOR CONDITION:

Completely remove all old antifouling paint, using Interlux Interstrip 299E for fiberglass, and wood, and by sandblasting or grinding to near white metal for steel. Follow application systems below.

BARE FIBERGLASS:

It is very important that bare fiberglass be properly prepared to prevent delamination of the antifouling paint. Remove mold release wax and surface contamination by using one of the following Interlux products: [Fiberglass Surface Prep YMA601 or Fiberglass Solvent Wash 202] following the product label instructions. Fill any surface imperfections with Interlux Watertite YAV135 following the label instructions. After the surface has been properly cleaned, proceed with one of the application systems below.

APPLICATION SYSTEMS**BARE FIBERGLASS - NO SAND SYSTEM:**

Clean the surface following the preparation procedure above. Apply one coat, of [Interlux InterProtect® 2000 or Fiberglass No-Sand Primer YPA200] following the label instructions for applying the primer and over coating with antifouling paint. Apply two coats of [Uni-Kote HT], allowing for the appropriate dry times.

BARE FIBERGLASS - SANDING SYSTEM:

Clean the surface following the preparation procedure above for bare fiberglass. Sand the entire surface with 80-grit sandpaper until a flat matte finish is obtained. Wipe the sanding residue off the surface with Fiberglass Solvent Wash 202. Sand and wipe clean. Apply two coats of [Uni-Kote HT] allowing for appropriate dry times.

BARE FIBERGLASS - BLISTER PREVENTION SYSTEM:

Apply the InterProtect system for the prevention of blisters. Contact the Interlux Technical Service Department at 1-800-468-7589 or visiting yachtpaint.com for complete instructions on the application of the InterProtect system.

BARE WOOD:

Sand the entire surface with 80-grit sandpaper. Wipe the sanding residue off the surface with Special Thinner 216. Apply the first coat of [Uni-Kote HT] thinned 10% with [Special Thinner 216 or Brush-Ease 433]. Fill seams with Interlux Seam Compound 30 (if necessary). Apply two more coats of [Uni-Kote HT] unthinned, allowing for the appropriate dry times.

UNDERWATER METALS:

Contact the Interlux Technical Service Department at 1-800-468-7589 for full information on how to properly prime underwater metals or steel hulls. More systems and information available on www.interlux.com. DO NOT USE ON ALUMINUM.

COLOR DIFFERENCE MAY OCCUR BETWEEN ACTUAL PAINT AND COLOR SWATCH ON FRONT OF CAN.

[Subset B]

[ABLATIVE PLUS PREMIUM ANTIFOULING PAINT]

[GRAPHICS]



[NOTE TO REVIEWER]

This label Subset B will carry all other statutory language as listed below:

- Signal word
- Keep Out of Reach of Children
- First aid Statements
- Precautionary Statements
- Environmental Hazards
- Physical and Chemical hazards and
- Storage & Disposal language

NOTICE TO BUYER: Seller's guarantee shall be limited to the terms set out on the label, and subject thereto, the buyer assumes the risk to persons or property arising from the use or handling of this product and accepts the product on that condition.

PRODUCT DESCRIPTION:

[Ablative Plus Premium Antifouling Paint, this product] is an antifouling product effective against fouling organisms and slime. An ablative antifouling suitable for professional and consumer application onto vessels in fresh, salt, and brackish water. Provides protection for up to one year. Can be applied up to 6 months before launch.

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labelling.

COMPATIBILITY: [Ablative Plus Premium Antifouling Paint, this product] can be applied over most other antifouling paints provided the old coating is tightly adhered, is in sound condition and has been thoroughly sanded with **[80-120, 80, 100, 120] [grit, grade, wet or dry] sandpaper** Ablative Plus Premium Antifouling Paint can be applied by brush, roller or spray.

V.O.C.: Less than 465 grams/liter

THEORETICAL COVERAGE: 400 sq. ft./ gallon (3.9 lbs./gallon). yields 2 mils dry film thickness.

THINNER: [Acetone, Anti-fouling thinner]

THINNING: Thin only when necessary. Do not exceed 10% maximum.

APPLICATION TEMPERATURE: 50°F (10°C) *and above (air and hull).

Preparation

PREVIOUSLY PAINTED SURFACES - GOOD CONDITION: Remove all traces of loose paint and contamination by sanding the entire surface with [80-120, 80, 100, 120] [grit, grade, wet or dry] sandpaper; wipe surface clean. Apply 2 coats of [Ablative Plus Premium Antifouling Paint, this product].

PREVIOUSLY PAINTED SURFACES - POOR CONDITION: Completely remove all old antifouling paint. Follow application systems below.

BARE FIBERGLASS: It is very important that bare fiberglass be properly prepared to prevent delamination of the antifouling paint. Remove mold release wax and surface contamination. Clean surface with [Surface Prep or Acetone, Acetone] following the product label instructions. Fill any surface imperfections with an [Epoxy Filler, epoxy filler] following the label instructions. After the surface has been properly cleaned, proceed with one of the application systems below.

APPLICATION SYSTEMS

BARE FIBERGLASS - NO SAND SYSTEM: Clean the surface following the preparation procedure above. Apply one coat, of [underwater Epoxy Primer or non-sanding primer, underwater epoxy primer, non-sanding primer] following the label instructions for applying the primer and over coating with antifouling paint. Apply two coats of [Ablative Plus Premium Antifouling Paint, this product], allowing for the appropriate dry times.

BARE FIBERGLASS - SANDING SYSTEM: Clean the surface following the preparation procedure above for bare fiberglass. Sand the entire surface with [80-120, 80, 100, 120] [grit, grade, wet or dry] sandpaper until a flat matte finish is obtained. Wipe the sanding residue off the surface with [Yacht Thinner, Boat Thinner, Acetone]. Apply two coats of [Ablative Plus Premium Antifouling Paint, this product] allowing for appropriate dry times.

BARE WOOD: Sand the entire surface with [80-120, 80, 100, 120] [grit, grade, wet or dry] sandpaper. Wipe the sanding residue off the surface. Apply the first coat of [Ablative Plus Premium Antifouling Paint, this product] thinned 10% with [Acetone, Boat Thinner, Yacht Thinner]. Fill seams with [Seam Compound, Seam Filler] (if necessary). Apply one coat of [Ablative Plus Premium Antifouling Paint, this product] unthinned, allowing for the appropriate dry times.

UNDERWATER METALS: Contact SEACHOICE (954)-581-1188
DO NOT USE ON ALUMINUM. Color difference may occur between actual paint and color swatch on front of can.

[Distributed by...]

[Marketing Descriptors:]

[Season-to-Season Anti-Fouling Protection]

[Universal, a cost-effective choice for all power and sail boats in all waters]

[Paint and launch on the same day]

[DISCLAIMER]

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Seachoice Products including surface preparation, proper application, and environmental conditions. Therefore, Seachoice products cannot guarantee this product's suitability for your particular purpose or application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. In no event shall Seachoice Products be liable for loss of use of its consumer product nor for other incidental or consequential costs, expenses or damages incurred by any person. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the replacement of the product.