



U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs
Antimicrobials Division (7510C)
1200 Pennsylvania Avenue NW
Washington, D.C. 20460

EPA Reg. Number:

2693-229

Date of Issuance:

DEC 23 2011

Term of Issuance:

Conditional

Name of Pesticide Product:

Latenac III Antifouling Red

NOTICE OF PESTICIDE:

Registration
 Reregistration

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

International Paint, LLC
2270 Morris Avenue
Union, N. J. 07083

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for re-registration of your product under FIFRA section 4.
2. Make the labeling changes listed below before you release the product for shipment:
 - a. Revise the "EPA Registration Number to read, "EPA Reg. No. 2693-229".

Signature of Approving Official:

Marshall Swindell
Product Manager Team-33
Regulatory Management Branch I
Antimicrobials Division (7510P)

Date:

DEC 23 2011

b. Under the "Hazard to Humans and Domestic Animals" section of the product label, change "Mining Enforcement and Safety Administration" to read "Mine Safety and Health Administration (MSHA)."

c. Under the "Hazard to Humans and Domestic Animals" section of the product label, change "National Institute of Occupational Health" to read "National Institute for Occupational Safety and Health (NIOSH)."

d. Under the "Storage and Disposal" section of the product label, add a "Pesticide Storage" subheading and provide instructions for storing the product. Guidance on developing appropriate pesticide storage instructions can be found at <http://www.epa.gov/oppfead1/labeling/lrm/>, Chapter 13 (Storage and Disposal).


3. Please note that the studies for the storage stability and corrosion characteristics must be submitted to the Agency within one (1) year from the date of this Notice of Registration.

4. Submit two (2) copies of your final printed labeling before distributing or selling the product bearing the revised labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the "accepted" label is enclosed for your records.

Sincerely,



Marshall Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510P)

Enclosure: (Stamped Label)

3/11

Latenac III Antifouling Red

Dual Resin Technology
Dependable Season Long Protection
Fast Dry, Paint and Launch the Same Day
Compatible Over Most Antifouling Paints
Long Lasting
VOC Compliant, Reduced Solvent Emissions

Active Ingredient:

Cuprous Oxide = 33.40%

EPA Registration No. 2693-

Inert Ingredients: = 66.60%
100.00%

EPA Establishment No. 2693-NJ-1

Copper as Metallic = 29.66%

Contains Petroleum Distillates.

KEEP OUT OF REACH OF CHILDREN

WARNING

See side panel for additional precautionary statements

NET CONTENTS: ONE U.S. GALLON (3.785 LITERS)

ACCEPTED
with COMMENTS
EPA Letter Dated:

DEC 23 2011

This is a Federal Insecticide,
Fungicide, and Rodenticide Act as
defined in the Federal Insecticide,
Fungicide, and Rodenticide Act,
registered under EPA Reg. No.

2693-229

DISCLAIMER: The performance of any marine coating depends on many factors outside the control of International Paint LLC, including the surface preparation, proper application and the environmental conditions. Therefore, International Paint LLC cannot guarantee the suitability of this product for your particular purpose or application. **IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT LLC SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.** By purchase or use of the product buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at the discretion of International Paint LLC.

International Paint LLC
2270 Morris Avenue
Union, New Jersey 07083

4/11

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
WARNING**

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes, or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

FIRST AID

If Swallowed:

- Immediately call a poison control center or doctor.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give **any** liquid to the person.
- Do not give anything by mouth to an unconscious person.

If on skin or clothing:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

If inhaled:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

If in eyes:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

Other: Have the product container or label with you when calling a poison control center or doctor or going for treatment.

Note to Physician: Contains petroleum distillate - vomiting may cause aspiration pneumonia.

ACCEPTED
with COMMENTS
by EPA Letter Dated:

DEC 23 2001

Under the authority of the
EPA Administrator, this product is
approved for sale, use, and
distribution as
registered under EPA Reg. No.

2693-229

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD: Flammable. Keep away from heat and open flame.

STORAGE AND DISPOSAL

Do not contaminate water, food, feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

ACCEPTED
with COMMENTS
EPA REGIONAL OFFICE

DEC 23 2011

Under Federal Executive Order 13174, this program is not as authorized as of 10/10/2009, and is not being reauthorized, registered under EPA Reg. No.

2693-229

[Subset A – For use on Pleasure Craft]

PRODUCT DESCRIPTION:

This product is performance, value and reliability all in one. The fast dry formula allows the boat to be painted and launched in the same day and can be applied directly over most properly prepared antifouling paints. This product is recommended for use on the underwater areas of fiberglass, wood, and properly primed metal (except aluminum) boat hulls. It can be used in fresh, salt and brackish waters.

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

COMPATIBILITY: This product can be applied over most other antifouling paints provided the old coating is tightly adhered, is in sound condition and has been thoroughly sanded with 80 grit wet-or-dry sandpaper.

V.O.C.: Less than 480 grams/liter. (4.0 lbs./gal.)	THEORETICAL COVERAGE: 400 sq. ft./gal. yields 2 mils dry film thickness
THINNER: Interlux Special Thinner 216 or Interlux Brush Ease 433	THINNING: Thin only when necessary. Do not to exceed 10% maximum.
CLEAN UP: Interlux Special Thinner 216 or Interlux Brush Ease 433	APPLICATION TEMPERATURE: 50°F (10°C)* and above (air and hull).

ESTIMATED DRY TIMES:

Temperature °F (°C)	Touch Dry	Overcoating Time Minimum	Immersion Time	
			Minimum	Maximum
50°F (10°C)	3 Hours	6 Hours	12 Hours	60 Days
60°F (15°C)	2 Hours	5 Hours	10 Hours	60 Days
75°F (24°C)	1 Hour	4 Hours	8 Hours	60 Days
95°F (35°C)	30 Minutes	2 Hours	6 Hours	60 Days

*If the air temperature falls below 50°F (10°C) during the dry time extend the dry times by 12 hours minimum.

ACCEPTED
with COMMENTS
to EPA Letter Dated:

DEC 23 2011

Under the Federal Insecticide,
Fungicide and Rodenticide Act as
amended, and under the
regulation of EPA Reg. No.

2693-229

RECEIVED
7/11
DATE: _____

DEC 23 2011

PREPARATION

Under the Trade Marks Act,
Fungicide, registered under EPA Reg. No.
2693-229

PREVIOUSLY PAINTED SURFACES - GOOD CONDITION:

Remove all traces of loose paint and contamination by sanding the entire surface with 80 grit wet-or-dry sandpaper; wipe surface clean with Interlux Special Thinner 216. Apply at least 2 coats of this product.

PREVIOUSLY PAINTED SURFACES - POOR CONDITION:

Completely remove all old antifouling paint, using Interlux Interstrip 299E for fiberglass, and wood, and by sandblasting to near white metal for steel. Follow application systems below.

BARE FIBERGLASS:

It is very important that bare fiberglass be properly prepared to prevent delamination of the antifouling paint. Begin by scrubbing the surface thoroughly with a stiff brush using Interlux All-Purpose Boat Soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry.

Remove mold release wax using one of the following Interlux products. Fiberglass Surface Prep YMA601 or Fiberglass Solvent Wash 202 following the product label instructions. To be certain that all of the contamination has been removed, run water over the surface. If the water beads up or separates, clean again. When the water sheets off, all contamination has been removed. After the surface has been properly cleaned, proceed with one of the application systems below.

APPLICATION SYSTEMS

BARE FIBERGLASS - NO SAND SYSTEM:

Clean the surface following the preparation procedure above. Apply one coat, of Interlux InterProtect® 2000 or YPA200 Fiberglass No-Sand Primer following the label instructions for applying the primer and overcoating with antifouling paint. Apply two coats of this product, allowing for the appropriate dry times.

BARE FIBERGLASS - SANDING SYSTEM:

Clean the surface following the preparation procedure above for bare fiberglass. Sand the entire surface with 80-grit sandpaper until a flat matte finish is obtained. Wipe the sanding residue off the surface with Interlux Fiberglass Solvent Wash 202. Sand and wipe clean. Apply two coats of this product allowing for appropriate dry times.

BARE WOOD:

Sand the entire surface with 80-grit sandpaper. Wipe the sanding residue off the surface with Interlux Special Thinner 216. Apply the first coat of this product thinned 10% with Special Thinner 216 or Brush-Ease 433. Fill seams with Interlux Seam Compound 30 (if necessary). Apply two more coats of this product unthinned, allowing for the appropriate dry times.

UNDERWATER METALS:

Contact the Interlux Technical Service Department at 1-800-468-7589 for full information on how to properly prime underwater metals. DO NOT USE ON ALUMINUM.

COLOR DIFFERENCE MAY OCCUR BETWEEN ACTUAL PAINT AND COLOR SWATCH ON FRONT OF CAN.

RECEIVED
 INTERLUX TECHNICAL SERVICE
 DEPT.
 DEC 23 2011
 This product is a pesticide,
 registered under FIFRA Act as
 a wood preservative,
 registered under EPA Reg. No.
 2693-229

[Subset B: Alternate Directions for Use for Pleasure Craft]

PRODUCT DESCRIPTION: This product uses a dual resin technology that provides a VOC compliant antifouling paint that delivers the benefits of both hard and polishing antifouling paints for use on all power and sailboats. The universal formula has the durability of a traditional hard paint but a slow polishing mechanism that continuously smoothes and renews the active surface avoiding heavy build-up much like a polishing antifouling paint. This product is a high solids VOC compliant antifouling that reduces solvent emissions. The fast dry formula allows the boat to be painted and launched in the same day. The efficient use of copper in this product provides effective long lasting protection against all types of algae, weeds, barnacles, and other shell fouling. This product is for use on the underwater areas of fiberglass, wood, and properly primed metal (except aluminum) boat hulls. It can be used in fresh, salt and brackish waters.

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

COMPATIBILITY: This product can be applied over most other antifouling paints provided the old coating is tightly adhered, is in sound condition and has been thoroughly sanded with 80 grit wet-or-dry sandpaper. For additional information consult the Interlux Antifouling Compatibility Chart. This product can be applied by brush, roller or spray. Do not use on aluminum.

V.O.C.: Less than 330 grams/liter. (2.75 lbs. /gal.).	THEORETICAL COVERAGE: 330 sq. feet/gal at 3 mils dry film thickness.
CLEAN UP: Special Thinner 216 or Brush Ease 433.	APPLICATION TEMPERATURE: 50°F (10°C)* and above (air and hull).

ACCEPTED
 With COMMENTS
 Date: DEC 23 2017
 2693-229
 registered trademark No.

ESTIMATED DRY TIMES:

Temperature	Touch Dry	Overcoating Time	Immersion Time	
			Minimum	Maximum
50°F (10°C)	4 Hours	12 Hours	16 Hours	Indefinite
77°F (25°C)	2 Hours	6 Hours	8 Hours	Indefinite
95°F (35°C)	1 Hours	3 Hours	4 Hours	Indefinite

*If the air temperature falls below 50°F (10°C) during the dry time extend the dry times by 12 hours minimum.

PREPARATION

BARE FIBERGLASS:

It is very important that bare fiberglass be properly prepared to prevent delamination of the antifouling paint. Scrub the surface thoroughly with a stiff brush using soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry. Remove mold release wax and surface contamination by using Low VOC Fiberglass Solvent Wash 202V following the product label instructions. Fill any surface imperfections with Interlux Watertite YAV135 following the label instructions. After the surface has been properly cleaned, proceed with one of the application systems below.

PREVIOUSLY PAINTED SURFACES - GOOD CONDITION:

Remove all traces of loose paint and contamination by sanding the entire surface with 80 grit wet-or-dry sandpaper; wipe surface clean with Low VOC Fiberglass Solvent Wash 202V. Rinse completely and let dry. Apply at least 2 coats of this product.

PREVIOUSLY PAINTED SURFACES - POOR CONDITION:

Completely remove all old antifouling paint, using Interlux Interstrip 299E for fiberglass, and wood, and by sandblasting or grinding to near white metal for steel. Follow application systems below.

with...
Date: DEC 23 2011

APPLICATION SYSTEMS

Interlux Interstrip 299E
EPA Reg. No. 2693-229

GENERAL APPLICATION NOTES: Shake or mix well prior to use. Apply at least 2 full coats brush or solvent resistant 3/8" nap roller. Do not apply thin coats. Certain areas of hull experience faster wear than other areas. These areas include the waterline, the leading edge of the keel and rudder, and the bow stem. On these areas, it is suggested that an additional coat of paint be applied to ensure that this product does not wear away before the other areas of the bottom.

BARE FIBERGLASS - NO SAND SYSTEM:

Clean the surface following the preparation procedure above. Apply one coat, of Interlux InterProtect® 2000 VOC following the label instructions for applying the primer and over coating with antifouling paint. Apply two coats of this product, allowing for the appropriate dry times.

BARE FIBERGLASS - SANDING SYSTEM:

Clean the surface following the preparation procedure above for bare fiberglass. Sand the entire surface with 80-grit sandpaper until a flat matte finish is obtained. Wipe the sanding residue off the surface with Low VOC Fiberglass Solvent Wash 202V. Rinse completely and let dry. Apply two coats of this product allowing for appropriate dry times.

11/11

BARE FIBERGLASS - BLISTER PREVENTION SYSTEM:

Apply the InterProtect system for the prevention of blisters. Contact the Interlux Technical Service Department at 1-800-468-7589 or visit yachtpaint.com for complete instructions on the application of the InterProtect system.

Color difference may occur between actual paint and color swatch on front of can.

ACCEPTED
with COMMENTS
EPI Letter Dated:

DEC 23 2011

Used for the purpose of...
registered under EPA Reg. No.

2693-229