



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION

June 15, 2021

Vanessa Villagran  
PSRA Specialist  
International Paint LLC  
6001 Antoine Drive  
Houston, TX 77091

Subject: Label Amendment – Re-formatting and updating the label  
Product Name: Trilux 44 II-White  
EPA Registration Number: 2693-230  
Application Date: November 4, 2020  
Action Code Case Number: 00217201

Dear Ms. Villagran:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. You must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance

Page 2 of 2  
EPA Reg. No. 2693-230  
Decision No. 00217210

with FIFRA section 6. If you have any questions, please contact Tara Flint via email at [flint.tara@epa.gov](mailto:flint.tara@epa.gov).

Sincerely,



Aline Heffernan  
Acting Product Manager Team 31  
Regulatory Management Branch I  
Antimicrobials Division (7510P)  
Office of Pesticide Programs

Enclosure

# Trilux 44 II - White

[Antifouling Paint]  
[Copper Free Antifouling]  
[Biolux with Econea]  
[Bright Colors]  
[Copper-free, multi-seasonal antifouling]  
[Suitable for all boats, all waters]

[Alternate Brand Names (ABNs):]

- [INTERLUX®]
- [MICRON® CF]
- [MICRON® CF YBD100 BLUE]
- [MICRON® CF YBD101 GREEN]
- [MICRON® CF YBD102 RED]
- [MICRON® CF YBD103 BLACK]
- [MICRON® CF YBD104 SHELL WHITE]
- [INTERLUX® MICRON CF YBD100 BLUE]
- [INTERLUX® MICRON CF YBD101 GREEN]
- [INTERLUX® MICRON CF YBD102 RED]
- [INTERLUX® MICRON CF YBD104 SHELL WHITE]
- [INTERLUX® MICRON CF YBD103 BLACK]

**ACCEPTED**


Jun 15, 2021

Under the Federal Insecticide, Fungicide  
and Rodenticide Act as amended, for the  
pesticide registered under  
EPA Reg. No. 2693-230

[GRAPHICS]

**AkzoNobel**



 Micron, Biolux, Interlux and the AkzoNobel logo are trademarks of AkzoNobel. © AkzoNobel [XXXX-year label is printed].

 Interlux and the AkzoNobel logo are trademarks of Akzo Nobel.



**[Front Panel]**

*[Note to Reviewer: In accordance with 40 CFR 156.68(d), all first aid statements, as prescribed, will appear on the front panel of the label.]*

**KEEP OUT OF REACH OF CHILDREN**

**DANGER**

Active Ingredients:

1 H-Pyrrole-3-carbonitrile, 4-bromo -2-(4-chlorophenyl)-5-(trifluoromethyl)	3.90%
Zinc 2-Pyridinethiol 1-Oxide*	4.12%

Other Ingredients:

91.98%  
100.00%

Contains petroleum distillates.

\* Zinc Pyrithione

EPA Reg. No.: 2693-230

EPA Est. No.: 2693-TX-1

**FIRST AID**

<b>IF IN EYES:</b>	<ul style="list-style-type: none"><li>• Hold eye open and rinse slowly and gently with water for 15-20 minutes.</li><li>• Remove contact lenses, if present, after the first 5 minutes, and then continue rinsing.</li><li>• Call a Poison Control Center or doctor for treatment advice.</li></ul>
<b>IF SWALLOWED:</b>	<ul style="list-style-type: none"><li>• Immediately call a poison control center or doctor.</li><li>• Do not induce vomiting unless told to do so by a poison control center or doctor.</li><li>• Do not give any liquid to the person.</li><li>• Do not give anything by mouth to an unconscious person.</li></ul>
<b>IF ON SKIN OR CLOTHING:</b>	<ul style="list-style-type: none"><li>• Take off contaminated clothing.</li><li>• Rinse skin immediately with plenty of water for 15-20 minutes.</li><li>• Call a poison-control center, or doctor for treatment advice.</li></ul>
<b>IF INHALED:</b>	<ul style="list-style-type: none"><li>• Move a person to fresh air.</li><li>• If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.</li><li>• Call a poison control center or doctor for further treatment advice.</li></ul>
<b>Other:</b> Have the product container or label with you when calling a poison control center or doctor or going for treatment. For medical emergencies, call the poison control center at 1-800-222-1222. For general information on this product, contact the National Pesticides Information Center (NPIC) at 1-800-858-7378, Monday through Friday, 8 AM to 12 PM PST, or at <a href="http://npic.orst.edu">http://npic.orst.edu</a> .	

**Note to Physician:** Contains petroleum distillate - vomiting may cause aspiration pneumonia.

See side panel for additional Precautionary Statement

**[DISCLAIMER:** The performance of any marine paint or coating depends on many factors outside the control of INTERNATIONAL PAINT, LLC., including surface preparations, proper application and environmental conditions. Therefore, INTERNATIONAL PAINT, LLC., cannot guarantee this product's suitability for your particular purpose of application. To the extent consistent with applicable law, INTERNATIONAL PAINT, LLC., EXPRESSLY DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE or otherwise that extend beyond the statements made on this label, and shall not be liable for special, incidental, or consequential damages resulting from the use or handling of this product, the exclusive

remedy being the replacement of this product. To the extent consistent with applicable law, buyer/user assumes all risk of possession, handling, or use of this material when use and/or handling is contrary to label instructions.]

**International Paint LLC  
6001 Antoine Drive  
Houston, TX 77091**

**[[Interlux.com](http://Interlux.com)]**

NET CONTENTS: ONE GALLON (3.785 LITERS)

**[Side Panel]**

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS  
KEEP OUT OF REACH OF CHILDREN  
DANGER**

Corrosive. Causes irreversible eye damage or skin burns. Harmful if absorbed through skin. Do not get in eyes, on skin or on clothing. Harmful if swallowed or inhaled. Do not breathe dust, vapor or spray mist. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.

Residential (non-commercial) users are advised to wear chemical resistant gloves, protective eyewear (goggles, safety glasses, or face shield), long sleeved shirt and long pants, socks and shoes. In addition to these minimum PPE, commercial users must wear a disposable coverall with hood and chemical resistant footwear.

While removing existing paint by sanding or blasting, or applying new antifoulant paint, commercial users must wear a minimum of an NIOSH-approved elastomeric half mask respirator with organic vapor (OV) cartridges and a combination N, R, or P filter; OR a NIOSH-approved gas mask with OV canisters; OR a NIOSH-approved powered air-purifying respirator with OV cartridges and combination HE filters. Residential (non-commercial) users are advised to wear the same respirators, cartridges, and prefilters as required by commercial users.

**ENVIRONMENTAL HAZARDS:**

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and particulate generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**PHYSICAL OR CHEMICAL HAZARD:**

**FLAMMABLE.** Keep away from heat and open flame.

[Subset A] [Pleasure Craft] [Alternate Brand Name, Micron® CF]

**PRODUCT DESCRIPTION:** [alternate brand name, Micron® CF, this product] is a copper free multi-seasonal antifouling that provides excellent protection from shell and weed fouling. It uses Biolux® Technology to block slime and Ecomea® to ward off barnacles and zebra mussels. The fast-dry formula of [alternate brand name, Micron® CF, this product] allows the boat to be painted and launched quickly and its polishing action reduces paint build up and helps to improve fuel efficiency. [alternate brand name, Micron® CF, this product] is available in [bright, crisp, popular] colors and is suitable for use on all boats including fiberglass, aluminum, wood, and steel and can be used in all waters [alternate brand name, Micron® CF, this product] can be brush or roller applied.

**DIRECTIONS FOR USE**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

DO NOT APPLY BY SPRAY APPLICATOR.

**STORAGE AND DISPOSAL**

Do not contaminate water, food or feed by storage or disposal.

**STORAGE:** Exposure to air and extremes of temperature must be avoided. Keep the container firmly closed. Keep out of direct sunlight. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition.

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**CONTAINER HANDLING:** Nonrefillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

[For Chemical Emergency, Spill, Leak, Exposure or Accident, Call Toll Free – Day or Night – CHEMTREC 1-800-424-9300. Medical Advisory Number – Contact your Local Poison Control Center or Call 1-800-854-6813.]

**GENERAL APPLICATION PROCEDURES**

Apply only in outdoor, non-enclosed spaces.

Apply 2 full coats of [Alternate brand name, Micron® CF, this product] by brush or solvent resistant 3/8" nap roller. Do not apply thin coats. Keep in mind that the life of the paint is directly related to the amount of paint applied. Certain areas of the hull, such as the leading edge of the keel and rudder, the waterline and the bow stem polish faster than other areas, hence can benefit from an additional coat.

<b>THEORETICAL COVERAGE:</b> 536 ft <sup>2</sup> /gal (2 mils dry film thickness), or 357 ft <sup>2</sup> /gal at 3 mils	<b>V.O.C.:</b> Less than 330 grams/liter (2.75 lbs./gallon)
<b>CLEAN-UP:</b> [SPECIAL THINNER 216™ or Brush-Ease 433™, Special Thinner, Brush Ease, Boat Thinner, Yacht Thinner]	<b>THINNING:</b> Not recommended. If necessary, do not exceed 10% by volume. Thinning may void VOC compliance.

**APPLICATION TEMPERATURES: 41 °F (5°C) and above (air + hull)**

Temperature °F (°C)	Touch Dry	Overcoating Time	Immersion Time	
	MIN	MIN	MIN	MAX
41°F(5°C)	6 hrs	12 hrs	18 hrs	6 months
50°F(10°C)	3 hrs	6 hrs	9 hrs	6 months
73°F (23°C)	2 hrs	4 hrs	6 hrs	6 months
95°F (35°C)	1 hr	2 hrs	4 hrs	6 months

\*If the air temperature falls below 41 °F (5°C) during the 6 hour dry time extend the dry times to 24 hours minimum.

**PREPARATION**

**BARE FIBERGLASS:**

It is very important that bare fiberglass be properly prepared in order to prevent delamination of the antifouling paint. Begin by scrubbing the surface thoroughly with a stiff brush using soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry.

Remove mold release wax using one of the following products: [Interlux Fiberglass Surface Prep YMA601V, Interlux Fiberglass Solvent Wash 202, Fiberglass Surface Prep YMA601V, Fiberglass Solvent Wash 202, Fiberglass Surface Prep, Solvent Wash, Acetone, Boat Prep] following the product label instructions. To be certain that all the contamination has been removed, run water over the surface; if the water beads up or separates, clean again. When the water sheets off, all contamination has been removed. After the surfaces has been properly cleaned, proceed with one of the application systems below.

**BARE FIBERGLASS - NO SAND SYSTEM:**

Clean the surface using [Interlux Fiberglass Surface Prep YMA601V, Fiberglass Surface Prep, Boat Prep] following the preparation procedure described. Apply one coat of [InterProtect 2000E, InterProtect HS, InterProtect] following the label instructions for applying the primer and overcoating with antifouling paint. Apply 2 coats of [Alternative Brand Name, Micron® CF, this product] allowing for the appropriate dry times.

**BARE FIBERGLASS - SANDING SYSTEM:**

Clean the surface following the preparations procedure described. Sand the entire surface with [80-120, 80, 100, 120] [grit, grade, wet or dry] sandpaper and wipe clean with [Interlux Fiberglass Solvent Wash 202, Fiberglass Solvent Wash 202, Fiberglass Solvent Wash, Solvent Wash, Acetone, Boat Thinner, Interlux Fiberglass Surface Prep YMA601V, Fiberglass Surface Prep YMA601V, Fiberglass Surface Prep, Surface Prep, Boat Surface Prep] to remove sanding residue. Repair any surface imperfections with [Watertite, Watertite Epoxy Filler, Interfill, Interfill Epoxy Filler, Epoxy Filler, Boat Filler]. Sand and wipe clean. Apply 2 coats [Micron® CF, this product] allowing for appropriate dry times.

**BARE WOOD:**

Sand the entire surface with [80-120, 80, 100, 120] [grit, grade, wet or dry] sandpaper and wipe clean with [Special Thinner 216, Interlux Special Thinner 216, Special Thinner, Acetone, Fiberglass Solvent Wash 202, Interlux Fiberglass Solvent Wash 202, Solvent Wash, Boat Thinner]. Repair imperfections with [Watertite, Watertite Epoxy Filler, Interfill, Interfill Epoxy Filler]. Apply the first coat of this product thinned 10% with [Special Thinner 216, Interlux Special Thinner 216, Special Thinner, Acetone, Interlux Brush Ease 433, Brush Ease 433, Brush Ease]. Fill seams with [Seam Compound 30, Seam Compound, Seam Filler], if necessary. Apply 2nd coat of [Micron® CF, this product] unthinned, following the overcoating times.



## **ALUMINUM & UNDERWATER METALS:**

[Gritblast or sand, Gritblast, sand] with medium grade (grit) emery cloth to a bright metal finish and remove residue [wipe clean, with a clean broom or air line]. Apply one coat of InterProtect 2000E that has been thinned 15-20% with Reducing Solvent 2316N. Apply InterProtect 2000E the [same day, immediately after] as blasting or sanding. Apply 3-4 additional coats of InterProtect 2000E unthinned. When the InterProtect 2000E is thumbprint tacky, apply the first coat of [Alternate Brand Name, this product]. Apply second coat of [Alternate Brand Name, this product] following the proper dry times.

## **PREVIOUSLY PAINTED SURFACES**

### **In Good Condition:**

Remove all traces of loose paint and contamination by sanding the entire surface with [80, 80-120, 100, 120] [grit, grade, wet or dry] sandpaper: wipe surface clean with [Special Thinner 216, Special Thinner, Thinner 216, Antifouling Thinner, Yacht Thinner, Boat Thinner, Acetone]. Apply 2 coats of [Alternate brand name, Micron® CF, this product]

**In Poor Condition:** Completely remove all old antifouling paint [by paint stripper, sanding, abrasive media blasting, sanding or abrasive media blasting]. Proceed with application system for bare system.

## **APPLICATION**

Apply two coats of [**Alternate brand name, Micron® CF, this product**] by brush or roller (Residential users).

**NOTE: Important:** Do not apply this product above the true waterline.

[Color difference may occur between actual paint and color swatch on front of can.]

[Micron, Biolux, Interlux and the AkzoNobel logo are trademarks of AkzoNobel. © AkzoNobel 2020.]